Code Review — By Tsz Him Lee and Daniil Simoyan

1. Externalized hard-coded matrix using JSON & added LevelLoader

- Moved the previously hard-coded tile matrix out of the codebase and replaced it with a JSON-based configuration for better maintainability.
- Implemented a new LevelLoader class to handle loading levels and cleaned up GameView accordingly.
  Commits: 6624b5d → 022e134

2. Reduced duplicated code & improved readability for entity spawning

- Refactored repeated logic in GameView related to spawning entities.
- Improved the structure to make behavior easier to follow and maintain.
  Commit: e3c5383

3. Centralized input handling to prevent duplication

- Removed the redundant InputHandler instance from GameView.
- Consolidated input handling inside the dedicated InputHandlerClass.
  Commit: bc0d670

4. Consolidated window dimension constants

- Menu and game scenes were using duplicated window size values.
- Created a shared class to store window dimension constants and removed the duplicated hard-coded values.
  Commit: 80cbd9b

5. Eliminated duplication of TILE_SIZE = 32

- The tile size was duplicated across multiple files.
- Moved TILE_SIZE into GameConstant to ensure a single source of truth.
  Commit: e0c264d

6. Centralized game constants into GameConstant.java

- Grouped all global game constants into the GameConstant class for easier maintenance and consistency.
  Commit: 7e623c0

7. Removed unused imports

- Cleaned up unnecessary import statements across the codebase.
  Commit: 7706137

8. Improved logic for finding safe spawn locations

- Refactored the nested loop responsible for locating the nearest safe spawn point for the player.
- Improved logic flow and clarity, acting as a simple spawn-protection system.
  Commit: b3b14f9