



11	43A41410-2557J	See Drawing		1
10	2242003	See parts store for more information		1
9	2251189 & 1011298	See parts store for more information		1
8	43A41410-2557F	See Drawing		1
7	43A41410-2557H	See Drawing	Tube	2
6	43A41410-2557I	See Drawing		1
5	43A41410-2557Z	See Drawing		1
4	43A41410-2557C	See Drawing		1
3	2251216	See parts store for more information		1
2	43A41410-2557B	See Drawing		1
1	43A41410-2557A	See Drawing		1
ITEM	PART NUMBER	STOCK SIZE	DESCRIPTION	QTY

ENSURE ALL SHARP EDGES ARE BROKEN  
USE BOLT HOLES FOR PRIORITY ALIGNMENT  
WELD AS NEEDED UNLESS SPECIFIED

THE GOODYEAR TIRE & RUBBER COMPANY				UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES AND THE TOLERANCE OF ALL DIMENSIONS IS: ± 0.010 BETWEEN FINISHED SURFACES ± 0.040 BETWEEN UNFINISHED SURFACES ± 0.25 DEGREES ON ANGLES			
THIS DRAWING AND THE SUBJECT MATTER THEREIN ARE THE PROPERTY OF THE GOODYEAR TIRE & RUBBER COMPANY, AKRON, OHIO AND CONTAINS CONFIDENTIAL AND/OR PROPRIETARY INFORMATION AND MAY NOT BE COPIED, USED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF THE GOODYEAR TIRE & RUBBER COMPANY. COPIES THEREOF WILL BE RETURNED OR DESTROYED ON REQUEST.		CHECKED BY AC91384	DATE 6/13/2024	ALL DATES ARE SHOWN AS MONTH/DAY/YEAR	DEPT. NO. ISO 2768-1	SCALE DRAWING STANDARD	TITLE
DRAWING NUMBER 43A41410-2557		1	OF	1	0	REV	
SHEET		TOTAL	REV				
0		Initial Drawing	REV		REVISION DESCRIPTION		
			DATE		REV. BY		