```
PS C:\Users\Deana Naveen\OneDrive\Desktop\git\L6_L7_15_movie_tickets\La
b 7> python movie_tickets.py
==== Running parse_seat ====
Enter a seat number (e.g. H12): H12
Row and Seat: ('H', 12)

==== Running total_price ====
Enter ticket prices as CSV (e.g. 150,250,400): 150,250,400
Total with GST: 944.0

==== Running average_rating ====
Enter ratings separated by spaces (e.g. 4 5 3): 4 5 3
Average Rating: 4.0
```

```
test_movie_tickets.py:58:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _

seat = ''

    def parse_seat(seat):
>       return seat[0].upper(), int(seat[1:])
               ^^^^^^^
E       IndexError: string index out of range

movie_tickets.py:2: IndexError
========================= short test summary info ==========================
FAILED test_movie_tickets.py::test_parse_seat_no_crash - ExceptionGroup: Hypothesis found 3 dis
tinct failures. (3 sub-excep...
FAILED test_movie_tickets.py::test_total_price_no_crash - ExceptionGroup: Hypothesis found 2 di
stinct failures. (2 sub-excep...
FAILED test_movie_tickets.py::test_average_rating_no_crash - ExceptionGroup: Hypothesis found 3
 distinct failures. (3 sub-excep...
FAILED test_movie_tickets.py::test_non_string_inputs_no_crash - ExceptionGroup: Hypothesis foun
d 3 distinct failures. (3 sub-excep...
FAILED test_movie_tickets.py::test_known_bad_inputs - IndexError: string index out of range
==================== 5 failed, 4 passed in 6.68s ====================
PS C:\Users\Deana Naveen\OneDrive\Desktop\git\L6_L7_15_movie_tickets\Lab 7>
```

```
Enter a seat number (e.g. H12): H12
Row and Seat: ('H', 12)

==== Running total_price ====
Enter ticket prices as CSV (e.g. 150,250,400): 150,250,400
Total with GST: 944.0

==== Running average_rating ====
Enter ratings separated by spaces (e.g. 4 5 3): 4 5 3
Average Rating: 4.0
PS C:\Users\Deana Naveen\OneDrive\Desktop\git\L6_L7_15_movie_tickets\La
b 7> python movie_tickets.py
==== Running parse_seat ====
Enter a seat number (e.g. H12): H12
Row and Seat: ('H', 12)

==== Running total_price ====
Enter ticket prices as CSV (e.g. 150,250,400): 50,,200
Invalid prices

==== Running average_rating ====
Enter ratings separated by spaces (e.g. 4 5 3): 1 2 3
Average Rating: 2.0
```

```
PS C:\Users\Deana Naveen\OneDrive\Desktop\git\L6_L7_15_movie_tickets\La
b 7> python -m pytest test_movie_tickets.py
========================= test session starts =========================
platform win32 -- Python 3.12.10, pytest-9.2.0, pluggy-1.7.0
rootdir: C:\Users\Deana Naveen\OneDrive\Desktop\git\L6_L7_15_movie_tick
ets\Lab 7
plugins: anyio-4.8.0, hypothesis-6.170.15
collected 9 items

test_movie_tickets.py .........                                  [100%]

========================== 9 passed in 8.57s ==========================
PS C:\Users\Deana Naveen\OneDrive\Desktop\git\L6_L7_15_movie_tickets\La
b 7>
```