



中国科学院大学
University of Chinese Academy of Sciences

硕士学位论文

基于深度学习的场景光照估计研究

作者姓名：程大川

指导教师：陈彦云 研究员

中国科学院软件研究所

学位类别：工学硕士

学科专业：计算机图形学

培养单位：中国科学院软件研究所

2019 年 6 月

Deep Scene Illumination Estimation

**A thesis submitted to the
University of Chinese Academy of Sciences
in partial fulfillment of the requirement
for the degree of
Master of Engineering
in Computer Graphics**

By

CHENG Dachuan

Supervisor: Professor Chen Yanyun

Institute of Software, Chinese Academy of Sciences

June, 2019

中国科学院大学 学位论文原创性声明

本人郑重声明：所呈交的学位论文是本人在导师的指导下独立进行研究工作所取得的成果。尽我所知，除文中已经注明引用的内容外，本论文不包含任何其他个人或集体已经发表或撰写过的研究成果。对论文所涉及的研究工作做出贡献的其他个人和集体，均已在文中以明确方式标明或致谢。本人完全意识到本声明的法律结果由本人承担。

作者签名：

日 期：

中国科学院大学 学位论文授权使用声明

本人完全了解并同意遵守中国科学院大学有关保存和使用学位论文的规定，即中国科学院大学有权保留送交学位论文的副本，允许该论文被查阅，可以按照学术研究公开原则和保护知识产权的原则公布该论文的全部或部分内容，可以采用影印、缩印或其他复制手段保存、汇编本学位论文。

涉密及延迟公开的学位论文在解密或延迟期后适用本声明。

作者签名：

日 期：

导师签名：

日 期：

摘 要

摘要

关键词： 关键词

Abstract

Keywords: keywords

目 录

| | |
|---------------------------|----|
| 第1章 绪论 | 1 |
| 1.1 选题的背景及意义 | 1 |
| 1.2 国内外研究现状 | 2 |
| 1.2.1 光照的表示 | 2 |
| 1.2.2 使用光探测物估计光照 | 3 |
| 1.2.3 使用特定设备估计光照 | 4 |
| 1.2.4 使用额外信息估计光照 | 5 |
| 1.2.5 使用简化的光照模型 | 7 |
| 1.2.6 基于图像分析估计光照 | 7 |
| 1.2.7 用户交互辅助估计光照 | 7 |
| 1.2.8 反向渲染过程 | 7 |
| 1.2.9 光照估计相关数据集 | 7 |
| 1.2.10 利用深度学习工具估计光照 | 7 |
| 第2章 光照估计数据集 | 9 |
| 2.1 引言 | 9 |
| 2.2 高动态范围全景图像 | 9 |
| 2.2.1 全景图像 | 9 |
| 2.2.2 高动态范围全景图像 | 9 |
| 2.2.3 拍摄与合成 | 9 |
| 2.3 光照估计数据集 | 9 |
| 2.4 讨论 | 9 |
| 2.5 本章小结 | 9 |
| 第3章 基于深度学习的光照估计方法 | 11 |
| 3.1 引言 | 11 |
| 3.2 相关工作 | 11 |
| 3.3 问题求解范围 | 11 |
| 3.4 光照分布的球形谐波表示 | 11 |
| 3.5 卷积神经网络结构 | 11 |
| 3.6 损失函数 | 11 |
| 3.7 实验结果与评估 | 11 |
| 3.8 深入研究光照估计网络 | 11 |
| 3.9 讨论 | 11 |
| 3.10 本章小结 | 11 |

| | |
|-------------------------------|----|
| 第4章 光照估计的应用 | 13 |
| 4.1 引言 | 13 |
| 4.2 电脑端应用 | 13 |
| 4.3 移动端应用 | 13 |
| 4.4 本章小结 | 13 |
| 第5章 总结与展望 | 15 |
| 5.1 本文工作总结 | 15 |
| 5.2 未来工作展望 | 15 |
| 附录 A 附录 | 17 |
| 参考文献 | 19 |
| 作者简历及攻读学位期间发表的学术论文与研究成果 | 23 |
| 致谢 | 25 |

图形列表

| | |
|----------------------|---|
| 1.1 光照估计的应用 | 1 |
| 1.2 光照表示模型的示例 | 3 |
| 1.3 使用特殊设备估计光照 | 5 |

表格列表

符号列表

字符

| Symbol | Description | Unit |
|----------|-----------------|------|
| I_{ij} | identity tensor | 1 |

算子

| Symbol | Description |
|----------|-------------------|
| ∇ | gradient operator |

缩写

| | |
|-----|------------------------------|
| CFD | Computational Fluid Dynamics |
|-----|------------------------------|

第1章 绪论

1.1 选题的背景及意义

光照估计（又称光照分布估计）是从已知的彩色图像信息中，预测、估计、恢复出整个场景的光照分布。该问题的输入通常是若干张彩色图片，或者是一段视频，有时已知的几何或材质信息也被用来辅助估计光照。场景的光照分布是指场景中各个方向的光照的颜色和强度。较为常见的光照分布表示方法包括高动态范围（High Dynamic Range, HDR）全景图、球形谐波（Spherical Harmonics, SH）函数表示、基于物理的Sun-Sky模型表示等。其中精度最高、使用比较广泛的是HDR全景图像，而在实时渲染领域使用较多的是光照的SH表示。基于物理的光照模型则多用于室外场景。

光照估计作为计算机图形学和计算机视觉的基础问题之一，有着广泛的实际应用场景。例如：基于图像的渲染（Image Based Rendering, IBR）、增强现实（Augmented Reality, AR）、电影后期制作、真实感虚实交互等。图1.1展示了光照估计的应用之一。光照估计也与这两个学科中的许多其它问题息息相关。例如：双向反射分布函数（BRDF）估计、场景几何重构、本征信息提取、图像增强，等等。高质量的光照估计结果通常能够为这些问题的解决带来很大的帮助。



图 1.1 光照估计的应用之一。使用单张图片估计场景的光照，并利用估计的光照渲染一个新的物体合成到图像中。可以看出使用估计光照渲染后的3D物体，与场景中的已有物体在视觉上较为一致。

Figure 1.1 3D rendering under the predicted illumination. visual effect of the 3D rendering is in line with the original image.

从有限的图像信息估计出整个场景的光照分布是一个复杂的问题。首先，图像的视野范围比较有限，例如一张视场角（FOV）为60°的照片所拍摄到的区域，在其对应的全景图中占比不足6%。此外，一幅图片是光照分布、场景几何结构、物体材质、摄像机参数等多个单位之间的复杂交互结果（公式 1.1）。

$$Image = ComplexInteraction(Light, Geometry, Material, Camera) \quad (1.1)$$

通过公式1.1可以看出，在其它三个信息未知的情况下，从图像（Image）反推出光照（Light）是一个严重的不适定（ill-posed）问题。不仅如此，在不同的条件下拍摄的彩色图像可能存在很多误差。例如图像中的过曝光/欠曝光区域、相机畸变、不正确的白平衡等。这些都会对光照估计造成一定程度的干扰，增加光照估计的难度。

研究者在光照估计问题上开展了一系列的研究。Debevec[1] 首次提出可以通过拍摄不同曝光下的镜面球体，来获取一张高动态范围的全景图片。 *Related limited methods*. 不难看出，这些方法或依赖特殊的探针、或依赖特殊的拍摄设备、或依赖额外的辅助信息与模型假设。均具有一定的局限性。

近年来，深度学习在多种计算机视觉问题上大放异彩，用于分割、检测、标识、分类的神经网络层出不穷。一些研究者尝试将深度学习应用在光照估计问题当中。 *Related learning based methods*. 不过，目前已有的深度学习方法也有一定的局限性。训练一个鲁棒的神经网络往往需要大量的数据，而目前用于光照估计问题的数据集比较有限，主要包括：大规模的低动态范围全景数据集（SUN360 *CITE*等）和中小规模特定场景的高动态范围全景数据集（Laval Indoor等 *CITE*）。这些数据集在规模和质量上很难同时到达训练深度神经网络的要求。

在这样的背景下，本文在光照估计的两个方向开展研究。其一是构建一个具有一定规模和质量光照估计的数据集。这样的数据集不仅能被用来训练更加鲁棒的光照估计网络，也可以被应用到其它多种相关的深度学习问题当中。其二是在已有数据集和本文构建的数据集基础上，深入探索基于深度学习的光照估计方法，对其中的网络结构，网络参数，损失函数，光照表示等多个模块进行细致的对比和研究。

1.2 国内外研究现状

1.2.1 光照的表示

光照的表示对光照估计问题至关重要。场景的光照分布有着多种多样的表示方法。其中高动态范围（High Dynamic Range，简称HDR）全景图是一种被广泛使用而且精度较高的光照表示方式。与普通的8位三通道图像不同，HDR图像的颜色值范围可以从0取到非常大。这意味着HDR图像可以更细致地表示每个像素位置的真实亮度值。因此无论是HDR全景图表示的光照，还是使用其渲染的物体，都能更接近真实值。Reinhard等人在 *High Dynamic Range Imaging*[2]中

对HDR图像进行了详细的介绍。

研究者们也提出了一些小巧、高效的光照近似模型，代价是牺牲一部分精度。Ramamoorthi和Hanrahan[3]提出使用球形谐波函数来表示场景的光照。这种方法表示的光照，不仅参数规模较小，而且其在渲染物体时非常高效。他在文章中指出，该模型仅使用9个系数时，在漫反射物体上渲染结果的平均误差也不超过1%。不过由于球形谐波函数本身的特性，这种方式不能很好的保留光照分布的高频细节。尽管如此，它的简洁和高效使得它成为实时渲染中的重要方式之一[4, 5]。许多光照估计方法中采用了这种模型来表示场景的光照分布。图1.2展示了不同的几种光照表示示例。



图 1.2 几种不同的光照表示模型对比

Figure 1.2 Comparison of different representations of illumination

在室外场景中，光线的主要来源是太阳光、光在空气中的散射折射、以及光在地面的反射。因此基于物理的光照表示模型更加适合表示室外场景。Richard等人[6]提出一个参数化的物理模型来表示天空中的发光度（Luminance）分布。之后的许多工作 [7–10] 考虑了空气散射和折射、大气浑浊度的影响，将该模型扩展为多种不同类型颜色模型。Hosek和Wilkie[11, 12]基于这些工作，考虑并加入了多种因素，整理出一个可调节太阳位置、大气浑浊度、地面反照率的物理参数模型。这类模型的参数量较小，精度也很可观，因此成为室外场景光照估计问题中常用的光照表示方法。

光照分布也有很多其它的表示方式。Ng等人[13]提出使用小波函数来近似光照分布。LeGendre等人[14]提出了一个实用的框架，能够使用LED灯台精确地重构出各个方向的场景光照。近期Weber[15]结合深度学习，使用自编码器（auto-encoder）对光照分布进行建模，为光照估计问题提供了新的思路。

1.2.2 使用光探测物估计光照

光照估计是一个复杂的问题，研究者们常常采用多种方法的组合来解决这个问题。使用光探测物（light probe）来估计光照就是这些方法之一。常见的光照探测物包括：镜面球体，漫反射球体，镜面反射/漫反射混合球体，人眼，人脸等等。Debevec[1]建立了一个基于光照模型的虚拟物体插入系统。其中所涉

及光照的就是使用镜面反射球体作为光探测物来估计的。该工作首次提出可以通过拍摄不同曝光下的镜面球体，来获取一张高动态范围的全景图片。在之后的工作中，Reinhard等人[2]和Debevec等人[16]指出，使用一个漫反射球体，或者漫反射与镜面反射表面混合的球体，也可以达到同样的效果。值得一提的是，Debevec在其工作[1]中，将远距离场景、近距离场景、以及待插入的虚拟物体分离开，并假设插入的虚拟物体并不会造成远距离场景的变化。之后的虚拟物体插入、增强现实等工作都遵从了这个假设。

上述的光探测物大多是已知物体几何和表面材质、且预先放置在场景中的规则物体。还有一些特殊的“物体”也可以作为光探测物。例如人的眼球，人脸，人手等常出现照片中的元素。Tsumra等人[17]在假设人眼是规则球体的前提下，利用眼球上光线的反射，估计场景的光照。Nishino和Nayar[18]分析了眼球的大致结构，并利用包含眼球的照片估计场景的光照分布。不过该方法需要分辨率和清晰度较高的相机，而且其文中也指出该方法没有考虑瞳孔颜色、虹膜颜色等因素。而这些因素都会对光照估计产生较大影响。人脸作为照片中经常出现的物体，也经常被用作光探测物。Wen等人[19]通过一张人脸照片，估计出光照的SH表示进而对人脸实现重照（relight）Wang等人[20]提出一种基于马尔科夫随机场的能量最小化框架，意图从正脸照片中恢复出人脸的形状、反射率和光照。在之后的工作中Shim[21]、Knorr等人[22]、Shahlaei和Blanz[23]探索了如何从人脸照片中估计较为精确的光照。Yao等人[24]使用普通相机和深度相机下的人体手部图像，通过人手的亮度和法线，估计出由若干个球形谐波系数近似的低频光照。

可以看出，这类估计光照的方法都需要一个已知其类型、几何、材质的光探测物存在于场景内。无论是规则的球体，还是人的各个部位，它们都需要照片中包含指定的物体和元素。而在大多数的光照估计问题中，很难保证这些标志物或探测物一定存在，这无疑限制了此类方法的应用。

1.2.3 使用特定设备估计光照

降低光照估计问题难度的另一个思路是使用特定的设备、装置、应用。Pilet等人[25]使用多个不同位置的相机和一个平面标定物构建了一个3D估计系统。通过追踪该平面标定物并计算其中的高光和阴影，估计出场景中的几何和光照。Yoo和Lee[26]提出了一个由鱼眼镜头、中性衰减片（Neural Density Filter, ND）和普通相机构成的光照探测系统。他们通过鱼眼镜头获取一个半球面，使用ND片直接感知明亮区域，并通过一系列算法实时地估计场景中的光

照。Cossairt[27]等人使用一组透镜、光场相机、光场映射器，构建了一个适合单光源较暗场景下的光照估计系统。随后Imai等人[28]使用多光谱成像设备，探究了可变亮度阈值、色调、偏振滤镜在检测光照条件较为复杂的场景下的高光分布。提出了适用于偏高光反射物体上的光照估计方法。Tocci等人[29]构建了一个光学设备，用以获取影视级别的高动态范围视频。Manakov等人[30]提供了一个插件类型的相机硬件，用以与高动态范围图像，多光谱、偏振和光场等相关的应用。Cailian等人[31]使用一个阴影探测器，来解决实时增强现实中的光照估计问题。Kán和Peter[32]通过全景图像拼接技术，建立了一个在智能相机中用于捕捉高动态范围全景图的应用。

不过，通过这些使用特殊设备或者特定应用获取场景光照的方法并不是严格意义上的光照估计。他们其实是倾向于解决快速获取高动态范围图像或视频的工程问题。图1.3展示了上述的一些的光照估计系统的使用情景，可以看出，



图 1.3 几种使用特殊设备估计场景光照的系统

Figure 1.3 Illumination estimation system using specific devices.

这种光照估计方法所需的设备通常比较复杂。虽然在实验室环境中能够有效运行，但是这些设备的类型和数量无疑提高了这种方法的应用门槛。

1.2.4 使用额外信息估计光照

从单张图片恢复或估计出整个场景的光照分布是个复杂的问题。大部分的光照估计方法考虑借用额外的信息来辅助估计光照。例如，深度图像信息、场景几何形状、物体几何结构等。

深度信息对于光照估计问题有着很大的帮助。Knecht等人[33]借助深度相机和鱼镜头重建场景模型并提取了光源位置。Meilland等人[34]利用深度相机实时地创建稠密的高动态范围全景图，并使用K-means算法从环境贴图中提取点光源位置。Barron和Mailk[35]提出了一种从彩色图像和深度图像中提取本征信息的方法。他们使用具有噪声的深度图像来辅助估计场景的几何结构，并在这些信息的基础上进一步提取彩色图像中的本征信息。Zhang等人[36]使用RGBD相机，将拍摄到的室内场景建模为一个包含光源、材质和几何的没有杂物的房间模型。并提供了对该模型进行场景编辑的方法。

在已知场景或物体几何结构的情况下估计光照的分布也是主要的研究方向之一。例如，在形状类似桌子、平台、平板等结构的场景中，Li等人[37]的方法可以结合图片中的阴影、明暗、高光信息估计出多个方向的光源信息。Ramamoorthi和Hanrahan[38]使用物体的几何结构和多个视角下的照片作为输入，估计出照片中物体的表面材质并进一步计算所在场景的静态光照信息。不过该方法需要多种假设——曲线表面、各向同性BRDF、没有多重反射等。Sato等人[39]指出通过物体遮挡关系估计场景光照的有效性。他们通过分析给定几何的物体上的明亮区域和阴影区域，估计出较为真实的场景光照。在给定朗伯体（Lambertian）反射的物体几何时，Wang和Samaras[40]的方法可以从单张图片估计出多个方向的光照信息。Panagopoulos等人[41]提出了一个新的框架，来从单幅图片和粗糙的3D几何中，恢复出光照环境和估计场景中的投影阴影。该方法描述了一个高阶马尔可夫随机场（MRF）照明模型。该模型将低阶阴影证据与高阶先验知识相结合，用于投影阴影和照明环境的联合估计。

此外还有一些方法在已知物体类型的情况下，利用图片中物体的先验或者假设知识来帮助估计光照。例如前文提到的Nishino和Nayar[18]假设人的眼球是规则的球体，并基于此假设从人眼估计场景的光照。类似的方法[42–44]虽然不需要预先知道精确的场景几何结构，但都要通过图像中物体的类型得到一些先验知识假设和约束。进而分析、预测、估计、恢复出场景光照。

增加彩色图片的数量也会对光照估计有很大帮助。Sato等人[45]使用两张全方位的照片构建出场景的大致几何，然后根据不同快门速度拍摄的全方向图像序列计算场景的辐射度，并将其映射到构建的几何模型上。这个映射到几何上的辐照度分布就可以作为光照来渲染新的3D物体。Nishino等人[46, 47]在已知物体的大致几何的情况下，分别对发光体和普通物体拍摄多张图片来估计场景光照。Yu等人[48]则通过多视角图片来恢复出固定光照条件下的物体纹理和光照分布。Shan等人[49]在解决重构场景的问题时，提出了一种从大规模不同光照条件图片集中估计结点反照率和光照参数的方法。受到该方法的启发，Lalonde和Matthews[50]在同一个室外建筑物的不同图片中恢复出每幅图片对应的光照条件。

需要注意的是，以上几种增加辅助信息的方式并不是互斥的，研究者们可以选择使用多种额外信息共同辅助估计光照。例如Marschner[51]在已知物体几何的前提下，使用一组照片估计出物体表面的反射情况，进而估计出场景光照信息。Haber等人[52]利用一个物体在多个角度下的图片和已知几何结构估计其

光照分布。使用一种或多种额外的信息来辅助光照估计一直是解决光照估计问题的主要方法，也是能够提升光照估计的效果的主要方式。但是此类方法通常需要使用额外的输入设备（例如深度相机），繁琐的获取步骤（例如多次拍摄），以及一些先验知识。而且使用的额外信息越多，所需的设备就越多，步骤就越繁琐，这难免限制了它们的应用场景。

1.2.5 使用简化的光照模型

光照估计是一个已知条件较少，求解结果较大，涉及因素复杂的问题。除了使用额外的设备，增加输入信息的方法外，降低该问题难度的另一个思路是简化光照的表示。从图片中恢复一整张高动态范围全景图是比较困难的。

1.2.6 基于图像分析估计光照

1.2.7 用户交互辅助估计光照

1.2.8 反向渲染过程

1.2.9 光照估计相关数据集

1.2.10 利用深度学习工具估计光照

深度学习与光照估计的结合是主流趋势之一。

第2章 光照估计数据集

2.1 引言

2.2 高动态范围全景图像

2.2.1 全景图像

2.2.2 高动态范围全景图像

2.2.3 拍摄与合成

2.3 光照估计数据集

2.4 讨论

2.5 本章小结

第3章 基于深度学习的光照估计方法

- 3.1 引言
- 3.2 相关工作
- 3.3 问题求解范围
- 3.4 光照分布的球形谐波表示
- 3.5 卷积神经网络结构
- 3.6 损失函数
- 3.7 实验结果与评估
- 3.8 深入研究光照估计网络
- 3.9 讨论
- 3.10 本章小结

第4章 光照估计的应用

- 4.1 引言
- 4.2 电脑端应用
- 4.3 移动端应用
- 4.4 本章小结

第5章 总结与展望

5.1 本文工作总结

5.2 未来工作展望

附录 A 附录

参考文献

- [1] DEBEVEC P. Rendering synthetic objects into real scenes: bridging traditional and image-based graphics with global illumination and high dynamic range photography[C]//Proceedings of the 25th annual conference on Computer graphics and interactive techniques. ACM, 1998: 189-198.
- [2] REINHARD E, WARD G, PATTANAIK S, et al. High dynamic range imaging: Acquisition, display, and image-based lighting[M]. Elsevier, 2005.
- [3] RAMAMOORTHI R, HANRAHAN P. An efficient representation for irradiance environment maps[C]//Proceedings of the 28th annual conference on Computer graphics and interactive techniques. ACM, 2001: 497-500.
- [4] GREEN R. Spherical harmonic lighting: The gritty details[C]//Archives of the Game Developers Conference: volume 56. 2003: 4.
- [5] SLOAN P P. Stupid spherical harmonics (sh) tricks[C]//Game developers conference: volume 9. 2008: 42.
- [6] PEREZ R, SEALS R, MICHALSKY J. All-weather model for sky luminance distribution—preliminary configuration and validation[J]. Solar energy, 1993, 50(3):235-245.
- [7] NISHITA T, DOBASHI Y, NAKAMAE E. Display of clouds taking into account multiple anisotropic scattering and sky light[C]//Proceedings of the 23rd annual conference on Computer graphics and interactive techniques. ACM, 1996: 379-386.
- [8] SIRAI T N T, NAKAMAE K T E. Display of the earth taking into account atmospheric scattering[C]//Siggraph: volume 93. Citeseer, 1993: 175.
- [9] PREETHAM S. A practical analytic model for daylight[J]. 1999.
- [10] RAAB M, SEIBERT D, KELLER A. Unbiased global illumination with participating media [M]//Monte Carlo and Quasi-Monte Carlo Methods 2006. Springer, 2008: 591-605.
- [11] HOSEK L, WILKIE A. An analytic model for full spectral sky-dome radiance[J]. ACM Transactions on Graphics (TOG), 2012, 31(4):95.
- [12] HOŠEKHOŠEK L, WILKIE A. Adding a solar-radiance function to the hošek-wilkie skylight model[J]. IEEE computer graphics and applications, 2013, 33(3):44-52.
- [13] NG R, RAMAMOORTHI R, HANRAHAN P. All-frequency shadows using non-linear wavelet lighting approximation[C]//ACM Transactions on Graphics (TOG): volume 22. ACM, 2003: 376-381.
- [14] LEGENDRE C, YU X, LIU D, et al. Practical multispectral lighting reproduction[J]. ACM Transactions on Graphics (TOG), 2016, 35(4):32.
- [15] WEBER H, PRÉVOST D, LALONDE J F. Learning to estimate indoor lighting from 3d objects[C]//2018 International Conference on 3D Vision (3DV). IEEE, 2018: 199-207.

- [16] DEBEVEC P, GRAHAM P, BUSCH J, et al. A single-shot light probe[C]//ACM SIGGRAPH 2012 Talks. ACM, 2012: 10.
- [17] TSUMURA N, DANG M N, MAKINO T, et al. Estimating the directions to light sources using images of eye for reconstructing 3d human face[C]//Color and Imaging Conference: volume 2003. Society for Imaging Science and Technology, 2003: 77-81.
- [18] NISHINO K, NAYAR S K. Eyes for relighting[J]. ACM Transactions on Graphics (TOG), 2004, 23(3):704-711.
- [19] WEN Z, LIU Z, HUANG T S. Face relighting with radiance environment maps[C]//2003 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2003. Proceedings.: volume 2. IEEE, 2003: II-158.
- [20] WANG Y, LIU Z, HUA G, et al. Face re-lighting from a single image under harsh lighting conditions[C]//2007 IEEE Conference on Computer Vision and Pattern Recognition. IEEE, 2007: 1-8.
- [21] SHIM H. Faces as light probes for relighting[J]. Optical Engineering, 2012, 51(7):077002.
- [22] KNORR S B, KURZ D. Real-time illumination estimation from faces for coherent rendering [C]//2014 IEEE International Symposium on Mixed and Augmented Reality (ISMAR). IEEE, 2014: 113-122.
- [23] SHAHLAEI D, BLANZ V. Realistic inverse lighting from a single 2d image of a face, taken under unknown and complex lighting[C]//2015 11th IEEE international conference and workshops on automatic face and gesture recognition (FG): volume 1. IEEE, 2015: 1-8.
- [24] YAO Y, KAWAMURA H, KOJIMA A. The hand as a shading probe[C]//ACM SIGGRAPH 2013 Posters. ACM, 2013: 108.
- [25] PILET J, GEIGER A, LAGGER P, et al. An all-in-one solution to geometric and photometric calibration[C]//2006 IEEE/ACM International Symposium on Mixed and Augmented Reality. IEEE, 2006: 69-78.
- [26] YOO J D, LEE K H. Real time light source estimation using a fish-eye lens with nd filters[C]// 2008 International Symposium on Ubiquitous Virtual Reality. IEEE, 2008: 41-42.
- [27] COSSAIRT O, NAYAR S, RAMAMOORTHY R. Light field transfer: global illumination between real and synthetic objects[C]//ACM Transactions on Graphics (TOG): volume 27. ACM, 2008: 57.
- [28] IMAI Y, KATO Y, KADOI H, et al. Estimation of multiple illuminants based on specular highlight detection[C]//International Workshop on Computational Color Imaging. Springer, 2011: 85-98.
- [29] TOCCI M D, KISER C, TOCCI N, et al. A versatile hdr video production system[C]//ACM Transactions on Graphics (TOG): volume 30. ACM, 2011: 41.
- [30] MANAKOV A, RESTREPO J, KLEHM O, et al. A reconfigurable camera add-on for high dynamic range, multispectral, polarization, and light-field imaging[J]. ACM Transactions on Graphics, 2013, 32(4):47-1.

- [31] CALIAN D A, MITCHELL K, NOWROUZEZAHRAI D, et al. The shading probe: Fast appearance acquisition for mobile ar[C]//SIGGRAPH Asia 2013 Technical Briefs. ACM, 2013: 20.
- [32] KÁN P. Interactive hdr environment map capturing on mobile devices.[C]//Eurographics (Short Papers). 2015: 29-32.
- [33] KNECHT M, TRAXLER C, MATTAUSCH O, et al. Reciprocal shading for mixed reality[J]. Computers & Graphics, 2012, 36(7):846-856.
- [34] MEILLAND M, BARAT C, COMPORT A. 3d high dynamic range dense visual slam and its application to real-time object re-lighting[C]//2013 IEEE International Symposium on Mixed and Augmented Reality (ISMAR). IEEE, 2013: 143-152.
- [35] BARRON J T, MALIK J. Intrinsic scene properties from a single rgb-d image[C]//Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition. 2013: 17-24.
- [36] ZHANG E, COHEN M F, CURLESS B. Emptying, refurnishing, and relighting indoor spaces [J]. ACM Transactions on Graphics (TOG), 2016, 35(6):174.
- [37] LI Y, LU H, SHUM H Y, et al. Multiple-cue illumination estimation in textured scenes[C]//Proceedings Ninth IEEE International Conference on Computer Vision. IEEE, 2003: 1366-1373.
- [38] RAMAMOORTHY R, HANRAHAN P. A signal-processing framework for inverse rendering [C]//Proceedings of the 28th annual conference on Computer graphics and interactive techniques. ACM, 2001: 117-128.
- [39] SATO I, SATO Y, IKEUCHI K. Illumination from shadows[J]. IEEE Transactions on Pattern Analysis and Machine Intelligence, 2003, 25(3):290-300.
- [40] WANG Y, SAMARAS D. Estimation of multiple illuminants from a single image of arbitrary known geometry[C]//European conference on computer vision. Springer, 2002: 272-288.
- [41] Panagopoulos A, Wang C, Samaras D, et al. Illumination estimation and cast shadow detection through a higher-order graphical model[C/OL]//CVPR 2011. 2011: 673-680. DOI: [10.1109/CVPR.2011.5995585](https://doi.org/10.1109/CVPR.2011.5995585).
- [42] BARRON J T, MALIK J. Shape, illumination, and reflectance from shading[J]. IEEE transactions on pattern analysis and machine intelligence, 2015, 37(8):1670-1687.
- [43] LOPEZ-MORENO J, HADAP S, REINHARD E, et al. Compositing images through light source detection[J]. Computers & Graphics, 2010, 34(6):698-707.
- [44] REMATAS K, RITSCHER T, FRITZ M, et al. Deep reflectance maps[C]//Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition. 2016: 4508-4516.
- [45] SATO I, SATO Y, IKEUCHI K. Acquiring a radiance distribution to superimpose virtual objects onto a real scene[J]. IEEE transactions on visualization and computer graphics, 1999, 5(1):1-12.
- [46] NISHINO K, ZHANG Z, IKEUCHI K. Determining reflectance parameters and illumination distribution from a sparse set of images for view-dependent image synthesis[C]//Proceedings

- Eighth IEEE international conference on computer vision. ICCV 2001: volume 1. IEEE, 2001: 599-606.
- [47] NISHINO K, IKEUCHI K, ZHANG Z. Re-rendering from a sparse set of images[J]. Department of Computer Science, Drexel University, 2005.
- [48] YU T, WANG H, AHUJA N, et al. Sparse lumigraph relighting by illumination and reflectance estimation from multi-view images[C]//ACM SIGGRAPH 2006 Sketches. ACM, 2006: 175.
- [49] SHAN Q, ADAMS R, CURLESS B, et al. The visual turing test for scene reconstruction[C]//2013 International Conference on 3D Vision-3DV 2013. IEEE, 2013: 25-32.
- [50] LALONDE J F, MATTHEWS I. Lighting estimation in outdoor image collections[C]//2014 2nd International Conference on 3D Vision: volume 1. IEEE, 2014: 131-138.
- [51] MARSCHNER S R, GREENBERG D P. Inverse lighting for photography[C]//Color and Imaging Conference: volume 1997. Society for Imaging Science and Technology, 1997: 262-265.
- [52] HABER T, FUCHS C, BEKAER P, et al. Relighting objects from image collections[C]//2009 IEEE Conference on Computer Vision and Pattern Recognition. IEEE, 2009: 627-634.

作者简历及攻读学位期间发表的学术论文与研究成果

作者简历

作者基本情况

程大川，男，汉族人，1994年11月11日生，山东菏泽人

2012年2月–2016年6月 山东科技大学信息学院软件工程工学学士

2016年9月–2019年6月 中国科学院大学软件研究所计算机应用技术工学硕士

联系方式

通讯地址：北京市海淀区中关村南四街4号中国科学院软件研究所

计算机科学国家重点实验室

邮政编码：100190

电子邮箱：chengdc@ios.ac.cn

已发表(或正式接受)的学术论文:

[1] Cheng, Dachuan, Jian Shi, Yanyun Chen, Xiaoming Deng, and Xiaopeng Zhang. "Learning Scene Illumination by Pairwise Photos from Rear and Front Mobile Cameras." In Computer Graphics Forum, vol. 37, no. 7, pp. 213-221. 2018.

致 谢

致谢

