TOPIC 7 | ASSESSMENT EVIDENCE

Working with Webhooks and Event-Driven APIs

Evidence compiled from actual n8n and Postman screenshots shared during testing on 30 October 2026.

Implementation summary

Postman POST request → n8n Webhook (receive-leads) → Extract Lead Details. Fixed-secret Header Auth protects the endpoint; the Edit Fields node maps leadId, name, email and receivedAt.

Test results

Test	Observed evidence	Result
Test webhook	Incoming JSON payload visible in n8n	PASS
Authorized request	200 OK returned by Postman	PASS
Lead extraction	Four mapped fields populated	PASS
Unauthorized request	403 Forbidden when signature header unchecked	PASS
Production endpoint	200 OK; workflow was started	PASS
Workflow nodes	Webhook and Edit Fields green, 1 item	PASS

Evidence gallery

Sensitive authentication values are masked in the following images. The screenshots show observed test results, not a cryptographic HMAC verification.




Figure 1. Test webhook received the incoming JSON lead payload.




Figure 2. Extract Lead Details maps lead fields and timestamp.




Figure 3. Missing authentication header rejected with HTTP 403.




Figure 4. Authenticated production POST returned HTTP 200.




Figure 5. Both n8n workflow nodes completed successfully.

Assessment scope and caveats

Verified: POST webhook receipt, successful fixed-header authentication, rejected missing-header request, lead mapping, production endpoint HTTP 200, and successful two-node execution.

Not verified: HMAC-SHA256 signature calculation/comparison. The final canvas image does not show the execution mode, so it is not by itself proof of a production-mode execution.

Security action: Rotate the previously exposed header secret. Use a new private credential for any further testing or deployment.