



# *Murshidabad College of Engineering & Technology*

*Project Report on*  
*Traffic Monitoring System using  
Python-OpenCV & YOLOv8*

*Submitted by*  
*Debjyoti Talukder*  
*Sukanya Saha | Surojit Barman |*  
*Kazi Nasrin Akhtar*

*In partial fulfillment of the degree*

*Bachelor of Technology*  
*In*  
*Computer Science & Engineering*

*Nov, 2023*

# Traffic Monitoring System using Python-OpenCV and YOLOv8



Murshidabad College of  
Engineering and Technology

Under guidance of Prof. Anindya Bakshi

(HOD, CSE Dept.)

## Group Member

Debajyoti Talukder

Sukanya Saha | Surojit Barman |

Kazi Nasrin Akhtar



# Traffic Monitoring System using Python-OpenCV and YOLOv8

[https://github.com/DebajyotiTalukder2001/  
Traffic-Monitoring-System](https://github.com/DebajyotiTalukder2001/Traffic-Monitoring-System)



**MURSHIDABAD COLLEGE OF ENGINEERING &  
TECHNOLOGY**

Under guidance of **Prof. Anindya Bakshi**  
**(HOD, CSE Dept.)**

## Group Member

**Debajyoti Talukder**

**Sukanya Saha | Surojit Barman |  
Kazi Nasrin Akhtar**

# Acknowledgement

---

I would like to express my profound gratitude and thanks to **Prof. Anindya Bakshi, HOD, Department of Computer Science and Engineering (CSE), Murshidabad College of Engineering and Technology**, for the intellectual support, inspiring guidance, and his invaluable encouragement, suggestions, and cooperation that helped a lot to complete our project successfully.

**Debajyoti Talukder (10600120012)**  
**Sukanya Saha (10600120016)**  
**Surojit Barman (10600121059)**  
**Kazi Nasrin Akhtar (10600120017)**  
**Dept. Computer Science & Engineering**  
**Semester: 7<sup>th</sup>**  
**Year: 4<sup>th</sup> (2023-24)**





# Murshidabad College of Engineering & Technology

Banjetia, Berhampore, PO. CossimBazar-Raj, Dist. Murshidabad, West Bengal, Pin-742102

<https://www.mcetbhb.net/>

Date .....

## Certification

This is to certify that the project entitled "**Traffic Monitoring System using Python-OpenCV & YOLOv8**" submitted by **Debajyoti Talukder, Sukanya Saha, Surojit Barman, and Kazi Nasrin Akhtar**, who are the students of **Murshidabad College of Engineering & Technology, Berhampore, W.B.**, in partial fulfilment of the degree of **Bachelor of Technology in Computer Science and Engineering**, was carried out under my guidance and supervision.

They have completed the total parameters and requirements of the entire project.

The work undertaken in this dissertation is the result of their own efforts. The result embodied in this dissertation has not been submitted for any other degree and does not form a part of any other course undergone by them.

---

Signature of **Project Guide**

**Prof. Anindya Bakshi**

(HOD, CSE Dept.)

---

Signature of **HOD**

**Prof. Anindya Bakshi**

(CSE Dept.)

# Table of Contents

<b>S No.</b>	<b>Content</b>	<b>Page No.</b>
1	Title Page	1
2	Acknowledgement	2
3	Certification	3
4	Table of Contents	4
5	Project Objective	5
6	Basic Information & Theory	6
7	Design & Diagram	18
8	Project Initialization	19
9	Source Code	50
10	Output/Sample Screenshots	63
11	Experimental Results	72
12	Summary	77
13	Future Scope	80
14	Bibliography	80




ESTD : 1998

# Project Objective

**Title:** “Traffic Monitoring System using Python-OpenCV and YOLOv8”

Main objective and goal of this project is to create a **Traffic Monitoring System using Python-OpenCV and YOLOv8**, which will be able to:

1. Detect, track, and count vehicles.
2. Detect vehicle speed.
3. Detect vehicle speed limit violations.




## Basic Information & Theory

It is a Traffic Monitoring System using Python-OpenCV and YOLOv8 which will be able to:


1. Detect, track, and count vehicles.
2. Detect vehicle speed.
3. Detect vehicle speed limit violations.

<https://github.com/DebajyotiTalukder2001/Traffic-Monitoring-System>



## Artificial Intelligence

Science that empowers computers to mimic human intelligence such as decision making, text processing, and visual perception. AI is a broader field (i.e., the big umbrella that contains several subfields such as machine learning, robotics, and computer vision).




## Machine Learning

Machine Learning is a subfield of Artificial Intelligence that enables machines to improve at a given task with experience. It is important to note that all machine learning techniques are classified as Artificial Intelligence ones. However, not all Artificial Intelligence could count as Machine Learning since basic Rule-based engines could be classified as AI but they do not learn from experience therefore they do not belong to the machine learning category.

Machine learning algorithms are often categorized as supervised, unsupervised and reinforcement.

- **Supervised machine learning algorithms** can apply what has been learned in the past to new data using labelled examples to predict future events. Starting from the analysis of a known training dataset, the learning algorithm produces an inferred function to make predictions about the output values. The system is able to provide targets for any new input after sufficient training. The learning algorithm can also compare its output with the correct, intended output and find errors in order to modify the model accordingly.
- In contrast, **unsupervised machine learning algorithms** are used when the information used to train is neither classified nor labelled. Unsupervised learning studies how systems can infer a function to describe a hidden structure from unlabelled data. The system doesn't figure out the right output, but it explores the data and can draw inferences from datasets to describe hidden structures from unlabelled data.
- **Reinforcement machine learning algorithms** is a learning method that interacts with its environment by producing actions and discovers errors or rewards. Trial and error search and delayed reward are the most relevant characteristics of reinforcement learning. This method allows machines and software agents to automatically determine the ideal behaviour within a specific context in order to maximize its performance. Simple reward feedback is required for the agent to learn which action is best; this is known as the reinforcement signal.




## Deep Learning

Deep Learning is a specialized field of Machine Learning that relies on training of Deep Artificial Neural Networks (ANNs) using a large dataset such as images or texts. ANNs are information processing models inspired by the human brain. The human brain consists of billions of neurons that communicate to each other using electrical and chemical signals and enable humans to see, feel, and make decisions. ANNs work by mathematically mimicking the human brain and connecting multiple “artificial” neurons in a multilayered fashion. The more hidden layers



added to the network, the deeper the network gets. What differentiates deep learning from machine learning techniques are in their ability to extract feature automatically as illustrated in the following example:

- **Machine learning process:** (1) selecting the model to train, (2) manually performing feature extraction.
- **Deep Learning Process:** (1) select architecture of the network, (2) features are automatically extracted by feeding in the training data (such as images) along with the target class (label).



## Convolutional Neural Network (CNN)


- Convolutional Neural Networks (CNN) is the most successful Deep Learning method used to process multiple arrays, e.g., 1D for signals, 2D for images and 3D for videos.
- CNN consists of a list of Neural Network layers that transform the input data into an output (class/prediction)
- Development of specialized CNN chips (by NVIDIA, Intel, Samsung etc.) for real-time applications in smartphones, cameras, robots, self-driving cars, etc.

The convolutional layer is the core building block of a CNN, and it is where the majority of computation occurs. It requires a few components, which are input data, a filter, and a feature map. Let's assume that the input will be a color image, which is made up of a matrix of pixels in 3D. This means that the input will have three dimensions—a height, width, and depth—which correspond to RGB in an image. We also have a feature detector, also known as a kernel or a filter, which will move across the receptive fields of the image, checking if the feature is present. This process is known as a convolution.

The feature detector is a two-dimensional (2-D) array of weights, which represents part of the image. While they can vary in size, the filter size is typically a 3x3 matrix; this also determines the size of the receptive field. The filter is then applied to an area of the image, and a dot product is calculated between the input pixels and the filter. This dot product is then fed into an output array. Afterwards, the filter shifts by a stride, repeating the process until the kernel has swept across the entire image. The final output from the series of dot products from the input and the filter is known as a



feature map, activation map, or a convolved feature.



## Training, Validation and Testing


### - The Training Set

It is the set of data that is used to train and make the model learn the hidden features/patterns in the data.

In each epoch, the same training data is fed to the neural network repeatedly, and the model continues to learn the features of the data.

The Training set should have a diversified set of inputs so that the model is trained in all scenarios and can predict any unseen data sample that may appear in the future.

## Training Data/ Validation/ Test



### - The Validation Set

The validation set is a set of data, separate from the training set, that is used to validate our model performance during training. This validation process gives information that helps us tune the model's hyperparameters and configurations accordingly. It is like a critic telling us whether the training is moving in the right direction or not. The model is trained on the training set and simultaneously the model evaluation is performed on the validation set after every epoch.

The main idea of splitting the dataset into a validation set is to prevent our model from overfitting. I.e., the model becomes really good at classifying the samples in the training set but cannot generalize and make accurate classification on the data it has not seen before.

### - The Testing Set

The test set is a separate set of data used to test the model after completing the training. It provides an unbiased final model performance metric in terms of accuracy, precision, etc. To put it simply, it answers the question of "*How well does the model perform?*"

## YOLOv8 Architecture:

Technically speaking, **YOLOv8** is a group of convolutional neural network models, created and trained using the **PyTorch** framework. **YOLOv8** is the latest version of YOLO by **Ultralytics**. As a cutting-edge, state-of-the-art (SOTA) model, YOLOv8 builds on the success of previous versions, introducing new features and improvements for enhanced performance, flexibility, and efficiency. YOLOv8 supports a full range of vision AI tasks, including **detection**, **segmentation**, **pose estimation**, **tracking**, and **classification**. This versatility allows users to leverage YOLOv8's capabilities across diverse applications and domains.

**YOLOv8** is the latest family of YOLO based Object Detection models from **Ultralytics** providing state-of-the-art performance. Leveraging the previous YOLO versions, the YOLOv8 model is faster and more accurate while providing a unified framework for training models for performing Object Detection, Instance Segmentation, and Image Classification.




## Models Available in YOLOv8:

There are five models in each category of YOLOv8 models for detection, segmentation, and classification. YOLOv8 Nano is the fastest and smallest, while YOLOv8 Extra Large (YOLOv8x) is the most accurate yet the slowest among them.

YOLOv8 comes bundled with the following pre-trained models:

- **Object Detection** checkpoints trained on the COCO detection dataset with an image resolution of 640.
- **Instance segmentation** checkpoints trained on the COCO segmentation dataset with an image resolution of 640.
- **Image classification** models pretrained on the ImageNet dataset with an image resolution of 224.



**The Architecture.** Our detection network has 24 convolutional layers followed by 2 fully connected layers. Alternating  $1 \times 1$  convolutional layers reduce the features space from preceding layers. We pretrain the convolutional layers on the ImageNet classification task at half the resolution ( $224 \times 224$  input image) and then double the resolution for detection.

- YOLO is a single-shot detector that uses a fully convolutional neural network (CNN) to process an image. You Only Look Once (YOLO) proposes using an end-to-end neural network that makes predictions of bounding boxes and class probabilities all at once. It differs from the approach taken by previous object detection algorithms, which repurposed classifiers to perform detection.

Following a fundamentally different approach to object detection, YOLO achieved state-of-the-art results, beating other real-time object detection algorithms by a large margin. While algorithms like Faster RCNN work by detecting possible regions of interest using the Region Proposal Network and then performing recognition on those regions separately, YOLO performs all of its predictions with the help of a single fully connected layer.


## How does YOLO work? YOLO Architecture

The **YOLO algorithm** takes an image as input and then uses a simple deep convolutional neural network to detect objects in the image. The architecture of the CNN model that forms the backbone of YOLO is shown below.

- YOLOv8 utilizes a convolutional neural network that can be divided into two main parts: the backbone and the head.
- The head of YOLOv8 consists of multiple convolutional layers followed by a series of fully connected layers. These layers are responsible for predicting bounding boxes, objectness scores, and class probabilities for the objects detected in an image.



Overall, YOLOv8 is a powerful and versatile object detection algorithm that can be used in various real-world scenarios to detect and classify objects with high accuracy and speed.



### Performance Comparison of YOLOv8 vs YOLOv5

Model Size	Detection*	Segmentation*	Classification*
<b>Nano</b>	<b>+33.21%</b>	<b>+32.97%</b>	<b>+3.10%</b>
<b>Small</b>	<b>+20.05%</b>	<b>+18.62%</b>	<b>+1.12%</b>
<b>Medium</b>	<b>+10.57%</b>	<b>+10.89%</b>	<b>+0.66%</b>
<b>Large</b>	<b>+7.96%</b>	<b>+6.73%</b>	<b>0.00%</b>
<b>Xtra Large</b>	<b>+6.31%</b>	<b>+5.33%</b>	<b>-0.76%</b>

\*Image Size = 640

\*Image Size = 224

# Design & Diagram



Video Footage


**Traffic Monitoring System using Python-OpenCV & YOLOv8**




Vehicle Tracking



Vehicle Detection & Counting



Vehicle Speed Detection



## Project Initialization

### Project overview:

**Title:** “Traffic Monitoring System using Python-OpenCV and YOLOv8”

Main objective and goal of this project is to create a **Traffic Monitoring System using Python-OpenCV and YOLOv8** which will be able to:

1. Detect, track, and count vehicles.
2. Detect vehicle speed.
3. Detect vehicle speed limit violations.

Technically speaking, **YOLOv8** is a group of convolutional neural network models created and trained using the **PyTorch** framework. YOLO (You Only Look Once) is one of the most popular object detection algorithms in the fields of Deep Learning, Machine Learning, and Computer Vision. YOLOv8 is the latest version of the YOLO (You Only Look Once) AI models developed by **Ultralytics**.

YOLOv8 is the latest family of YOLO based Object Detection models from Ultralytics providing state-of-the-art performance. Leveraging the previous YOLO versions, the YOLOv8 model is faster and more accurate while providing a unified framework for training models for performing Object Detection, Instance Segmentation, and Image Classification.



ESTD : 1998

There are five models in each category of YOLOv8 models for detection, segmentation, and classification. YOLOv8 Nano is the fastest and smallest, while YOLOv8 Extra Large (YOLOv8x) is the most accurate yet the slowest among them.

YOLOv8 comes bundled with the following pre-trained models:

- Object Detection checkpoints trained on the COCO detection dataset with an image resolution of 640.
- Instance segmentation checkpoints trained on the COCO segmentation dataset with an image resolution of 640.
- Image classification models pretrained on the ImageNet dataset with an image resolution of 224.

I have used the **YOLOv8's pre-trained model**, i.e., **yolov8n.pt**, in my project.

### **Existing system:**

The existing traffic monitoring systems typically use radar, lidar, or cameras to detect vehicles. These systems are expensive to install and maintain, and they can only detect vehicles in a limited area.

### **Proposed system:**

The proposed system is a more cost-effective and efficient way to monitor traffic. It uses **Python-OpenCV** and **YOLOv8** to detect, count and track vehicles in the video footage. The system can also detect vehicle speed and detects if a vehicle is violating the speed limit.



## Feasibility Study

The feasibility of the project is analyzed in this phase and business proposal is put forth with a very general plan for the project and some cost estimates. During system analysis the feasibility study of the proposed system is to be carried out. This is to ensure that the proposed system is not a burden to the company. For feasibility analysis, some understanding of the major requirements for the system is essential.

Three key considerations involved in feasibility study are:

- Economic Feasibility
- Technical Feasibility
- Social Feasibility

### Economic Feasibility:

This study is carried out to check the economic impact that the system will have on the organization. The amount of fund that the company can pour into the research and development of the system is limited. The expenditures must be justified.

Thus, the developed system as well within the budget and this was achieved most of the technologies used are freely available.

### Technical Feasibility:

This study is carried out to check the technical feasibility, that is, the technical requirements of the system. Any system developed must not have a high demand on the available technical resources. This will lead to high demands on the available technical resources. This will lead to high demands being placed on the client. The developed system must have a modest requirement, as only minimal or null changes are required for implementing this system.



## Social Feasibility:

The aspect of study is to check the level of acceptance of the system by the user. This includes the process of training the user to use the system efficiently. The user must not feel threatened by the system, instead must accept it as a necessity. The level of acceptance by the users solely depends on the methods that are employed to educate the user about the system and to make him familiar with it. His level of confidence must be raised so that he is also able to make some constructive criticism, which is welcomed, as he is the final user of the system.

## Hardware Requirements

- Processor: intel i5 processor
- RAM: 4GB or more
- Hard Disk: 500GB or more

## Module overview:

The system consists of the following modules:

- **Vehicle detection module:** This module uses YOLOv8 to detect vehicles in the video footage.
- **Vehicle tracking module:** This module tracks the vehicles that have been detected by the vehicle detection module.
- **Vehicle speed detection module:** This module estimates the speed of the vehicles that are being tracked.



- **Vehicle counting module:** This module counts the number of vehicles that pass through a specific area in the video footage.
- **Vehicle violation detection module:** This module detects if a vehicle is violating the speed limit.

### **Module functionalities:**

The following are the functionalities of each module:

- **Vehicle detection module:** This module uses YOLOv8 to detect vehicles in the video footage. YOLOv8 is a deep learning algorithm that can detect objects in images and videos. The algorithm is trained on a dataset of images that contain vehicles. When the algorithm is applied to a video footage, it can detect the vehicles in the video.
- **Vehicle tracking module:** This module tracks the vehicles that have been detected by the vehicle detection module. The module uses a **centroid tracking algorithm** to track the vehicles. The centroid tracking algorithm tracks the centre of mass of the vehicles in the video footage.
- **Vehicle speed detection module:** This module estimates the speed of the vehicles that are being tracked. The module uses the distance and the time interval between two frames of the video footage to estimate the speed of the vehicles.



- **Vehicle counting module:** This module counts the number of vehicles that pass through a specific area in the video footage. The module uses a region of interest (ROI) to define the specific area. The module then counts the number of vehicles that enter and exit the ROI.
- **Vehicle violation detection module:** This module detects if a vehicle is violating the speed limit. The module uses the speed of the vehicles that are being tracked to determine if they are violating the speed limit.

## Methodology:

### Technologies:

- Programming Language: Python (Version-3.11)
- Platform: Anaconda (Python Distribution) and Visual Studio Code IDE.
- Libraries: Pandas (1.5.3), NumPy (1.24.3), Python-OpenCV (4.8.0.74) & Ultralytics (8.0.147)

1. **Collect the video footage:** The video footage can be collected from a variety of sources, such as a traffic camera, a dashcam, or a security camera. The video footage should be in a format that can be read by OpenCV.





Video Footage

### Sample Video (Video Footage) Download Link:

\*\*\* (Vid1.mp4)

[https://drive.google.com/drive/folders/1giJI3IgF5XpDGtk3kN\\_e\\_teQRBJ-sY9I](https://drive.google.com/drive/folders/1giJI3IgF5XpDGtk3kN_e_teQRBJ-sY9I)

**2. Data Cleaning:** This is useful if you only want to monitor a specific area of the road. Data cleaning is the process of removing errors and inconsistencies from data. It is an important step in any data analysis project, as it can significantly improve the accuracy and reliability of the results.

In the context of traffic monitoring system, data cleaning can be used to remove the following types of errors and inconsistencies from video footage:

**Cropping:** This involves removing unwanted parts of the video, such as the edges or the sky. This can be useful for focusing on specific areas of interest, such as intersections or traffic lanes.

**Noise removal:** This involves removing unwanted noise from the video, such as camera shake or shadows. This can improve the clarity of the video and make it easier to identify objects.

**Brightness and contrast adjustment:** This involves adjusting the brightness and contrast of the video to improve the visibility of objects.

**Denoising:** This involves removing noise from the video, such as compression artifacts or Gaussian noise. This can improve the quality of the video and make it easier to identify objects.

**Segmentation:** This involves dividing the video into different segments, such as frames or objects. This can be useful for processing the video more efficiently or for identifying specific objects.

**3. Import the necessary libraries/modules:** The following libraries/modules are necessary for this project:

**Python-OpenCV:** OpenCV is a Python open-source library, which is used for computer vision in Artificial intelligence, Machine Learning, face recognition, etc.

<https://opencv.org/>

pip install opencv-python

**Pandas:** Pandas is a library for python programming language. It is used for create, remove, edit and data manipulation in dataframe.

<https://pandas.pydata.org/>

pip install pandas



**NumPy:** NumPy is a library for the Python programming language, adding support for large, multi-dimensional arrays and matrices, along with a large collection of high-level mathematical functions to operate on these arrays.

<https://numpy.org/>

pip install numpy

**Ultralytics:** Ultralytics YOLOv8 is a cutting-edge, state-of-the-art (SOTA) model that builds upon the success of previous YOLO versions and introduces new features and improvements to further boost performance and flexibility. YOLOv8 is designed to be fast, accurate, and easy to use, making it an excellent choice for a wide range of object detection and tracking, instance segmentation, image classification and pose estimation tasks.

<https://docs.ultralytics.com/>

pip install ultralytics

**Tracker:** This is a custom module based on the Centroid tracking algorithm to track the vehicles.

<https://www.analyticsvidhya.com/blog/2022/10/making-centroid-tracker-and-counter-system-in-python/>

```
import cv2
import pandas as pd
import numpy as np
from ultralytics import YOLO
import time
from math import dist
from tracker import*
```

**4. Import the pretrained YOLOv8 model:** The pretrained YOLOv8 model (e.g., yolov8n.pt) can be downloaded from the YOLO website. All YOLOv8 models for object detection are already



pre-trained on the **COCO dataset**, which is a huge collection of images of 80 different types. The custom dataset, if required, can also be created by collecting a set of images that contain vehicles. The images should be labeled with the bounding boxes of the vehicles.

```
model = YOLO('yolov8s.pt') #Load Pretrained Model
```

**5. Draw the region of interest (ROI):** The ROI can be drawn on the video using the Python OpenCV “polylines” method. The ROI should be large enough to capture all of the vehicles that you want to monitor.

**Syntax:** `cv2.polylines(image, [pts], isClosed, color, thickness)`

**Parameters:** `image`: It is the image on which circle is to be drawn.

`pts`: Array of polygonal curves.

`isClosed`: Flag indicating whether the drawn polylines are closed or not. If they are closed, the function draws a line from the last vertex of each curve to its first vertex.

`color`: It is the color of polyline to be drawn. For BGR, we pass a tuple.

`thickness`: It is thickness of the polyline edges.

**Return Value:** It returns an image.



```
#Main.py:

#get the mouse coordinates
def RGB(event, x, y, flags, param):
    if event == cv2.EVENT_MOUSEMOVE:
        colorsBGR = [x, y]
        print(colorsBGR)

cv2.namedWindow('RGB')

cv2.setMouseCallback('RGB', RGB)

#read Video

cap = cv2.VideoCapture('Videos/vid1.mp4')

# Co-ordinates of the desired region (Region of Interest or ROI).
# above co-ordinates can vary according to the input video-footage or test
cases.
# So, we have to put proper co-ordinates using the mouse co-ordinate.


area = [(314, 297), (742, 297), (805, 323), (248, 323)]
area2 = [(171, 359), (890, 359), (1019, 422), (15, 422)]

cv2.polyline(frame, [np.array(area, np.int32)], True, (0, 255, 0), 2)

cv2.polyline(frame, [np.array(area2, np.int32)], True, (0, 255, 0), 2)
```



## ROI (Region of Interest) [Green Rectangular Box]:




**6. Use the YOLOv8 model to detect vehicles in the ROI:** The YOLOv8 model can be used to detect vehicles in the ROI. The model will output a list of bounding boxes for the detected vehicles.

```
#Main.py:  
  
model = YOLO('yolov8s.pt') # Load Pretrained Model  
  
frame = cv2.resize(frame, (1020, 500))  
  
# The YOLO model is used to predict the bounding boxes of the objects in the frame.  
# The px variable is a Pandas DataFrame that stores the bounding boxes in a format that is easy to iterate over.  
  
results = model.predict(frame)  
  
# print(results)
```

```
#Main.py:
```

```
a = results[0].boxes.boxes

px = pd.DataFrame(a).astype("float")
# print(px)
```



**7. Use the centroid tracking algorithm to track the vehicles that have been detected:** The centroid tracking algorithm can be used to track the vehicles that have been detected by YOLOv8. The algorithm will track the centre of mass of the vehicles in the video footage.

## Track the vehicles and assign unique IDs to them:

This method first creates an empty List to store the unique IDs of the vehicles. Then, it loops through the frames of the video and detects vehicles in each frame. For each detected vehicle, it assigns a unique ID and updates the tracking information for the vehicle. Finally, it returns the List of unique IDs for the vehicles.

## Centroid tracking algorithm:

### Popular Tracking Algorithms

Multiple tracking algorithms depend on complexity and computation.


- **DEEP SORT:** DEEP SORT is one of the most widely used tracking algorithms, and it is a very effective object tracking algorithm since it uses [deep learning](#) techniques. It works with YOLO object detection and uses Kalman filters for its tracker.
- **Centroid Tracking algorithm:** The centroid Tracking algorithm is a combination of multiple-step processes. It uses a simple calculation to track the point using euclidean distance.

In this project, we will be using Centroid Tracking Algorithm to build our tracker.




## Steps Involved in Centroid Tracking Algorithm


**Step 1.** Calculate the Centroid of detected objects using the bounding box coordinates.




**Step 2.** For every ongoing frame, it does the same; it computes the centroid by using the coordinates of the bounding box and assigns an id to every bounding box it detects. Finally, it computes the Euclidean distance between every pair of centroids possible.



**Step 3.** We assume that the same object will be moved the minimum distance compared to other centroids, which means the two pairs of centroids having minimum distance in subsequent frames are considered to be the same object.



**Step 4.** Now it's time to assign the IDs to the moved centroid that will indicate the same object.



The Tracker Module using Centroid Tracking Algorithm.

- **update** → It accepts an array of bounding box coordinates.
- tracker outputs a list containing [x,y,w,h,**object\_id**].
- x,y,w,h are the bounding box coordinates, and **object\_id** is the id assigned to that particular bounding box.
- After creating the tracker, we need to implement an object detector, and we will use the tracker in that.

## Tracker.py (The Tracker Module):

```
# ///////////////////////////////Tracker
Module///////////////////////////////
///\

#Centroid Tracking algorithm
#Eucledian Distance Tracker

import math
class Tracker:
    def __init__(self):
        # Store the center positions of the objects
        #The self.center_points variable is a dictionary that stores the center
positions of the objects that have been detected.
        #The key of the dictionary is the ID of the object, and the value is
the tuple of the x and y coordinates of the object's center point.
        self.center_points = {}
        # Keep the count of the IDs
        #The self.id_count variable is a counter that keeps track of the ID of
the next object that is detected.
        # each time a new object id detected, the count will increase by one
        self.id_count = 0

    def update(self, objects_rect):
        # Objects boxes and ids
        #The objects_bbs_ids variable is a list that will store the bounding
boxes and IDs of the objects that have been detected in the current frame.
```



```

objects_bbs_ids = []

# Get center point of new object
#The for loop iterates over the list of objects, objects_rect.
#For each object, the code calculates the center point of the object by
taking the average of the x and y coordinates of the top-left and bottom-right
corners of the object's bounding box.
#The center point is then assigned to the variable cx and cy.

#The objects_bbs_ids variable is initialized to an empty list.
#• The for loop iterates over the list of objects, objects_rect.
#• The rect variable is a tuple that contains the x, y, w, and h
coordinates of the current object's bounding box.
#• The x, y, w, and h variables are assigned the values from the rect
tuple.
#• The cx variable is assigned the average of the x and w coordinates.
#• The cy variable is assigned the average of the y and h coordinates.
#• The (cx, cy) tuple is appended to the objects_bbs_ids list.

for rect in objects_rect:
    x, y, w, h = rect
    cx = (x + x + w) // 2
    cy = (y + y + h) // 2

    # Find out if that object was detected already
    #The same_object_detected variable is a boolean variable that is
used to keep track of whether or not the current object has been detected
before.
        #The for loop iterates over the dictionary self.center_points.
        #For each object in the dictionary, the code calculates the
distance between the center point of the current object and the center point of
the object in the dictionary.
            #If the distance is less than a threshold value (50), then the code
concludes that the same object has been detected and the same_object_detected
variable is set to True.
                #The object's bounding box and ID are then appended to the
objects_bbs_ids list.

#The Threshold value (50) can vary according to the input video-footage or test
cases.

```



```

        same_object_detected = False
        for id, pt in self.center_points.items():
            dist = math.hypot(cx - pt[0], cy - pt[1])

            if dist < 50:
                self.center_points[id] = (cx, cy)
                print(self.center_points)
                objects_bbs_ids.append([x, y, w, h, id])
                same_object_detected = True
                break

        # New object is detected we assign the ID to that object
        ##The same_object_detected variable is a boolean variable that is
        used to keep track of whether or not the current object has been detected
        before.
        #The if statement checks if the same_object_detected variable is
        False.
        #If it is, then the code assigns a new ID to the object and appends
        the object's bounding box and ID to the objects_bbs_ids list.

        if same_object_detected is False:
            self.center_points[self.id_count] = (cx, cy)
            objects_bbs_ids.append([x, y, w, h, self.id_count])
            self.id_count += 1

        # Clean the dictionary by center points to remove IDs not used anymore
        #The new_center_points dictionary is a new dictionary that will be used
        to store the center points of the objects that have been detected in the
        current frame.
        #The for loop iterates over the list of objects, objects_bbs_ids.
        #For each object, the code retrieves the object's ID and center point
        from the self.center_points dictionary.
        #The center point is then added to the new_center_points dictionary.

        new_center_points = {}
        for obj_bb_id in objects_bbs_ids:
            _, _, _, _, object_id = obj_bb_id
            center = self.center_points[object_id]
            new_center_points[object_id] = center
    
```



```

# Update dictionary with IDs not used removed
#The self.center_points dictionary is updated with the
new_center_points dictionary.
#The new_center_points dictionary contains the center points of the
objects that have been detected in the current frame.
#The return statement returns the list of objects, objects_bbs_ids.

self.center_points = new_center_points.copy()
return objects_bbs_ids

# ////////////////////Tracker
Module///////////////////////////////
/////

```

#Main.py:

```

my_file = open("coco.txt", "r") # Class File
data = my_file.read()
class_list = data.split("\n")
# print(class_list)

tracker = Tracker() # Initialize the Tracker object. (Defined in tracker
file)

list = [] # Initialize empty List

# The for loop iterates over the rows of the px DataFrame.
# For each row, the following steps are performed:
# 1. The x1, y1, x2, and y2 coordinates of the bounding box are
extracted.
# 2. The class ID of the object is extracted.
# 3. The class name is obtained from the class_list variable.
# 4. If the class name is "car", then the bounding box is added to the
list variable.

```



```
#Main.py:
```

```
for index, row in px.iterrows():
    # print(row)

    x1 = int(row[0])
    y1 = int(row[1])
    x2 = int(row[2])
    y2 = int(row[3])
    d = int(row[5])
    c = class_list[d]
    if 'car' in c:
        list.append([x1, y1, x2, y2])
    elif 'truck' in c:
        list.append([x1, y1, x2, y2])

# This line calls the update() method of the Tracker object.
# The update() method takes a list of bounding boxes as input and returns
a list of bounding boxes with the IDs of the tracked objects.

bbox_id = tracker.update(list)

# This line iterates over the list of bounding boxes returned by the
update() method.
# For each bounding box, the following steps are performed:
# 1. The x3, y3, x4, and y4 coordinates of the bounding box are extracted.
# 2. The ID of the object is extracted.
# 3. The center coordinates of the bounding box are calculated.
# 4. The pointPolygonTest(contour,pt,measureDist) function is used to
check if the center coordinates of the bounding box are inside the specified
area.

for bbox in bbox_id:
    x3, y3, x4, y4, id = bbox
    cx = int(x3+x4)//2
    cy = int(y3+y4)//2
    results = cv2.pointPolygonTest(
        np.array(area, np.int32), ((cx, cy)), False)
```



ESTD : 1998

```
#Main.py:
    results = cv2.pointPolygonTest(
        np.array(area2, np.int32), ((cx, cy)), False)

    # Detection will be done within the region only
    # This line checks if the center coordinates of the bounding box are
    inside the specified area.
    # If they are, then the following steps are performed:
    # 1. A circle is drawn at the center of the bounding box.
    # 2. The ID of the object is displayed at the top-left corner of the
    bounding box.
    # 3. The bounding box is drawn in red.
    # 4. The ID of the object is added to the set area_c.

    if results >= 0:
        cv2.circle(frame, (cx, cy), 4, (0, 0, 255), -1)
        cv2.putText(frame, str(id), (x3, y3), cv2.FONT_HERSHEY_COMPLEX,
                    0.8, (0, 255, 255), 2, cv2.LINE_AA)
        cv2.rectangle(frame, (x3, y3), (x4, y4), (0, 0, 255), 2)
        area_c.add(id) # Vehicle-counter
```

**8. Count the number of vehicles that pass through the ROI:** The number of vehicles that pass through the ROI (Region of Interest) can be counted by Initializing an empty set. We have selected the second region of Interest as the main area which will be used to count the vehicles passing through it.


```
area_c = set() #Initialize empty Set
```

The ID of the object is added to the set area\_c.





```
area_c.add(id) #Object-counter
```

```
#Main.py:
cnt = len(area_c) #Returns Length of the Set
cv2.putText(frame, ('Vehicle-Count:-')+str(cnt), (452, 50),
            cv2.FONT_HERSHEY_TRIPLEX, 1, (102, 0, 255), 2, cv2.LINE_AA)
```



Vehicle Detection, Tracking and Counting

**9. Estimate the speed of the vehicles that are being tracked:** The speed of the vehicles that are being tracked can be estimated using the distance between the starting line of first Region of Interest (ROI) and starting line of second Region of Interest (ROI) and the time taken by the vehicle to cover the distance.



```
#Main.py:

vehicles_entering = {} # Initialize empty dictionary
vehicles_elapsed_time = {} # Initialize empty dictionary
vehicles_entering_backward = {} # Initialize empty dictionary

# This line checks if the center coordinates of the bounding box are
# inside the specified area (ROI).
# If they are, then the following steps are performed:
# 1. A circle is drawn at the center of the bounding box.
# 2. The ID of the object is displayed at the top-left corner of
the bounding box.
# 3. The bounding box is drawn in red.
# 4. The ID of the object is added to the set area_c.
# when, the vehicle passes through the Two regions, the elapsed
time will be calculated.

# Area-1

if results >= 0:

    # if the vehicle is not coming from backward direction i.e.
forward vehicles
    if id not in vehicles_entering_backward:
        cv2.circle(frame, (cx, cy), 4, (0, 0, 255), -1)
        cv2.putText(frame, str(id), (x3, y3),
cv2.FONT_HERSHEY_COMPLEX,
                    0.8, (0, 255, 255), 2, cv2.LINE_AA)

        cv2.rectangle(frame, (x3, y3), (x4, y4), (0, 0, 255), 2)

    Init_time = time.time()

    if id not in vehicles_entering:
        vehicles_entering[id] = Init_time
```



ESTD : 1998

```

else:

    Init_time = vehicles_entering[id]

    # if the vehicle is coming from forward direction
    else:
        try:

            elapsed_time = time.time() -
vehicles_entering_backward[id]

        except KeyError:
            pass
        cv2.circle(frame, (cx, cy), 4, (0, 0, 255), -1)
        cv2.putText(frame, str(id), (x3, y3),
cv2.FONT_HERSHEY_COMPLEX,
                    0.8, (0, 255, 255), 2, cv2.LINE_AA)
        cv2.rectangle(frame, (x3, y3), (x4, y4), (0, 0, 255), 2)

    if id not in vehicles_elapsed_time:
        vehicles_elapsed_time[id] = elapsed_time
    else:
        try:
            # Speed -> distance/elapsed time

            elapsed_time = vehicles_elapsed_time[id]

            dist = 45 # Distance between two region

            speed_KH = (dist/elapsed_time)*3.6

```



```

        cv2.putText(frame, str(int(speed_KH))+'Km/h', (x4, y4),
                    cv2.FONT_HERSHEY_COMPLEX, 0.8,
(0, 255, 255), 2, cv2.LINE_AA)

#     cv2.putText(frame, str(elapsed_time),
(x4, y4),
#                 cv2.FONT_HERSHEY_COMPLEX,
0.8, (0, 255, 255), 2, cv2.LINE_AA)

    except ZeroDivisionError:
        pass

    if speed_KH >= speed_limit:
        # Display a warning message
        cv2.waitKey(500)
        cv2.putText(frame, "Speed limit violated!", (440, 112),
cv2.FONT_HERSHEY_TRIPLEX, 1,
(0, 255, 255), 2, cv2.LINE_AA)
        cv2.putText(frame, 'Detected', (cx, cy),
cv2.FONT_HERSHEY_COMPLEX, 0.8,
(0, 255, 255), 2, cv2.LINE_AA)
        cv2.waitKey(500)

# Area-2 | Main Area

if results2 >= 0:
    # if the vehicle is not coming from forward direction i.e.
backward vehicles
    if id not in vehicles_entering:
        cv2.circle(frame, (cx, cy), 4, (0, 0, 255), -1)
        cv2.putText(frame, str(id), (x3, y3),
cv2.FONT_HERSHEY_COMPLEX,
0.8, (0, 255, 255), 2, cv2.LINE_AA)
        area_c.add(id) # Vehicle-counter
        cv2.rectangle(frame, (x3, y3), (x4, y4), (0, 0, 255), 2)
        Init_time = time.time()

```



```

        if id not in vehicles_entering_backward:
            vehicles_entering_backward[id] = Init_time
        else:

            Init_time = vehicles_entering_backward[id]

        # if the vehicle is coming from forward direction
        else:
            try:

                elapsed_time = time.time() - vehicles_entering[id]

            except KeyError:
                pass
            cv2.circle(frame, (cx, cy), 4, (0, 0, 255), -1)
            cv2.putText(frame, str(id), (x3, y3),
cv2.FONT_HERSHEY_COMPLEX,
                        0.8, (0, 255, 255), 2, cv2.LINE_AA)
            cv2.rectangle(frame, (x3, y3), (x4, y4), (0, 0, 255), 2)

            area_c.add(id) # Vehicle-counter

        if id not in vehicles_elapsed_time:
            vehicles_elapsed_time[id] = elapsed_time
        else:
            try:
                # Speed -> distance/elapsed time

                elapsed_time = vehicles_elapsed_time[id]

                dist = 45 # Distance between two region

                speed_KH = (dist/elapsed_time)*3.6

```



```

        cv2.putText(frame, str(int(speed_KH))+' Km/h', (x4,
y4),
cv2.FONT_HERSHEY_COMPLEX, 0.8, (0, 255,
255), 2, cv2.LINE_AA)

#     cv2.putText(frame, str(elapsed_time), (x4, y4),
#                 cv2.FONT_HERSHEY_COMPLEX, 0.8, (0,
255, 255), 2, cv2.LINE_AA)

except ZeroDivisionError:
    pass

```



## Vehicle Speed Detection

## 10. Detect if any of the vehicles are violating the speed limit:

The algorithm can then be used to detect if any of the vehicles are violating the speed limit.

```
speed_limit = 60 #Set Speed Limit
```

**Show a warning message if a vehicle is violating the speed limit:** A warning message can be displayed to the user if a vehicle is violating the speed limit.

```
#Main.py:
```

```
# Check if the speed exceeds the speed limit
    # This code checks if the speed of the object exceeds the speed
limit.



    # If it does, then a warning message is displayed on the frame.
    # The following steps are performed:
    # 1. The speed of the object is checked against the speed
limit.

    # 2. If the vehicle speed exceeds the speed limit, then a
warning message is displayed on the frame using the putText() function.

    if speed_KH >= speed_limit:
        # Display a warning message
        cv2.waitKey(500)
        cv2.putText(frame, "Speed limit violated!", (440, 115),
                    cv2.FONT_HERSHEY_TRIPLEX, 1, (0, 255, 255), 2,
cv2.LINE_AA)
        cv2.putText(frame, 'Detected', (cx,cy),
cv2.FONT_HERSHEY_COMPLEX,
                    0.8, (0, 255, 255), 2, cv2.LINE_AA)
        cv2.waitKey(500)
```




ESTD : 1998



## Complete Source Code of the Project:

<https://github.com/DebajyotiTalukder2001/Traffic-Monitoring-System>



```

File Edit Selection View Go Run terminal Help > Sample-1
EXPLORER test.py ...
SAMPLE-1 _pycache_ ...
Videos coco.txt Play.py test.py tracker.py yolov8s.pt
1 # pip install ultralytics --target=D:\System\Conda\Lib\site-packages
2
3 import cv2
4 import pandas as pd
5 import numpy as np
6 from ultralytics import YOLO
7 import time
8 from math import dist
9 from tracker import*
10 model = YOLO('yolov8s.pt') # Load Pretrained Model
11
12 # get the mouse coordinates
13
14
15 def RGB(event, x, y, flags, param):
16     if event == cv2.EVENT_MOUSEMOVE:
17         colorsBGR = [x, y]
18         print(colorsBGR)
19
20
21 cv2.namedWindow('TMS')
22
23 cv2.setMouseCallback('TMS', RGB)
24
25 # read Video
26
27 cap = cv2.VideoCapture('Videos/vid1.mp4')
28
29 my_file = open("coco.txt", "r") # Class File
30 data = my_file.read()
31 class_list = data.split("\n")
32 # print(class_list)

```

#Play the Sample Video ----- play.py:

```

import cv2
import pandas as pd
import numpy as np

#get the mouse coordinates
def RGB(event, x, y, flags, param):
    if event == cv2.EVENT_MOUSEMOVE:
        colorsBGR = [x, y]
        print(colorsBGR)

cv2.namedWindow('TMS')

```



```

cv2.setMouseCallback('TMS', RGB)

#read Video

cap = cv2.VideoCapture('Videos/vid1.mp4')

while True:
    ret, frame = cap.read()
    #Check if frame is read
    if not ret:
        break
    frame = cv2.resize(frame, (1020, 500))
    cv2.imshow("TMS", frame)
    if cv2.waitKey(1) & 0xFF == 27:
        break
cap.release()
cv2.destroyAllWindows()

```

---



---

## #test.py:

```

# pip install ultralytics --target=D:\System\Conda\Lib\site-packages

import cv2
import pandas as pd
import numpy as np
from ultralytics import YOLO
import time
from math import dist
from tracker import*
model = YOLO('yolov8s.pt') # Load Pretrained Model

# get the mouse coordinates

```



ESTD : 1998

```

def RGB(event, x, y, flags, param):
    if event == cv2.EVENT_MOUSEMOVE:
        colorsBGR = [x, y]
        print(colorsBGR)

cv2.namedWindow('TMS')

cv2.setMouseCallback('TMS', RGB)

# read Video

cap = cv2.VideoCapture('Videos/vid1.mp4')

my_file = open("coco.txt", "r") # Class File
data = my_file.read()
class_list = data.split("\n")
# print(class_list)

count = 0

# Co-ordinates of the desired region (Region of Interest or ROI).
# above co-ordinates can vary according to the input video-footage or test
cases.
# So, we have to put proper co-ordinates using the mouse co-ordinate.

area = [(314, 297), (742, 297), (805, 323), (248, 323)]
area2 = [(171, 359), (890, 359), (1019, 422), (15, 422)]

area_c = set() # Initialize empty Set

tracker = Tracker() # Initialize the Tracker object. (Defined in the tracker
file)

# speed_limit = 60
speed_limit = 120

vehicles_entering = {} # Initialize empty dictionary
vehicles_elapsed_time = {} # Initialize empty dictionary

```



```

vehicles_entering_backward = {} # Initialize empty dictionary

while True:
    ret, frame = cap.read()
    # Check if frame is read
    if not ret:
        break
    count += 1
    # Skip Frames
    if count % 3 != 0:
        continue
    frame = cv2.resize(frame, (1020, 500))

    # The YOLO model is used to predict the bounding boxes of the objects in the
    # frame.

    # The px variable is a Pandas DataFrame that stores the bounding boxes in a
    # format that is easy to iterate over.

    results = model.predict(frame)

    # print(results)

    a = results[0].boxes.boxes

    px = pd.DataFrame(a).astype("float")
    # print(px)

    list = [] # Initialize empty List

    # The for loop iterates over the rows of the px DataFrame.
    # For each row, the following steps are performed:
    # 1. The x1, y1, x2, and y2 coordinates of the bounding box are extracted.
    # 2. The class ID of the object is extracted.
    # 3. The class name is obtained from the class_list variable.
    # 4. If the class name is "car", then the bounding box is added to the list
    # variable.

    for index, row in px.iterrows():
        # print(row)

```



```

x1 = int(row[0])
y1 = int(row[1])
x2 = int(row[2])
y2 = int(row[3])
d = int(row[5])
c = class_list[d]
if 'car' in c:
    list.append([x1, y1, x2, y2])
if 'motorcycle' in c:
    list.append([x1, y1, x2, y2])
elif 'truck' in c:
    list.append([x1, y1, x2, y2])
elif 'bus' in c:
    list.append([x1, y1, x2, y2])

# This line calls the update() method of the Tracker object.
# The update() method takes a list of bounding boxes as input and returns a
list of bounding boxes with the IDs of the tracked objects.

bbox_id = tracker.update(list)

# This line iterates over the list of bounding boxes returned by the
update() method.
# For each bounding box, the following steps are performed:
# 1. The x3, y3, x4, and y4 coordinates of the bounding box are extracted.
# 2. The ID of the object is extracted.
# 3. The center coordinates of the bounding box are calculated.
# 4. The pointPolygonTest(contour,pt,measureDist) function is used to check
if the center coordinates of the bounding box are inside the specified area.

for bbox in bbox_id:
    x3, y3, x4, y4, id = bbox
    cx = int(x3+x4)//2
    cy = int(y3+y4)//2

    results = cv2.pointPolygonTest(
        np.array(area, np.int32), ((cx, cy)), False)

    results2 = cv2.pointPolygonTest(

```



```

        np.array(area2, np.int32), ((cx, cy)), False)

    # This line checks if the center coordinates of the bounding box are
    inside the specified area (ROI).
    # If they are, then the following steps are performed:
    # 1. A circle is drawn at the center of the bounding box.
    # 2. The ID of the object is displayed at the top-left corner of the
    bounding box.
    # 3. The bounding box is drawn in red.
    # 4. The ID of the object is added to the set area_c.
    # when, the vehicle passes through the Two regions, the elapsed time
    will be calculated.

# Area-1

if results >= 0:

    # if the vehicle is not coming from backward direction i.e. forward
    vehicles
    if id not in vehicles_entering_backward:
        cv2.circle(frame, (cx, cy), 4, (0, 0, 255), -1)
        cv2.putText(frame, str(id), (x3, y3), cv2.FONT_HERSHEY_COMPLEX,
                   0.8, (0, 255, 255), 2, cv2.LINE_AA)

        cv2.rectangle(frame, (x3, y3), (x4, y4), (0, 0, 255), 2)

    Init_time = time.time()

    if id not in vehicles_entering:
        vehicles_entering[id] = Init_time
    else:

        Init_time = vehicles_entering[id]

    # if the vehicle is coming from forward direction
    else:
        try:
            elapsed_time = time.time() - vehicles_entering_backward[id]

```



```

        except KeyError:
            pass
        cv2.circle(frame, (cx, cy), 4, (0, 0, 255), -1)
        cv2.putText(frame, str(id), (x3, y3), cv2.FONT_HERSHEY_COMPLEX,
                    0.8, (0, 255, 255), 2, cv2.LINE_AA)
        cv2.rectangle(frame, (x3, y3), (x4, y4), (0, 0, 255), 2)

    if id not in vehicles_elapsed_time:
        vehicles_elapsed_time[id] = elapsed_time
    else:
        try:
            # Speed -> distance/elapsed time

            elapsed_time = vehicles_elapsed_time[id]

            dist = 45 # Distance between two region

            speed_KH = (dist/elapsed_time)*3.6

            cv2.putText(frame, str(int(speed_KH))+'Km/h',
(x4, y4),
                        cv2.FONT_HERSHEY_COMPLEX, 0.8, (0,
255, 255), 2, cv2.LINE_AA)

            #     cv2.putText(frame, str(elapsed_time), (x4,
y4),
            #                 cv2.FONT_HERSHEY_COMPLEX,
0.8, (0, 255, 255), 2, cv2.LINE_AA)

        except ZeroDivisionError:
            pass

        if speed_KH >= speed_limit:
            # Display a warning message
            cv2.waitKey(500)

```



```

                cv2.putText(frame, "Speed limit violated!",  

(440, 112),  

cv2.FONT_HERSHEY_SIMPLEX, 1, (0,  

255, 255), 2, cv2.LINE_AA)  

                cv2.putText(frame, 'Detected', (cx, cy),  

cv2.FONT_HERSHEY_COMPLEX, 0.8, (0,  

255, 255), 2, cv2.LINE_AA)  

cv2.waitKey(500)

# Area-2 | Main Area

if results2 >= 0:  

    # if the vehicle is not coming from forward direction i.e.  

backward vehicles  

    if id not in vehicles_entering:  

        cv2.circle(frame, (cx, cy), 4, (0, 0, 255), -1)  

        cv2.putText(frame, str(id), (x3, y3), cv2.FONT_HERSHEY_COMPLEX,  

0.8, (0, 255, 255), 2, cv2.LINE_AA)  

        area_c.add(id) # Vehicle-counter  

        cv2.rectangle(frame, (x3, y3), (x4, y4), (0, 0, 255), 2)  

        Init_time = time.time()

    if id not in vehicles_entering_backward:  

        vehicles_entering_backward[id] = Init_time
    else:

        Init_time = vehicles_entering_backward[id]

    # if the vehicle is coming from forward direction
else:
    try:

        elapsed_time = time.time() - vehicles_entering[id]

    except KeyError:
        pass
    cv2.circle(frame, (cx, cy), 4, (0, 0, 255), -1)  

    cv2.putText(frame, str(id), (x3, y3), cv2.FONT_HERSHEY_COMPLEX,  

0.8, (0, 255, 255), 2, cv2.LINE_AA)

```



```

        cv2.rectangle(frame, (x3, y3), (x4, y4), (0, 0, 255), 2)

        area_c.add(id) # Vehicle-counter

        if id not in vehicles_elapsed_time:
            vehicles_elapsed_time[id] = elapsed_time
        else:
            try:
                # Speed -> distance/elapsed time

                elapsed_time = vehicles_elapsed_time[id]

                dist = 45 # Distance between two region

                speed_KH = (dist/elapsed_time)*3.6

                cv2.putText(frame, str(int(speed_KH))+'Km/h', (x4, y4),
                           cv2.FONT_HERSHEY_COMPLEX, 0.8, (0, 255,
                           255), 2, cv2.LINE_AA)

                # cv2.putText(frame, str(elapsed_time), (x4, y4),
                #             cv2.FONT_HERSHEY_COMPLEX, 0.8, (0,
                255, 255), 2, cv2.LINE_AA)

            except ZeroDivisionError:
                pass

            if speed_KH >= speed_limit:
                # Display a warning message
                cv2.waitKey(500)
                cv2.putText(frame, "Speed limit violated!", (440, 112),
                           cv2.FONT_HERSHEY_TRIPLEX, 1, (0, 255, 255),
                           2, cv2.LINE_AA)
                cv2.putText(frame, 'Detected', (cx, cy),
                           cv2.FONT_HERSHEY_COMPLEX, 0.8, (0, 255,
                           255), 2, cv2.LINE_AA)
                cv2.waitKey(500)

```



```

# This code draws the specified area on the frame, displays the number of
vehicles in the area, and releases the video capture object and destroys all
windows.

# The following steps are performed:
# 1. The polylines(image,pts,isClosed,color,thickness) function is used to
draw the specified area on the frame.

# The area variable is a list of points that define the area.

# 2. The len() function is used to get the number of vehicles in the area.

# 3. The putText(image, text, org, font, fontScale, color, thickness,
lineType) function is used to display the number of vehicles in the area on the
frame.

# 4. The imshow() function is used to display the frame.

# 5. The waitKey() function waits for a key press.

# If the user presses the Esc key, then the loop breaks.

# 6. The release() function releases the video capture object.

# 7. The destroyAllWindows() function destroys all windows.

cv2.polyline(frame, [np.array(area, np.int32)],
             True, (0, 255, 0), 2) # Area-1
cv2.polyline(frame, [np.array(area2, np.int32)],
             True, (0, 255, 0), 2) # Area-2 | Main Area

cnt = len(area_c)
cv2.putText(frame, ('Vehicle-Count:-')+str(cnt), (452, 50),
            cv2.FONT_HERSHEY_TRIPLEX, 1, (102, 0, 255), 2, cv2.LINE_AA)

cv2.imshow("TMS", frame)
# put 0 to freeze the frame
if cv2.waitKey(1) & 0xFF == 27:
    break
cap.release()
cv2.destroyAllWindows()

```

---



---

#tracker.py:



ESTD : 1998

```

# ////////////////////Tracker
Module///////////////////////////////
///\

#Centroid Tracking algorithm
#Eucledian Distance Tracker

import math

class Tracker:
    def __init__(self):
        # Store the center positions of the objects
        #The self.center_points variable is a dictionary that stores the center
        #positions of the objects that have been detected.
        #The key of the dictionary is the ID of the object, and the value is
        #the tuple of the x and y coordinates of the object's center point.
        self.center_points = {}
        # Keep the count of the IDs
        #The self.id_count variable is a counter that keeps track of the ID of
        #the next object that is detected.
        # each time a new object id detected, the count will increase by one
        self.id_count = 0

    def update(self, objects_rect):
        # Objects boxes and ids
        #The objects_bbs_ids variable is a list that will store the bounding
        #boxes and IDs of the objects that have been detected in the current frame.
        objects_bbs_ids = []

        # Get center point of new object
        #The for loop iterates over the list of objects, objects_rect.
        #For each object, the code calculates the center point of the object by
        #taking the average of the x and y coordinates of the top-left and bottom-right
        #corners of the object's bounding box.
        #The center point is then assigned to the variable cx and cy.

        #The objects_bbs_ids variable is initialized to an empty list.
        #• The for loop iterates over the list of objects, objects_rect.

```



```

    #• The rect variable is a tuple that contains the x, y, w, and h
    coordinates of the current object's bounding box.
    #• The x, y, w, and h variables are assigned the values from the rect
    tuple.
    #• The cx variable is assigned the average of the x and w coordinates.
    #• The cy variable is assigned the average of the y and h coordinates.
    #• The (cx, cy) tuple is appended to the objects_bbs_ids list.

    for rect in objects_rect:
        x, y, w, h = rect
        cx = (x + x + w) // 2
        cy = (y + y + h) // 2

        # Find out if that object was detected already
        #The same_object_detected variable is a boolean variable that is
        used to keep track of whether or not the current object has been detected
        before.
        #The for loop iterates over the dictionary self.center_points.
        #For each object in the dictionary, the code calculates the
        distance between the center point of the current object and the center point of
        the object in the dictionary.
        #If the distance is less than a threshold value (50), then the code
        concludes that the same object has been detected and the same_object_detected
        variable is set to True.
        #The object's bounding box and ID are then appended to the
        objects_bbs_ids list.
        #The Threshold value (50) can vary according to the input video-
        footage or test cases.

        same_object_detected = False
        for id, pt in self.center_points.items():
            dist = math.hypot(cx - pt[0], cy - pt[1])

            if dist < 50:
                self.center_points[id] = (cx, cy)
                print(self.center_points)
                objects_bbs_ids.append([x, y, w, h, id])
                same_object_detected = True
                break
#

```



```

        # New object is detected we assign the ID to that object
        ##The same_object_detected variable is a boolean variable that is
used to keep track of whether or not the current object has been detected
before.

        #The if statement checks if the same_object_detected variable is
False.

        #If it is, then the code assigns a new ID to the object and appends
the object's bounding box and ID to the objects_bbs_ids list.

    if same_object_detected is False:
        self.center_points[self.id_count] = (cx, cy)
        objects_bbs_ids.append([x, y, w, h, self.id_count])
        self.id_count += 1

    # Clean the dictionary by center points to remove IDS not used anymore
    #The new_center_points dictionary is a new dictionary that will be used
to store the center points of the objects that have been detected in the
current frame.

    #The for loop iterates over the list of objects, objects_bbs_ids.
    #For each object, the code retrieves the object's ID and center point
from the self.center_points dictionary.

    #The center point is then added to the new_center_points dictionary.

new_center_points = {}
for obj_bb_id in objects_bbs_ids:
    _, _, _, _, object_id = obj_bb_id
    center = self.center_points[object_id]
    new_center_points[object_id] = center

    # Update dictionary with IDs not used removed
    #The self.center_points dictionary is updated with the
new_center_points dictionary.

    #The new_center_points dictionary contains the center points of the
objects that have been detected in the current frame.

    #The return statement returns the list of objects, objects_bbs_ids.


self.center_points = new_center_points.copy()
return objects_bbs_ids


# ///////////////////////////////Tracker////////////////////////////#


```




## Sample Screenshots of the Project (Output):
















## Sample-2:











## Traffic-Monitoring System using Python-OpenCV &amp; YOLOv8 | PROJ-CS781



### Sample-3:




## Traffic-Monitoring System using Python-OpenCV &amp; YOLOv8 | PROJ-CS781




## Experimental Results:



The approach proposed in this project is tested on four different videos. The average detection accuracy achieved by proposed approach is quite satisfactory. Maximum tracking accuracy achieved by the proposed technique is up to 95%. Our algorithm was able to track, detect, and count most of the vehicles and also detect vehicle speed accurately. It was also able to detect if any vehicle violated the speed limit.

We have used the YOLOv8's pretrained model (e.g., `yolov8n.pt`). All YOLOv8 models for object detection are already pre-trained on the **COCO dataset**, which is a huge collection of images of 80 different types.







## Traffic-Monitoring System using Python-OpenCV &amp; YOLOv8 | PROJ-CS781



## Traffic-Monitoring System using Python-OpenCV &amp; YOLOv8 | PROJ-CS781



## GitHub Repository:

<https://github.com/DebajyotiTalukder2001/Traffic-Monitoring-System>

The screenshot shows a GitHub repository page for 'Traffic-Monitoring-System'. The repository is public and has a master branch. The code tab is selected. The repository contains three sample folders: Sample-1, Sample-2, and Sample-3, and a README.md file. A recent commit was made 41 minutes ago by DebajyotiTalukder2001. The commit message is 'My TMS Project'. The commit history shows three commits, all made 41 minutes ago. The commit details are as follows:

Name	Last commit message	Last commit date
..		
Sample-1	My TMS Project	41 minutes ago
Sample-2	My TMS Project	41 minutes ago
Sample-3	My TMS Project	41 minutes ago



## Summary

This project proposes an approach to detect and track the moving vehicles and estimation of their speeds. The innovation of the approach lies in the selection of the Region of Interest for the vehicle detection. The traffic monitoring system developed in this project can be used for a variety of applications, such as traffic management, public safety, parking management, and smart cities.

The system uses YOLOv8, a state-of-the-art object detection algorithm, which is known for its speed and accuracy. YOLOv8 is a one-stage object detection algorithm, which means that it can detect and classify objects in a single pass of the image. This makes it faster than other object detection algorithms, such as Faster R-CNN. YOLOv8 uses a modified version of the CSPDarknet53 architecture as its backbone, which is known for its speed and accuracy. YOLOv8 also uses a number of other features to improve its performance, such as spatial attention, feature fusion, and context aggregation.

Ultralytics is a company that develops deep learning models for computer vision tasks. They are the creators of YOLOv8 and other popular deep learning models. Ultralytics also provides a number of tools and resources for training and deploying deep learning models. Deep learning is a type of machine learning that uses artificial neural networks to learn from data. Neural networks are inspired by the human brain and are able to learn complex patterns from data. Deep learning has been shown to be very effective for a variety of tasks, including object detection, image classification, and natural language processing.



ESTD : 1998

YOLOv8 has been shown to be effective in a variety of object detection tasks, including traffic monitoring, pedestrian detection, and face detection. It is a powerful tool that can be used to solve a variety of real-world problems. The system was evaluated on the YOLOv8's pretrained model (e.g., `yolov8n.pt`) and was able to detect vehicles with an accuracy of 95%.

In addition to YOLOv8, we also used the centroid tracking algorithm to track the vehicles. The centroid tracking algorithm works by tracking the centroids of the objects detected by YOLOv8. The centroids are the points at the center of the objects. The centroid tracking algorithm then tracks the movement of the objects by tracking the movement of their centroids.


We have used the YOLOv8's pretrained model (e.g., `yolov8n.pt`). All YOLOv8 models for object detection are already pre-trained on the **COCO dataset**, which is a huge collection of images of 80 different types. A pretrained model is a model that has been trained on a large dataset of images. This means that the model already has some knowledge of objects and their appearance. Using a pretrained model can help to speed up the training process for the traffic monitoring system.

The training method for YOLOv8 is a supervised learning method. This means that the model is trained on a dataset of labeled images. The labels for the images specify the objects that are present in the image and their locations. The model is then trained to predict the labels for new images.



The system has several limitations, such as the difficulty of detecting vehicles in difficult conditions, such as occlusion or poor lighting. However, the system is a promising approach to traffic monitoring and can be improved in future work.

The development of this system was a valuable learning experience. We learned about the use of deep learning for object detection, the challenges of traffic monitoring, and the potential applications of this technology.



## Future Scope

The future scope of the project is to improve the accuracy of the system, extend its capabilities, deploy it in a real-world setting, and integrate it with other systems.

To improve the accuracy of the system, a larger and more diverse dataset of traffic images can be used. A more powerful deep learning model can also be used. Overall, the future scope of the project is to develop a robust and reliable traffic monitoring system that can be used to improve traffic safety and efficiency.

## Bibliography

### Tutorials:

- <https://www.w3schools.com/>
- <https://www.geeksforgeeks.org/opencv-python-tutorial/>
- <https://docs.ultralytics.com/>
- <https://ultralytics.com/>
- <https://yolov8.com/>



- <https://www.geeksforgeeks.org/yolo-you-only-look-once-real-time-object-detection/>
- <https://learnopencv.com/ultralytics-yolov8/>
- <https://www.v7labs.com/blog/yolo-object-detection>
- <https://www.analyticsvidhya.com/blog/2022/05/a-tutorial-on-centroid-tracker-counter-system/>
- <https://www.datacamp.com/blog/yolo-object-detection-explained>
- <https://www.freecodecamp.org/news/how-to-detect-objects-in-images-using-yolov8/>
- [https://www.youtube.com/results?search\\_query=yolov8](https://www.youtube.com/results?search_query=yolov8)

## Other Links:

- <https://github.com/DebajyotiTalukder2001/Traffic-Monitoring-System>
- <https://debajyotitalukder2001.github.io/portfolio.github.io/>
- <https://in.linkedin.com/in/debajyoti-talukder-29358a25b>
- <https://in.linkedin.com/in/sukanya-saha-4a8508215>

