

(Bad) Producer Consumer using a lock

- The producer might write into a full buffer
- The consumer might read from an empty buffer

```
void producer () {  
    while(1) {  
        item := produce()  
        acquire(lock)  
        write(buffer, item)  
        release(lock)  
    }  
}
```

```
void consumer () {  
    while(1) {  
        acquire(lock)  
        item := read(buffer)  
        release(lock)  
        consume(item)  
    }  
}
```

```
lock := init()
```

(Bad) Producer Consumer **using a lock**

```
lock := init()
```

```
void producer () {  
    while(1) {  
        item := produce()  
        acquire(lock)  
        write(buffer, item)  
        release(lock)  
    }  
}
```

```
void consumer () {  
    while(1) {  
        acquire(lock)  
        item := read(buffer)  
        release(lock)  
        consume(item)  
    }  
}
```

- The producer might write into a full buffer
- The consumer might read from an empty buffer

(Good) Producer consumer **using a lock**

```
lock := init()
```

```
void producer () {  
    while(1) {  
        item := produce()  
        acquire(lock)  
        while (!empty(buffer)) {  
            release(lock)  
            yield();  
            acquire(lock)  
        }  
        write(buffer, item)  
        release(lock)  
    }  
}
```

```
void consumer () {  
    while(1) {  
        acquire(lock)  
        while (empty(buffer)) {  
            release(lock)  
            yield();  
            acquire(lock)  
        }  
        item := read(buffer)  
        release(lock)  
        consume(item)  
    }  
}
```