

CODES OF MODULE 1:

Part 1:

```
import time
from selenium import webdriver
from selenium.webdriver import ActionChains
from selenium.webdriver.common.by import By
from selenium.webdriver.support.select import Select

driver=webdriver.Chrome()
driver.get("https://testautomationpractice.blogspot.com")
driver.maximize_window()
#email
driver.find_element(By.CSS_SELECTOR, "#email").send_keys("test@gmail.com")
#name
driver.find_element(By.XPATH, "//input[@id='name']").send_keys("Rachel")
#phone
driver.find_element(By.XPATH, "//input[@id='phone']").send_keys("84656576515"
)

#gender
driver.find_element(By.XPATH, "//input[@id='female']").click()

#day
driver.find_element(By.XPATH, "//input[@id='sunday']").click()

#country
countrydrop=driver.find_element(By.CSS_SELECTOR, "div.form-group >
select#country")
selectcountry=Select(countrydrop)
selectcountry.select_by_value("germany")

#colors
colordrop=driver.find_element(By.ID, "colors")
selectcolors=Select(colordrop)
selectcolors.select_by_value("blue")

#Sorted list
listdrop=driver.find_element(By.ID, "animals")
selectlist=Select(listdrop)
selectlist.select_by_value("dog")

#date picker1
date1=driver.find_element(By.ID, "datepicker")
```

```

date1.clear()
date1.send_keys("08/31/2026")
date1.send_keys("\n")

#date picker 2
date2=driver.find_element(By.ID,"txtDate")
date2.send_keys("10/10/2025")
date2.send_keys("\n")

#date range
startdate=driver.find_element(By.ID,"start-date")
startdate.send_keys("10/10/2025")
startdate.send_keys("\n")

enddate=driver.find_element(By.ID,"end-date")
enddate.send_keys("31/08/2026")
enddate.send_keys("\n")

#submit button
driver.find_element(By.XPATH,"//*[@id='post-body-1307673142697428135']/div[8]/button").click()

#mouse actions
action=ActionChains(driver)
action.move_to_element(driver.find_element(By.CSS_SELECTOR,".dropbtn")).perform()
action.double_click(driver.find_element(By.XPATH,"//*[@id='HTML10']/div[1]/button")).perform()
to_drag=driver.find_element(By.CSS_SELECTOR,"#draggable")
to_drop=driver.find_element(By.CSS_SELECTOR,"#droppable")
action.drag_and_drop(to_drag,to_drop).perform()
time.sleep(60)
driver.quit()

```

Part 2:

```

import time
from selenium import webdriver
from selenium.webdriver.common.by import By
from selenium.webdriver.support import expected_conditions
from selenium.webdriver.support.select import Select
from selenium.webdriver.support.wait import WebDriverWait

driver=webdriver.Chrome()

```

```

driver.get("https://rahulshettyacademy.com/AutomationPractice")

#radio button
driver.find_element(By.XPATH, "//*[@id='radio-btn-example']/fieldset/label[2]/input").click()

#suggestion class example
country=driver.find_element(By.XPATH, "//*[@id='autocomplete']")
country.send_keys("Germany")
option=WebDriverWait(driver,5).until(
    expected_conditions.element_to_be_clickable(
        (By.XPATH, "//li[normalize-space()='Germany']")
    )
)
option.click()

#checkbox all
checkboxes=driver.find_elements(By.XPATH, "//div[@id='checkbox-example']/input[@type='checkbox']")
for checkbox in checkboxes:
    if not checkbox.is_selected():
        checkbox.click()

#alert example
driver.find_element(By.ID, "name").send_keys("Rachel")
driver.find_element(By.ID, "alertbtn").click()
alert=driver.switch_to.alert
alert_text=alert.text
print(alert_text)
alert.accept()

time.sleep(60)
driver.quit()

```

Part 3:

```

from selenium import webdriver
import time

driver = webdriver.Chrome()

driver.get("https://rahulshettyacademy.com/AutomationPractice")

parent_window = driver.current_window_handle
print("Parent window:", parent_window)

driver.execute_script("window.open('https://www.google.com', '_blank');")

```

```
time.sleep(2)

all_windows = driver.window_handles
print("All windows:", all_windows)

for window in all_windows:
    if window != parent_window:
        driver.switch_to.window(window)
        print("Switched to new window")
        print("Title:", driver.title)

driver.switch_to.window(parent_window)
print("Back to parent:", driver.title)

driver.quit()
```