

Codes of Module 2:

Unittest:

```
from selenium import webdriver
import time
import unittest

from selenium.webdriver.common.by import By

class GoogleTestCase(unittest.TestCase):
    def setUp(self) -> None:
        self.driver=webdriver.Chrome()
        self.driver.maximize_window()
        self.driver.get("https://www.google.com")
        time.sleep(5)

    def test_google_images(self):
        images_link=self.driver.find_element(By.LINK_TEXT,"Images")
        images_link.click()
        assert 'Google Images' in self.driver.title
        time.sleep(5)

    def test_google_search(self):
        search_box=self.driver.find_element(By.NAME,"q")
        search_box.send_keys("Selenium with Python")
        search_box.submit()
        time.sleep(5)
    def tearDown(self) -> None:
        self.driver.quit()

if __name__=="__main__":
    unittest.main()
```

Pytest:

```
import pytest
import warnings

def test_price():
    result=0.1+0.2
    assert result==pytest.approx(0.3)
```

```

def test_login():
    login_successful=False

    if not login_successful:
        pytest.fail("Login was not succesful")

def test1_login():
    browser_available=False

    if not browser_available:
        pytest.skip("Browser is not available")
    assert True

def test2_login():
    server_available=False

    if not server_available:
        pytest.exit("Server is not available")
    assert True

def test_homepage():
    assert True

def divide(a,b):
    return a/b

def test_divide_byzero():
    with pytest.raises(ZeroDivisionError):
        divide(10,0)

def old_function():
    warnings.warn("This function is deprecated", UserWarning)

def test_old_function():
    with pytest.warns(UserWarning):
        old_function()

```

Base Page of Page Object Model:

```

#Page Object Model (Base Page Only)
from selenium.webdriver.support.ui import WebDriverWait
from selenium.webdriver.support import expected_conditions as EC
from selenium.webdriver.common.action_chains import ActionChains
from selenium.webdriver.support.ui import Select

class BasePage:
    def __init__(self,driver):
        self.driver=driver

```

```
self.wait=WebDriverWait(driver,10)

def get_title(self):
    return self.driver.title

def get_current_url(self):
    return self.driver.current_url

def find(self,locator):
    return self.wait.until(EC.presence_of_element_located(locator))

def click(self,locator):
    element=self.wait.until(EC.element_to_be_clickable(locator))
    element.click()

def enter_text(self,locator,text):
    element=self.wait.until(EC.visibility_of_element_located(locator))
    element.send_keys(text)
```