

Component

DOM

EVENTS

PROPERTIES



# Module Overview



Property Binding


Handling Events with Event Binding

Handling Input with Two-way Binding

Transforming Data with Pipes



# Application Architecture



# Property Binding

```
<img [src]='product.imageUrl'>
```

```
<img src={{product.imageUrl}}>
```

Element  
Property

Template  
Expression

```
product.imageUrl}}'>
```

# Event Binding

Template

Class

```
<h1>{{pageTitle}}</h1>
```

```
<img [src]='product.imageUrl'>
```

```
<button (click)='toggleImage()'>
```

```
export class ListComponent {
```

<https://developer.mozilla.org/en-US/docs/Web/Events>

()

Target Event

''

Template  
Statement

# Two-way Binding

Template

```
<input [ (ngModel) ] = 'listFilter' >
```

Class

```
export class ListComponent {  
  listFilter: string = 'cart';  
}
```

# Two-way Binding

Template

```
<input [ (ngModel) ] = 'listFilter' >
```

Class

```
export class ListComponent {  
  listFilter: string = 'cart';  
}
```

# Two-way Binding

Template

```
<input [ (ngModel) ]='listFilter'>
```

Class

```
export class ListComponent {  
  listFilter: string = 'cart';  
}
```



# Two-way Binding

Template

`<input [ (ngModel) ] = 'listFilter' >`

Class

```
export class ListComponent {  
  listFilter: string = 'cart';  
}
```

`[()]`

Banana in a Box

# Transforming Data with Pipes

Transform  
bound  
properties  
before  
display

## Built-in pipes

- date
- number, decimal, percent, currency
- json, slice
- etc

Custom  
pipes

# Pipe Examples

```
{{ product.productCode | lowercase }}
```

```
<img [src]='product.imageUrl'  
      [title]='product.productName | uppercase'>
```

```
{{ product.price | currency | lowercase }}
```

```
{{ product.price | currency:'USD':true:'1.2-2' }}
```

# Data Binding

## DOM


```
▼ <pm-app>
  ▼ <div>
    <h1>Acme Product Management</h1>
    ▼ <pm-products>
      ▼ <div class="panel panel-primary">
        <div class="panel-heading">
          Product List
        </div>
        ▼ <div class="panel-body">
          ::before
          ▶ <div class="row">...</div>
          ▶ <div class="row">...</div>
          ▼ <div class="table-responsive">
            <!--template bindings={}-->
            ▼ <table class="table">
              ▶ <thead>...</thead>
              ▶ <tbody>...</tbody>
            </table>
          </div>
          ::after
        </div>
      </div>
    </pm-products>
  </div>
</pm-app>
```

## product-list.component.ts

```
@Component ({
  selector: 'pm-products',
  templateUrl: 'product-list.component.html'
})
export class ProductListComponent {
  pageTitle: string = 'Product List';
  listFilter: string = 'cart';
  products: any[] = [...];
  toggleImage(): void {...}
}
```



# Data Binding



# Checklist: Pipes



\_\_\_\_\_



\_\_\_\_\_



\_\_\_\_\_

Pipe character |

Pipe name

Pipe parameters

- Separated with colons

Example

- `{{ product.price |  
currency:'USD':true:'1.2-2' }}`

# Summary



Property Binding

Handling Events with Event Binding

Handling Input with Two-way Binding

Transforming Data with Pipes



# Application Architecture

