

LAB 11

Course Code: CSC 2209

Course Title: Operating Systems



**Dept. of Computer Science
Faculty of Science and Technology**

Lecturer No:	11	Week No:	11	Semester:	
Lecturer:	<i>Name & email</i>				

Lecture Outline



1. Array
2. File Parsing from Shell Script
3. File Parsing With Separator
4. Checking file existence

Array

- ❑ Bash Supports simple single dimension array
- ❑ In bash you can add value in any array position
- ❑ Gaps in indices are okay in bash
- ❑ You can treat any variable as an array but the value will be assigned into the 0th index

- ❑ Syntax

```
os=('ubuntu', 'windows', 'linux')
```

```
echo "${os[0]}"
```

```
echo "${os[1]}"
```

```
echo "${os[2]}"
```

Array (cont'd)

- ❑ Get the length of the array

```
echo "${#os[@]}"
```

- ❑ Removing value from array

```
unset os[2]
```

- ❑ Taking array as an input

Read -a variablename [separate input with space and then press enter]

File Parsing from Shell Script

- ☐ File can be viewed with cat command easily.
- ☐ We can also parse file from shell script.
- ☐ For parsing file we need input redirection of file.
- ☐ Input redirection means the read command will read from file rather taking input from terminal.
- ☐ Input redirection is done by < operator.
- ☐ File is read by while loop.

Syntax

```
#!/bin/bash
while read filecontent
do
    echo $filecontent
done < filename
```

This will read the whole content of the file and give output in terminal.

File Parsing With Separator

Suppose we want to parse the file and its contents

For example the below is a content of a file

Name-ID

Tanvir Ahmed-123466

Sabbir Ahmed-456792

Masum Ahmed-454679

Here you can see the name and id are separated by -.

This is a separator. In many files linux uses separator to separate file contents.

Example

- ❑ Run `cat /etc/passwd`

- ❑ This file contains the user information like username, password, user home directory etc.

See the below content. This contains username and user's home directory.

`uidd:/usr/sbin/nologin`

`dnsmasq:/usr/sbin/nologin`


`landscape:/usr/sbin/nologin`

`sshd:/usr/sbin/nologin`

- ❑ Here the contents are separated with : (colon). So, to read the attribute like user and user's home directory independently we have to use File Separator.
- ❑ To do so we need to use IFS = Internal Field Separator. It basically separates word with a separator.

Syntax

```
while IFS=':' read username userhomedirectory
do
    echo $username $userhomedirectory
done < filename
```



```
quidd /usr/sbin/nologin
dnsmasq /usr/sbin/nologin
landscape /usr/sbin/nologin
sshd /usr/sbin/nologin
```

Output of the above code.

For reading n attribute we need to use n variables. As we are reading 2 attributes we are using 2 variables.

Checking file existence

```
filename=info.txt
```

```
if [ -f $filename ]
```

```
then
```

```
    #do operation
```

```
else
```

```
    echo "File not exists"
```

Here the `-f` flag checks for the existence of the file.



Books

- ❑ Unix Shell Programming
 - ❑ Written by Yashavant P. Kanetkar