

Phone Keypad Combinations

You are given a string containing digits from 2 to 9 inclusive. Each digit maps to a set of letters as on a traditional phone keypad:

1	2 abc	3 def
4 ghi	5 jkl	6 mno
7 pqrs	8 tuv	9 wxyz

Return all possible letter combinations the input digits could represent.

Example:

```
Input: digits = '69'
```

```
Output: ['mw', 'mx', 'my', 'mz', 'nw', 'nx', 'ny', 'nz', 'ow', 'ox', 'oy', 'oz']
```

Intuition


At each digit in the string, we have a decision to make: which letter will this digit represent? Based on this decision, let's illustrate the state space tree that represents the choices at each digit of the input string.

State space tree


Consider the input string "69". Let's start with the root node of the tree, which is an empty string:

""


At the first digit, 6, we have the choice of starting our combination with 'm', 'n', or 'o':



For each of these combinations we've created, we now have a new decision to make: which letter of digit 9 ('w', 'x', 'y', 'z') should we choose? These choices are illustrated below:



One important thing missing from this state space tree is information on which digit we're making a decision on at each node. We can use an index *i* to determine which digit we're considering at each node:



The final level of this decision tree (i.e., when *i* == *n*, where *n* denotes the length of the input string) represents all possible combinations that can be created from the provided string. Similar to our approach in *Find All Subsets*, let's use **backtracking** to obtain these keypad combinations.

Mapping digits to letters

The final thing we need to figure out is a way to determine which letters correspond to which digits. A hash map is great for this purpose. In the hash map, digits are the keys, and the associated sets of letters are their values. This allows us to access the letters in constant time:

keypad_map	
'2'	"abc"
'3'	"def"
'4'	"ghi"

digit	letters
'5'	"jkl"
'6'	"mno"
'7'	"pqrs"
'8'	"tuv"
'9'	"wxyz"

Implementation

Python

JavaScript

Java

```
def phone_keypad_combinations(digits: str) → List[str]:  
    keypad_map = {  
        '2': 'abc', '3': 'def', '4': 'ghi', '5': 'jkl',  
        '6': 'mno', '7': 'pqrs', '8': 'tuv', '9': 'wxyz'  
    }  
    res = []  
    backtrack(0, [], digits, keypad_map, res)  
    return res  
  
def backtrack(i: int, curr_combination: List[str], digits: str,  
              keypad_map: Dict[str, str], res: List[str]) → None:  
    # Termination condition: if all digits have been considered, add the  
    # current combination to the output list.  
    if len(curr_combination) == len(digits):  
        res.append("".join(curr_combination))  
        return  
    for letter in keypad_map[digits[i]]:  
        # Add the current letter.  
        curr_combination.append(letter)  
        # Recursively explore all paths that branch from this combination.  
        backtrack(i + 1, curr_combination, digits, keypad_map, res)  
        # Backtrack by removing the letter we just added.  
        curr_combination.pop()
```

Complexity Analysis

Time complexity: The time complexity of `phone_keypad_combinations` is $O(n \cdot 4^n)$. This is because the state space tree will branch down until a decision is made for all n elements. This results in a tree of height n with a branching factor of 4 since there are up to 4 decisions we can make at each

digit. For each of the 4^n combinations created, we convert it into a string and add it to the output list, which takes $O(n)$ time per combination. This results in a total time complexity of $O(n \cdot 4^n)$.

Space complexity: The space complexity is $O(n)$ due to the recursive call stack, which can grow up to a maximum depth of n . The `keypad_map` only takes constant space since there are only 8 key-value pairs.

Interview Tip

Tip: Check if you can skip trivial implementations.

During an interview, it's crucial to manage your time effectively. If you encounter a trivial and time-consuming task, such as creating the `keypad_map` in this problem, it's possible the interviewer may allow you to skip it or implement it later if there's time left in the interview. Ensure you at least briefly mention how the implementation you're skipping would work before requesting to move on to the core logic of the problem.