



C/C++ CodeCount™

Counting Standard

University of Southern California

Center for Systems and Software Engineering

June , 2007

Revision Sheet

Date	Version	Revision Description	Author
6/22/2007	1.0	Original Release	CSSE
10/16/2007	1.1	Updated the example of switch statement	Vu Nguyen
1/2/2013	1.2	Updated document template	CSSE
1/14/2013	1.3	Added cyclomatic complexity	CSSE

Table of Contents

No.	Contents	Page No.
1.0	Definitions	4
1.1	SLOC	4
1.2	Physical SLOC	4
1.3	Logical SLOC	4
1.4	Data declaration line	4
1.5	Compiler directive	4
1.6	Blank line	5
1.7	Comment line	5
1.8	Executable line of code	5
2.0	Checklist for source statement counts	6
3.0	Examples of logical SLOC counting	7
3.1	Executable Lines	7
3.1.1	Selection Statements	7
3.1.2	Iteration Statements	8
3.1.3	Jump Statements	9
3.1.4	Expression Statements	10
3.1.5	Block Statements	10
3.2	Declaration lines	11
3.3	Compiler directives	11
4.0	Cyclomatic Complexity	12

1. Definitions

- 1.1. **SLOC** – Source Lines of Code is a unit used to measure the size of software program. SLOC counts the program source code based on a certain set of rules. SLOC is a key input for estimating project effort and is also used to calculate productivity and other measurements.
- 1.2. **Physical SLOC** – One physical SLOC is corresponding to one line starting with the first character and ending by a carriage return or an end-of-file marker of the same line, and which excludes the blank and comment line.
- 1.3. **Logical SLOC** – Lines of code intended to measure “statements”, which normally terminate by a semicolon (C/C++, Java, C#) or a carriage return (VB, Assembly), etc. Logical SLOC are not sensitive to format and style conventions, but they are language-dependent.
- 1.4. **Data declaration line or data line** – A line that contains declaration of data and used by an assembler or compiler to interpret other elements of the program.

The following table lists the C/C++ keywords that denote data declaration lines:

Simple Data Types	Compound and User Defined Data Types	Access Specifiers	Type Qualifiers
bool	class	private	const
char	struct	protected	volatile
double	union	public	
float	enum	friend	
int	typedef	Storage Class Specifiers	Miscellaneous
long	template	auto	asm
short	typename	extern	explicit
signed		mutable	inline
unsigned		register	namespace
void		static	using
wchar_t			operator
			virtual

Table 1 Data Declaration Types

- 1.5. **Compiler Directives** – A statement that tells the compiler how to compile a program, but not what to compile.

The following table lists the C/C++ keywords that denote compiler directive lines:

#define	#ifndef	#include	#dictionary
#undef	#else	#line	#module
#if	#elif	#pragma	#import
#ifdef	#endif	#error	#using

Table 2 Compiler Directives

- 1.6. **Blank Line** – A physical line of code, which contains any number of white space characters (spaces, tabs, form feed, carriage return, line feed, or their derivatives).
- 1.7. **Comment Line** – A comment is defined as a string of zero or more characters that follow language-specific comment delimiter.

C/C++ comment delimiters are “//” and “/*”. A whole comment line may span one line and does not contain any compilable source code. An embedded comment can co-exist with compilable source code on the same physical line. Banners and empty comments are treated as types of comments.

- 1.8. **Executable Line of code** – A line that contains software instruction executed during runtime and on which a breakpoint can be set in a debugging tool. An instruction can be stated in a simple or compound form.

- An executable line of code may contain the following program control statements:
 - Selection statements (if, ? operator, switch)
 - Iteration statements (for, while, do-while)
 - Empty statements (one or more “;”)
 - Jump statements (return, goto, break, continue, exit function)
 - Expression statements (function calls, assignment statements, operations, etc.)
 - Block statements
- An executable line of code may not contain the following statements:
 - Compiler directives
 - Data declaration (data) lines
 - Whole line comments, including empty comments and banners
 - Blank lines

2. Checklist for source statement counts

<u>PHYSICAL SLOC COUNTING RULES</u>			
MEASUREMENT UNIT	ORDER OF PRECEDENCE	PHYSICAL SLOC	COMMENTS
Executable Lines	1	One Per line	Defined in 1.8
Non-executable Lines			
Declaration (Data) lines	2	One per line	Defined in 1.4
Compiler Directives	3	One per line	Defined in 1.5
Comments			Defined in 1.7
On their own lines	4	Not Included (NI)	
Embedded	5	NI	
Banners	6	NI	
Empty Comments	7	NI	
Blank Lines	8	NI	Defined in 1.6

<u>LOGICAL SLOC COUNTING RULES</u>				
NO.	STRUCTURE	ORDER OF PRECEDENCE	LOGICAL SLOC RULES	COMMENTS
R01	"for", "while" or "if" statement	1	Count Once	"while" is an independent statement.
R02	<i>do {...} while (...); statement</i>	2	Count Once	Braces {...} and semicolon ; used with this statement are not counted.
R03	Statements ending by a semicolon	3	Count once per statement, including empty statement	Semicolons within "for" statement are not counted. Semicolons used with R01 and R02 are not counted.
R04	Block delimiters, braces {...}	4	Count once per pair of braces {...}, except where a closing brace is followed by a semicolon, i.e. }; or an opening brace comes after a keyword "else".	Braces used with R01 and R02 are not counted. Function definition is counted once since it is followed by {...}.
R05	Compiler Directive	5	Count once per directive	

3. Examples

EXECUTABLE LINES

SELECTION Statement

ESS1 – if, else if, else and nested if statements

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
if (<boolean expression> <statements>;	if (x != 0) printf ("non-zero");	1 1
if (<boolean expression>) <statement>; else <statement>;	if (x > 0) printf ("positive"); else printf ("negative");	2 1
if (<boolean expression> <statements>; else if (<boolean expression> <statements>; . . else <statements>;	if (x == 0) printf ("zero"); else if (x > 0) printf ("positive"); else printf ("negative");	1 1 1 1 0 1
if (<boolean expression> { <statements>; } else { <statements>; }	if ((x != 0) && (x > 0)) printf ("%d", x); if (x != 0) { printf ("non-zero"); } else { printf ("zero"); }	1 1 1 0 0 0 1 0
NOTE: complexity is not considered, i.e. multiple "&&" or " " as part of the expression.		

ESS2 – ? operator

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
Exp1?Exp2:Exp3	x > 0 ? printf ("+") : printf ("-");	1

ESS3 – switch and nested switch statements

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
<pre>switch (<expression>) { case <constant 1> : <statements>; break; case <constant 2> : <statements>; break; case <constant 3> : <statements>; break; default <statements>; }</pre>	<pre>switch (number) { case 1: case 11: foo1(); break; case 2: foo2(); break; case 3: foo3(); break; default printf ("invalid case"); }</pre>	<pre>1 0 0 0 1 1 0 1 1 0 1 0 1 0</pre>

ESS4 – try-catch

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
<pre>try {} catch() {}</pre>	<pre>try { cout << "Calling func \n"; } Catch(IOException e) { cout << "Error: " << e; }</pre>	<pre>1 0 1 0 1 0 1 0</pre>

ITERATION Statement**EIS1 – for**

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
<pre>for (initialization; condition; increment) statement;</pre> <p>NOTE: “for” statement counts as one, no matter how many optional expressions it contains, i.e.</p> <pre>for (i = 0, j = 0; i < 5, j < 10; i++, j++)</pre>	<pre>for (i = 0; i < 10; i++) printf ("%d", i);</pre> <pre>for (i = 0; i < 10; i++) { printf ("%d", i); }</pre>	<pre>1 1</pre> <pre>1 0 1 0</pre>

EIS2 – empty statements (could be used for time delays)

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
for (i = 0; i < SOME_VALUE; i++) ;	for (i = 0; i < 10; i++) ;	2

EIS3 – while

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
while (<boolean expression>) <statement>;	while (i < 10) { printf ("%d", i); i++; }	1 0 1 1 0

EIS4 – do-while

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
do { <statements>; } while (<boolean expression>;	do { ch = getchar(); } while (ch != '\n');	0 0 1 1

JUMP Statement**EJS1 – return**

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
return expression	If (i=0) return;	2

EJS2 – goto, label

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
goto label;	loop1: x++; if (x < y) goto loop1;	0 1 2

EJS3 – break

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
break;	if (i > 10) break;	2

EJS4 – exit function

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
void exit (int return_code);	if (x < 0) exit (1);	2

EJS5 – continue

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
continue;	<pre>while (!done) { ch = getchar(); if (char == '\n') { done = true; continue; } }</pre>	<pre>1 0 1 1 0 1 1 0 0</pre>

EXPRESSION Statement**EES1 – function call**

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
<function_name> (<parameters>);	read_file (name);	1

EES2 – assignment statement

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
<name> = <value>;	<pre>x = y; char name[6] = "file1"; a = 1; b = 2; c = 3;</pre>	<pre>1 1 3</pre>

EES3 – empty statement (is counted as it is considered to be a placeholder for something to call attention)

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
one or more “;” in succession	;	1 per each

BLOCK Statement**EBS1 – block=related statements treated as a unit**

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
<pre>/* start of block */ { <definitions> <statement> } /* end of block */</pre>	<pre>/* start of block */ { i = 0; printf ("%d", i); } /* end of block */</pre>	<pre>0 0 1 1 1 0</pre>

DECLARATION OR DATA LINES**DDL1 – function prototype, variable declaration, struct declaration, typedef**

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
<type> <name> (< parameter_list>);	void foo (int param);	1
<type> <name>;	double amount, price;	1
	int index;	1
struct <name>	struct S	0
{	{	0
<type> <name>;	int x;	1
<type> <name>;	int y;	1
}	};	1
struct	struct	0
{	{	0
<type> <name>;	int x;	1
<type> <name>;	int y;	1
} <name>;	} S;	2
typedef <type> <name>;	typedef int MY_INT;	1
typedef struct <name>	typedef struct S	0
{	{	0
<type> <name>;	int i;	1
...	char ch;	1
} <struct_name>;	} <struct_name>;	2
using namespace <name>	using namespace std;	1
<type> <name> (< parameter_list>)	void main()	0
{	{	0
...	printf("hello");	1
}	}	1

COMPILER DIRECTIVES**CDL1 – directive types**

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
#define <name> <value>	#define MAX_SIZE 100	1
#include <library_name>	#include <stdio.h>	1

4. Cyclomatic Complexity

Cyclomatic complexity measures the number of linearly independent paths through a program. It is measured for each function, procedure, or method according to each specific program language. This metric indicates the risk of program complexity and also determines the number of independent test required to verify program coverage.

The cyclomatic complexity is computed by counting the number of decisions plus one for the linear path. Decisions are determined by the number of conditional statements in a function. A function without any decisions would have a cyclomatic complexity of one. Each decision such as an if condition or a for loop adds one to the cyclomatic complexity.

The cyclomatic complexity metric $v(G)$ was defined by Thomas McCabe. Several variations are commonly used but are not included in the UCC. The modified cyclomatic complexity counts select blocks as a single decision rather than counting each case. The strict or extended cyclomatic complexity includes boolean operators within conditional statements as additional decisions.

Cyclomatic Complexity	Risk Evaluation
1-10	A simple program, without much risk
11-20	More complex, moderate risk
21-50	Complex, high risk program
> 50	Untestable program, very high risk

For C/C++, the following table lists the conditional keywords used to compute cyclomatic complexity.

Statement	CC Count	Rationale
if	+1	if adds a decision
else if	+1	else if adds a decision
else	0	Decision is at the if statement
switch case	+1 per case	Each case adds a decision – not the switch
switch default	0	Decision is at the case statements
for	+1	for adds a decision at loop start
while	+1	while adds a decision at loop start or at end of do loop
do	0	Decision is at while statement – no decision at unconditional loop
try	0	Decision is at catch statement
catch	+1	catch adds a decision
ternary ? :	+1	Ternary ? adds a decision – : is similar to default or else