Lecture given at the

WCS Workshop on Land Change Modeling for REDD

October 25–29, 2010

Wildlife Conservation Society - Bronx Zoo Bronx, New York, USA

Hosted by

Clark Labs and the Wildlife Conservation Society



This workshop was generously supported by the American people through the United States Agency for International Development (USAID), under the terms of the TransLinks Cooperative Agreement No.EPP-A-00-06-00014-00 to the Wildlife Conservation Society (WCS). TransLinks is a partnership of WCS, The Earth Institute, Enterprise Works/VITA, Forest Trends and the Land Tenure Center. The contents are the responsibility of the authors and do not necessarily reflect the views of USAID or the United States government.



Introduction to Land Change Modeling for REDD







General Steps

- Develop Project Idea Note
- Discuss with host government
- Seek project development funding
- Project Design
- Creation of PDD
- Host Country Approval
- Project Validation
- Project Registration
- Project Implementation
- Verification
- Credit Issuance





Creation of PDD

- Standard set of VCS methodologies
- A number of organizations
- Modular
 - Carbon Pool Modules
 - Baseline Modules
 - Leakage Modules
 - Emission Modules
 - Net emission Modules
 - Monitoring Modules
 - Miscellaneous Modules
- Eventually Pre-Approved by VCS
- Fairly general open to interpretation





Baseline Development

- Carbon Pools
 - Usually around 3-5 carbon strata in a landscape
- Project Geography
 - Project area
 - Reference area
 - Leakage belt
- Monitoring deforestation
- Baseline Prediction




Some straight forward/some not



Baseline Prediction

- Expected deforestation in the absence of the project
 - additionality
- Integral in identifying the number of carbon credits the project can sell
 - Difference between expected baseline emissions and actual emissions at the end of crediting period
- Possibly the most difficult aspect to get right







Based on *very* conservative estimates





Project Geography









Baseline Development

- Past land cover analysis
 - Leads to land cover change maps
- Assessment of drivers
 - Drivers as spatial layers
- Develop model of change
- Predict future location of change
 - By carbon strata






Past Land Cover Analysis





Past Land Cover Analysis



Land Change Modeling for REDD Workshop - October, 2010



Past Land Cover Analysis

- Need a minimum of 2 dates
 - 3 realistically (2 periods of LC change)
- Dependent on good satellite images
 - Or existing data
- Ground truth data
- Remote sensing analyst familiar with landscape
- Standard RS techniques for land cover analysis
 - Potentially use updated methods



CLARK LABS Fairly simple classes




Drivers of Change








Drivers of Deforestation

- Landscape factors
- Human infrastructure
- Land tenure and management











- Intimate knowledge of landscape and local actors
- Threats assessments
- Convert drivers to spatial representations
 - Proximate causes
 - Growth in agriculture = distance to market





Models of Future Deforestation






Model of Future Deforestation


- Three step procedure
 - 1 Calibrate model
 - 2 Validate model
 - 3 Predict future land deforestation








2 Model Validation







Models


- Many models
- Range from simple to extremely complex
- No specific model specified
 - GEOMOD expert opinion based
 - LCM Logistic regression
- Good at predicting location of deforestation but not amount
- Testing other models more analytical
 - CART
 - Neural network

Model Of Change (p1, p2, p3, ..., pn)





Predicting Location






Predicted Location of Change


- Simply selects pixels with highest risk until "correct" number of pixels deforested
- Cannot account for stochastic occurrences
 - The deforestation patch far from a road or village







Actual Deforestation (1084 Km2) 2002 - 2008



Predicted Deforestation (1187 Km2) 2002 - 2008






Rates of Change

- Based on previous rates from Reference Region
- Extrapolated into future
- Regression analysis
 - Based on threats and historic change
- Modeling?
- Different VCS methodologies have suggest different algorithms









Land Change Modeling for REDD Workshop - October, 2010




Accuracy Assessment

- How do we assess the accuracy of models
 - Calibration validation stage
 - Predicted baselines
- Standard methods (RS methods)
 - Kappa stats
 - ROC curves
- Assess accuracy on a pixel by pixel basis





Accuracy



Pixel by pixel Results





Accuracy Assessment


- Might be better to look at accuracy across an area
 - Carbon strata
 - Grid
- How well do we predict change within that area
- Kappa by location





Scenario Development

- Predict LC change
 - Deforestation by carbon strata
- Different scenarios
 - Business as usual
 - Increasing deforestatic
 - New protected areas
 - Others



 Include final Baseline Prediction in PDD to represent carbon credits





Carbon Mis-Credits





Potential Problems

- Goals of any REDD project
 - Accuracy
 - Transparency
 - Repeatable
 - Cost effective
 - Conservative estimate
- If anybody ran the analysis, would the baseline model come out the same?
- More questions then answers





Potential Problems

- Logistical issues
 - Especially in past land cover and land cover change analysis
- Methodological issues
 - Mapping drivers
 - Predicting rates of change
 - Changes over time
 - Other methodological gaps
- The spatial domain






Remote Sensing

- Getting good images
 - Especially current
- Processing difficulties





Clouds






Scan Line Correction Error





Scan Line Correction





RS Potential Error Sources

- Mis-registration of images
- Pre/post processing
- Interpretation of land use/cover types
 - What is a forest?
 - Natural an anthropogenic non-forest
 - Grasslands





Other RS issues

- Accuracy assessment on historic images
- Remote sensing capacity in the field





Significant Gaps in Methodology

- Changing drivers
- Two Models or One?
 - Predict the rate of change
 - Predict the location of change
 - Can one model predict location and rate accurately?
- Location of predicted deforestation
- Time/Space
- Accuracy assessment
- What about degradation




- What methods do we use to identify most important drivers?
 - Threats assessment
- Change over time?
- Project drivers into future?
 - Create new risk map





Mapping drivers

- Do the threats we map actually represent drivers of deforestation?
- Rising agricultural prices



Scale of threats





Rates of Change

- We assume that past history informs future trends
- Based on previous rates from Reference Region
 - Are historic rates a good predictor of future rates?
 - Do 3 points in time provide a trend?
- Studies certainly show that rates are not linear through time
- What if a driver changes








Location of change

- Right now, based on that risk map
- But what about the farmer who finds a nice forested area away from villages or roads
- May not be significant but we should account for randomness in humans
- Use risk map as probability surface







The Time Factor


- Land cover change is non-stationary over time
 - Drivers will change
 - Rates will change
- But we base models of deforestation in the future on drivers and models from the past.
- Can cause significant differences in projected carbon credits available





Spatial Domain

- How do we know if we are picking the right Reference Region
- Does it represent the future Project Region in the absence of the project
 - Increasing road density
 - Increasing population density
- Or do they need similar attributes now
- Different methods have different recommendations
- Should Reference Area include Project Region
- In either case, can it be used to develop a deforestation scenario for the project area?





Not As Bad as it Seems

- Better understanding of models of change
 - Better baseline projections
 - Other conservation outcomes
- Approved methodology will help clarify issues
- Approved project to see how its done
- Working with partners and other organizations to develop standards
- **CLARK LABS** Ensure quality and reliability of models



Next Steps

- RS and modeling capacity in field
 - On-line training course
- Access to satellite images
 - ASTER SPOT or other sources beyond Landsat
- Final methodology to work with
- Continue to develop tools with partners
 - Other NGOs
 - Clark Labs
- Conference focused on models of change





Questions?

