




[Docs \(/guide\)](#)

[Docs \(/guide\)](#)

You are looking at documentation for an older release. Not what you want? See the current release documentation ([../current/index.html](#)).

[Filebeat Reference \[5.3\] \(index.html\)](#) » [Getting Started With Filebeat \(filebeat-getting-started.html\)](#) » **Step 2: Configuring Filebeat**

« [Step 1: Installing Filebeat \(filebeat-installation.html\)](#)

[Step 3: Configuring Filebeat to Use Logstash » \(config-filebeat-logstash.html\)](#)

Step 2: Configuring Filebeat

edit <https://github.com/elastic/beats/edit/5.3/filebeat/docs/getting-started.asciidoc>



Filebeat modules ([filebeat-modules-overview.html](#)) provide the fastest getting started experience for common log formats. See [Quick Start for Common Log Formats \(filebeat-modules-quickstart.html\)](#) to learn how to get started with modules. If you use Filebeat modules to get started, you can skip the content in this section, including the remaining getting started steps, and go directly to the [Quick Start for Common Log Formats \(filebeat-modules-quickstart.html\)](#) page.

To configure Filebeat manually, you edit the configuration file. For rpm and deb, you'll find the configuration file at `/etc/filebeat/filebeat.yml`. For mac and win, look in the archive that you just extracted. There's also a full example configuration file called `filebeat.full.yml` that shows all non-deprecated options.

See the [Config File Format \(http://www.elastic.co/guide/en/beats/libbeat/5.3/config-file-format.html\)](#) section of the *Beats Platform Reference* for more about the structure of the config file.

Here is a sample of the `filebeat` section of the `filebeat.yml` file. Filebeat uses predefined default values for most configuration options.

```
filebeat.prospectors:  
- input_type: log  
  paths:  
    - /var/log/*.log  
    #- c:\programdata\elasticsearch\logs\*
```

To configure Filebeat:

1. Define the path (or paths) to your log files.

For the most basic Filebeat configuration, you can define a single prospector with a single path. For example:

```
filebeat.prospectors:  
- input_type: log  
  paths:  
    - /var/log/*.log
```

The prospector in this example harvests all files in the path `/var/log/*.log`, which means that Filebeat will harvest all files in the directory `/var/log/` that end with `.log`. All patterns supported by Golang Glob

(<https://golang.org/pkg/path/filepath/#Glob>) are also supported here.

To fetch all files from a predefined level of subdirectories, the following pattern can be used: `/var/log/*/*.log`. This fetches all `.log` files from the subfolders of `/var/log`. It does not fetch log files from the `/var/log` folder itself. Currently it is not possible to recursively fetch all files in all subdirectories of a directory.

2. If you are sending output to Elasticsearch, set the IP address and port where Filebeat can find the Elasticsearch installation:

```
output.elasticsearch:  
  hosts: ["192.168.1.42:9200"]
```

If you are sending output to Logstash, see Step 3: Configuring Filebeat to Use Logstash ([config-filebeat-logstash.html](#)) instead.



To test your configuration file, change to the directory where the Filebeat binary is installed, and run Filebeat in the foreground with the following options specified: `./filebeat -configtest -e` Make sure your config files are in the path expected by Filebeat (see [Directory Layout \(directory-layout.html\)](#)). If you installed from DEB or RPM packages, run `./filebeat.sh -configtest -e`.

Before starting Filebeat, you should look at the configuration options in the configuration file, for example `C:\Program Files\Filebeat\filebeat.yml` or `/etc/filebeat/filebeat.yml`. For more information about these options, see *Configuration Options (Reference)* ([filebeat-configuration-details.html](#)).

« [Step 1: Installing Filebeat \(filebeat-installation.html\)](#)

[Step 3: Configuring Filebeat to Use Logstash \(config-filebeat-logstash.html\)](#) »

Top Videos

- [Elasticsearch Demo \(https://www.elastic.co/webinars/getting-started-elasticsearch?baymax=default&elektra=docs&storm=top-video\)](https://www.elastic.co/webinars/getting-started-elasticsearch?baymax=default&elektra=docs&storm=top-video)
- [Kibana 101 \(https://www.elastic.co/webinars/getting-started-kibana?baymax=default&elektra=docs&storm=top-video\)](https://www.elastic.co/webinars/getting-started-kibana?baymax=default&elektra=docs&storm=top-video)
- [Logstash Primer \(https://www.elastic.co/webinars/getting-started-logstash?baymax=default&elektra=docs&storm=top-video\)](https://www.elastic.co/webinars/getting-started-logstash?baymax=default&elektra=docs&storm=top-video)

Filebeat Reference: 5.3 ▼
Overview (filebeat-overview.html)
Getting Started With Filebeat (filebeat-getting-started.html) <ul style="list-style-type: none"> Step 1: Installing Filebeat (filebeat-installation.html) Step 2: Configuring Filebeat (filebeat-configuration.html) Step 3: Configuring Filebeat to Use Logstash (config-filebeat-logstash.html) Step 4: Loading the Index Template in Elasticsearch (filebeat-template.html) Step 5: Starting Filebeat (filebeat-starting.html) Step 6: Loading the Kibana Index Pattern (filebeat-index-pattern.html) Quick Start for Common Log Formats (filebeat-modules-quickstart.html) Command Line Options (filebeat-command-line.html) Directory Layout (directory-layout.html) Repositories for APT and YUM (setup-repositories.html)
Upgrading Filebeat (upgrading-filebeat.html)
How Filebeat Works (how-filebeat-works.html)
Configuring Filebeat (configuring-howto-filebeat.html)
Modules (filebeat-modules.html)