AI Driven Cyber Deception and Attack Detection Framework

Project Website and Demonstration Documentation

Group 58
Project Guide Dr. Radhika G.
Prepared 25 October 2026

This document presents our cyber deception project, its architecture, the deployed demonstration and the project website. The live browser test confirmed event classification, storage and a backend-reported blockchain anchor. A separate populated demonstration contains 1,228 explicitly simulated events for presentation purposes.

Project team

Name	Roll number
N.Sisir Reddy	CB.SC.U4CSE23129
C.Pranav Sharma	CB.SC.U4CSE23611
N.Surya Tejeswar Reddy	CB.SC.U4CSE23127
B.Guru Sai Prasad Reddy	CB.SC.U4CSE23111
R.Vishnu Satwick Reddy	CB.SC.U4CSE23644

Submission links

Project website
https://honeypot-dashboard-tau.vercel.app/showcase/

Live dashboard
https://honeypot-dashboard-tau.vercel.app/

Populated simulated demonstration
https://honeypot-dashboard-tau.vercel.app/?demo=1

Source repository
https://github.com/Deceptive-HoneyPot/CODE

Project purpose and scope

The framework provides decoy services that resemble systems attackers may encounter. It records interactions so researchers can inspect activity without using genuine business data. AI-generated responses are intended to improve the variety and plausibility of the deception. The project is a research prototype, not a production intrusion prevention system.

Five honeypot services

Service	Purpose
Shadow Shell	SSH shell and login interaction capture
Oracle AI	Internal AI API and prompt injection observation
Vault SQL	Database query imitation and synthetic records
Ledger Trap	Ethereum JSON RPC interface imitation
Forge CI	Jenkins style build automation imitation

System architecture

Incoming interaction → Proxy → Selected decoy → AI response engine as needed
Decoy event → FastAPI backend → Rule based classification → SHA 256 hash
Backend → Redis event storage and Ganache hash anchoring
Backend → WebSocket broadcast → React dashboard

The AI engine uses three response tiers: a static response dictionary, Redis cache and an OpenRouter hosted model. The backend also contains a separate AI verdict endpoint. The standard logging endpoint uses keyword rules; this distinction matters when interpreting the verified demonstration.

Technology stack


Layer	Technology
Frontend	React 18 and WebSocket
API and decoys	Python and FastAPI with service specific libraries
Storage and cache	Redis compatible storage
Evidence	SHA 256 and local Ganache Ethereum test chain
AI response provider	OpenRouter when configured
Deployment	Vercel frontend and Render backend services

Hosted demonstration verification

Verification date 25 October 2026. The backend health endpoint returned status ok, redis true and blockchain true. The browser showed Live feed connected and Chain anchoring active.

Check	Observed result
Sample text	uname -a && whoami && hostname
Submission	Logged
Intent	reconnaissance
Hash prefix	0cb6e46587d7
Backend anchor status	anchored on chain
Live feed	Matching event displayed as Anchored

The event was submitted using the dashboard Try an attack form and was marked simulated by that form. The payload was processed as text. This test did not execute a shell command on a target machine or traverse a real SSH decoy.



Captured live feed showing the newly submitted reconnaissance event and its Anchored label.

What the verification establishes

The test establishes that the browser can submit a sample event, receive a classification and anchor status, and display the event in the feed. It does not independently verify an Ethereum transaction receipt, validate AI response quality or prove that all five network decoys are publicly reachable.

Populated presentation dataset

The populated demonstration is a browser side fixture containing 1,228 simulated events. Its counts are illustrative and are not measured attack statistics. The dataset does not write to Redis, call the backend or claim blockchain anchoring.

Honeypot category	Simulated events
SSH	402
SQL database	319
CI CD	239
AI API	169
Web3 node	99
Total	1228

When sorted from largest to smallest, adjacent differences are 83, 80, 70 and 70 events. Therefore every pair of category totals differs by at least 70. Source addresses use a documentation range. Event timestamps are generated for the current presentation session.

Demonstration sequence

• Open the project website and introduce the problem and five decoy designs.

• Open the populated demonstration and identify its SIMULATED DATA label. Explain the distribution across five services.

• Switch to the live backend view. Wait for the feed to connect if the free service is waking.

• Open Try an attack and submit the Recon on a fresh shell sample.

• Confirm Logged, reconnaissance and anchored on chain when available, then locate the new event in the live feed.

• Explain the limits of a local test blockchain and close with the team and project guide.

Narrated video

The accompanying MP4 uses synthesized English narration and actual interface screenshots. It is an edited walkthrough, not an uninterrupted screen recording. It distinguishes the illustrative dataset from the separately verified live submission. Captions and a text transcript accompany the video.

Setup and operation

For local use, install Git and Docker with Compose. Clone the repository, copy .env.example to .env, configure required provider credentials locally and run docker compose up --build. Open http://localhost:3000. See the repository README for detailed service configuration and platform requirements.

Deployment arrangement

The React frontend is hosted on Vercel. The team Render dashboard showed honeypot backend and honeypot AI engine as deployed, with honeypot Redis available in Singapore. The backend public URL is https://honeypot-backend-rcqz.onrender.com. The showcase assets live in dashboard/public/showcase and are included in the frontend build.

Limitations

• Ganache is a local development blockchain. Its in memory state can reset when the container restarts. Hash anchoring here is not permanent public chain notarization.

• Hashes help detect changes relative to a trusted commitment; they do not establish that an original event was genuine.

• Free services can sleep, restart or reach usage limits. A successful check is a point in time observation, not an uptime guarantee.

• The browser sample form bypasses the network decoys. The deployed test did not validate all five protocol services or the AI model path.

• The three historical records seen before the verification were labelled Local. They were not retroactively treated as anchored.

• AI providers can have usage costs and availability limits independent of frontend hosting.

References

Project repository and README
https://github.com/Deceptive-HoneyPot/CODE

Implementation references: backend/main.py, backend/ai_classifier.py, ai-engine, dashboard/src, render.yaml and backend/start-render.sh. The source revision reviewed before these presentation changes was ba890ce.