

CSE4080 - Blockchain Technology


Lab Experiment 4

Task: Create a solidity based smart contract


Solidity programming:

Use remix IDE - Remix is a Solidity IDE that's used to write, compile and debug Solidity code. Solidity is a high-level, contract-oriented programming language for writing smart contracts.

Open remix.ethereum.org in the browser.




In default_workspace – contracts folder – create your file MyContract.sol (Use file icon)




Ensure solidity compiler is in auto-compile mode as follows: If not select the compiler icon highlighted in red and check auto-compile

CSE4080 - Blockchain Technology

Lab Experiment 4




Creating smart contract:




Select Solidity Compiler: (icon with green tick and has tooltip solidity compiler in the leftmost)

CSE4080 - Blockchain Technology

Lab Experiment 4



Click Compilation details button and observe generated bytecodes of smart contract



Click other links and study

.....


The smart contract you developed is auto-compiled and the bytecodes are generated.

.....


Now we need to interact with the smart contract. So normally we need cryptowallet like metamask. However, remix provides an inprocess and free deployment. This is the icon below solidity compiler.

CSE4080 - Blockchain Technology

Lab Experiment 4



Observe the environment: Remix VM




There is account, gas limit and ether value to work with.


Now select Remix VM London and deploy. Observe Deployed Contracts:

CSE4080 - Blockchain Technology

Lab Experiment 4



Click on the transaction in the transaction log to see details:



Now let us run the Smart Contract:


Select an account.

Deploy - Click


ourString - Click

CSE4080 - Blockchain Technology

Lab Experiment 4



Observe below ourString- Hello World is displayed i.e Smart Contract is running
Observe transaction log that suggests Smart contract created and called:




.....END.....


CSE4080 - Blockchain Technology

Lab Experiment 4


Adding a function in smart contract:



Deploy:



Check transaction log for the function being called:





.....END.....

CSE4080 - Blockchain Technology

Lab Experiment 4

Datatypes:




Observe increment8 was clicked 6 times and hence a range error is displayed.


Called increment256 twice then call myUint256

CSE4080 - Blockchain Technology

Lab Experiment 4





Similarly for int called `increment_int` thrice and then `myInt`



CSE4080 - Blockchain Technology

Lab Experiment 4


String manipulation:




CSE4080 - Blockchain Technology

Lab Experiment 4


Bytes:



Address-stores 20bytes of Ethereum address




- ✓ Copy the address on deploy-account
- ✓ Let this copied address be the argument of setSomeAddress
- ✓ Then click getBalance()




CSE4080 - Blockchain Technology


Lab Experiment 4



msg.sender will have the account address that interacted with the contract




Now click updatesomeAddress and then someAddress msg.sender picks the account address associated with this contract (see the account address above it will be the same).




CSE4080 - Blockchain Technology

Lab Experiment 4

Reading and writing functions:
getter function




Another 2 types of reading functions are view and pure
view can read storage variable or a variable with global scope. Pure function can read only local variable.




Function for writing. This function will be in orange color.

CSE4080 - Blockchain Technology

Lab Experiment 4



Constructor – will be called only once
Normally first address will be 00000 and then you assign. But constructor will assign at creation. So copy paste address near deploy it self. Then use myAddress.




.....END.....


CSE4080 - Blockchain Technology

Lab Experiment 4

Blockchain messenger:




updateTheMessage then see the other values.




.....END.....

CSE4080 - Blockchain Technology Lab Experiment 4

Smart Money deposit and withdrawals:




Click sandwich icon in metamask and check the transaction on etherscan




Now to transact from one account to another:

CSE4080 - Blockchain Technology

Lab Experiment 4




click send button-add account2 address and transact .001 ethers




Transaction pending to be added in blockchain:

CSE4080 - Blockchain Technology


Lab Experiment 4



Now added to blockchain




Remix and the Injected Web3 Provider:
Create a new smart contract:




CSE4080 - Blockchain Technology

Lab Experiment 4



- Rightclick metamask- manage extension – developer mode on – update
- Reload
- Now you can connect with injected web3.




Select account:


- ✓ Next connect
- ✓ Now account address will reflect in metamask
- ✓ Deploy

CSE4080 - Blockchain Technology

Lab Experiment 4



Confirm




When you click updateString a call is made and the data - Dechen Dorji 20BPS1156 is maintained in the transaction


CSE4080 - Blockchain Technology

Lab Experiment 4

Block created



Click myString it will not call the metamask as it is read only and not write



.....END.....