ICPC Team Notebook

1 Template **1**
- 1.1 Contest Template . . . 1
- 1.2 Debug Checklist . . . 1

2 Data Structures **1**
- 2.1 Short Segment Tree . . . 2
- 2.2 Fenwick Tree . . . 2
- 2.3 Monotonic Stack and Queue . . . 2
- 2.4 Disjoint Set Union . . . 3
- 2.5 Sqrt Decomposition . . . 3
- 2.6 Lazy Segment Tree . . . 4
- 2.7 Sparse Table . . . 5
- 2.8 Persistent Segment Tree . . . 6
- 2.9 Line Container . . . 6
- 2.10 Short Segment Tree Beats . . . 7
- 2.11 Full Segment Tree Beats . . . 8
- 2.12 Segment Tree Beats Invariants . . . 8
- 2.13 DSU on Segment Tree . . . 9
- 2.14 Cartesian Tree . . . 9
- 2.15 Implicit Treap . . . 10
- 2.16 Mo's Algorithm . . . 11
- 2.17 Link-Cut Tree . . . 11
- 2.18 Link-Cut Tree Operations . . . 12
- 2.19 Wavelet Tree . . . 13
- 2.20 Priority Queue with Delete . . . 14
- 2.21 Two-Stack Aggregate Queue . . . 14

3 String **15**
- 3.1 Rolling Hash . . . 15
- 3.2 KMP Prefix Function . . . 15
- 3.3 Tries . . . 15
- 3.4 Manacher . . . 16
- 3.5 Suffix Array . . . 16
- 3.6 Kasai LCP . . . 17
- 3.7 Suffix Automaton . . . 17
- 3.8 Palindromic Tree (Eertree) . . . 18
- 3.9 Minimum Rotation . . . 19
- 3.10 Z Function . . . 19
- 3.11 Aho-Corasick . . . 19

4 Graph **21**
- 4.1 Dinic Max Flow . . . 21
- 4.2 Maximum-Weight Closure . . . 21
- 4.3 Min-Cut Modeling Recipes . . . 22
- 4.4 Dijkstra . . . 22
- 4.5 Multi-source and 0-1 BFS . . . 23
- 4.6 Kuhn Bipartite Matching . . . 23
- 4.7 LCA Binary Lifting . . . 24
- 4.8 Topological Sort . . . 25
- 4.9 Functional Graph . . . 25
- 4.10 Heavy Light Decomposition . . . 25
- 4.11 Bridges and Articulation Points . . . 26
- 4.12 Rerooting DP . . . 27
- 4.13 Centroid Decomposition . . . 27
- 4.14 CDQ 3D Dominance . . . 28
- 4.15 Min Cost Flow . . . 29
- 4.16 Strongly Connected Components . . . 30
- 4.17 DSU on Tree Sack . . . 30
- 4.18 Virtual Tree . . . 31
- 4.19 Deterministic Tree Canonization . . . 31
- 4.20 Bellman–Ford / Difference Constraints 31
- 4.21 Kruskal MST . . . 32
- 4.22 Block-Cut Tree . . . 32
- 4.23 2-SAT . . . 33
- 4.24 Floyd–Warshall . . . 34
- 4.25 Euler Walk . . . 34
- 4.26 Offline Dynamic Connectivity . . . 35
- 4.27 Hungarian Assignment . . . 36
- 4.28 Kruskal Reconstruction Forest . . . 36
- 4.29 Global Min Cut . . . 37
- 4.30 Maximum Clique . . . 37

5 Math **39**
- 5.1 Number Theory Essentials . . . 39
- 5.2 FFT . . . 39
- 5.3 FFT Mod . . . 40
- 5.4 NTT . . . 40
- 5.5 Formal Power Series . . . 41
- 5.6 FPS Newton Formulas . . . 41

5.7 Inclusion–Exclusion 42
5.8 Inclusion–Exclusion Formulas 42
5.9 Counting and Number Theory Formulas 43
5.10 Matrix Power 45
5.11 Zeta and Mobius Transforms 45
5.12 Sieve 46
5.13 Gaussian Elimination mod p 46
5.14 XOR Linear Basis 46
5.15 Floor Sum 47
5.16 Floor-Sum Notes 47
5.17 Catalan Numbers 47
5.18 Mobius Sieve 48
5.19 Mobius Inversion Notes 48
5.20 Sprague–Grundy 48
5.21 Lucas Theorem 49
5.22 Lucas and Kummer 49
5.23 Primitive Root 49
5.24 Discrete Log 50
5.25 Discrete kth Roots mod Prime 50
5.26 Mod Inverse Table 51
5.27 Miller Rabin and Pollard Rho 51
5.28 Lagrange Interpolation 52
5.29 Lagrange Formula 52
5.30 CRT 52
5.31 Floating Simplex 53
5.32 Simplex Modeling 53
5.33 XOR FWHT 54
5.34 Fraction Finder 54

6 Geometry **55**
6.1 Geometry Base 55
6.2 Exact Integer Geometry Kit 55
6.3 Convex Hull and Geometry Routines . 56
6.4 Point in Convex Polygon 58
6.5 Half-Plane Intersection 58
6.6 Circle Tangents 59
6.7 Minkowski Sum 59
6.8 Closest Pair 60
6.9 Rectangle Union Area 60
6.10 Sweep-Line Event Ordering 61
6.11 Minimum Enclosing Circle 61
6.12 Concave Max-Plus Convolution 62

7 Dynamic Programming **63**
7.1 Fast Knapsack and Subset Sum 63
7.2 Fast Knapsack Formulas 64
7.3 Bitmask DP 64
7.4 Bitmask DP Formulas 64
7.5 Digit DP 65
7.6 Digit DP State Design 65
7.7 Longest Increasing Subsequence 65
7.8 Meet in the Middle 66
7.9 Slope Trick 66
7.10 Slope Trick Formulas 67
7.11 Lagrangian Relaxation (Aliens/WQS) 67
7.12 Lagrangian Relaxation Proof 67
7.13 Divide and Conquer DP 68
7.14 Divide and Conquer DP Notes 68
7.15 k Smallest Subset Sums 68
7.16 Knuth Optimization 69

8 Misc **70**
8.1 Quick Local Test Script 70
8.2 Stress Test Kit 70
8.3 Python Brute Force Recipes 70
8.4 In-Process Stress Test 73
8.5 Interactive Grader Helper 73
8.6 mt19937 RNG 74
8.7 mt19937_64 RNG 74
8.8 Random Hashing 74
8.9 Zobrist Hashing 74
8.10 Quick Select 75
8.11 GNU Extensions 75
8.12 Parallel Binary Search 75
8.13 Custom Hash for unordered_map . . . 76
8.14 Deep Recursion Stack 76

9 Hacks **77**
9.1 Shared Setup 77
9.2 Berlekamp–Massey and Nth Term . . 77
9.3 Tutte Matrix Matching Size 78
9.4 Small-Budget Vertex Cover 78
9.5 Color-Coding for Short Paths 79
9.6 Bit-Parallel LCS Length 79
9.7 Bitmask Exact Cover 79
9.8 Posa Rotations 80
9.9 Shuffled Window Subset Sum 80
9.10 Schoning Randomized 3-SAT 81
9.11 General Lagrange Interpolation 82
9.12 Connected Subsets with One Centroid 82

10 Appendix **83**
10.1 Binomial (auto-extend) 83
10.2 Block-Cut Tree Query Driver 83
10.3 Critical Cities Dominator 83
10.4 Randomized Hill Climbing Skeleton . . 85

1 Template

1.1 Contest Template

Use: Default C++17 starting file.
Complexity: $O(1)$ setup.
Pitfalls: Uses `#define int long long`; remove multi-test loop if input has one case. Current return expression is intentional source text.
Assumptions/deps: Includes `bits/stdc++.h`, macros, and `solve()`.

```cpp
#include<bits/stdc++.h>
using namespace std;
#define int long long
#define all(x) (x).begin(), (x).end()
#define rep(i, a, b) for(int i = (a); i < (b); i++)
#define repd(i, a, b) for(int i = (a); i >= (b); i--)
#define hha(x) cout << #x << " = " << x << " "
#define hhal(x) cout << #x << " = " << x << endl
#define print(a) cout << #a << " = "; for(auto x: a) cout << x << " "; cout << endl;
void solve()
{

}
signed main()
{
    ios::sync_with_stdio(0); cin.tie(NULL);
    int t; cin >> t; while(t--)
    solve();
    return 8 >> 13;
}
```

1.2 Debug Checklist

Use: Before submit, after a WA, RE/TLE/MLE, and one line per member.
Complexity: Checklist.
Pitfalls: Use before rewriting blindly; each WA costs 20 minutes.
Assumptions/deps: Built from our own wrong runs (`team_bugs.md`); stress kit in Misc.

Before submit

- Samples pass; output format exact.
- Constants copied from the statement: modulus, limits.
- Overflow: products of inputs need `__int128`; INF above every answer.
- Array sizes ($2n$, $n+1$); time and memory estimated.
- Edges: $n = 1$, zeros, all equal, $k = n$, empty part.
- Globals reset per test; debug prints and loop caps removed.
- Unproven greedy or formula: stress test first.

After a WA

- Two WAs: stop. Stress test, or a teammate reads it cold.
- Resubmit only a found bug, never the same code.
- Print the state on the smallest failing test.
- Off-by-one, ties (`<` or `<=`), duplicates, unreachable states.
- `priority_queue` is a max-heap; comparators must be strict.
- Wrong model: rewrite from the invariant, do not patch.

RE, TLE, MLE

- **RE:** out of bounds, zero division, bad iterators, recursion depth.
- **TLE:** hidden nested work, container copies, slow I/O, hash attacks.
- **MLE:** count $\times$ 8 bytes, recursion stack, not clearing between tests.

Per member

- **Dedi:** samples first; constants aloud; casework on paper; flush queries.
- **Erdene:** model checked on samples; `__int128` on 64-bit g++; definitions literal.
- **Tamir:** ties in stacks and sorts; verify the full answer; zero parameters.

Known killers

- Hashing mod 2^{64} by overflow: Thue-Morse pairs collide. Use the mod $2^{61}-1$ hash.
- Default `unordered_map/set` can be attacked: use `chash` (Custom Hash).
- 10^6 nested recursive calls overflow an 8 MB stack: `raise_stack()` or iterate.
- Kuhn is $O(VE)$ and fails on dense adversarial graphs: unit-capacity Dinic.
- Large FFT coefficients lose precision: prefer NTT or FFT-mod.
- `rand()` and `random_shuffle` are banned: use `mt19937`.

2 Data Structures

2.1 Short Segment Tree

Use: Iterative point set and ordered range query.
Complexity: Build $O(n)$, set/query $O(\log n)$; memory $O(n)$.
Pitfalls: Half-open `[l,r)`; associative op with identity. Use `query(0,n)`, not `t[1]`, for ordered full queries.
Assumptions/deps: `ShortST s; s.build(a); s.set(p,x); s.query(l,r);`. Edit `V,op,ID`.

```cpp
// Iterative segment tree: point set and ordered range query [l,r).
// Build O(n), set/query O(log n), memory O(n).
// Edit V, op and ID; op must be associative, ID its identity.
// Pitfalls: 0 <= l <= r <= n; set needs p < n; arithmetic must fit V.
// For noncommutative ops, use query(0,n), not t[1], for the full result.
// Example: ShortST s; s.build({1,2,3}); s.set(1,5); // query(0,3)==9
struct ShortST {
    using V = long long;
    static constexpr V ID = 0;
    static V op(V a, V b) { return a + b; }
    int n;
    vector<V> t;
    ShortST(int n = 0) : n(n), t(2*n, ID) {}
    void build(const vector<V>& a) {
        n = a.size();
        t.assign(2*n, ID);
        copy(a.begin(), a.end(), t.begin() + n);
        for (int i = n-1; i > 0; --i) t[i] = op(t[2*i], t[2*i+1]);
    }
    void set(int p, V x) {
        for (t[p += n] = x; p >>= 1; ) t[p] = op(t[2*p], t[2*p+1]);
    }
    V query(int l, int r) {
        V left = ID, right = ID;
        for (l += n, r += n; l < r; l >>= 1, r >>= 1) {
            if (l&1) left = op(left, t[l++]);
            if (r&1) right = op(t[--r], right);
        }
        return op(left, right);
    }
};
```

2.2 Fenwick Tree

Use: Prefix sums, range sums, kth by prefix.
Complexity: All operations $O(\log n)$.
Pitfalls: External indices are 0-based; `lower_bound` needs nonnegative frequencies.
Assumptions/deps: Uses `long long`; half-open query `[l,r)`.

```cpp
// Fenwick tree for prefix sums.
// Complexity: add/sum/rangeSum/lower_bound are O(log n).
// Pitfalls: external indices are 0-based; lower_bound assumes all values nonnegative.
// add(i,x) increments a[i]; sumPrefix(r) sums a[0..r), and rangeSum(l,r)
// sums a[l..r). lower_bound(s) finds the first index whose inclusive prefix
// reaches s (or n if none).
// Example: Fenwick f(3); f.add(0,2); f.add(2,5); f.rangeSum(1,3)==5;
// f.lower_bound(3)==2.
struct Fenwick {
    int n;
    vector<long long> bit;
    Fenwick(int n = 0) { init(n); }
    void init(int n_) {
        n = n_;
        bit.assign(n + 1, 0);
    }
    void add(int idx, long long val) {
        for (++idx; idx <= n; idx += idx & -idx) bit[idx] += val;
    }
    long long sumPrefix(int r) {
        long long res = 0;
        for (; r > 0; r -= r & -r) res += bit[r];
        return res;
    }
    long long rangeSum(int l, int r) {
        return sumPrefix(r) - sumPrefix(l);
    }
    int lower_bound(long long need) {
        // first idx with sumPrefix(idx+1) >= need, or n if total < need
        if (need <= 0) return 0;
        int idx = 0;
        for (int step = n ? 1LL << __lg(n) : 0; step; step >>= 1) {
            int next = idx + step;
            if (next <= n && bit[next] < need) {
                idx = next;
                need -= bit[next];
            }
        }
        return idx;
    }
};
```

2.3 Monotonic Stack and Queue

Use: Nearest-smaller boundaries and sliding-window maximum.
Complexity: $O(n)$.

Pitfalls: Duplicate tie rule is left $<$ and right $\leq$; change comparisons deliberately.
Assumptions/deps: 0-indexed; deque stores indices.

```cpp
// Monotonic stack boundaries and sliding-window maximum.
// Complexity: O(n); every index enters and leaves once.
// Pitfalls: duplicate tie rule is asymmetric: left < a[i], right <= a[i].
// Usage: auto [left,right]=smaller_bounds(a); auto mx=sliding_max(a,k);
pair<vector<int>, vector<int>> smaller_bounds(const vector<long long>& a) {
    int n = (int)a.size();
    vector<int> left(n, -1), right(n, n), st;
    for (int i = 0; i < n; ++i) {
        while (!st.empty() && a[st.back()] >= a[i]) {
            right[st.back()] = i;
            st.pop_back();
        }
        if (!st.empty()) left[i] = st.back();
        st.push_back(i);
    }
    return {left, right};
}

vector<long long> sliding_max(const vector<long long>& a, int k) {
    if (k <= 0 || k > (int)a.size()) return {};
    deque<int> q;
    vector<long long> ans;
    for (int i = 0; i < (int)a.size(); ++i) {
        while (!q.empty() && q.front() <= i - k) q.pop_front();
        while (!q.empty() && a[q.back()] <= a[i]) q.pop_back();
        q.push_back(i);
        if (i + 1 >= k) ans.push_back(a[q.front()]);
    }
    return ans;
}
```

2.4 Disjoint Set Union

Use: Dynamic connectivity, Kruskal, components.
Complexity: Amortized $O(\alpha(n))$.
Pitfalls: Reinitialize per test case. `unite` returns false when already joined.
Assumptions/deps: 0-indexed; uses `vector`, `iota`.

```cpp
// Disjoint Set Union.
// Complexity: amortized O(alpha(n)).
// Pitfalls: init per test case; unite returns false if already same set.
// Operations: find(v) gives a representative; unite(a,b) merges components
// and says whether they were distinct; same/size query the current component.
// Example: DSU d(3); d.unite(0,2); d.same(0,2)==true; d.size(0)==2.
struct DSU {
    vector<int> p, sz;
    DSU(int n = 0) { init(n); }
    void init(int n) {
        p.resize(n);
        iota(p.begin(), p.end(), 0);
        sz.assign(n, 1);
    }
    int find(int x) {
        return p[x] == x ? x : p[x] = find(p[x]);
    }
    bool unite(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return false;
        if (sz[a] < sz[b]) swap(a, b);
        p[b] = a;
        sz[a] += sz[b];
        return true;
    }
    bool same(int a, int b) {
        return find(a) == find(b);
    }
    int size(int x) {
        return sz[find(x)];
    }
};
```

2.5 Sqrt Decomposition

Use: Range update/query with an editable operation block.
Complexity: Build $O(n)$; operations $O(\sqrt{n})$.
Pitfalls: Half-open ranges `[l,r)`; partial blocks push lazy tags.
Assumptions/deps: Default range add/range sum; edit only marked types/operations.

```cpp
// Sqrt decomposition. 0-indexed, half-open ranges [l,r). O(sqrt(n)) per op.
// To reuse for another operation, edit ONLY the marked block below.
// Configured for: range-add update, range-sum query.
// Pitfalls: applyVal must work for both one cell and a whole block;
// L needs equality with LID. Partial operations push the block tag.
// update(l,r,x) adds x to a[l..r); query(l,r) returns that range's sum.
// Example: SqrtDecomp s({1,2,3}); s.update(1,3,4); s.query(0,3)==14.
struct SqrtDecomp {
    // ---- customize for the operation ----------------------------------
    using V = long long;
    using L = long long;
    static constexpr V VID = 0;
    static constexpr L LID = 0;
    static V merge(V a, V b) { return a + b; }
```

```
    static V applyVal(V a, L f, int len) { return a + f * len; }
    static L compose(L a, L f) { return a + f; }
    // ------------------------------------------------------------------------

    int n, B, blocks;
    vector<V> a, aggregate;
    vector<L> lazy;

    SqrtDecomp(const vector<V>& values) : n(values.size()), a(values) {
        B = (int)sqrt(n) + 1;
        blocks = (n + B - 1) / B;
        aggregate.assign(blocks, VID);
        lazy.assign(blocks, LID);
        for (int i = 0; i < n; ++i)
            aggregate[i / B] = merge(aggregate[i / B], a[i]);
    }
    int block_end(int b) const { return min(n, (b + 1) * B); }

    void rebuild(int b) {
        aggregate[b] = VID;
        for (int i = b * B; i < block_end(b); ++i)
            aggregate[b] = merge(aggregate[b], a[i]);
    }
    void push(int b) {
        if (lazy[b] == LID) return;
        for (int i = b * B; i < block_end(b); ++i)
            a[i] = applyVal(a[i], lazy[b], 1);
        lazy[b] = LID;
    }
    void update(int l, int r, L f) {
        while (l < r) {
            int b = l / B, e = block_end(b);
            if (l == b * B && e <= r) {
                aggregate[b] = applyVal(aggregate[b], f, e - l);
                lazy[b] = compose(lazy[b], f);
                l = e;
            } else {
                push(b);
                int stop = min(r, e);
                while (l < stop) a[l] = applyVal(a[l], f, 1), ++l;
                rebuild(b);
            }
        }
    }
    V query(int l, int r) {
        V ans = VID;
        while (l < r) {
            int b = l / B, e = block_end(b);
            if (l == b * B && e <= r) {
                ans = merge(ans, aggregate[b]);
                l = e;
            } else {
                push(b);
                int stop = min(r, e);
                while (l < stop) ans = merge(ans, a[l++]);
            }
        }
        return ans;
    }
};
```

2.6 Lazy Segment Tree

Use: Range update + range query; edit only the marked block for other ops.
Complexity: Build $O(n)$, operations $O(\log n)$.
Pitfalls: Half-open 0-indexed bounds `[l,r)`. Default is range add / range sum; tested variants follow.
Assumptions/deps: Public wrappers: `update(l,r,f)`, `query(l,r)`, `init(vec)`.

```
// Lazy segment tree. 0-indexed, half-open ranges [l, r). O(log n) per op.
// To reuse for another operation, edit ONLY the marked block below:
// types V (node) / L (tag), the two identities, and merge/applyVal/compose.
// Configured for: range-add update, range-sum query.
// Pitfalls: compose(a,f) applies OLD a then NEW f; arithmetic must fit V.
// Input: init(a), then valid 0-indexed intervals [l,r).
// Effect: update(l,r,x) adds x on [l,r). Empty updates do nothing.
// Output: query(l,r) returns the range sum, or VID for an empty range.
// See the usage notes for complete, tested alternative configurations.
struct SegTree {
    // ---- customize for the operation ----------------------------------
    using V = long long; // node value type
    using L = long long; // lazy tag type
    static constexpr V VID = 0; // merge identity (returned for empty range)
    static constexpr L LID = 0; // "no pending update" tag
    static V merge(V a, V b) { return a + b; } // combine children
    static V applyVal(V a, L f, int len){ return a + f * len; } // tag over len cells
    static L compose(L a, L f) { return a + f; } // apply f on top of a
    // -------------------------------------------------------------------

    int n;
    vector<V> t;
    vector<L> lz;

    SegTree(int n = 0) { init(n); }
    void init(int n_) { n = n_; t.assign(4 * n, VID); lz.assign(4 * n, LID); }
    void init(const vector<V>& a) { init(a.size()); if (n) build(a, 1, 0, n); }

    void apply(int x, L f, int len) {
        t[x] = applyVal(t[x], f, len);
```

```
        lz[x] = compose(lz[x], f);
    }
    void push(int x, int l, int r) {
        if (lz[x] == LID) return;
        int m = (l + r) / 2;
        apply(2 * x, lz[x], m - l);
        apply(2 * x + 1, lz[x], r - m);
        lz[x] = LID;
    }
    void build(const vector<V>& a, int x, int l, int r) {
        if (r - l == 1) { t[x] = a[l]; return; }
        int m = (l + r) / 2;
        build(a, 2 * x, l, m);
        build(a, 2 * x + 1, m, r);
        t[x] = merge(t[2 * x], t[2 * x + 1]);
    }
    void update(int x, int l, int r, int ql, int qr, L f) {
        if (qr <= l || r <= ql) return;
        if (ql <= l && r <= qr) { apply(x, f, r - l); return; }
        push(x, l, r);
        int m = (l + r) / 2;
        update(2 * x, l, m, ql, qr, f);
        update(2 * x + 1, m, r, ql, qr, f);
        t[x] = merge(t[2 * x], t[2 * x + 1]);
    }
    V query(int x, int l, int r, int ql, int qr) {
        if (qr <= l || r <= ql) return VID;
        if (ql <= l && r <= qr) return t[x];
        push(x, l, r);
        int m = (l + r) / 2;
        return merge(query(2 * x, l, m, ql, qr), query(2 * x + 1, m, r, ql, qr));
    }
    void update(int l, int r, L f) { if (l < r) update(1, 0, n, l, r, f); }
    V query(int l, int r) { return l < r ? query(1, 0, n, l, r) : VID; }
};
```

Use: add to an interval, then ask its sum

Ranges are half-open `[l,r)`. `init(a)` builds the initial values and `init(n)` fills leaves with `VID` (zero for the default). Empty ranges return `VID`.

```
// Input: a={2,1,4}; half-open update/query intervals.
SegTree st;
st.init(vector<long long>{2, 1, 4});
// Add 3 to a[0..2), producing {5,4,4}.
st.update(0, 2, 3);
// Expected sum over a[1..3) is 8.
auto sum = st.query(1, 3);
```

Adapt: range add, range minimum

Replace the marked block with the following. Build from a vector of actual values: `VID` is a query identity, not an initial array value.

```
using V = long long;
using L = long long;
static constexpr V VID = LLONG_MAX;
static constexpr L LID = 0;
static V merge(V a, V b) { return min(a, b); }
static V applyVal(V a, L f, int) { return a + f; }
static L compose(L a, L f) { return a + f; }
```

On the same array and update above, `query(1,3)` returns **4**. Real values and all updated values must fit `long long`.

Adapt: range assignment, range sum

Replace the marked block with the following. The sentinel `LLONG_MIN` is reserved: it cannot be an assigned value. Assigning zero works.

```
using V = long long;
using L = long long;
static constexpr V VID = 0;
static constexpr L LID = LLONG_MIN;
static V merge(V a, V b) { return a + b; }
static V applyVal(V a, L f, int len) {
    return f == LID ? a : f * len;
}
static L compose(L a, L f) { return f == LID ? a : f; }
```

Starting from `[2,1,4]`, `update(0,2,0)` assigns zero to two cells and `query(0,3)` returns **4**. All three configurations build in $O(n)$, use $O(n)$ memory, and take $O(\log n)$ per operation. For other configurations, `merge` must be associative with identity `VID`; applying a tag must agree with merging the updated children. `compose(old,new)` must preserve that order.

2.7 Sparse Table

Use: Static idempotent range query (min default).
Complexity: Build $O(n \log n)$, query $O(1)$.
Pitfalls: Range is `[l,r)` and must be nonempty; op must be idempotent.
Assumptions/deps: EDIT ONLY `op()` (min/max/gcd/and/or).

```
// Sparse table for static idempotent range query, [l, r) with l < r, O(1).
// Build O(n log n). EDIT ONLY op(): must be idempotent (min/max/gcd/and/or).
struct SparseTable {
    static long long op(long long a, long long b) { return min(a, b); }

    vector<vector<long long>> st; // st[j][i] = op over a[i..i+2^j)
    SparseTable() {}
    SparseTable(const vector<long long>& a) { build(a); }
    void build(const vector<long long>& a) {
        st.assign(1, a);
```

```
        for (int j = 1; (1 << j) <= (int)a.size(); j++) {
            st.emplace_back(a.size() - (1 << j) + 1);
            for (int i = 0; i < (int)st[j].size(); i++)
                st[j][i] = op(st[j - 1][i], st[j - 1][i + (1 << (j - 1))]);
        }
    }
    long long query(int l, int r) {
        int j = __lg(r - l);
        return op(st[j][l], st[j][r - (1 << j)]);
    }
};
```

2.8 Persistent Segment Tree

Use: Point updates and range queries across versions.
Complexity: $O(\log n)$ per op; $O(\log n)$ new nodes per update.
Pitfalls: 0-indexed inclusive bounds. Versions share nodes.
Assumptions/deps: Start with an empty `Node` and save each returned root. Default is point add and range sum.

```
// Persistent point add and range sum. Start with Node root{} on [0,n-1].
// Keep the root returned by each update. All bounds are inclusive.
// Update/query O(log n), with O(log n) new nodes per update.
struct Node {
    // ---- customize for the operation ----
    using V = long long;
    static constexpr V VID = 0;
    static V merge(V a, V b) { return a + b; }
    static V apply(V a, V x) { return a + x; } // use x for assignment

    V val = VID;
    Node *lc = 0, *rc = 0;
    static V get(Node *v) { return v ? v->val : VID; }

    Node* update(int l, int r, int p, V x) {
        Node *v = new Node(*this);
        if (l == r) {
            v->val = apply(val, x);
            return v;
        }
        int m = l + (r - l) / 2;
        Node empty, *&c = p <= m ? v->lc : v->rc;
        c = (c ? c : &empty)->update(
            p <= m ? l : m + 1, p <= m ? m : r, p, x);
        v->val = merge(get(v->lc), get(v->rc));
        return v;
    }

    V query(int l, int r, int L, int R) {
        if (r < L || R < l) return VID;
        if (L <= l && r <= R) return val;
        int m = l + (r - l) / 2;
        return merge(lc ? lc->query(l, m, L, R) : VID,
                     rc ? rc->query(m + 1, r, L, R) : VID);
    }
};
```

Usage on branching versions

Start with an empty root. Each update copies one path and shares the other subtrees with older versions. Use the same 0-based inclusive domain for every operation on a version.

```
Node empty;
Node *a = empty.update(0, 3, 1, 4);
Node *b = a->update(0, 3, 1, -2);
Node *c = a->update(0, 3, 3, 7);
long long sumA = a->query(0, 3, 1, 3); // 4
long long sumB = b->query(0, 3, 1, 3); // 2
long long sumC = c->query(0, 3, 1, 3); // 11
```

Use `n >= 1` and `0 <= p < n`. Choose an associative `merge` with identity `VID`, the value of untouched leaves. For point assignment, make `apply` return `x`. Use `__int128` for `V` if sums can exceed `long long`.

Each update allocates nodes with `new`. If memory must be reclaimed between cases, use a pool with stable addresses and reset it after discarding all versions of the case. Recursive deletion from each root can double-delete shared nodes.

2.9 Line Container

Use: Dynamic convex hull trick: add lines, query maximum at x.
Complexity: Amortized $O(\log n)$ add; $O(\log n)$ query.
Pitfalls: Breakpoints/evaluation use `__int128`; query result is 128-bit. For MIN negate coefficients/result; coefficients must not equal `LLONG_MIN`.
Assumptions/deps: Keeps `#define int long long`; do not narrow the result unless it fits.

```
// CHT: add lines y = k*x + m, query MAXIMUM at x. Amortized O(log n) per op.
// For MINIMUM: add(-k, -m) and use -get(x).
// Keeps the notebook's #define int long long convention.
// Breakpoints and evaluations use __int128; coefficients/x are signed 64-bit.
// get returns __int128: do not narrow unless the result fits long long.
// MIN via negation requires k,m != LLONG_MIN (negating them would overflow).
// add(k,m) inserts y=kx+m; get(x) returns the largest inserted line value.
// Example: add(2,1); add(-1,7); get(3)==7. get needs a nonempty container.
```

```cpp
#define int long long
struct Line {
  int k, m;
  mutable __int128 p;
  bool operator<(const Line& o) const { return k < o.k; }
  bool operator<(int x) const { return p < x; }
};
struct LineContainer : multiset<Line, less<>> {
  static constexpr __int128 inf = (__int128)1 << 126;
  __int128 div(__int128 a, __int128 b) { // floored division
    return a / b - ((a < 0) != (b < 0) && a % b); }
  bool isect(iterator x, iterator y) {
    if (y == end()) return x->p = inf, 0;
    if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
    else x->p = div((__int128)y->m - x->m, (__int128)x->k - y->k);
    return x->p >= y->p;
  }
  void add(int k, int m) {
    auto z = insert({k, m, 0}), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
    while ((y = x) != begin() && (--x)->p >= y->p)
      isect(x, erase(y));
  }
  __int128 get(int x) {
    assert(!empty());
    auto l = *lower_bound(x);
    return (__int128)l.k * x + l.m;
  }
};
```

2.10 Short Segment Tree Beats

Use: Range chmin and range sum/max.
Complexity: $O((n+q)\log n)$ for q operations.
Pitfalls: A whole node can be capped only above its strict second maximum. Reserve `LLONG_MIN`.
Assumptions/deps: 0-indexed `[l,r)`. Use this version when only upper clamps are needed.

```cpp
// Range chmin (a[i] = min(a[i], v)) and range sum/max on [l,r).
// O((n+q) log n) total for q operations, O(n) memory.
// Only cap a whole node when second < v < mx. Equality needs descent.
// Keep LLONG_MIN reserved and all segment sums within long long.
// Example: Beats b({5,2,5}); b.chmin(0,3,3); b.sum(0,3)==8.
struct Beats {
    using ll = long long;
    struct Node {
        ll sum = 0, mx = LLONG_MIN, second = LLONG_MIN;
        int cnt = 0;
    };
    int n;
    vector<Node> t;
    Beats(const vector<ll>& a) : n(a.size()), t(4*n) {
        if (n) build(1, 0, n, a);
    }
    Node merge(Node a, Node b) {
        if (a.mx < b.mx) swap(a,b);
        a.sum += b.sum;
        if (a.mx == b.mx) {
            a.cnt += b.cnt;
            a.second = std::max(a.second, b.second);
        } else a.second = std::max(a.second, b.mx);
        return a;
    }
    void build(int p, int l, int r, const vector<ll>& a) {
        if (r-l == 1) {
            t[p] = {a[l], a[l], LLONG_MIN, 1};
            return;
        }
        int m = (l+r)/2;
        build(2*p, l, m, a);
        build(2*p+1, m, r, a);
        t[p] = merge(t[2*p], t[2*p+1]);
    }
    void cap(int p, ll v) {
        auto& a = t[p];
        if (a.mx <= v) return;
        a.sum = a.sum + ((__int128)v - a.mx) * a.cnt;
        a.mx = v;
    }
    void push(int p) {
        cap(2*p, t[p].mx);
        cap(2*p+1, t[p].mx);
    }
    void chmin(int p, int l, int r, int ql, int qr, ll v) {
        if (qr <= l || r <= ql || t[p].mx <= v) return;
        if (ql <= l && r <= qr && t[p].second < v) {
            cap(p,v);
            return;
        }
        push(p);
        int m = (l+r)/2;
        chmin(2*p, l, m, ql, qr, v);
        chmin(2*p+1, m, r, ql, qr, v);
        t[p] = merge(t[2*p], t[2*p+1]);
    }
    Node query(int p, int l, int r, int ql, int qr) {
        if (qr <= l || r <= ql) return {};
        if (ql <= l && r <= qr) return t[p];
```

```
        push(p);
        int m = (l+r)/2;
        return merge(query(2*p,l,m,ql,qr), query(2*p+1,m,r,ql,qr));
    }
    void chmin(int l, int r, ll v) { if (l < r) chmin(1,0,n,l,r,v); }
    ll sum(int l, int r) { return l < r ? query(1,0,n,l,r).sum : 0; }
    ll max(int l, int r) { return l < r ? query(1,0,n,l,r).mx : LLONG_MIN; }
};
```

2.11 Full Segment Tree Beats

Use: Range add/chmin/chmax plus sum/min/max.
Complexity: Add/query $O(\log n)$; clamps amortized $O(\log^2 n)$.
Pitfalls: Strict second extrema and strict fast-path comparisons are essential; overflow bounds.
Assumptions/deps: 0-indexed half-open ranges. High-risk; read invariant note below.

```
// Segment tree beats: range add/chmin/chmax and range sum/min/max on [l,r).
// Reference: Ji Ruyi's strict-second-extrema formulation.
// Complexity: add/query O(log n); chmin/chmax amortized O(log^2 n).
// Pitfalls: mx2/mn2 are STRICT second extrema; comparisons in the fast-path
// conditions must stay strict. Keep values far inside +/-INF; sums
// and lazy additions can overflow long long.
// Input: initial values and valid 0-indexed half-open intervals [l,r).
// Effect: add adds; chmin caps from above; chmax floors from below on [l,r).
// Output: sum/min/max aggregate [l,r); empty ranges give 0/INF/NINF.
struct SegTreeBeats {
    using ll=long long;
    static constexpr ll INF=(1LL<<60),NINF=-INF;
    struct Node {
        ll sum=0,mx1=NINF,mx2=NINF,mn1=INF,mn2=INF,add=0;
        int mxc=0,mnc=0;
    };
    int n;
    vector<Node>t;
    SegTreeBeats(const vector<ll>&a={}){init(a);}
    Node mergeNode(const Node&a,const Node&b) {
        Node c;c.sum=a.sum+b.sum;
        if(a.mx1==b.mx1)c.mx1=a.mx1,c.mxc=a.mxc+b.mxc,c.mx2=std::max(a.mx2,b.mx2);
        else if(a.mx1>b.mx1)c.mx1=a.mx1,c.mxc=a.mxc,c.mx2=std::max(a.mx2,b.mx1);
        else c.mx1=b.mx1,c.mxc=b.mxc,c.mx2=std::max(a.mx1,b.mx2);
        if(a.mn1==b.mn1)c.mn1=a.mn1,c.mnc=a.mnc+b.mnc,c.mn2=std::min(a.mn2,b.mn2);
        else if(a.mn1<b.mn1)c.mn1=a.mn1,c.mnc=a.mnc,c.mn2=std::min(a.mn2,b.mn1);
        else c.mn1=b.mn1,c.mnc=b.mnc,c.mn2=std::min(a.mn1,b.mn2);
        return c;
    }
    void init(const vector<ll>&a){n=a.size();t.assign(4*n,{});if(n)build(1,0,n,a);}
    void build(int x,int l,int r,const vector<ll>&a){
        if(r-l==1){t[x].sum=t[x].mx1=t[x].mn1=a[l];t[x].mxc=t[x].mnc=1;return;}
        int m=(l+r)/2;build(2*x,l,m,a);build(2*x+1,m,r,a);t[x]=mergeNode(t[2*x],t[2*x
            +1]);
    }
    void applyAdd(int x,ll v,int len){auto&z=t[x];z.sum+=v*len;z.mx1+=v;if(z.mx2!=
        NINF)z.mx2+=v;z.mn1+=v;if(z.mn2!=INF)z.mn2+=v;z.add+=v;}
    void applyChmin(int x,ll v){auto&z=t[x];z.sum+=(v-z.mx1)*z.mxc;if(z.mn1==z.mx1)z
        .mn1=v;else if(z.mn2==z.mx1)z.mn2=v;z.mx1=v;}
    void applyChmax(int x,ll v){auto&z=t[x];z.sum+=(v-z.mn1)*z.mnc;if(z.mx1==z.mn1)z
        .mx1=v;else if(z.mx2==z.mn1)z.mx2=v;z.mn1=v;}
    void push(int x,int l,int r){
        int m=(l+r)/2;
        if(t[x].add){applyAdd(2*x,t[x].add,m-l);applyAdd(2*x+1,t[x].add,r-m);t[x].add
            =0;}
        if(t[2*x].mx1>t[x].mx1)applyChmin(2*x,t[x].mx1);
        if(t[2*x+1].mx1>t[x].mx1)applyChmin(2*x+1,t[x].mx1);
        if(t[2*x].mn1<t[x].mn1)applyChmax(2*x,t[x].mn1);
        if(t[2*x+1].mn1<t[x].mn1)applyChmax(2*x+1,t[x].mn1);
    }
    void add(int x,int l,int r,int ql,int qr,ll v){if(qr<=l||r<=ql)return;if(ql<=l&&r
        <=qr){applyAdd(x,v,r-l);return;}push(x,l,r);int m=(l+r)/2;add(2*x,l,m,ql,qr,
        v);add(2*x+1,m,r,ql,qr,v);t[x]=mergeNode(t[2*x],t[2*x+1]);}
    void chmin(int x,int l,int r,int ql,int qr,ll v){if(qr<=l||r<=ql||t[x].mx1<=v)
        return;if(ql<=l&&r<=qr&&t[x].mx2<v){applyChmin(x,v);return;}push(x,l,r);int
        m=(l+r)/2;chmin(2*x,l,m,ql,qr,v);chmin(2*x+1,m,r,ql,qr,v);t[x]=mergeNode(t
        [2*x],t[2*x+1]);}
    void chmax(int x,int l,int r,int ql,int qr,ll v){if(qr<=l||r<=ql||t[x].mn1>=v)
        return;if(ql<=l&&r<=qr&&t[x].mn2>v){applyChmax(x,v);return;}push(x,l,r);int
        m=(l+r)/2;chmax(2*x,l,m,ql,qr,v);chmax(2*x+1,m,r,ql,qr,v);t[x]=mergeNode(t
        [2*x],t[2*x+1]);}
    Node query(int x,int l,int r,int ql,int qr){if(ql<=l&&r<=qr)return t[x];push(x,l,
        r);int m=(l+r)/2;if(qr<=m)return query(2*x,l,m,ql,qr);if(m<=ql)return query
        (2*x+1,m,r,ql,qr);return mergeNode(query(2*x,l,m,ql,qr),query(2*x+1,m,r,ql,
        qr));}
    void add(int l,int r,ll v){if(l<r)add(1,0,n,l,r,v);}
    void chmin(int l,int r,ll v){if(l<r)chmin(1,0,n,l,r,v);}
    void chmax(int l,int r,ll v){if(l<r)chmax(1,0,n,l,r,v);}
    ll sum(int l,int r){return l<r?query(1,0,n,l,r).sum:0;}
    ll min(int l,int r){return l<r?query(1,0,n,l,r).mn1:INF;}
    ll max(int l,int r){return l<r?query(1,0,n,l,r).mx1:NINF;}
};
```

2.12 Segment Tree Beats Invariants

Use: Why strict extrema permit lazy clamps.
Complexity: Amortized $O(\log^2 n)$ per clamp.
Pitfalls: Do not change inequality ties without re-deriving invariants.

Assumptions/deps: Pairs with the implementation above.

Stored invariant

The short version stores the sum and maximum-side fields. Use the full version when the problem also needs range addition or a lower clamp.

The full version stores the sum and two extrema in each direction.

- mx_1: maximum; mx_2: **strict** second maximum; mx_c: count of mx_1.
- mn_1: minimum; mn_2: **strict** second minimum; mn_c: count of mn_1.

Range `chmin(x)`

- $mx_1 \le x$: nothing changes.
- $mx_2 < x < mx_1$: only the mx_c maxima change, so update the node in $O(1)$.
- Otherwise descend; more than one value class would change.

Range `chmax` is symmetric. Push lazy addition first, then clamp each child to the parent's current mx_1 and mn_1. Pull recomputes strict extrema and their counts.

Every failed $O(1)$ clamp can be charged to a strict-extremum level change, giving the usual amortized $O(\log^2 n)$ bound. Never change `<` to `<=` in a fast-path condition without re-deriving the invariant.

For the short version, charge each forced descent on a fully covered node to the disappearance of a distinct value in that node. A cap can introduce at most one new distinct value at each partially covered node. There are $O(\log n)$ such nodes per cap and the initial sum of distinct counts over all nodes is $O(n \log n)$.

2.13 DSU on Segment Tree

Use: Mergeable frequency/count segment trees, usually per DSU/tree node.
Complexity: Update/query $O(\log V)$; merge proportional to touched nodes.
Pitfalls: Reset `tp=1` and roots between tests. Positions lie in `[0, POSMAX+1)` and queries are half-open.
Assumptions/deps: Roots are ints (0 = empty); `merge(u,v)` destroys `v`.

```
// Mergeable dynamic segment trees (sum) over positions [0, POSMAX].
// Each multiset is a root id (0 = empty). upd changes one position; query(u,l,r)
// sums the half-open position interval [l,r); merge combines disjoint roots and
// invalidates v.
// Example: upd(a,5,2); upd(b,7,1); a=merge(a,b); query(a,5,8)==3.
// Total O(inserts*logP); merging all roots is proportional to touched nodes.
// Pool grows as needed. Use deque so references survive allocation.
// Pitfalls: reset tp = 1 and all roots to 0 between test cases.
const int POSMAX = 1e9;
struct node {
  long long s = 0;
  int l = 0, r = 0;
};
deque<node> tree(1);
int tp = 1;
void upd(int &u, int pos, long long delta, int tl = 0, int tr = POSMAX + 1)
{
  if(!u) {
    u = tp++;
    if(u == (int)tree.size()) tree.emplace_back();
    else tree[u] = {};
  }
  tree[u].s += delta;
  if(tr - tl > 1) {
    int tm = tl + (tr - tl) / 2;
    if(pos < tm) upd(tree[u].l, pos, delta, tl, tm);
    else upd(tree[u].r, pos, delta, tm, tr);
  }
}
long long query(int u, int l, int r, int tl = 0, int tr = POSMAX + 1)
{
  if(!u || l >= r || r <= tl || tr <= l) return 0;
  if(l <= tl && tr <= r) return tree[u].s;
  int tm = tl + (tr - tl) / 2;
  return query(tree[u].l, l, r, tl, tm) + query(tree[u].r, l, r, tm, tr);
}
int merge(int u, int v)
{
  if(!u || !v) return u | v;
  tree[u].s += tree[v].s;
  tree[u].l = merge(tree[u].l, tree[v].l);
  tree[u].r = merge(tree[u].r, tree[v].r);
  return u;
}
```

2.14 Cartesian Tree

Use: Linear construction of min-heap tree whose inorder is the array.
Complexity: $O(n)$.
Pitfalls: Strict pop makes the earlier equal value the ancestor; duplicate policy matters.
Assumptions/deps: Returns root, parent, left, and right arrays.

```
// Min Cartesian tree: inorder is the array; parent value <= child value.
// Complexity: O(n) time/memory using a monotonic stack.
// Pitfalls: strict '>' makes the EARLIER equal value the ancestor; changing
// the comparison changes duplicate tie behavior.
```

```cpp
// Example: a={3,1,2} gives root=1, left[1]=0, right[1]=2.
struct CartesianTree {
    int root=-1;
    vector<int>parent,left,right;
};
CartesianTree cartesian_tree(const vector<long long>& a) {
    int n=a.size();
    CartesianTree t;
    t.parent.assign(n,-1);t.left.assign(n,-1);t.right.assign(n,-1);
    vector<int>st;
    for(int i=0;i<n;++i) {
        int last=-1;
        while(!st.empty() && a[st.back()]>a[i]) last=st.back(),st.pop_back();
        if(!st.empty()) t.right[st.back()]=i,t.parent[i]=st.back();
        if(last!=-1) t.left[i]=last,t.parent[last]=i;
        st.push_back(i);
    }
    if(n) t.root=st.front();
    return t;
}
```

2.15 Implicit Treap

Use: Sequence split/merge/reverse by position.
Complexity: Expected $O(\log n)$ per split/merge.
Pitfalls: Use random priorities. Push reversal tags before descending.
Assumptions/deps: `new item(value,rng64())`. Reverse uses `[l,r)`.

```cpp
// Implicit treap: the inorder traversal is a sequence; subtree sizes are keys.
// split(t,l,r,k) puts the first k values in l and the rest in r; merge(t,l,r)
// concatenates l then r. reverse(t,l,r) reverses [l,r).
// Expected O(log n) per split/merge; traversal is O(n).
// Pitfalls: use random priorities; push before descent and pull afterward.
// Example: pitem t=nullptr; merge(t,t,new item(42,rng64()));
typedef struct item * pitem;
struct item {
    uint64_t prior;
    long long value;
    int cnt = 1;
    bool rev = false;
    pitem l = nullptr, r = nullptr;
    item(long long value, uint64_t prior) : prior(prior), value(value) {}
};

int cnt (pitem it) {
    return it ? it->cnt : 0;
}

void upd_cnt (pitem it) {
    if (it)
        it->cnt = cnt(it->l) + cnt(it->r) + 1;
}

void push (pitem it) {
    if (it && it->rev) {
        it->rev = false;
        swap (it->l, it->r);
        if (it->l) it->l->rev ^= true;
        if (it->r) it->r->rev ^= true;
    }
}

void merge (pitem & t, pitem l, pitem r) {
    push (l);
    push (r);
    if (!l || !r)
        t = l ? l : r;
    else if (l->prior > r->prior)
        merge (l->r, l->r, r), t = l;
    else
        merge (r->l, l, r->l), t = r;
    upd_cnt (t);
}

void split (pitem t, pitem & l, pitem & r, int k) {
    if (!t) { l = r = nullptr; return; }
    push (t);
    int left = cnt(t->l);
    if (k <= left)
        split (t->l, l, t->l, k), r = t;
    else
        split (t->r, t->r, r, k-left-1), l = t;
    upd_cnt (t);
}

void reverse (pitem& t, int l, int r) {
    if (l >= r) return;
    pitem t1, t2, t3;
    split (t, t1, t2, l);
    split (t2, t2, t3, r-l);
    t2->rev ^= true;
    merge (t, t1, t2);
    merge (t, t, t3);
}

void output (pitem t) {
    if (!t) return;
    push (t);
    output (t->l);
    cout << t->value << ' ';
```

```
    output (t->r);
}
```

2.16 Mo's Algorithm

Use: Offline statistics on static ranges $[l, r)$.
Complexity: $O((n+q)\sqrt{n+1})$ moves and $O(q \log q)$ sorting.
Pitfalls: Start with empty window state. Store answers by query ID.
Assumptions/deps: `mo(n,queries,add,remove,answer)`. Empty ranges supported.

```cpp
// Mo's algorithm on static queries [l,r), including empty ranges.
// Start with empty state. add/remove take an index; answer takes a query id.
// State on return represents the last processed window.
// O((n+q)*sqrt(n+1)) moves, O(q log q) sorting and O(q) extra space.
template<class Add, class Remove, class Answer>
void mo(int n, const vector<pair<int,int>>& queries, Add add, Remove remove,
        Answer answer) {
    int q=queries.size(), block=max<int>(1,sqrt(n));
    vector<int> order(q);
    iota(order.begin(),order.end(),0);
    sort(order.begin(),order.end(),[&](int i,int j) {
        int bi=queries[i].first/block, bj=queries[j].first/block;
        if(bi!=bj) return bi<bj;
        return (bi&1) ? queries[i].second>queries[j].second
                      : queries[i].second<queries[j].second;
    });
    int l=0, r=0;
    for(int id:order) {
        auto [ql,qr]=queries[id];
        while(l>ql) add(--l);
        while(r<qr) add(r++);
        while(l<ql) remove(l++);
        while(r>qr) remove(--r);
        answer(id);
    }
}
```

Usage with distinct counts

```cpp
vector<int> a = {0, 1, 0, 2};
vector<pair<int,int>> queries = {{0,3}, {1,4}, {2,2}};
vector<int> freq(3), ans(queries.size());
int distinct = 0;
mo(a.size(), queries,
   [&](int i) { if (++freq[a[i]] == 1) ++distinct; },
   [&](int i) { if (--freq[a[i]] == 0) --distinct; },
   [&](int id) { ans[id] = distinct; }); // {2,3,0}
```

Use half-open query ranges on a static array. This example compresses values to use them as frequency indices. Start with an empty window on each call. Store answers by query ID and read them in input order.

2.17 Link-Cut Tree

Use: Dynamic-forest link/cut/connectivity and path sum.
Complexity: Amortized $O(\log n)$ per operation.
Pitfalls: Cut requires a direct edge; query requires connectivity; all intermediate sums must fit the value type.
Assumptions/deps: Configured for commutative path sum; point-set updates only.

```cpp
// Dynamic forest: link/cut, connectivity, vertex assignment and path sum.
// Complexity: amortized O(log n) per operation; O(n) memory.
// Usage: LinkCut lct(vector<long long>{2,3}); lct.link(0,1);
// lct.pathQuery(0,1) == 5. Vertices are 0-indexed, initially isolated.
// Pitfalls: cut only DIRECT edges; query only connected vertices.
// All intermediate sums must fit V; use __int128 if necessary.
// High-risk splay code; only commutative aggregates work with this reversal.
struct LinkCut {
    // Customize only this commutative aggregate (and Node's initial values).
    using V = long long;
    static V identity() { return 0; }
    static V merge(V a, V b) { return a + b; }

    struct Node {
        int ch[2] = {-1, -1}, p = -1;
        bool rev = false;
        V val = 0, agg = 0;
    };
    vector<Node> t;

    LinkCut(int n = 0) : t(n) {}
    LinkCut(const vector<V>& a) : t(a.size()) {
        for (int i = 0; i < (int)a.size(); ++i)
            t[i].val = t[i].agg = a[i];
    }
    bool isRoot(int x) const {
        int p = t[x].p;
        return p == -1 || (t[p].ch[0] != x && t[p].ch[1] != x);
    }
    V aggregate(int x) const { return x == -1 ? identity() : t[x].agg; }
    void pull(int x) {
        auto& a = t[x];
        a.agg = merge(merge(aggregate(a.ch[0]), a.val), aggregate(a.ch[1]));
    }
    void applyReverse(int x) {
```

```
        if (x != -1) swap(t[x].ch[0], t[x].ch[1]), t[x].rev ^= 1;
    }
    void push(int x) {
        if (!t[x].rev) return;
        for (int c : t[x].ch) applyReverse(c);
        t[x].rev = false;
    }
    void pushPath(int x) {
        vector<int> st{x};
        while (!isRoot(x)) st.push_back(x = t[x].p);
        while (!st.empty()) { push(st.back()); st.pop_back(); }
    }
    void rotate(int x) {
        int p = t[x].p, g = t[p].p, d = t[p].ch[1] == x;
        int b = t[x].ch[d ^ 1];
        if (!isRoot(p)) t[g].ch[t[g].ch[1] == p] = x;
        t[x].p = g; t[p].p = x;
        t[x].ch[d ^ 1] = p; t[p].ch[d] = b;
        if (b != -1) t[b].p = p;
        pull(p); pull(x);
    }
    void splay(int x) {
        pushPath(x);
        while (!isRoot(x)) {
            int p = t[x].p, g = t[p].p;
            if (!isRoot(p))
                rotate((t[p].ch[1] == x) == (t[g].ch[1] == p) ? p : x);
            rotate(x);
        }
    }
    int access(int x) {
        int last = -1;
        for (int y = x; y != -1; y = t[y].p) {
            splay(y); t[y].ch[1] = last; pull(y); last = y;
        }
        splay(x);
        return last;
    }
    void makeRoot(int x) { access(x); applyReverse(x); }
    int findRoot(int x) {
        access(x);
        while (push(x), t[x].ch[0] != -1) x = t[x].ch[0];
        splay(x);
        return x;
    }
    bool connected(int u, int v) { return u == v || findRoot(u) == findRoot(v); }
    bool link(int u, int v) {
        makeRoot(u);
        if (findRoot(v) == u) return false;
        t[u].p = v;
        return true;
    }
    bool cut(int u, int v) {
        makeRoot(u); access(v);
        if (t[v].ch[0] != u || t[u].ch[1] != -1) return false;
        t[v].ch[0] = t[u].p = -1;
        pull(v);
        return true;
    }
    void setValue(int v, V value) { access(v); t[v].val = value; pull(v); }
    V pathQuery(int u, int v) {
        assert(connected(u, v));
        makeRoot(u); access(v);
        return t[v].agg;
    }
};
```

2.18 Link-Cut Tree Operations

Use: Preferred paths, access, makeroot, link, cut, and path query.
Complexity: Amortized $O(\log n)$.
Pitfalls: Push reversals before rotations and pull after child changes.
Assumptions/deps: Explains the narrow implementation above.

Mental model

The represented forest is split into preferred paths, each stored as a splay tree. A splay parent may also be a virtual/path parent when the node is not its actual splay child.

Operations

- `access(v)`: expose the represented-tree path from its root to `v`.
- `makeRoot(v)`: `access(v)`, then lazily reverse the exposed path.
- `link(u,v)`: make `u` a represented-tree root, then attach it under `v`.
- `cut(u,v)`: `makeRoot(u)`, `access(v)`, then verify and remove the direct edge.
- `pathQuery(u,v)`: `makeRoot(u)`, `access(v)`; `v` stores the path aggregate.

Before each rotation, push reversals from ancestors; after changing children, pull aggregates. This version uses commutative path sum. Noncommutative aggregates need forward and reverse values; path updates need another lazy tag.

Usage: link, query, update, and cut

Vertices start isolated. Paths include both endpoint vertices. `link` and `cut` return whether the requested forest change was valid.

```
// Input: three isolated vertices with values {2,3,5}.
LinkCut lct(vector<long long>{2, 3, 5});
bool a = lct.link(0, 1);
bool b = lct.link(1, 2);
bool cycle = lct.link(0, 2);
```

```
long long sum1 = lct.pathQuery(0, 2);

// Effect: set vertex 1 to 7, then remove direct edge (1,2).
lct.setValue(1, 7);
long long sum2 = lct.pathQuery(0, 2);
bool removed = lct.cut(1, 2);
bool joined = lct.connected(0, 2);
// Expected: a,b,removed=true; cycle,joined=false; sum1=10; sum2=14.
```

Never call `pathQuery(u,v)` while disconnected; it asserts connectivity.

Complexity and pitfalls

Each public operation takes amortized $O(\log n)$ time; a single operation can take $O(n)$. Storage is $O(n)$, including the iterative ancestor stack in `pushPath`, which avoids recursion overflow on a deep splay tree.

All intermediate sums must fit `V`, even if the final queried sum fits. Use `__int128` for larger bounds. Only commutative aggregates are supported; changing to min/max also requires updating the identity and initial values. There are no subtree queries or path updates. Prefer HLD for a static tree. Construct a fresh `LinkCut` for each test case.

The test compares random operations (including rejected links/cuts) against a BFS forest oracle and checks a long chain with reversals and updates.

2.19 Wavelet Tree

Use: Static range kth/count-less/count-equal queries.
Complexity: Build $O(n \log \sigma)$; queries $O(\log \sigma)$.
Pitfalls: Half-open ranges; kth is 0-based and requires a nonempty range; static only.
Assumptions/deps: Values are internally compressed, including negatives and duplicates.

```
// Static wavelet tree over compressed values. Index ranges are half-open [l,r).
// Complexity: build O(n log sigma); queries O(log sigma); memory O(n log sigma).
// Pitfalls: kth uses 0-based k and needs l<r; static only; values are compressed
// internally, so negatives and duplicates work.
// kth(l,r,k) selects by 0-based order; countLess/countEqual count values in
// a[l..r). Example: wt({4,1,4,2}); kth(1,4,1)==2; countEqual(0,3,4)==2.
struct WaveletTree {
    struct Node { int lo,hi,left=-1,right=-1; vector<int>pref; };
    vector<long long>values;
    vector<Node>nodes;
    int root=-1;

    WaveletTree(const vector<long long>& a={}) { init(a); }
    int build(const vector<int>& a,int lo,int hi) {
        int x=nodes.size();nodes.push_back({lo,hi,-1,-1,{}});
        nodes[x].pref.assign(a.size()+1,0);
        if(lo==hi || a.empty()) return x;
        int mid=(lo+hi)/2;
        vector<int>L,R;L.reserve(a.size());R.reserve(a.size());
        for(int i=0;i<(int)a.size();++i) {
            bool left=a[i]<=mid;
            nodes[x].pref[i+1]=nodes[x].pref[i]+left;
            (left?L:R).push_back(a[i]);
        }
        nodes[x].left=build(L,lo,mid);
        nodes[x].right=build(R,mid+1,hi);
        return x;
    }
    void init(const vector<long long>& a) {
        values=a;sort(values.begin(),values.end());values.erase(unique(values.begin()
            ,values.end()),values.end());
        nodes.clear();root=-1;
        if(values.empty())return;
        vector<int>rank(a.size());
        for(int i=0;i<(int)a.size();++i)rank[i]=lower_bound(values.begin(),values.end
            (),a[i])-values.begin();
        root=build(rank,0,values.size()-1);
    }
    int kthRank(int x,int l,int r,int k) const {
        auto& nd=nodes[x];if(nd.lo==nd.hi)return nd.lo;
        int before=nd.pref[l],inside=nd.pref[r]-before;
        if(k<inside)return kthRank(nd.left,before,nd.pref[r],k);
        return kthRank(nd.right,l-before,r-nd.pref[r],k-inside);
    }
    int countRank(int x,int l,int r,int rank) const {
        if(l>=r)return 0;
        auto& nd=nodes[x];
        if(rank<=nd.lo)return 0;
        if(nd.hi<rank)return r-l;
        int bl=nd.pref[l],br=nd.pref[r];
        return countRank(nd.left,bl,br,rank)+countRank(nd.right,l-bl,r-br,rank);
    }
    long long kth(int l,int r,int k) const {
        assert(root!=-1 && 0<=l && l<r && r<(int)nodes[root].pref.size() && 0<=k && k
            <r-l);
        return values[kthRank(root,l,r,k)];
    }
    int countLess(int l,int r,long long x) const {
        if(root==-1)return 0;
        int rank=lower_bound(values.begin(),values.end(),x)-values.begin();
        return countRank(root,l,r,rank);
    }
    int countEqual(int l,int r,long long x) const {
        if(root==-1)return 0;
        int rank=lower_bound(values.begin(),values.end(),x)-values.begin();
        if(rank==(int)values.size() || values[rank]!=x)return 0;
        return countRank(root,l,r,rank+1)-countRank(root,l,r,rank);
```

```
    }
};
```

2.20 Priority Queue with Delete

Use: Lazy deletion for max heap: `push/erase/top/pop/size`.
Complexity: Amortized $O(\log n)$.
Pitfalls: `top()/pop()` need `size()>0`; only erase values currently in the heap.
Assumptions/deps: Uses two `priority_queue<int>`.

```
// Heap with lazy deletion. Only erase values that are currently in the heap.
// top()/pop() require nonempty heap (size() > 0). All ops O(log n).
// erase(v) removes one active copy, even if v is not currently at the top.
// Example: push(4), push(9), erase(9) => top()==4 and size()==1.
struct Heap {
  priority_queue<int> in, out;
  void push(int v) { in.push(v); }
  void erase(int v) { out.push(v); }
  int size() { return in.size() - out.size(); }
  int top() {
    while (out.size() && in.top() == out.top()) in.pop(), out.pop();
    return in.top();
  }
  void pop() { top(); in.pop(); }
};
```

2.21 Two-Stack Aggregate Queue

Use: Push back, pop front, and query the aggregate of the whole queue: two pointers on gcd/min/OR/affine windows.
Complexity: Amortized $O(1)$ per operation; memory $O(n)$.
Pitfalls: `pop()` needs `size()>0`. Keep `op(older,newer)` order for noncommutative ops; empty `query()` returns `ID`.
Assumptions/deps: Edit `V, op, ID` (default gcd). Any associative op; no inverse needed.

```
// Two-stack queue: push back, pop front, aggregate of the whole queue.
// Amortized O(1) per op (each element moves between stacks once); memory O(n).
// Edit V, op and ID. op must be associative with identity ID; it need not be
// commutative or invertible (gcd, min, OR, matrix or affine composition).
// op(older, newer): query() combines front ... back in queue order.
// Pitfalls: pop() needs size() > 0; empty query() returns ID.
// Use: two pointers whose window condition is a gcd/min/... of the window.
// Example: AggQueue q; q.push(12); q.push(18); // query()==6; pop() -> 18
struct AggQueue {
    using V = long long;
    static constexpr V ID = 0;
    static V op(V a, V b) { return gcd(a, b); }
    vector<V> in, inAgg{ID}, outAgg{ID}; // inAgg: back part, outAgg: front part
    void push(V x) { in.push_back(x); inAgg.push_back(op(inAgg.back(), x)); }
    void pop() {
        if (outAgg.size() == 1) { // front part empty: move the back part over
            for (; !in.empty(); in.pop_back())
                outAgg.push_back(op(in.back(), outAgg.back()));
            inAgg.resize(1);
        }
        outAgg.pop_back();
    }
    V query() { return op(outAgg.back(), inAgg.back()); }
    int size() { return in.size() + outAgg.size() - 1; }
};
```

3 String

3.1 Rolling Hash

Use: Polynomial substring hash mod $2^{61}-1$, runtime-random base.
Complexity: Build $O(n)$, query $O(1)$.
Pitfalls: NEVER hash mod 2^{64} by overflow: Thue-Morse pairs collide for every base. Half-open `get(l,r)`.
Assumptions/deps: All objects share global base `HB`; uses `__int128`.

```cpp
// Polynomial rolling hash mod 2^61-1 with runtime-random base.
// get(l, r) hashes s[l..r) (HALF-OPEN) in O(1) after O(n) build.
// NEVER hash mod 2^64 via overflow: Thue-Morse strings of length 2048
// collide for EVERY base, and setters include such tests.
// All Hash objects share base HB, so hashes compare across strings.
// Collision prob per pair ~ n/2^61: single hash is fine at ICPC sizes.
const uint64_t HASH_MOD = (1ULL << 61) - 1;
const uint64_t HB =
    mt19937_64(chrono::steady_clock::now().time_since_epoch().count())()
    % (HASH_MOD - 300) + 257;

struct Hash {
    vector<uint64_t> h, p;

    static uint64_t mul(uint64_t a, uint64_t b) {
        __uint128_t c = (__uint128_t)a * b;
        uint64_t r = (uint64_t)(c >> 61) + ((uint64_t)c & HASH_MOD);
        return r >= HASH_MOD ? r - HASH_MOD : r;
    }

    Hash(const string& s) {
        int n = s.size();
        h.assign(n + 1, 0);
        p.assign(n + 1, 1);
        for (int i = 0; i < n; i++) {
            h[i + 1] = mul(h[i], HB) + (unsigned char)s[i] + 1;
            if (h[i + 1] >= HASH_MOD) h[i + 1] -= HASH_MOD;
            p[i + 1] = mul(p[i], HB);
        }
    }

    // hash of s[l..r)
    uint64_t get(int l, int r) {
        uint64_t x = h[r] + HASH_MOD - mul(h[l], p[r - l]);
        return x >= HASH_MOD ? x - HASH_MOD : x;
    }
};
```

3.2 KMP Prefix Function

Use: Borders and single-pattern matching helper.
Complexity: $O(n)$.
Pitfalls: For matching, run on `pattern + sep + text`; choose sep absent from alphabet.
Assumptions/deps: 0-indexed prefix lengths.

```cpp
// Prefix function: pi[i] is the longest proper prefix of s[0..i] that is a suffix.
// O(n) time/memory. Empty input returns {}; pi[0]=0.
// Matching pitfall: a separator in pattern + separator + text must be absent.
// Example: prefix_function("ababa") == vector<int>({0,0,1,2,3}).
vector<int> prefix_function(const string& s) {
    int n = (int)s.length();
    vector<int> pi(n);
    for (int i = 1; i < n; i++) {
        int j = pi[i-1];
        while (j > 0 && s[i] != s[j])
            j = pi[j-1];
        if (s[i] == s[j])
            j++;
        pi[i] = j;
    }
    return pi;
}
```

3.3 Tries

Use: Word/prefix counts and a 63-bit maximum-xor trie.
Complexity: $O(|s|)$ or $O(63)$ per operation.
Pitfalls: Erase only present binary values; word trie default alphabet is lowercase.
Assumptions/deps: Edit marked alphabet block or `MAX_BIT`; reusable public APIs.

```cpp
// Lowercase trie and nonnegative 63-bit xor trie.
// Complexity: O(length) / O(63) per insert, erase, query.
// Trie count_word returns exact multiplicity; count_prefix counts stored words
// below a prefix. BinaryTrie max_xor(x) returns the maximum XOR value, not its mate.
// Examples: insert("app"), insert("apple") => count_prefix("app")==2.
// insert 2 and 7 => max_xor(4)==6 (using stored value 2).
// Pitfalls: lowercase alphabet only; erase only values currently present.
struct Trie {
    // ---- customize alphabet here ----------------------------------------
    static const int A = 26;
```

```
    static int id(char c) { return c-'a'; }
    // ------------------------------------------------------------------
    struct Node {
        array<int, A> next;
        int pass = 0, end = 0;
        Node() { next.fill(-1); }
    };
    vector<Node> tr{Node()};
    void insert(const string& s) {
        int v = 0; ++tr[v].pass;
        for (char c : s) {
            int x = id(c);
            if (tr[v].next[x] == -1) tr[v].next[x] = tr.size(), tr.emplace_back();
            v = tr[v].next[x]; ++tr[v].pass;
        }
        ++tr[v].end;
    }
    int walk(const string& s) const { // node of s, or -1
        int v = 0;
        for (char c : s) if ((v = tr[v].next[id(c)]) == -1) return -1;
        return v;
    }
    int count_word(const string& s) const { int v = walk(s); return v < 0 ? 0 : tr[v
        ].end; }
    int count_prefix(const string& s) const { int v = walk(s); return v < 0 ? 0 : tr[
        v].pass; }
};

struct BinaryTrie {
    static const int MAX_BIT = 62;
    struct Node { int ch[2] = {-1, -1}, cnt = 0; };
    vector<Node> tr{Node()};
    void add(unsigned long long x, int delta) {
        int v = 0; tr[v].cnt += delta;
        for (int b = MAX_BIT; b >= 0; --b) {
            int bit = x >> b & 1;
            if (tr[v].ch[bit] == -1) tr[v].ch[bit] = tr.size(), tr.push_back(Node());
            v = tr[v].ch[bit]; tr[v].cnt += delta;
        }
    }
    void insert(unsigned long long x) { add(x, 1); }
    void erase(unsigned long long x) { add(x, -1); }
    unsigned long long max_xor(unsigned long long x) const {
        assert(tr[0].cnt > 0);
        int v = 0; unsigned long long ans = 0;
        for (int b = MAX_BIT; b >= 0; --b) {
            int bit = x >> b & 1, want = bit ^ 1, to = tr[v].ch[want];
            if (to != -1 && tr[to].cnt > 0) ans |= 1ULL << b, v = to;
            else v = tr[v].ch[bit];
        }
        return ans;
    }
};
```

3.4 Manacher

Use: Palindrome radii (odd; even via separator trick in header).
Complexity: $O(n)$.
Pitfalls: `p[i]` counts odd palindromes centered at i; longest has length `2p[i]-1`. Sentinels are bytes 1/2, safe for printable input.
Assumptions/deps: For both parities run on `#a#b#c#`; length is `p[i]-1` there.

```
// p[i] = # odd palindromes centered at i; longest has length 2*p[i]-1.
// For BOTH odd and even: run on t = "#a#b#c#" (insert '#' between chars and at
// both ends); then longest palindrome centered in t at i has length p[i]-1.
// Sentinels are bytes 1 and 2, so any printable input is safe (using '$'/'^'
// as sentinels breaks on inputs that contain those characters).
vector<int> manacher_odd(string s) {
    int n = s.size(), l = 0, r = 1;
    s = char(1) + s + char(2);
    vector<int> p(n + 2);
    for (int i = 1; i <= n; i++) {
        p[i] = min(r - i, p[l + (r - i)]);
        while (s[i - p[i]] == s[i + p[i]]) p[i]++;
        if (i + p[i] > r) l = i - p[i], r = i + p[i];
    }
    return vector<int>(begin(p) + 1, end(p) - 1);
}
```

3.5 Suffix Array

Use: Suffix array via cyclic shift sort; wrapper included.
Complexity: $O(n \log n)$.
Pitfalls: `suffix_array(s)` uses a virtual sentinel and accepts all bytes, including zero.
Assumptions/deps: Alphabet bytes 0..255; pair with Kasai LCP.

```
// Sort cyclic shifts or use suffix_array(s) for all suffixes. O(n log n).
// Bytes are compared unsigned; the optional sentinel is smaller than any byte.
vector<int> sort_cyclic_shifts(const string& s, bool sentinel = false) {
    int n = s.size() + sentinel;
    if (n == 0) return {};
    const int alphabet = 257;
    auto code = [&](int i) { return i == (int)s.size() ? 0 : 1 + (unsigned char)s[i];
        };
    vector<int> p(n), c(n), cnt(max(alphabet, n), 0);
```

```
    for (int i = 0; i < n; i++) cnt[code(i)]++;
    for (int i = 1; i < alphabet; i++) cnt[i] += cnt[i-1];
    for (int i = 0; i < n; i++) p[--cnt[code(i)]] = i;
    c[p[0]] = 0;
    int classes = 1;
    for (int i = 1; i < n; i++) {
        if (code(p[i]) != code(p[i-1])) classes++;
        c[p[i]] = classes - 1;
    }
    vector<int> pn(n), cn(n);
    for (int h = 0; (1 << h) < n && classes < n; ++h) { // stop once all distinct
        for (int i = 0; i < n; i++) pn[i] = (p[i] - (1 << h) + n) % n;
        fill(cnt.begin(), cnt.begin() + classes, 0);
        for (int i = 0; i < n; i++) cnt[c[pn[i]]]++;
        for (int i = 1; i < classes; i++) cnt[i] += cnt[i-1];
        for (int i = n-1; i >= 0; i--) p[--cnt[c[pn[i]]]] = pn[i];
        cn[p[0]] = 0;
        classes = 1;
        for (int i = 1; i < n; i++) {
            pair<int, int> cur = {c[p[i]], c[(p[i] + (1 << h)) % n]};
            pair<int, int> prev = {c[p[i-1]], c[(p[i-1] + (1 << h)) % n]};
            if (cur != prev) ++classes;
            cn[p[i]] = classes - 1;
        }
        c.swap(cn);
    }
    return p;
}

// sa[i] = start of i-th smallest suffix. Use with lcp_array (Kasai) from lcp.cpp.
vector<int> suffix_array(const string& s) {
    vector<int> p = sort_cyclic_shifts(s, true);
    return vector<int>(p.begin() + 1, p.end());
}
```

3.6 Kasai LCP

Use: LCP array from string and suffix array.
Complexity: $O(n)$.
Pitfalls: Requires valid suffix array for same string. Output size is `n-1`.
Assumptions/deps: Pairs with suffix array snippet.

```
// Kasai LCP array from string s and suffix array sa.
// lcp[i] = LCP(sa[i], sa[i+1]), size max(0, n-1).
// Time: O(n). Source: standard Kasai algorithm (cp-algorithms/USACO Guide).
vector<int> lcp_array(const string& s, const vector<int>& sa) {
    int n = (int)s.size();
    if (n == 0) return {};
    vector<int> rank(n), lcp(n - 1);
    for (int i = 0; i < n; i++) rank[sa[i]] = i;
    int h = 0;
    for (int i = 0; i < n; i++) {
        int r = rank[i];
        if (r == n - 1) {
            h = 0;
            continue;
        }
        int j = sa[r + 1];
        while (i + h < n && j + h < n && s[i + h] == s[j + h]) h++;
        lcp[r] = h;
        if (h) h--;
    }
    return lcp;
}
```

3.7 Suffix Automaton

Use: Substring membership/counts and number of distinct substrings.
Complexity: $O(|s|)$ build for fixed alphabet.
Pitfalls: Add all characters before occurrence propagation; lowercase by default.
Assumptions/deps: Edit marked alphabet block; clones and occurrence propagation included.

```
// Suffix automaton: substring membership, occurrences, distinct substrings.
// Complexity: O(|s|*A) memory here, O(|s|) build/finish for fixed alphabet.
// Input: lowercase text via constructor or extend(), all before finish().
// State v represents substring lengths (len[link[v]], len[v]] sharing the same
// end positions; this gives the distinct-substring sum below.
// Output: state/contains test membership; occurrences returns total matches;
// distinctSubstrings counts distinct nonempty substrings.
// Pitfalls: lowercase only; add all characters before occurrence queries.
struct SuffixAutomaton {
    // ---- customize alphabet here ----------------------------------------
    static const int A = 26;
    static int id(char c) { return c-'a'; }
    // ---------------------------------------------------------------------
    struct State {
        array<int,A> next;
        int link=-1, len=0;
        long long occ=0;
        State() { next.fill(-1); }
    };
    vector<State> st;
    int last;
    bool ready;

```

```
    SuffixAutomaton(const string& s="") {
        init(); for(char c:s) extend(c);
    }
    void init() {
        st.assign(1,State()); last=0; ready=false;
    }
    void extend(char ch) {
        assert(!ready); // occurrence counts have not been propagated yet
        int c=id(ch), cur=st.size(); st.push_back(State());
        st[cur].len=st[last].len+1; st[cur].occ=1;
        int p=last;
        while(p!=-1 && st[p].next[c]==-1) st[p].next[c]=cur,p=st[p].link;
        if(p==-1) st[cur].link=0;
        else {
            int q=st[p].next[c];
            if(st[p].len+1==st[q].len) st[cur].link=q;
            else {
                int clone=st.size(); st.push_back(st[q]);
                st[clone].len=st[p].len+1; st[clone].occ=0;
                while(p!=-1 && st[p].next[c]==q) st[p].next[c]=clone,p=st[p].link;
                st[q].link=st[cur].link=clone;
            }
        }
        last=cur;
    }
    void finish() { // Propagates occurrence counts; call after all extend() calls.
        if(ready) return;
        int mx=0; for(auto& s:st) mx=max(mx,s.len);
        vector<int> cnt(mx+1),order(st.size());
        for(auto& s:st) ++cnt[s.len];
        partial_sum(cnt.begin(),cnt.end(),cnt.begin());
        for(int i=(int)st.size()-1;i>=0;--i) order[--cnt[st[i].len]]=i;
        for(int i=(int)order.size()-1;i>0;--i) {
            int v=order[i]; st[st[v].link].occ+=st[v].occ;
        }
        ready=true;
    }
    int state(const string& s) const {
        int v=0;
        for(char ch:s) { int c=id(ch); if(c<0||c>=A||st[v].next[c]==-1)return -1; v=
             st[v].next[c]; }
        return v;
    }
    bool contains(const string& s) const {
        return state(s)!=-1;
    }
    long long occurrences(const string& s) {
        if(s.empty()) return st[last].len+1;
        finish(); int v=state(s); return v==-1?0:st[v].occ;
    }
    long long distinctSubstrings() const {
        long long ans=0;
        for(int v=1;v<(int)st.size();++v) ans+=st[v].len-st[st[v].link].len;
        return ans;
    }
};
```

3.8 Palindromic Tree (Eertree)

Use: Online distinct palindromes and occurrence counts.
Complexity: $O(n)$ build for fixed alphabet.
Pitfalls: Add all characters before propagating occurrences; lowercase by default.
Assumptions/deps: Nodes expose length, suffix link, first endpoint, and count.

```
// Palindromic tree (eertree): online distinct palindromes and occurrences.
// Complexity: O(n*A) memory here, O(n) build and occurrence propagation.
// Input: lowercase characters passed to add in text order.
// Each non-root node is one distinct palindrome. link[v] points to its
// longest proper palindromic suffix. Nodes 0/1 have
// lengths -1/0. Output: add returns the longest suffix node; after
// finishOccurrences(), tree[v].occ is the total count of palindrome v.
// Pitfalls: lowercase only; finish once after all adds, then do not extend.
struct Eertree {
    // ---- customize alphabet here ----------------------------------------
    static const int A=26;
    static int id(char c){return c-'a';}
    // ---------------------------------------------------------------------
    struct Node {
        int len=0,link=0,firstEnd=-1;
        long long occ=0;
        array<int,A>next;
        Node(int length=0):len(length){next.fill(-1);}
    };
    vector<Node>tree;
    vector<int>s;
    string text;
    int suffix;
    bool ready;

    Eertree(const string& str=""){
        init();for(char c:str)add(c);
    }
    void init(){
        tree={Node(-1),Node(0)};tree[0].link=0;tree[1].link=0;s={-1};text.clear();
             suffix=1;ready=false;
    }
    int getLink(int v,int pos,int c) const { // Internal: returns the longest
         extendable palindromic suffix node.
        while(s[pos-1-tree[v].len]!=c)v=tree[v].link;
        return v;
```

```
    }
    int add(char ch) {
        assert(!ready);
        int c=id(ch);assert(0<=c&&c<A);
        text.push_back(ch);s.push_back(c);
        int pos=s.size()-1,cur=getLink(suffix,pos,c);
        if(tree[cur].next[c]==-1) {
            int now=tree.size();tree.push_back(Node(tree[cur].len+2));
            tree[now].firstEnd=text.size()-1;
            if(tree[now].len==1)tree[now].link=1;
            else {int p=getLink(tree[cur].link,pos,c);tree[now].link=tree[p].next[c];}
            tree[cur].next[c]=now;
        }
        suffix=tree[cur].next[c];++tree[suffix].occ;
        return suffix;
    }
    int distinct() const{return (int)tree.size()-2;}
    int longestSuffix() const{return suffix;}
    string palindrome(int node) const {
        int r=tree[node].firstEnd;
        return text.substr(r-tree[node].len+1,tree[node].len);
    }
    void finishOccurrences() { // Propagates final occurrence counts; call after the
         last add().
        if(ready)return;
        for(int v=(int)tree.size()-1;v>=2;--v)
            tree[tree[v].link].occ+=tree[v].occ;
        ready=true;
    }
};
```

3.9 Minimum Rotation

Use: Lexicographically minimum cyclic rotation index.
Complexity: $O(n)$.
Pitfalls: For periodic strings returns one minimum index; empty string returns 0.
Assumptions/deps: 0-indexed index in original string.

```
// Booth's algorithm: start index of the lexicographically smallest cyclic
// rotation. O(n) time, O(n) memory; empty string returns 0.
// Example: min_rotation("baca")==3 because "abac" is smallest.
int min_rotation(string s) {
    s += s;
    int n = s.size(), i = 0, ans = 0;

    while (i < n / 2) {
        ans = i;
        int j = i + 1, k = i;

        while (j < n && s[k] <= s[j]) {
            if (s[k] < s[j]) k = i;
            else k++;
            j++;
        }

        while (i <= k) i += j - k;
    }

    return ans;
}
```

3.10 Z Function

Use: Longest prefix match starting at each position.
Complexity: $O(n)$.
Pitfalls: For pattern matching, use separator not in alphabet. `z[0]=0`.
Assumptions/deps: 0-indexed string.

```
// z[i] is the length of the prefix matching s starting at i; z[0]=0.
// O(n) time/memory. Empty input returns {}; internal window is [l,r).
// Matching pitfall: a separator in pattern + separator + text must be absent.
// Example: z_function("aaaa") == vector<int>({0,3,2,1}).
vector<int> z_function(const string& s) {
    int n = s.size(), l = 0, r = 0;
    vector<int> z(n);
    for (int i = 1; i < n; i++) {
        if (i < r) z[i] = min(r - i, z[i - l]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]]) z[i]++;
        if (i + z[i] > r) l = i, r = i + z[i];
    }
    return z;
}
```

3.11 Aho-Corasick

Use: Count matches of many patterns in text.
Complexity: Build $O(\textit{total length} \cdot A)$, scan $O(n)$.
Pitfalls: Call `build()` after all patterns; out-of-alphabet chars are UB.
Assumptions/deps: EDIT ONLY `A`/`idx()` for other alphabets. Stores counts, not ids.

```
// Aho-Corasick counts occurrences of many lowercase patterns in one text.
```

```cpp
// Input: add lowercase patterns, build once, then scan lowercase text.
// Effect: duplicate add calls add multiplicity; build fills failure transitions.
// Output: countMatches(text) returns total hits over all pattern copies.
// Complexity: build O(total pattern length*A), match O(text length); O(nodes*A).
// Pitfalls: build fills missing transitions, so do not add patterns afterward.
struct Aho {
    // EDIT ONLY A and idx() for other alphabets; out-of-range chars = UB.
    static const int A = 26;
    static int idx(char ch) { return ch - 'a'; }

    struct Node {
        int nxt[A], link = 0, out = 0;
        Node() { memset(nxt, -1, sizeof nxt); }
    };
    vector<Node> t{Node()};
    void add(const string& s) {
        int v = 0;
        for (char ch : s) {
            int c = idx(ch);
            if (t[v].nxt[c] == -1) t[v].nxt[c] = t.size(), t.emplace_back();
            v = t[v].nxt[c];
        }
        t[v].out++;
    }
    void build() { // Completes failure transitions; call after all patterns and
         before matching.
        queue<int> q;
        for (int c = 0; c < A; c++) {
            int u = t[0].nxt[c];
            if (u == -1) t[0].nxt[c] = 0;
            else q.push(u);
        }
        while (!q.empty()) {
            int v = q.front(); q.pop();
            t[v].out += t[t[v].link].out;
            for (int c = 0; c < A; c++) {
                int u = t[v].nxt[c];
                if (u == -1) t[v].nxt[c] = t[t[v].link].nxt[c];
                else t[u].link = t[t[v].link].nxt[c], q.push(u);
            }
        }
    }
    long long countMatches(const string& s) {
        int v = 0;
        long long ans = 0;
        for (char ch : s) v = t[v].nxt[idx(ch)], ans += t[v].out;
        return ans;
    }
};
```

Aho-Corasick: duplicate patterns

Add every pattern before `build()`. Duplicate insertions count as distinct pattern occurrences in the returned total.

```cpp
// Input: pattern "he" twice, pattern "she", then text "she".
Aho ac;
ac.add("he"); ac.add("he"); ac.add("she");
ac.build();
long long hits = ac.countMatches("she");
// Expected output: hits=3 ("she" once and "he" twice).
```

Eertree: save a palindrome node, then finalize counts

`add(c)` returns the node for the longest palindromic suffix after adding `c`. Save node ids while building; occurrence totals are final only after `finishOccurrences()`.

```cpp
// Input: lowercase text "ababa", added left to right.
Eertree e;
int aba = -1;
string s = "ababa";
for (int i = 0; i < (int)s.size(); ++i) {
    int suffix = e.add(s[i]);
    if (i == 2) aba = suffix;
}
string represented = e.palindrome(aba);
int kinds = e.distinct();
e.finishOccurrences();
long long copies = e.tree[aba].occ;
// Expected: represented="aba"; kinds=5; copies=2.
```

Suffix automaton: membership, occurrences, distinct substrings

The string constructor completes all `extend()` calls. `occurrences()` performs the one-time occurrence propagation automatically; do not extend afterward.

```cpp
// Input: lowercase text "ababa" and query substrings "bab"/"aba".
SuffixAutomaton sam("ababa");
bool has = sam.contains("bab");
long long copies = sam.occurrences("aba");
long long kinds = sam.distinctSubstrings();
// Expected: has=true; copies=2; kinds=9.
```

4 Graph

Checklist: `at` is the current vertex and `to` is its neighbor. Directed or undirected? weights negative? multiple edges/self-loops? clear globals between tests? recursion depth? 0-index input conversion?

4.1 Dinic Max Flow

Use: Directed max flow and min cut.
Complexity: General fast in practice; unit capacities have better listed bounds.
Pitfalls: Edges are directed; add both directions for undirected capacity. Capacities are `long long`.
Assumptions/deps: Requires `sz`, `rep`, `bits/stdc++.h`/STL.

```cpp
// Dinic maximum flow with capacity scaling. addEdge(u,v,c,rc) adds residual
// capacities in both directions; calc augments the current residual network.
// Use distinct terminals for min-cut queries. calc(s,s) returns zero.
// Afterwards leftOfMinCut(v) marks the source side and minCutEdges lists its
// original crossing arcs. Example: addEdge(0,1,5); calc(0,1)==5.
// Unit capacities: O(min(sqrt(E),V^(2/3))*E); bipartite matching O(sqrt(V)*E).
// Requires bits/stdc++.h and using namespace std.
using ll = long long;
using vi = vector<int>;
#ifndef sz
#define sz(x) (int)(x).size()
#endif
#ifndef rep
#define rep(i,a,b) for (int i = (a); i < (b); ++i)
#endif

struct Dinic {
  struct Edge {
    int to, rev;
    ll c, oc;
    ll flow() { return max(oc - c, 0LL); } // if you need flows
  };
  vi lvl, ptr, q;
  vector<vector<Edge>> adj;
  Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
  void addEdge(int a, int b, ll c, ll rcap = 0) {
    int i = sz(adj[a]), j = sz(adj[b]);
    adj[a].push_back({b, j + (a == b), c, c});
    adj[b].push_back({a, i, rcap, rcap});
  }
  ll dfs(int at, int t, ll f) {
    if (at == t || !f) return f;
    for (int& i = ptr[at]; i < sz(adj[at]); i++) {
      Edge& e = adj[at][i];
      if (lvl[e.to] == lvl[at] + 1)
        if (ll p = dfs(e.to, t, min(f, e.c))) {
          e.c -= p, adj[e.to][e.rev].c += p;
          return p;
        }
    }
    return 0;
  }
  ll calc(int s, int t) {
    if (s == t) return 0;
    ll flow = 0; q[0] = s;
    rep(L,0,31) do { // 'int L=30' maybe faster for random data
      lvl = ptr = vi(sz(q));
      int qi = 0, qe = lvl[s] = 1;
      while (qi < qe && !lvl[t]) {
        int at = q[qi++];
        for (Edge e : adj[at])
          if (!lvl[e.to] && e.c >> (30 - L))
            q[qe++] = e.to, lvl[e.to] = lvl[at] + 1;
      }
      while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
    } while (lvl[t]);
    return flow;
  }
  bool leftOfMinCut(int a) {
    return lvl[a] != 0;
  }
  vector<pair<int, int>> minCutEdges() {
    vector<pair<int, int>> cut;
    rep(at,0,sz(adj)) if (leftOfMinCut(at)) {
      for (Edge& e : adj[at])
        if (e.oc > 0 && e.c == 0 && !leftOfMinCut(e.to))
          cut.push_back({at, e.to});
    }
    return cut;
  }
};
```

4.2 Maximum-Weight Closure

Use: Choose profitable vertices under directed implications.
Complexity: One max-flow on $n + 2$ vertices.
Pitfalls: INF must exceed every finite cut; implication is directed.
Assumptions/deps: Requires Dinic immediately above.

```cpp
// Maximum-weight closure via one s-t min cut. Depends on Dinic.
```

```cpp
// If u is chosen and (u,v) is an implication, v must also be chosen.
// Complexity: one max-flow on n+2 vertices and O(n+m) edges.
// Pitfalls: MCF_INF must exceed total absolute weight; directed implications.
// Usage: auto [best,chosen]=max_weight_closure(weight,implications);
const long long MCF_INF = (1LL<<60);
struct MaxClosureResult { long long value; vector<int> chosen; };

MaxClosureResult max_weight_closure(
    const vector<long long>& weight, const vector<pair<int,int>>& implications) {
    int n=weight.size(), s=n, t=n+1;
    Dinic flow(n+2);
    long long positive=0;
    for (int v=0;v<n;++v) {
        if (weight[v]>0) flow.addEdge(s,v,weight[v]), positive+=weight[v];
        if (weight[v]<0) flow.addEdge(v,t,-weight[v]);
    }
    for (auto [u,v]:implications) flow.addEdge(u,v,MCF_INF);
    long long best=positive-flow.calc(s,t);
    vector<int> chosen;
    for (int v=0;v<n;++v) if (flow.leftOfMinCut(v)) chosen.push_back(v);
    return {best,chosen};
}
```

4.3 Min-Cut Modeling Recipes

Use: Closure, bipartite vertex cover, and binary labeling reductions.
Complexity: One max-flow after graph construction.
Pitfalls: Cut-side meaning and INF choice are common sources of reversed answers.
Assumptions/deps: Pair with Dinic and residual source-side query.

Choose INF strictly larger than every feasible finite cut, often $1+\sum_v |cost_v|$. After max flow, residual-reachable vertices form the source side of a minimum cut.

Maximum-weight closure

- $profit_v > 0$: edge $s \to v$ with capacity $profit_v$.
- $profit_v < 0$: edge $v \to t$ with capacity $-profit_v$.
- Choosing u requires v: edge $u \to v$ with capacity INF.
- Answer: $\sum_v \max(0, profit_v) -$ mincut.

Bipartite minimum-weight vertex cover

- $s \to u$ for each left vertex; capacity is its weight.
- $v \to t$ for each right vertex; capacity is its weight.
- For every graph edge, add $u \to v$ with capacity INF.
- Cover = left vertices outside the source side + right vertices inside it.

Binary labeling

Use $s \to v$ for the cost of label 1, $v \to t$ for label 0, and undirected capacity w for disagreement penalty w.

Pitfalls: an INF edge is hard only if no optimum can cut it. Decide which side means "chosen." General pairwise rewards require submodularity and may not be graph-representable.

4.4 Dijkstra

Use: Single-source shortest paths with nonnegative weights.
Complexity: $O((n+m)\log n)$.
Pitfalls: No negative edges. `INFLL` must exceed all finite shortest paths.
Assumptions/deps: Graph as `vector<vector<pair<int,ll>>>`.

```cpp
// Dijkstra shortest paths for nonnegative edge weights.
// Complexity: O((n + m) log n).
// Pitfalls: no negative edges. INFLL must exceed all finite shortest paths.
// Usage: vector<vector<pair<int,ll>>> g(n); auto d = dijkstra(g, s);
// Path reconstruction: add vector<int> par(n,-1); set par[to]=at next to
// dist[to]=d+w; walk par[] back from t.
using ll = long long;
const ll INFLL = (1LL << 62);

vector<ll> dijkstra(const vector<vector<pair<int, ll>>>& g, int s) {
    int n = (int)g.size();
    vector<ll> dist(n, INFLL);
    priority_queue<pair<ll, int>, vector<pair<ll, int>>, greater<pair<ll, int>>> pq;
    dist[s] = 0;
    pq.push({0, s});
    while (!pq.empty()) {
        auto [d, at] = pq.top();
        pq.pop();
        if (d != dist[at]) continue;
        for (auto [to, w] : g[at]) {
            if (w < dist[to] - d) {
                dist[to] = d + w;
                pq.push({dist[to], to});
            }
        }
    }
    return dist;
}
```

4.5 Multi-source and 0-1 BFS

Use: Nearest-source distances and shortest paths with weights 0/1.
Complexity: $O(n+m)$.
Pitfalls: Every weighted edge must be exactly 0 or 1; unreachable values differ by function.
Assumptions/deps: Adjacency-list functions; duplicate sources handled.

```cpp
// Multi-source BFS and 0-1 BFS shortest paths.
// Complexity: O(n+m); -1/INF means unreachable.
// Pitfalls: 0-1 BFS requires every edge weight to be exactly 0 or 1.
// Usage: bfs_multi(g,sources); bfs01(weighted_graph,source);
vector<int> bfs_multi(const vector<vector<int>>& g, const vector<int>& sources) {
    vector<int> d(g.size(), -1);
    queue<int> q;
    for (int s : sources) if (0 <= s && s < (int)g.size() && d[s] == -1)
        d[s] = 0, q.push(s);
    while (!q.empty()) {
        int at = q.front(); q.pop();
        for (int to : g[at]) if (d[to] == -1) d[to] = d[at] + 1, q.push(to);
    }
    return d;
}

vector<long long> bfs01(const vector<vector<pair<int, int>>>& g, int s) {
    const long long INF = (1LL << 62);
    vector<long long> d(g.size(), INF);
    deque<pair<long long, int>> q;
    d[s] = 0; q.push_front({0, s});
    while (!q.empty()) {
        auto [distAt, at] = q.front(); q.pop_front();
        if (distAt != d[at]) continue;
        for (auto [to, w] : g[at]) if (d[to] > distAt + w) {
            d[to] = distAt + w;
            if (w == 0) q.push_front({d[to], to});
            else q.push_back({d[to], to});
        }
    }
    return d;
}
```

4.6 Kuhn Bipartite Matching

Use: Maximum bipartite matching for smaller/simple cases; `DenseKuhn` for dense graphs up to about 5000 per side.
Complexity: Usually $O(VE)$ worst case; dense bitset variant $O(n(n+m)R/64)$, $R =$`DK_MAXR`.
Pitfalls: Left side size `n`, right side `m`. Konig notes in header. `DenseKuhn`: right ids below `DK_MAXR`.
Assumptions/deps: Large sparse graphs: Dinic with unit caps ($O(E\sqrt{V})$, = Hopcroft-Karp).

```cpp
// Kuhn max bipartite matching, left size n / right size m. O(V*E) worst case
// but fast in practice with the repeat loop. add(l,r) adds an edge;
// matching() returns (left,right) pairs; match[r] = left partner of r or -1.
// Large/adversarial graphs: use Dinic (dinic_2.cpp) with unit capacities
// source->left->right->sink: O(E sqrt V), same as Hopcroft-Karp.
// Konig: min vertex cover size = max matching; complement = max independent set.
// Example: edges (0,1),(1,0) produce two pairs (order unspecified).
struct bipartite {
    int n, m;
    vector<vector<int>> g;
    vector<int> match;
    vector<bool> visited;
    bipartite(int n, int m) : n(n), m(m), g(n), match(m, -1) {}
    void add(int a, int b) { g[a].push_back(b); }
    bool kuhn(int at) {
        if (visited[at]) return false;
        visited[at] = true;
        for (int to : g[at])
            if (match[to] == -1 || kuhn(match[to])) { match[to] = at; return true; }
        return false;
    }
    vector<pair<int, int>> matching() {
        fill(match.begin(), match.end(), -1);
        vector<bool> paired(n);
        for (bool repeat = true; repeat;) {
            repeat = false;
            visited.assign(n, false);
            for (int i = 0; i < n; i++)
                if (!paired[i] && kuhn(i)) paired[i] = repeat = true;
        }
        vector<pair<int, int>> ans;
        for (int r = 0; r < m; r++) if (match[r] != -1) ans.emplace_back(match[r], r)
            ;
        return ans;
    }
};

// Dense variant (e.g. n=m=5000, ~n^2/2 edges): rows are bitsets, right ids < DK_MAXR
    .
// O(n*(n+m)*DK_MAXR/64) worst case; memory n*DK_MAXR/8 bytes. Recursion depth <= n.
// Tries a free neighbor first; keeps seen marks across FAILED searches (still dead).
// adj[l][r]=1 adds edge l-r; solve() returns the size; mt[r] = left partner or -1.
// Pitfall: keep the AND in member tmp; a bitset temporary per frame overflows stack.
const int DK_MAXR = 5000;
struct DenseKuhn {
    vector<bitset<DK_MAXR>> adj;
```

```
    bitset<DK_MAXR> unseen, freeR, tmp;
    vector<int> mt;
    DenseKuhn(int n) : adj(n), mt(DK_MAXR, -1) {}
    int first(int at, const bitset<DK_MAXR>& b) { tmp = adj[at]; tmp &= b; return tmp
        ._Find_first(); }
    bool dfs(int at) {
        int to = first(at, freeR);
        if (to < DK_MAXR) { freeR[to] = 0; mt[to] = at; return true; }
        while ((to = first(at, unseen)) < DK_MAXR) { // to is matched
            unseen[to] = 0;
            if (dfs(mt[to])) { mt[to] = at; return true; }
        }
        return false;
    }
    int solve() {
        fill(mt.begin(), mt.end(), -1);
        freeR.set(), unseen.set();
        int res = 0;
        for (int i = 0; i < (int)adj.size(); i++) if (dfs(i)) res++, unseen.set();
        return res;
    }
};
```

4.7 LCA Binary Lifting

Use: LCA, distance, kth ancestor, dfs order `tin`.
Complexity: Build $O(n \log n)$, query $O(\log n)$.
Pitfalls: Call `build(root)`; recursion depth can overflow on large chain.
Assumptions/deps: Graph must be a tree; 0-indexed. `tin` feeds Virtual Tree.

```
// Binary lifting LCA for rooted trees. Also provides dfs-order tin
// (used by virtual_tree.cpp) and kth-ancestor lift.
// Complexity: build O(n log n), query O(log n).
// addEdge loads the tree; build(root) fixes parents/depths. lift(v,k) moves k
// parent edges (stays at root above it); lca/dist query two built vertices.
// Example on edges 0-1,1-2,1-3 rooted at 0: lca(2,3)==1; dist(2,3)==2.
// Pitfalls: build before queries; graph must be a tree; recursion depth on chains.
struct LCA {
    int n, LOG, timer = 0;
    vector<vector<int>> g, up;
    vector<int> depth, tin;
    LCA(int n = 0) { init(n); }
    void init(int n_) {
        n = n_;
        LOG = 1;
        while ((1LL << LOG) <= n) LOG++;
        g.assign(n, {});
        up.assign(LOG, vector<int>(n));
        depth.assign(n, 0);
        tin.assign(n, 0);
        timer = 0;
    }
    void addEdge(int u, int v) {
        g[u].push_back(v);
        g[v].push_back(u);
    }
    void dfs(int at, int p) {
        tin[at] = timer++;
        up[0][at] = p;
        for (int j = 1; j < LOG; j++) up[j][at] = up[j - 1][up[j - 1][at]];
        for (int to : g[at]) if (to != p) {
            depth[to] = depth[at] + 1;
            dfs(to, at);
        }
    }
    void build(int root = 0) {
        timer = 0;
        depth[root] = 0;
        dfs(root, root);
    }
    int lift(int v, int k) {
        k = min(k, depth[v]);
        for (int j = 0; j < LOG; j++) if (k >> j & 1) v = up[j][v];
        return v;
    }
    int lca(int a, int b) {
        if (depth[a] < depth[b]) swap(a, b);
        a = lift(a, depth[a] - depth[b]);
        if (a == b) return a;
        for (int j = LOG - 1; j >= 0; j--) if (up[j][a] != up[j][b]) {
            a = up[j][a];
            b = up[j][b];
        }
        return up[0][a];
    }
    int dist(int a, int b) {
        int c = lca(a, b);
        return depth[a] + depth[b] - 2 * depth[c];
    }
};
```

4.8 Topological Sort

Use: DFS order and directed-cycle detection.
Complexity: $O(n+m)$.
Pitfalls: An empty result also represents an empty graph; check input size separately if needed.
Assumptions/deps: DFS lambda uses three states; recursion depth can reach n.

```cpp
// Topological order: each edge u->v puts u before v. O(n+m) time, O(n) space.
// Pitfalls: recursive depth O(n); empty result means cycle or empty graph.
// Usage: auto order=topological_sort(g); bool dag=order.size()==g.size();
vector<int> topological_sort(const vector<vector<int>>& g) {
    vector<int> state(g.size()), order; // 0=unseen, 1=active, 2=finished
    auto dfs = [&](auto&& self, int at) -> bool {
        if (state[at]) return state[at] == 2;
        state[at] = 1;
        for (int to : g[at]) if (!self(self, to)) return false;
        state[at] = 2;
        order.push_back(at);
        return true;
    };
    for (int v = 0; v < (int)g.size(); ++v)
        if (!dfs(dfs, v)) return {};
    reverse(order.begin(), order.end());
    return order;
}
```

4.9 Functional Graph

Use: 64-bit successor jumps, cycle id, entry, and distance to cycle.
Complexity: Build $O(64n)$; jump $O(64)$.
Pitfalls: Every successor must be valid; cycle ids are arbitrary and reset per object. Memory is $4 \cdot \texttt{LOG} \cdot n$ bytes (51 MB at $n = 2 \cdot 10^5$): lower `LOG` for small jump counts.
Assumptions/deps: 0-indexed; supports full unsigned 64-bit jump count.

```cpp
// Functional graph: 64-bit successor jumps plus cycle metadata.
// Complexity: O(n log K) build, O(log K) jump, O(1) metadata queries.
// Pitfalls: next[v] must be valid; dist=0 exactly on a cycle; reset per test.
// Memory is 4*LOG*n bytes (51 MB at n=2e5): lower LOG when k < 2^LOG.
// go(v,k) follows k edges. cycle[v] identifies the eventual cycle; dist[v]
// is steps to it and entry[v] is the first cycle vertex reached.
// Example: next={1,2,1}; go(0,3)==1, dist[0]==1, entry[0]==1.
struct FunctionalGraph {
    static constexpr int LOG = 64; // EDIT: go() needs k < 2^LOG
    vector<vector<int32_t>> up; // int32_t: not widened by #define int
    vector<int> cycle, dist, entry;

    FunctionalGraph(const vector<int>& next) {
        int n = (int)next.size();
        up.assign(LOG, vector<int32_t>(n));
        up[0].assign(next.begin(), next.end());
        for (int b = 1; b < LOG; ++b) for (int v = 0; v < n; ++v)
            up[b][v] = up[b - 1][up[b - 1][v]];

        vector<int> indeg(n), alive(n, 1), order;
        for (int to : next) ++indeg[to];
        queue<int> q;
        for (int v = 0; v < n; ++v) if (!indeg[v]) q.push(v);
        while (!q.empty()) {
            int at = q.front(); q.pop(); alive[at] = 0; order.push_back(at);
            if (--indeg[next[at]] == 0) q.push(next[at]);
        }
        cycle.assign(n, -1); dist.assign(n, -1); entry.assign(n, -1);
        int cid = 0;
        for (int s = 0; s < n; ++s) if (alive[s] && cycle[s] == -1) {
            int v = s;
            do { cycle[v] = cid; dist[v] = 0; entry[v] = v; v = next[v]; } while (v !=
                s);
            ++cid;
        }
        reverse(order.begin(), order.end());
        for (int v : order) {
            int to = next[v];
            cycle[v] = cycle[to]; dist[v] = dist[to] + 1; entry[v] = entry[to];
        }
    }

    int go(int v, unsigned long long k) const {
        for (int b = 0; k; ++b, k >>= 1) if (k & 1) v = up[b][v];
        return v;
    }
};
```

4.10 Heavy Light Decomposition

Use: Convert tree paths and subtrees into array intervals.
Complexity: $O(n)$ build; $O(\log n)$ intervals per path; one per subtree.
Pitfalls: Root is 0. Path intervals may arrive out of order.
Assumptions/deps: `process(u,v,op)` visits half-open intervals. `subtree(v)` returns one.

```cpp
// HLD: split paths and subtrees into half-open intervals on a 0-rooted tree.
```

```cpp
// Build O(n) time/space; process(u,v,op) emits O(log n) intervals;
// subtree(v) gives one interval in O(1). pos[v] is the vertex's index.
// VALS_EDGES stores edges at their deeper endpoints and skips the LCA.
// Path intervals may be empty or arrive out of path order. DFS is recursive.
template <bool VALS_EDGES> struct HLD {
    int N, tim = 0;
    vector<vector<int>> adj;
    vector<int> par, siz, rt, pos;
    HLD(vector<vector<int>> adj_)
        : N(adj_.size()), adj(move(adj_)), par(N, -1), siz(N, 1), rt(N), pos(N) {
        if (N) { dfsSz(0); dfsHld(0); }
    }
    void dfsSz(int at) {
        if (par[at] != -1) adj[at].erase(find(adj[at].begin(), adj[at].end(), par[at
            ]));
        for (int& to : adj[at]) {
            par[to] = at;
            dfsSz(to);
            siz[at] += siz[to];
            if (siz[to] > siz[adj[at][0]]) swap(to, adj[at][0]);
        }
    }
    void dfsHld(int at) {
        pos[at] = tim++;
        for (int to : adj[at]) {
            rt[to] = (to == adj[at][0] ? rt[at] : to);
            dfsHld(to);
        }
    }
    template <class B> void process(int u, int v, B op) { // op gets [l, r), may be
        empty
        for (; rt[u] != rt[v]; v = par[rt[v]]) {
            if (pos[rt[u]] > pos[rt[v]]) swap(u, v);
            op(pos[rt[v]], pos[v] + 1);
        }
        if (pos[u] > pos[v]) swap(u, v);
        op(pos[u] + VALS_EDGES, pos[v] + 1);
    }
    pair<int, int> subtree(int v) {
        return {pos[v] + VALS_EDGES, pos[v] + siz[v]};
    }
};
```

Usage with range add and sum

Copy the default Lazy Segment Tree for this example.

```cpp
vector<vector<int>> g = {{1,2}, {0,3,4}, {0}, {1}, {1}};
HLD<false> h(g); // values on vertices
SegTree st(g.size());
h.process(3, 2, [&](int l, int r) { st.update(l, r, 5); });
long long pathSum = 0;
h.process(3, 2, [&](int l, int r) { pathSum += st.query(l, r); });
auto [l, r] = h.subtree(1);
long long subtreeSum = st.query(l, r);
// pathSum = 20, subtreeSum = 10
```

To load initial vertex values, put `value[v]` at `h.pos[v]` before building the segment tree. For `HLD<true>`, put each edge's value at its deeper endpoint. Path and subtree operations then skip the top vertex's incoming edge. Path intervals may arrive out of order, so use a commutative aggregate such as sum, min or max.

4.11 Bridges and Articulation Points

Use: Lowlink for undirected multigraphs.
Complexity: $O(n+m)$ time and memory.
Pitfalls: Insert each edge once; recursive DFS may overflow on chains.
Assumptions/deps: `Lowlink g(n); g.addEdge(u,v); g.build();` Results: bridge edge IDs in `bridges`, vertex flags in `is_cut`.

```cpp
#pragma once
// Bridges and articulation points of an undirected multigraph.
// O(n+m) time and memory. addEdge returns an edge ID; build resets results.
// bridges contains edge IDs; is_cut[v] marks articulation points.
// Pitfalls: insert each edge once; DFS recursion can overflow on long chains.
// Example: Lowlink g(3); g.addEdge(0,1); g.addEdge(1,2); g.build();
// Then g.bridges has both IDs and g.is_cut[1] is true.
struct Lowlink {
    int n, timer = 0, edges = 0;
    vector<vector<pair<int,int>>> adj;
    vector<int> tin, low, bridges;
    vector<bool> is_cut;
    Lowlink(int n) : n(n), adj(n) {}
    int addEdge(int u, int v) {
        adj[u].push_back({v, edges});
        adj[v].push_back({u, edges});
        return edges++;
    }
    void dfs(int v, int parent_edge = -1) {
        tin[v] = low[v] = timer++;
        int children = 0;
        for (auto [u, id] : adj[v]) {
            if (id == parent_edge) continue;
            if (tin[u] != -1) low[v] = min(low[v], tin[u]);
            else {
                dfs(u, id);
                low[v] = min(low[v], low[u]);
                if (low[u] > tin[v]) bridges.push_back(id);
                if (parent_edge != -1 && low[u] >= tin[v]) is_cut[v] = true;
                ++children;
```

```
            }
        }
        if (parent_edge == -1) is_cut[v] = children > 1;
    }
    void build() {
        timer = 0;
        bridges.clear();
        tin.assign(n, -1);
        low.resize(n);
        is_cut.assign(n, false);
        for (int v = 0; v < n; ++v) if (tin[v] == -1) dfs(v);
    }
};
```

4.12 Rerooting DP

Use: Compute a tree DP answer for every possible root.
Complexity: $O(n)$ for constant-time DP operations.
Pitfalls: Merge must be associative; recursion depth; input must be a tree.
Assumptions/deps: Default is sum of distances; edit only marked DP operations.

```
// Rerooting DP. Configured to compute sum of distances from every vertex.
// To reuse, edit ONLY DP/ID and merge/addEdge/addRoot in the marked block.
// Complexity: O(n) time and memory for constant-time DP operations.
// Pitfalls: merge must be associative; recursive DFS can overflow; tree only.
// Usage: Rerooting rr(g); vector<DP> answer=rr.solve(0);
struct Rerooting {
    // ---- customize the DP ------------------------------------------------
    struct DP { long long size, sum; };
    static DP id() { return {0,0}; }
    static DP merge(DP a,DP b) { return {a.size+b.size,a.sum+b.sum}; }
    static DP addEdge(DP a,int /*from*/,int /*to*/) { return {a.size,a.sum+a.size}; }
    static DP addRoot(DP a,int /*v*/) { ++a.size; return a; }
    // ----------------------------------------------------------------------

    int n;
    const vector<vector<int>>& g;
    vector<DP> down, answer;
    Rerooting(const vector<vector<int>>& graph):n(graph.size()),g(graph),down(n),
        answer(n){}

    DP dfsDown(int at,int p) {
        DP cur=id();
        for (int to:g[at]) if (to!=p) cur=merge(cur,addEdge(dfsDown(to,at),to,at));
        return down[at]=addRoot(cur,at);
    }
    void dfsAll(int at,int p,DP fromParent) {
        int d=g[at].size();
        vector<DP> side(d),pre(d+1,id()),suf(d+1,id());
        for (int i=0;i<d;++i) {
            int to=g[at][i];
            side[i]=(to==p?fromParent:addEdge(down[to],to,at));
            pre[i+1]=merge(pre[i],side[i]);
        }
        for (int i=d-1;i>=0;--i) suf[i]=merge(side[i],suf[i+1]);
        answer[at]=addRoot(pre[d],at);
        for (int i=0;i<d;++i) if (g[at][i]!=p) {
            DP without=addRoot(merge(pre[i],suf[i+1]),at);
            dfsAll(g[at][i],at,addEdge(without,at,g[at][i]));
        }
    }
    vector<DP> solve(int root=0) {
        if (!n) return {};
        dfsDown(root,-1); dfsAll(root,-1,id());
        return answer;
    }
};
```

4.13 Centroid Decomposition

Use: Build centroid-parent hierarchy for distance/path query structures.
Complexity: $O(n \log n)$.
Pitfalls: Recursive DFS can overflow; `build()` resets decomposition state but keeps edges.
Assumptions/deps: Reusable tree/forest object with `addEdge/build/parent`.

```
// Centroid decomposition of a tree/forest. Parent[] is the centroid tree.
// Complexity: O(n log n) time, O(n) memory.
// Pitfalls: recursive DFS can overflow on a long chain; build() resets state,
// but keeps edges. The input must be a forest.
// addEdge loads the forest; build fills parent[v] in the centroid forest
// (a centroid root has parent -1). Walk parent links for centroid-query updates.
struct CentroidDecomposition {
    int n;
    vector<vector<int>> g;
    vector<int> sub, parent;
    vector<char> dead;

    CentroidDecomposition(int n = 0) { init(n); }
    void init(int n_) {
        n = n_;
        g.assign(n, {});
        sub.resize(n);
        parent.assign(n, -1);
        dead.assign(n, false);
```

```
    }
    void addEdge(int u, int v) {
        g[u].push_back(v); g[v].push_back(u);
    }

    int sizes(int at, int p) {
        sub[at] = 1;
        for (int to : g[at]) if (to != p && !dead[to]) sub[at] += sizes(to, at);
        return sub[at];
    }
    int centroid(int at, int p, int total) {
        for (int to : g[at])
            if (to != p && !dead[to] && sub[to] > total / 2)
                return centroid(to, at, total);
        return at;
    }
    int decompose(int entry, int p) {
        int c = centroid(entry, -1, sizes(entry, -1));
        parent[c] = p;
        dead[c] = true;
        for (int to : g[c]) if (!dead[to]) decompose(to, c);
        return c;
    }
    void build() {
        fill(dead.begin(), dead.end(), false);
        fill(parent.begin(), parent.end(), -1);
        for (int v = 0; v < n; ++v) if (!dead[v]) decompose(v, -1);
    }
};
```

4.14 CDQ 3D Dominance

Use: Count points dominated coordinate-wise by each point.
Complexity: $O(n \log^2 n)$.
Pitfalls: Exact duplicates are grouped; result excludes the point itself.
Assumptions/deps: Coordinates may be negative; includes an internal Fenwick tree.

```
// 3D dominance: for each point, count OTHER points with x<=X,y<=Y,z<=Z.
// Complexity: O(n log^2 n) time, O(n) memory (CDQ + Fenwick).
// Pitfalls: exact duplicate points are grouped; coordinates may be negative.
// Usage: vector<long long> ans = dominance_count(points);
struct Point3 { long long x, y, z; };

vector<long long> dominance_count(const vector<Point3>& input) {
    struct Node {
        long long x, y, z, weight, ans;
        int zi;
        vector<int> ids;
    };
    int n = input.size();
    vector<int> order(n); iota(order.begin(), order.end(), 0);
    sort(order.begin(), order.end(), [&](int a, int b) {
        return tie(input[a].x, input[a].y, input[a].z) <
               tie(input[b].x, input[b].y, input[b].z);
    });
    vector<Node> a;
    for (int id : order) {
        auto p = input[id];
        if (a.empty() || tie(a.back().x, a.back().y, a.back().z) != tie(p.x, p.y, p.z
            ))
            a.push_back({p.x, p.y, p.z, 0, 0, 0, {}});
        ++a.back().weight;
        a.back().ids.push_back(id);
    }
    vector<long long> zs;
    for (auto& p : a) zs.push_back(p.z);
    sort(zs.begin(), zs.end()); zs.erase(unique(zs.begin(), zs.end()), zs.end());
    for (auto& p : a) {
        p.zi = lower_bound(zs.begin(), zs.end(), p.z) - zs.begin() + 1;
        p.ans = p.weight - 1;
    }
    vector<long long> bit(zs.size() + 1);
    auto add = [&](int i, long long v) { for (; i < (int)bit.size(); i += i&-i) bit[i
        ] += v; };
    auto sum = [&](int i) { long long s=0; for (; i; i-=i&-i) s+=bit[i]; return s; };
    vector<Node> tmp(a.size());
    function<void(int,int)> cdq = [&](int l, int r) {
        if (r-l <= 1) return;
        int m=(l+r)/2; cdq(l,m); cdq(m,r);
        int i=l;
        for (int j=m; j<r; ++j) {
            while (i<m && a[i].y<=a[j].y) add(a[i].zi,a[i].weight), ++i;
            a[j].ans += sum(a[j].zi);
        }
        while (i>l) --i, add(a[i].zi,-a[i].weight);
        merge(a.begin()+l,a.begin()+m,a.begin()+m,a.begin()+r,tmp.begin()+l,
              [](const Node& p,const Node& q){ return p.y<q.y; });
        copy(tmp.begin()+l,tmp.begin()+r,a.begin()+l);
    };
    cdq(0, a.size());
    vector<long long> ans(n);
    for (auto& p : a) for (int id : p.ids) ans[id]=p.ans;
    return ans;
}
```

4.15 Min Cost Flow

Use: Successive shortest path with potentials.
Complexity: $O(FE \log V)$ plus Bellman-Ford init.
Pitfalls: Negative costs ok, but no negative cost cycles. May return less than requested flow.
Assumptions/deps: Cap/cost are `long long`; directed edges.

```cpp
// Min-cost flow with potentials. Negative costs ok; no negative cost cycles.
// Source: Stanford/KACTL successive shortest path style.
// Complexity: O(F E log V), plus O(VE) Bellman-Ford init.
// addEdge(u,v,cap,cost) adds a directed choice; minCost(s,t,need) returns
// {flow,cost} for as much of need as the residual network can send.
// Example: addEdge(0,1,3,7); auto [flow,cost]=minCost(0,1,2); // 2, 14
// Pitfalls: costs/caps and cost*flow must fit long long; flow may be < need.
// minCost(s,s,need) returns {0,0}.
struct MCMF {
    using ll = long long;
    const ll INF = (1LL << 62);
    struct Edge {
        int to, rev;
        ll cap, cost;
    };
    int n;
    vector<vector<Edge>> g;
    vector<ll> pot, dist;
    vector<int> pv, pe;

    MCMF(int n = 0) { init(n); }
    void init(int n_) {
        n = n_;
        g.assign(n, {});
        pot.assign(n, 0);
        dist.resize(n);
        pv.resize(n);
        pe.resize(n);
    }
    void addEdge(int at, int to, ll cap, ll cost) {
        if (cap <= 0) return;
        Edge a{to, (int)g[to].size() + (at == to), cap, cost};
        Edge b{at, (int)g[at].size(), 0, -cost};
        g[at].push_back(a);
        g[to].push_back(b);
    }
    void setPotentials(int s) {
        fill(pot.begin(), pot.end(), INF);
        pot[s] = 0;
        for (int it = 0; it < n - 1; it++) {
            bool changed = false;
            for (int at = 0; at < n; at++) if (pot[at] != INF) {
                for (Edge& e : g[at]) if (e.cap && pot[e.to] > pot[at] + e.cost) {
                    pot[e.to] = pot[at] + e.cost;
                    changed = true;
                }
            }
            if (!changed) break;
        }
        for (ll& x : pot) if (x == INF) x = 0;
    }
    pair<ll, ll> minCost(int s, int t, ll need = (1LL << 62)) {
        if (s == t || need == 0) return {0, 0};
        setPotentials(s);
        ll flow = 0, cost = 0;
        while (flow < need) {
            fill(dist.begin(), dist.end(), INF);
            priority_queue<pair<ll, int>, vector<pair<ll, int>>, greater<pair<ll, int
                >>> pq;
            dist[s] = 0;
            pq.push({0, s});
            while (!pq.empty()) {
                auto [d, at] = pq.top();
                pq.pop();
                if (d != dist[at]) continue;
                for (int i = 0; i < (int)g[at].size(); i++) {
                    Edge& e = g[at][i];
                    if (!e.cap) continue;
                    ll nd = d + e.cost + pot[at] - pot[e.to];
                    if (nd < dist[e.to]) {
                        dist[e.to] = nd;
                        pv[e.to] = at;
                        pe[e.to] = i;
                        pq.push({nd, e.to});
                    }
                }
            }
            if (dist[t] == INF) break;
            for (int v = 0; v < n; v++) if (dist[v] != INF) pot[v] += dist[v];
            ll add = need - flow;
            for (int v = t; v != s; v = pv[v]) add = min(add, g[pv[v]][pe[v]].cap);
            for (int v = t; v != s; v = pv[v]) {
                Edge& e = g[pv[v]][pe[v]];
                e.cap -= add;
                g[v][e.rev].cap += add;
                cost += add * e.cost;
            }
            flow += add;
        }
        return {flow, cost};
    }
};
```

4.16 Strongly Connected Components

Use: Kosaraju SCC + condensation DAG.
Complexity: $O(n+m)$; `condense` $O(m \log m)$.
Pitfalls: Recursive DFS may overflow. Comp ids are topological (edges go low to high id): DP in id order.
Assumptions/deps: Directed graph; call `init` per test case.

```cpp
// Strongly connected components, Kosaraju.
// Pitfall: recursive DFS can overflow the stack on long chains.
// Complexity: O(n + m); condense() O(m log m).
// Comp ids are in topological order (every edge has comp[u] <= comp[v]),
// so DP over the DAG can just loop components in id order.
// addEdge loads arcs; build fills comp[v] and returns the component count;
// condense(count) returns the deduplicated component DAG.
// Example: edges 0->1,1->0,1->2 give build()==2, comp[0]==comp[1],
// comp[1]<comp[2].
struct SCC {
    int n;
    vector<vector<int>> g, rg;
    vector<int> comp, order, vis;
    SCC(int n = 0) { init(n); }
    void init(int n_) {
        n = n_;
        g.assign(n, {});
        rg.assign(n, {});
        comp.assign(n, -1);
    }
    void addEdge(int u, int v) {
        g[u].push_back(v);
        rg[v].push_back(u);
    }
    void dfs1(int v) {
        vis[v] = 1;
        for (int u : g[v]) if (!vis[u]) dfs1(u);
        order.push_back(v);
    }
    void dfs2(int v, int c) {
        comp[v] = c;
        for (int u : rg[v]) if (comp[u] == -1) dfs2(u, c);
    }
    int build() {
        fill(comp.begin(), comp.end(), -1);
        order.clear();
        vis.assign(n, 0);
        for (int i = 0; i < n; i++) if (!vis[i]) dfs1(i);
        reverse(order.begin(), order.end());
        int cnt = 0;
        for (int v : order) if (comp[v] == -1) dfs2(v, cnt++);
        return cnt;
    }
    vector<vector<int>> condense(int c) {
        vector<vector<int>> dag(c);
        set<pair<int, int>> seen;
        for (int at = 0; at < n; at++)
            for (int to : g[at])
                if (comp[at] != comp[to] && seen.insert({comp[at], comp[to]}).second)
                    dag[comp[at]].push_back(comp[to]);
        return dag;
    }
};
```

4.17 DSU on Tree Sack

Use: Answer all subtree queries offline.
Complexity: $O(n \log n)$ traversal; reset $O(n_{old} + m_{old})$.
Pitfalls: Call `init_sack(n)` before loading each test and run `dfs(root,-1,false)` so the state ends empty; recursion depth on chains.
Assumptions/deps: EDIT ONLY the marked block (`add_one`, `answer`); when `answer(v)` runs, exactly subtree(v) has been added.

```cpp
// DSU on tree / sack: answer all "subtree of v" queries offline, O(n log n).
// Per test: init_sack(n); fill g/col; dfs_sz(root,-1); dfs(root,-1,false);
// keep=false at the root undoes every add_one, so the counted state ends
// empty and init_sack costs only O(previous n). Storage O(MAXN).
// Pitfalls: vertices and colors in [0,MAXN); recursive DFS.
// Guarantee: when answer(v) runs, add_one(u,+1) has been applied exactly once
// for every u in subtree(v) and for nothing outside it.
const int MAXN = 200000 + 5;
vector<int> g[MAXN];
int sz[MAXN], st[MAXN], ft[MAXN], ver[MAXN], timer_sack, sack_n;

// ---- customize: counted state, one vertex in/out, answer hook -------------
int col[MAXN], freq[MAXN]; // example state: color frequencies
void add_one(int v, int d) { freq[col[v]] += d; }
void answer(int v) { (void)v; /* record answer for v from current state */ }
// ---- machinery below: do not edit -----------------------------------------
void init_sack(int n) { // call BEFORE loading each test case
    for (int i = 0; i < sack_n; ++i) g[i].clear();
    sack_n = n, timer_sack = 0;
}
void dfs_sz(int at, int p) {
    st[at] = timer_sack;
    ver[timer_sack++] = at;
    sz[at] = 1;
    for (int to : g[at]) if (to != p) dfs_sz(to, at), sz[at] += sz[to];
    ft[at] = timer_sack;
}
void add_subtree(int v, int d) {
```

```
    for (int i = st[v]; i < ft[v]; i++) add_one(ver[i], d);
}
void dfs(int at, int p, bool keep) {
    int big = -1;
    for (int to : g[at]) if (to != p && (big == -1 || sz[to] > sz[big])) big = to;
    for (int to : g[at]) if (to != p && to != big) dfs(to, at, false);
    if (big != -1) dfs(big, at, true);
    for (int to : g[at]) if (to != p && to != big) add_subtree(to, +1);
    add_one(at, +1);
    answer(at);
    if (!keep) add_subtree(at, -1);
}
```

4.18 Virtual Tree

Use: Build compressed tree from key vertices and LCAs.
Complexity: $O(k \log k)$ per call after LCA build.
Pitfalls: Process returned nodes in reverse for child-before-parent DP.
Assumptions/deps: Requires LCA (above) built on the tree. Returns nodes by tin (front = root); fills (parent,child) edges.

```
// Virtual (auxiliary) tree over key vertices.
// Requires LCA from lca_binary_lifting.cpp, built on the tree.
// Returns key vertices plus needed LCAs sorted by tin (front = root of the
// virtual tree) and fills edges as (parent, child) pairs. O(k log k) per call.
// Typical DP: process returned nodes in reverse (children before parents).
vector<int> vtree(vector<int> v, LCA& T, vector<pair<int, int>>& edges) {
    edges.clear();
    if (v.empty()) return {};
    auto byTin = [&](int a, int b) { return T.tin[a] < T.tin[b]; };
    sort(v.begin(), v.end(), byTin);
    int k = v.size();
    for (int i = 1; i < k; i++) v.push_back(T.lca(v[i - 1], v[i]));
    sort(v.begin(), v.end(), byTin);
    v.erase(unique(v.begin(), v.end()), v.end());
    for (int i = 1; i < (int)v.size(); i++)
        edges.push_back({T.lca(v[i - 1], v[i]), v[i]});
    return v;
}
```

4.19 Deterministic Tree Canonization

Use: Rooted/unrooted tree-isomorphism ids without hash collisions.
Complexity: $O(n \log n)$.
Pitfalls: Compare trees with the same `TreeCanon` dictionary; recursion depth.
Assumptions/deps: AHU child-id sorting; handles one or two tree centers.

```
// Deterministic AHU-style canonical ids for rooted/unrooted tree isomorphism.
// Complexity: O(n log n) from sorting child ids, memory O(n).
// Pitfalls: compare trees using the SAME TreeCanon object; recursive DFS depth;
// inputs must be trees. No probabilistic collisions.
// rooted(g,r) identifies a rooted tree; centers gives its one/two centers;
// unrooted roots there so isomorphic unrooted trees get the same id.
// Example: TreeCanon c; c.unrooted(path3)==c.unrooted(star3).
struct TreeCanon {
    map<vector<int>,int> id;
    int get(vector<int> children) {
        sort(children.begin(),children.end());
        return id.emplace(children,id.size()).first->second; // new id = old size
    }
    int rootedDfs(const vector<vector<int>>& g,int at,int p) {
        vector<int>children;
        for(int to:g[at]) if(to!=p) children.push_back(rootedDfs(g,to,at));
        return get(children);
    }
    int rooted(const vector<vector<int>>& g,int root) { return rootedDfs(g,root,-1);
     }
    vector<int> centers(const vector<vector<int>>& g) {
        int n=g.size();
        if(n<=2) {vector<int>c(n);iota(c.begin(),c.end(),0);return c;}
        vector<int>deg(n);queue<int>q;
        for(int v=0;v<n;++v) if((deg[v]=g[v].size())<=1)q.push(v);
        int left=n;
        while(left>2) {
            int take=q.size();left-=take;
            while(take--) {int at=q.front();q.pop();for(int to:g[at])if(--deg[to]==1)q
                 .push(to);}
        }
        vector<int>c;while(!q.empty())c.push_back(q.front()),q.pop();return c;
    }
    int unrooted(const vector<vector<int>>& g) {
        if(g.empty()) return -1;
        auto c=centers(g);
        if(c.size()==1) return rooted(g,c[0]);
        int a=rootedDfs(g,c[0],c[1]),b=rootedDfs(g,c[1],c[0]);
        return get({-1,a,b}); // tag the virtual root so it cannot match a real root
    }
};
```

4.20 Bellman–Ford / Difference Constraints

Use: Negative-edge paths, reachable negative cycles, and systems $x_v - x_u \le w$.
Complexity: $O(nm)$.

Pitfalls: Only source-reachable cycles affect shortest paths; feasible assignments must fit `long long`.
Assumptions/deps: Difference constraints return `nullopt` when infeasible.

```cpp
// Bellman-Ford shortest paths with reachable negative-cycle propagation.
// Complexity: O(nm), memory O(n+m).
// Pitfalls: INF/-INF are sentinels; sums are clamped with i128; only cycles
// reachable from source make neg[v] true.
// Usage: auto r=bellman_ford(n,edges,s); r.dist[v], r.neg[v], r.parent[v].
struct BFEdge { int from,to; long long weight; };
struct BFResult {
    static constexpr long long INF=(1LL<<62);
    vector<long long> dist;
    vector<int> parent;
    vector<char> neg;
};
__extension__ typedef __int128 BFInt;

BFResult bellman_ford(int n,const vector<BFEdge>& edges,int source) {
    const long long INF=BFResult::INF;
    const BFInt WINF=(BFInt)1<<120;
    vector<BFInt>d(n,WINF);
    vector<int>parent(n,-1),changed;
    vector<vector<int>>g(n);
    for(auto e:edges) g[e.from].push_back(e.to);
    d[source]=0;
    for(int it=0;it<n;++it) {
        changed.clear();
        for(auto e:edges) if(d[e.from]!=WINF) {
            BFInt cand=d[e.from]+e.weight;
            if(cand<d[e.to]) d[e.to]=cand,parent[e.to]=e.from,changed.push_back(e.to);
        }
        if(changed.empty()) break;
    }
    vector<char>neg(n);
    queue<int>q;
    for(int v:changed) if(!neg[v]) neg[v]=1,q.push(v);
    while(!q.empty()) {int at=q.front();q.pop();for(int to:g[at])if(!neg[to])neg[to
        ]=1,q.push(to);}
    vector<long long>dist(n,INF);
    for(int v=0;v<n;++v) {
        if(neg[v])dist[v]=-INF;
        else if(d[v]!=WINF)dist[v]=(long long)max((BFInt)-INF,min((BFInt)INF,d[v]));
    }
    return {dist,parent,neg};
}

// Constraints are x[to] - x[from] <= weight. nullopt means infeasible.
optional<vector<long long>> difference_constraints(int n,const vector<BFEdge>&
    constraints) {
    vector<BFInt>x(n);
    for(int it=0;it<n;++it) {
        bool changed=false;
        for(auto e:constraints) {
            BFInt value=x[e.from]+e.weight;
            if(x[e.to]>value) x[e.to]=value,changed=true;
        }
        if(!changed) {
            vector<long long>answer(n);
            for(int v=0;v<n;++v){assert(LLONG_MIN<=x[v]&&x[v]<=LLONG_MAX);answer[v]=(
                long long)x[v];}
            return answer;
        }
        if(it==n-1) return nullopt;
    }
    vector<long long>answer(n);return answer;
}
```

4.21 Kruskal MST

Use: Minimum spanning forest.
Complexity: $O(m \log m + m\alpha(n))$.
Pitfalls: Disconnected input returns a forest; total weight may overflow.
Assumptions/deps: Requires the DSU snippet.

```cpp
// Kruskal minimum spanning forest; requires the notebook DSU snippet.
// Complexity: O(m log m + m alpha(n)).
// Pitfalls: disconnected input returns a forest; connected iff used == n-1.
// Usage: auto [weight,used]=kruskal_mst(n,edges);
struct MSTEdge { int u, v; long long w; };

pair<long long, int> kruskal_mst(int n, vector<MSTEdge> edges) {
    sort(edges.begin(), edges.end(), [](const MSTEdge& a, const MSTEdge& b) {
        return a.w < b.w;
    });
    DSU dsu(n);
    long long weight = 0;
    int used = 0;
    for (auto e : edges) if (dsu.unite(e.u, e.v)) weight += e.w, ++used;
    return {weight, used};
}
```

4.22 Block-Cut Tree

Recognize it: connectivity after deleting a vertex

A **block** is a maximal biconnected piece; a bridge is a two-vertex block. `blocks[b]` lists its vertices, and block node `n+b` is joined to each one. The original vertices stay in the resulting forest, including isolated ones. An original vertex of degree greater than one in this forest is an articulation point.

Example: triangle `0-1-2-0`, bridge `2-3`, isolated vertex `4`. Block labels B and C below are illustrative; build order determines IDs.

```
Original              Block-cut forest
    1                      1
   / \                     |
  0---2---3           0---B---2---C---3
  4                   4
```

Removing `2` separates `0` and `3`; removing `1` does not. Two vertices in a block remain mutually reachable after deleting any other block vertex, so the forest path captures exactly the possible separation.

Example: forbidden-vertex queries. Given `n m q`, the edges, and queries `u v x`, print YES iff `u` reaches `v` after deleting `x`; each deletion is independent. The complete solution is below.

First reject originally disconnected `u,v` with DSU. Otherwise deletion changes reachability exactly when `x` lies on the block-cut path from `u` to `v`, tested by `dist(u,x)+dist(x,v)==dist(u,v)`; this includes deleted endpoints. A temporary LCA root joins components for preprocessing, while deleting a vertex in another component has no effect.

Dependencies: **BlockCutTree, DSU, LCA**. No self-loops; parallel edges work. Both DFS routines are recursive, so long chains can overflow the stack.

Build the forest: $O(n + m\log(m+1))$ time, $O(n+m)$ memory.

```cpp
// Vertex-biconnected components and block-cut forest of an undirected graph.
// Original vertices are 0..n-1; block nodes are n..n+blocks.size()-1.
// Complexity: O(n+m) plus sorting vertices inside blocks, O(n+m) memory.
// Pitfalls: use edge ids (parallel edges work); self-loops are not supported;
// recursive DFS can overflow. Isolated vertices stay isolated.
// Usage: BlockCutTree bc(n); bc.addEdge(u,v); bc.build();
struct BlockCutTree {
    int n, timer;
    vector<pair<int,int>> edges;
    vector<vector<pair<int,int>>> g;
    vector<int> tin, low, edgeStack;
    vector<vector<int>> blocks, tree;

    BlockCutTree(int n = 0) { init(n); }
    void init(int n_) { // Clears the graph and every previously built block.
        n=n_; timer=0; edges.clear(); g.assign(n,{});
        tin.assign(n,-1); low.resize(n); edgeStack.clear();
        blocks.clear(); tree.clear();
    }
    int addEdge(int u,int v) {
        int id=edges.size(); edges.push_back({u,v});
        g[u].push_back({v,id}); g[v].push_back({u,id});
        return id;
    }
    void makeBlock(int lastEdge) {
        vector<int> vertices;
        while (true) {
            int id=edgeStack.back(); edgeStack.pop_back();
            vertices.push_back(edges[id].first);
            vertices.push_back(edges[id].second);
            if (id==lastEdge) break;
        }
        sort(vertices.begin(),vertices.end());
        vertices.erase(unique(vertices.begin(),vertices.end()),vertices.end());
        blocks.push_back(vertices);
    }
    void dfs(int at,int parentEdge) {
        tin[at]=low[at]=timer++;
        for (auto [to,id]:g[at]) {
            if (id==parentEdge) continue;
            if (tin[to]==-1) {
                edgeStack.push_back(id); dfs(to,id);
                low[at]=min(low[at],low[to]);
                if (low[to]>=tin[at]) makeBlock(id);
            } else if (tin[to]<tin[at]) {
                edgeStack.push_back(id);
                low[at]=min(low[at],tin[to]);
            }
        }
    }
    void build() {
        timer=0; fill(tin.begin(),tin.end(),-1); edgeStack.clear(); blocks.clear();
        for (int v=0;v<n;++v) if (tin[v]==-1) dfs(v,-1);
        tree.assign(n+blocks.size(),{});
        for (int b=0;b<(int)blocks.size();++b) for (int v:blocks[b]) {
            tree[n+b].push_back(v); tree[v].push_back(n+b);
        }
    }
};
```

4.23 2-SAT

Use: Satisfiability + assignment for 2-CNF; implications, at-most-one.
Complexity: $O(n + clauses)$.
Pitfalls: Use `~x` for NOT x in calls; recursive SCC depth $\sim 2n$; `atMostOne` adds vars.

Assumptions/deps: `either(a,b)` = clause $(a \vee b)$; after `solve()`, `values[x]` is 0/1.

```cpp
// 2-SAT. Variables 0..n-1; use ~x (i.e. -x-1) for "NOT x" in clause calls.
// either(a,b) adds clause (a OR b). solve() = satisfiable; values[x] in {0,1}.
// Source: KACTL TwoSat. Time: O(n + clauses).
// Pitfalls: recursive SCC (stack depth ~ 2n); atMostOne adds new vars.
// Example: either(0,1); either(~0,1); solve()==true and values[1]==true.
struct TwoSat {
    int N;
    vector<vector<int>> gr;
    vector<int> values; // 0 = false, 1 = true

    TwoSat(int n = 0) : N(n), gr(2 * n) {}
    int addVar() {
        gr.emplace_back(); gr.emplace_back(); return N++;
    }
    void either(int f, int j) {
        f = max(2 * f, -1 - 2 * f);
        j = max(2 * j, -1 - 2 * j);
        gr[f].push_back(j ^ 1);
        gr[j].push_back(f ^ 1);
    }
    void setValue(int x) { either(x, x); }
    void atMostOne(const vector<int>& li) { // at most one of li is true
        if ((int)li.size() <= 1) return;
        int cur = ~li[0];
        for (int i = 2; i < (int)li.size(); i++) {
            int next = addVar();
            either(cur, ~li[i]);
            either(cur, next);
            either(~li[i], next);
            cur = ~next;
        }
        either(cur, ~li[1]);
    }
    vector<int> val, comp, z;
    int timer = 0;
    int dfs(int at) {
        int low = val[at] = ++timer, x;
        z.push_back(at);
        for (int to : gr[at]) if (!comp[to])
            low = min(low, val[to] ? val[to] : dfs(to));
        if (low == val[at]) do {
            x = z.back(); z.pop_back();
            comp[x] = low;
            if (values[x >> 1] == -1) values[x >> 1] = x & 1;
        } while (x != at);
        return val[at] = low;
    }
    bool solve() {
        timer = 0;
        values.assign(N, -1);
        val.assign(2 * N, 0);
        comp = val;
        for (int i = 0; i < 2 * N; i++) if (!comp[i]) dfs(i);
        for (int i = 0; i < N; i++) if (comp[2 * i] == comp[2 * i + 1]) return false;
        return true;
    }
};
```

4.24 Floyd–Warshall

Use: All-pairs shortest paths, including negative edges.
Complexity: $O(n^3)$ time, $O(n^2)$ memory.
Pitfalls: Guard INF addition; negative diagonal after the run indicates a negative cycle.
Assumptions/deps: Initialize diagonal to zero and absent edges to INF.

```cpp
// Floyd-Warshall all-pairs shortest paths.
// Complexity: O(n^3) time, O(n^2) memory.
// Pitfalls: finite candidate sums must fit long long. Negative cycles can
// make those sums very negative. d[v][v] < 0 detects a negative cycle.
// Usage: floyd_warshall(d, INF); initialize diagonal 0 and absent edges INF.
void floyd_warshall(vector<vector<long long>>& d, long long INF) {
    int n = (int)d.size();
    for (int k = 0; k < n; ++k)
        for (int i = 0; i < n; ++i) if (d[i][k] < INF)
            for (int j = 0; j < n; ++j) if (d[k][j] < INF)
                d[i][j] = min(d[i][j], d[i][k] + d[k][j]);
}
```

4.25 Euler Walk

Use: Eulerian path/circuit, directed or undirected.
Complexity: $O(V + E)$, iterative.
Pitfalls: Returns {} if none exists from chosen start. Undirected: push both directions with SAME edge id.
Assumptions/deps: Start vertex rules in header; ids `0..nedges-1`.

```cpp
// Eulerian path/circuit starting at src; returns node sequence (nedges+1
// nodes) or {} if none exists FROM src. Works for directed and undirected.
// gr[u] holds {v, edge_id}. Directed: push once. Undirected: push both
// directions with the SAME edge id. Ids must be 0..nedges-1.
// For a circuit pick any src with an edge; for a path start at an odd-degree
// (undirected) / out-in=1 (directed) vertex. Graph edges must be connected.
```

```cpp
// Source: KACTL EulerWalk. Time: O(V + E). Iterative, no stack issues.
vector<int> eulerWalk(vector<vector<pair<int, int>>>& gr, int nedges, int src = 0) {
    int n = gr.size();
    vector<int> D(n), its(n), eu(nedges), ret, s = {src};
    D[src]++; // to allow Euler paths, not just cycles
    while (!s.empty()) {
        int at = s.back(), to, e, &it = its[at], end = gr[at].size();
        if (it == end) { ret.push_back(at); s.pop_back(); continue; }
        tie(to, e) = gr[at][it++];
        if (!eu[e]) {
            D[at]--, D[to]++;
            eu[e] = 1;
            s.push_back(to);
        }
    }
    for (int x : D) if (x < 0 || (int)ret.size() != nedges + 1) return {};
    return {ret.rbegin(), ret.rend()};
}
```

4.26 Offline Dynamic Connectivity

Use: Connectivity and component aggregates with edge additions/removals.
Complexity: $O(n + T \log(T+1) \log(n+1))$ plus callbacks; $O(n + T \log(T+1))$ space.
Pitfalls: One active copy per undirected edge. Store answers by event time.
Assumptions/deps: `event(c,u,v)` returns a time for `solve(answer)`. Component aggregate defaults to XOR.

```cpp
// Offline add/remove-edge connectivity and component aggregates.
// Record 0-indexed events, then solve with a callback indexed by event time.
// Time O(n + T log(T+1) log(n+1)) plus callbacks, space O(n + T log(T+1)).
struct OfflineDSU {
    using V = long long;
    static V merge(V a, V b) { return a ^ b; } // or min(a, b)
    using E = pair<int, int>;

    int T = 0;
    vector<int> p, siz;
    vector<V> val;
    vector<tuple<int, int, V>> hist;
    vector<tuple<int, int, E>> intervals;
    vector<vector<E>> seg;
    map<E, int> active;

    OfflineDSU(vector<V> a) : p(a.size()), siz(a.size(), 1), val(a) {
        iota(p.begin(), p.end(), 0);
    }
    int find(int u) { return p[u] == u ? u : find(p[u]); }
    V component(int u) { return val[find(u)]; }

    void unite(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return;
        if (siz[a] < siz[b]) swap(a, b);
        hist.emplace_back(a, b, val[a]);
        p[b] = a, siz[a] += siz[b], val[a] = merge(val[a], val[b]);
    }
    void rollback(int s) {
        while ((int)hist.size() > s) {
            auto [a, b, old] = hist.back();
            hist.pop_back();
            p[b] = b, siz[a] -= siz[b], val[a] = old;
        }
    }

    int event(char c, int u = 0, int v = 0) {
        E e = minmax(u, v);
        if (c == '+') {
            assert(!active.count(e));
            active[e] = T;
        }
        if (c == '-') {
            assert(active.count(e));
            intervals.emplace_back(active[e], T, e);
            active.erase(e);
        }
        return T++;
    }

    void add(int l, int r, E e) {
        for (l += T, r += T; l < r; l /= 2, r /= 2) {
            if (l & 1) seg[l++].push_back(e);
            if (r & 1) seg[--r].push_back(e);
        }
    }
    template<class F>
    void dfs(int x, F& answer) {
        int s = hist.size();
        for (auto [u, v] : seg[x]) unite(u, v);
        if (x >= T) answer(x - T);
        else dfs(x * 2, answer), dfs(x * 2 + 1, answer);
        rollback(s);
    }
    template<class F>
    void solve(F answer) {
        if (!T) return;
        seg.assign(2 * T, {});
        for (auto [l, r, e] : intervals) add(l, r, e);
        for (auto [e, l] : active) add(l, T, e);
        dfs(1, answer);
```

```
    }
};
```

Usage on an edge timeline

`event(c,u,v)` appends an event and returns its 0-based time. Use `+` and `-` for undirected edges and `?` for a query slot. After recording the timeline, `solve(answer)` calls `answer(t)` at every event with the DSU in that event's state. Size `ask` and `ans` for all events and initialize `ask` to `-1`.

```
OfflineDSU dsu(values);
dsu.event('+', u, v); // link
dsu.event('-', u, v); // cut
int t = dsu.event('?'); // query time
ask[t] = u;

dsu.solve([&](int t) {
    if (ask[t] != -1)
        ans[t] = dsu.component(ask[t]); // component XOR
    // dsu.find(u) // component root
    // dsu.find(u) == dsu.find(v) // connected?
});
// Print answers in time order where ask[t] != -1.
```

Edge lifetimes are half-open. An edge is present at its addition and absent at its removal. Each removal must match an active insertion, and each edge has at most one active copy. Edges still active at the end last until `T`.

Callback order can differ from time order when `T` is not a power of two. Keep the callback read-only with respect to the DSU. Use an associative, commutative `merge` for fixed vertex values. Keep union by size and omit path compression so rollback only has to undo successful unions.

4.27 Hungarian Assignment

Use: Minimum-cost matching of every row to a distinct column.
Complexity: $O(rows^2 \cdot cols)$.
Pitfalls: Requires rows $\leq$ columns; minimizes; cost/potentials must fit `long long`.
Assumptions/deps: Rectangular matrices and negative costs supported.

```
// Minimum-cost assignment: match every row to a distinct column (rows<=cols).
// Complexity: O(rows^2 * cols), memory O(rows+cols).
// Pitfalls: minimizes cost; matrix must be rectangular and rows<=cols;
// potentials/cost total need long long. Negative costs work.
// Usage: auto [cost,column_of_row]=hungarian(cost_matrix);
pair<long long,vector<int>> hungarian(const vector<vector<long long>>& a) {
    int n=a.size();
    if(!n) return {0,{}};
    int m=a[0].size();
    assert(n<=m && m>0);
    for(auto& row:a) assert((int)row.size()==m);
    const long long INF=(1LL<<62);
    vector<long long>u(n+1),v(m+1),minv(m+1);
    vector<int>p(m+1),way(m+1);
    for(int i=1;i<=n;++i) {
        p[0]=i;
        int j0=0;
        vector<char>used(m+1);
        fill(minv.begin(),minv.end(),INF);
        do {
            used[j0]=1;
            int i0=p[j0],j1=0;
            long long delta=INF;
            for(int j=1;j<=m;++j) if(!used[j]) {
                long long cur=a[i0-1][j-1]-u[i0]-v[j];
                if(cur<minv[j]) minv[j]=cur,way[j]=j0;
                if(minv[j]<delta) delta=minv[j],j1=j;
            }
            for(int j=0;j<=m;++j) {
                if(used[j]) u[p[j]]+=delta,v[j]-=delta;
                else minv[j]-=delta;
            }
            j0=j1;
        } while(p[j0]!=0);
        do {
            int j1=way[j0];p[j0]=p[j1];j0=j1;
        } while(j0);
    }
    vector<int>column(n,-1);
    for(int j=1;j<=m;++j) if(p[j]) column[p[j]-1]=j-1;
    return {-v[0],column};
}
```

4.28 Kruskal Reconstruction Forest

Use: Merge nodes encode minimax path values.
Complexity: $O(m \log m + (n+m) \log n)$ time; $O(n+m)$ memory.
Pitfalls: LCA weight queries require distinct connected leaves. Leaf weights are placeholders.
Assumptions/deps: `KruskalTree k(n,edges)`; edges are `{w,u,v}` with 64-bit weights. `roots` lists all components; `tree` stores children.

```
// Kruskal reconstruction forest: leaves [0,n), merge nodes [n,total).
// Build O(m log m + (n+m) log n) time, O(n+m) memory (edges copied).
// weight[LCA(u,v)] is the minimax path value for DISTINCT connected leaves.
// roots lists every component, including isolated vertices; tree stores children.
```

```cpp
// Pitfalls: leaves have no edge weight; check connectivity before LCA queries.
// Example: KruskalTree k(3, {{7,0,1}}); // two roots, weight[3]==7
struct KruskalTree {
    struct Edge { long long w; int u, v; };
    int total;
    vector<int> parent, roots;
    vector<vector<int>> tree;
    vector<long long> weight;
    int find(int v) {
        int r = v;
        while (parent[r] != r) r = parent[r];
        while (v != r) { int u = parent[v]; parent[v] = r; v = u; }
        return r;
    }
    KruskalTree(int n, vector<Edge> edges) : total(n), parent(2*n),
        tree(2*n), weight(2*n) {
        iota(parent.begin(), parent.end(), 0);
        sort(edges.begin(), edges.end(), [](Edge a, Edge b) { return a.w < b.w; });
        for (auto e : edges) {
            int u = find(e.u), v = find(e.v);
            if (u == v) continue;
            int x = total++;
            weight[x] = e.w;
            tree[x] = {u,v};
            parent[u] = parent[v] = x;
        }
        for (int v = 0; v < total; ++v) if (parent[v] == v) roots.push_back(v);
    }
};
```

4.29 Global Min Cut

Use: Stoer-Wagner undirected global min cut.
Complexity: $O(V^3)$ with matrix version.
Pitfalls: Symmetric nonnegative capacities, zero diagonal. All capacity sums must fit.
Assumptions/deps: Returns weight and a side of the cut.

```cpp
// Stoer-Wagner global min cut. O(n^3) time, O(n^2) memory.
// Input: symmetric matrix of nonnegative capacities, diagonal zero.
// Returns {cut weight, one side}; n < 2 returns {0,{}}.
// All capacity sums must fit long long. Example: {{0,5},{5,0}} gives weight 5.
pair<long long, vector<int>> globalMinCut(vector<vector<long long>> a) {
    int n = a.size();
    if (n < 2) return {0, {}};
    vector<int> active(n);
    iota(active.begin(), active.end(), 0);
    vector<vector<int>> group(n);
    for (int i = 0; i < n; ++i) group[i] = {i};
    pair<long long, vector<int>> best = {LLONG_MAX, {}};
    while (active.size() > 1) {
        vector<long long> weight(n);
        vector<bool> used(n);
        int prev = -1;
        for (int i = 0; i < (int)active.size(); ++i) {
            int at = -1;
            for (int to : active)
                if (!used[to] && (at == -1 || weight[to] > weight[at])) at = to;
            if (i + 1 == (int)active.size()) {
                if (weight[at] <= best.first) best = {weight[at], group[at]};
                for (int to : active) if (to != prev && to != at)
                    a[prev][to] = a[to][prev] = a[prev][to] + a[at][to];
                group[prev].insert(group[prev].end(), group[at].begin(), group[at].end
                    ());
                active.erase(find(active.begin(), active.end(), at));
                break;
            }
            used[at] = true;
            for (int to : active) if (!used[to]) weight[to] += a[at][to];
            prev = at;
        }
    }
    return best;
}
```

4.30 Maximum Clique

Use: Branch-and-bound maximum clique / complement for independent set.
Complexity: Exponential; fast for about $n \leq 155$ in tested cases.
Pitfalls: Input must be symmetric bitset matrix, no self-edges. `bitset<200>` limits n.
Assumptions/deps: Requires `vi`, `sz`, `all`, `rep`.

```cpp
/**
 * Author: chilli, SJTU, Janez Konc
 * Date: 2019-05-10
 * License: GPL3+
 * Source: https://en.wikipedia.org/wiki/MaxCliqueDyn_maximum_clique_algorithm, https
     ://gitlab.com/janezkonc/mcqd/blob/master/mcqd.h
 * Description: Quickly finds a maximum clique of a graph (given as symmetric bitset
 * matrix; self-edges not allowed). Can be used to find a maximum independent
 * set by finding a clique of the complement graph.
 * Time: Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs
 * faster for sparse graphs.
 * Status: stress-tested
 */
```

```cpp
typedef vector<bitset<200>> vb;
struct Maxclique {
  double limit=0.025, pk=0;
  struct Vertex { int i, d=0; };
  typedef vector<Vertex> vv;
  vb e;
  vv V;
  vector<vi> C;
  vi qmax, q, S, old;
  void init(vv& r) {
    for (auto& v : r) v.d = 0;
    for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
    sort(all(r), [](auto a, auto b) { return a.d > b.d; });
    int mxD = r[0].d;
    rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
  }
  void expand(vv& R, int lev = 1) {
    S[lev] += S[lev - 1] - old[lev];
    old[lev] = S[lev - 1];
    while (sz(R)) {
      if (sz(q) + R.back().d <= sz(qmax)) return;
      q.push_back(R.back().i);
      vv T;
      for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
      if (sz(T)) {
        if (S[lev]++ / ++pk < limit) init(T);
        int j = 0, mxk = 1, mnk = max<int>(sz(qmax) - sz(q) + 1, 1);
        C[1].clear(), C[2].clear();
        for (auto v : T) {
          int k = 1;
          auto f = [&](int i) { return e[v.i][i]; };
          while (any_of(all(C[k]), f)) k++;
          if (k > mxk) mxk = k, C[mxk + 1].clear();
          if (k < mnk) T[j++].i = v.i;
          C[k].push_back(v.i);
        }
        if (j > 0) T[j - 1].d = 0;
        rep(k,mnk,mxk + 1) for (int i : C[k])
          T[j].i = i, T[j++].d = k;
        expand(T, lev + 1);
      } else if (sz(q) > sz(qmax)) qmax = q;
      q.pop_back(), R.pop_back();
    }
  }
  vi maxClique() { if (!V.empty()) init(V), expand(V); return qmax; }
  Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i,0,sz(e)) V.push_back({i});
  }
};
```

5 Math

Checklist: prime modulus? overflow in multiplication/lcm? zero inverse? random/probabilistic? clear bases/sieves? CRT residues compatible?

5.1 Number Theory Essentials

Use: Extended gcd, modular inverse, fast power.
Complexity: $O(\log n)$.
Pitfalls: `inv` uses Fermat: only prime modulus. Use `inv_any` for coprime composite mod.
Assumptions/deps: `modpow` uses `__int128`.

```cpp
// egcd for a,b >= 0: g = gcd(a,b), a*x+b*y = g. O(log max(a,b)).
// inv_any: inverse mod positive mod (or -1). inv: prime mod, a nonzero mod mod.
// modpow: nonnegative exponent, positive modulus. O(log e) time.
long long egcd(long long a, long long b, long long& x, long long& y) {
    if (!b) { x = 1, y = 0; return a; }
    long long g = egcd(b, a % b, y, x); // note swapped x, y
    y -= a / b * x;
    return g;
}

long long inv_any(long long a, long long mod) {
    a %= mod;
    if (a < 0) a += mod;
    long long x, y;
    long long g = egcd(a, mod, x, y);
    if (g != 1) return -1; // no inverse
    x %= mod;
    if (x < 0) x += mod;
    return x;
}

long long modpow(long long a, long long e, long long mod) {
    a %= mod;
    if (a < 0) a += mod;
    long long r = 1 % mod;
    while (e) {
        if (e & 1) r = (__int128)r * a % mod;
        a = (__int128)a * a % mod;
        e >>= 1;
    }
    return r;
}

long long inv(long long a, long long mod) {
    return modpow(a, mod - 2, mod);
}
```

5.2 FFT

Use: Polynomial convolution over doubles.
Complexity: $O(n \log n)$.
Pitfalls: Rounding fails for large coefficient energy; n rounded to power of two.
Assumptions/deps: Requires complex literals and helper macros `sz/all/rep`.

```cpp
/**
 * Description: fft(a) computes $\hat f(k) = \sum_x a[x] \exp(2\pi i \cdot k x / N)$
      for all $k$. N must be a power of 2.
   Useful for convolution:
   \texttt{conv(a, b) = c}, where $c[x] = \sum a[i]b[x-i]$.
   For convolution of complex numbers or more than two vectors: FFT, multiply
   pointwise, divide by n, reverse(start+1, end), FFT back.
   Rounding is safe if $(\sum a_i^2 + \sum b_i^2)\log_2{N} < 9\cdot10^{14}$
   (in practice $10^{16}$; higher for random inputs).
   Otherwise, use NTT/FFTMod.
 * Time: O(N \log N) with $N = |A|+|B|$ ($\tilde 1s$ for $N=2^{22}$)
 * Status: somewhat tested
 */
using ll = long long;
using vi = vector<int>;
#ifndef sz
#define sz(x) (int)(x).size()
#endif
#ifndef all
#define all(x) begin(x), end(x)
#endif
#ifndef rep
#define rep(i,a,b) for (int i = (a); i < (b); ++i)
#endif
using namespace std::complex_literals;

typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vector<complex<long double>> R(2, 1);
  static vector<C> rt(2, 1); // (^ 10% faster if double)
  for (static int k = 2; k < n; k *= 2) {
    R.resize(n); rt.resize(n);
    auto x = polar(1.0L, acos(-1.0L) / k);
    rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
```

```
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      // hand-rolled z = rt[j+k] * a[i+j+k], ~25% faster than complex*
      auto x = (double *)&rt[j+k], y = (double *)&a[i+j+k];
      C z(x[0]*y[0] - x[1]*y[1], x[0]*y[1] + x[1]*y[0]);
      a[i + j + k] = a[i + j] - z;
      a[i + j] += z;
    }
}
vd conv(const vd& a, const vd& b) {
  if (a.empty() || b.empty()) return {};
  vd res(sz(a) + sz(b) - 1);
  int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
  vector<C> in(n), out(n);
  copy(all(a), begin(in));
  rep(i,0,sz(b)) in[i].imag(b[i]);
  fft(in);
  for (C& x : in) x *= x;
  rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
  fft(out);
  rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
  return res;
}
```

5.3 FFT Mod

Use: Convolution modulo arbitrary int.
Complexity: $O(n \log n)$.
Pitfalls: Inputs must be in `[0,M)`; precision bound matters.
Assumptions/deps: Requires `fft_v2.cpp` before this snippet.

```
/**
 * Description: Higher precision FFT, can be used for convolutions modulo arbitrary
      integers
 * as long as $N\log_2N\cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice $10^{16}$
      or higher).
 * Inputs must be in $[0, \text{mod})$.
 * Time: O(N \log N), where $N = |A|+|B|$ (twice as slow as NTT or FFT)
 * Status: stress-tested
 */
// Requires fft_v2.cpp printed above this snippet (defines C, fft, ll, rep, sz).
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  vl res(sz(a) + sz(b) - 1);
  int B=32-__builtin_clz(sz(res)), n=1LL<<B, cut=(int)sqrt(M);
  vector<C> L(n), R(n), outs(n), outl(n);
  rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
  rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
  fft(L), fft(R);
  rep(i,0,n) {
    int j = -i & (n - 1);
    outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
    outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
  }
  fft(outl), fft(outs);
  rep(i,0,sz(res)) {
    ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
    ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
    res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
  }
  return res;
}
```

5.4 NTT

Use: Exact convolution mod 998244353.
Complexity: $O(n \log n)$, sizes to 2^{23}.
Pitfalls: Inputs in `[0,mod)`; only NTT-friendly primes (list in header).
Assumptions/deps: Self-contained; prefer over FFT when the modulus fits.

```
// NTT convolution mod 998244353 (primitive root 3). Exact, no precision issues.
// conv_ntt(a,b)[k] = sum a[i]*b[k-i] mod p. O(n log n), sizes up to 2^23.
// Inputs must be in [0, mod). For arbitrary mod use fft_mod.cpp.
// Other NTT primes (root 3): 167772161, 469762049, 1004535809.
using ll = long long;
const ll NTT_MOD = 998244353, NTT_G = 3;

ll ntt_pow(ll a, ll e) {
    ll r = 1;
    for (a %= NTT_MOD; e; e >>= 1, a = a * a % NTT_MOD)
        if (e & 1) r = r * a % NTT_MOD;
    return r;
}

void ntt(vector<ll>& a, bool inv) {
    int n = a.size(); // power of 2
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1) j ^= bit;
        j ^= bit;
        if (i < j) swap(a[i], a[j]);
    }
    for (int len = 2; len <= n; len <<= 1) {
        ll w = ntt_pow(NTT_G, (NTT_MOD - 1) / len);
        if (inv) w = ntt_pow(w, NTT_MOD - 2);
        for (int i = 0; i < n; i += len) {
```

```
            ll wn = 1;
            for (int j = 0; j < len / 2; j++, wn = wn * w % NTT_MOD) {
                ll u = a[i + j], v = a[i + j + len / 2] * wn % NTT_MOD;
                a[i + j] = (u + v) % NTT_MOD;
                a[i + j + len / 2] = (u - v + NTT_MOD) % NTT_MOD;
            }
        }
    }
    if (inv) {
        ll ninv = ntt_pow(n, NTT_MOD - 2);
        for (ll& x : a) x = x * ninv % NTT_MOD;
    }
}

vector<ll> conv_ntt(vector<ll> a, vector<ll> b) {
    if (a.empty() || b.empty()) return {};
    int res = a.size() + b.size() - 1, n = 1;
    while (n < res) n <<= 1;
    assert(n <= (1 << 23)); // beyond 2^23 the roots silently break for this mod
    a.resize(n); b.resize(n);
    ntt(a, false); ntt(b, false);
    for (int i = 0; i < n; i++) a[i] = a[i] * b[i] % NTT_MOD;
    ntt(a, true);
    a.resize(res);
    return a;
}
```

5.5 Formal Power Series

Use: Polynomial inverse, logarithm, and exponential modulo 998244353.
Complexity: $O(n \log^2 n)$.
Pitfalls: Constants must satisfy inverse $a_0 \neq 0$, $\log\ a_0 = 1$, $\exp\ a_0 = 0$.
Assumptions/deps: Requires the NTT immediately above; respects its size limit.

```
// Formal power series inverse/log/exp modulo 998244353. Depends on ntt.cpp.
// Returns first n coefficients. Complexity O(n log^2 n), memory O(n).
// Pitfalls: inverse needs a[0]!=0; log needs a[0]=1; exp needs a[0]=0;
// n and inputs must fit the NTT modulus/2^23 limits.
// Usage: fps_inv(a,n), fps_log(a,n), fps_exp(a,n).
vector<ll> fps_inv(const vector<ll>& a,int n) {
    if(!n)return {};
    assert(!a.empty() && a[0]!=0);
    vector<ll>r={ntt_pow(a[0],NTT_MOD-2)};
    while((int)r.size()<n) {
        int next=min(n,2*(int)r.size());
        vector<ll>f(next);
        for(int i=0;i<next&&i<(int)a.size();++i)f[i]=a[i];
        auto prod=conv_ntt(f,r);prod.resize(next);
        for(ll&x:prod)x=(NTT_MOD-x)%NTT_MOD;
        prod[0]=(prod[0]+2)%NTT_MOD;
        r=conv_ntt(r,prod);r.resize(next);
    }
    return r;
}
vector<ll> fps_derivative(const vector<ll>& a) {
    vector<ll>d(a.empty() ? 0 : a.size()-1);
    for(int i=1;i<(int)a.size();++i)d[i-1]=a[i]*i%NTT_MOD;
    return d;
}
vector<ll> fps_integral(const vector<ll>& a) {
    vector<ll>inverses(a.size()+1),r(a.size()+1);if(!a.empty())inverses[1]=1;
    for(int i=2;i<=(int)a.size();++i)inverses[i]=NTT_MOD-NTT_MOD/i*inverses[NTT_MOD%
        i]%NTT_MOD;
    for(int i=0;i<(int)a.size();++i)r[i+1]=a[i]*inverses[i+1]%NTT_MOD;
    return r;
}
vector<ll> fps_log(const vector<ll>& a,int n) {
    if(!n)return {};
    assert(!a.empty() && a[0]==1);
    auto r=conv_ntt(fps_derivative(a),fps_inv(a,n));
    if((int)r.size()>n-1)r.resize(n-1);
    r=fps_integral(r);r.resize(n);
    return r;
}
vector<ll> fps_exp(const vector<ll>& a,int n) {
    if(!n)return {};
    assert(a.empty() || a[0]==0);
    vector<ll>r={1};
    while((int)r.size()<n) {
        int next=min(n,2*(int)r.size());
        auto logarithm=fps_log(r,next);
        vector<ll>delta(next);
        for(int i=0;i<next;++i) {
            ll value=i<(int)a.size()?a[i]:0;
            delta[i]=(value-logarithm[i]+NTT_MOD)%NTT_MOD;
        }
        delta[0]=(delta[0]+1)%NTT_MOD;
        r=conv_ntt(r,delta);r.resize(next);
    }
    return r;
}
```

5.6 FPS Newton Formulas

Use: Precision-doubling identities for inverse/log/exp.
Complexity: $O(n \log^2 n)$ implementation.
Pitfalls: Formal series are truncated modulo x^n.

Assumptions/deps: Pairs with NTT and FPS code.

For $A(x) = \sum_i a_i x^i$, `a[i]` is the coefficient of x^i; every result keeps coefficients below x^n. All identities are modulo x^n over $\mathbb{F}_{998244353}$.

Inverse

Given $a_0 \neq 0$, start with $b = a_0^{-1}$ and double precision using

$$b \leftarrow b(2 - ab).$$

If $ab \equiv 1 \pmod{x^m}$, the new b is correct modulo x^{2m}.

Logarithm and exponential

For $a_0 = 1$,

$$\log a = \int \frac{a'}{a}.$$

For $a_0 = 0$, start with $b = 1$ and repeatedly apply

$$b \leftarrow b(1 + a - \log b).$$

The implementation uses the notebook NTT and the simple $O(n \log^2 n)$ doubling form. NTT root limits and coefficient normalization still apply.

Counting ordered compositions

If allowed part sizes are positive, let $P(x)$ contain one term x^s per allowed size. Then

$$1 + P + P^2 + \cdots = \frac{1}{1 - P}$$

and the coefficient of x^n counts ordered compositions of n. Since `P(0)=0`, `1-P` has an inverse. For parts 1 and 2, the answer for 5 is 8:

```
// Input: allowed part sizes {1,2}; target sum n=5.
int n=5;
vector<ll> oneMinusP={1,NTT_MOD-1,NTT_MOD-1};
auto ways=fps_inv(oneMinusP,n+1);
// Expected output: ways[5]=8 ordered compositions.
assert(ways[n]==8);
```

The vector is truncated to degree `n`, so read `ways[n]`. Use `fps_log` or `fps_exp` only when the problem's generating-function identity requires them; their constant-term restrictions remain in the header.

5.7 Inclusion–Exclusion

Use: Union sizes and onto-function counting helpers.
Complexity: $O(2^k)$ or $O(k^2 + k \log n)$.
Pitfalls: Intersection values must have exact mask meaning; union totals can overflow.
Assumptions/deps: Also view as subset-lattice Mobius inversion.

```
// Two concrete inclusion-exclusion helpers: union size from all intersections,
// and onto functions from n labeled items to k labeled boxes modulo mod.
// Complexity: O(2^k) / O(k^2+k log n). Memory O(k).
// Pitfalls: intersection[mask] must mean intersection of every set in mask;
// union answer may overflow long long. mod need not be prime.
// Usage: union_size_ie(intersections); surjections_ie(n,k,mod).
__extension__ typedef __int128 IEInt;
long long union_size_ie(const vector<long long>& intersection) {
    long long ans=0;
    for(int mask=1;mask<(int)intersection.size();++mask)
        ans+=(__builtin_popcount((unsigned)mask)&1?1:-1)*intersection[mask];
    return ans;
}
long long surjections_ie(long long n,int k,long long mod) {
    assert(mod>0);
    vector<long long>C(k+1);C[0]=1;
    for(int i=1;i<=k;++i) for(int j=i;j;--j) C[j]=(C[j]+C[j-1])%mod;
    auto power=[&](long long a,long long e){long long r=1%mod;for(;e;e>>=1,a=(IEInt)a
        *a%mod)if(e&1)r=(IEInt)r*a%mod;return r;};
    long long ans=0;
    for(int i=0;i<=k;++i) {
        long long term=(IEInt)C[i]*power(k-i,n)%mod;
        ans=((i&1)?ans-term:ans+term)%mod;
    }
    return (ans+mod)%mod;
}
```

5.8 Inclusion–Exclusion Formulas

Use: Union, complement, surjection, and derangement reminders.
Complexity: Formula-dependent.
Pitfalls: Define the universe and empty intersection explicitly.
Assumptions/deps: Use subset transforms when all masks are required.

For finite sets $A_1, \ldots, A_k$,

$$\left|\bigcup_i A_i\right| = \sum_{\emptyset \neq S \subseteq [k]} (-1)^{|S|+1} \left|\bigcap_{i \in S} A_i\right|.$$

To count objects avoiding bad properties B_i, apply this to the complement: total minus single bad sets, plus pair intersections, and so on.

Standard formulas

Onto functions $[n] \to [k]$, maps that use every one of the k values. The i-th term fixes i values that are missed and maps into the other $k - i$:

$$\sum_{i=0}^{k} (-1)^i \binom{k}{i} (k-i)^n.$$

Derangements, permutations with no fixed point ($p_i \neq i$ for all i). The i-th term fixes i chosen points and permutes the other $n - i$ freely:

$$!n = n! \sum_{i=0}^{n} \frac{(-1)^i}{i!}.$$

Inclusion-exclusion is Möbius inversion on the subset lattice. Use subset transforms when all 2^k masks are needed.

Pitfalls: define the universe and empty intersection; do not double-count inside an intersection; use a safe type or modulus.

5.9 Counting and Number Theory Formulas

Use: Floor blocks, exponent towers, binomial identities, Stirling/Bell/Eulerian/derangements, Cayley/Prüfer, Burnside, Manhattan rotation, Pick.
Complexity: Floor blocks $O(\sqrt{n})$; rest $O(1)$ or table recurrences.
Pitfalls: Reduce exponents mod $p - 1$, not p; keep $+\varphi(m)$ when $\gcd(a, m) > 1$; Burnside counts the identity.
Assumptions/deps: `power_tower` needs `modpow` from Number Theory Essentials. Every formula brute-force checked.

Floor-division blocks

$\lfloor n/i \rfloor$ takes at most $2\sqrt{n}$ distinct values, so sum over blocks of equal quotient. The block that starts at l is

$$q = \lfloor n/l \rfloor, \qquad r = \lfloor n/q \rfloor, \qquad \lfloor n/i \rfloor = q \ \text{ for all } l \le i \le r.$$

For two numbers at once (Möbius sums over $\lfloor n/i \rfloor$ and $\lfloor m/i \rfloor$) take the smaller end, $r = \min(\lfloor n/\lfloor n/l \rfloor \rfloor, \lfloor m/\lfloor m/l \rfloor \rfloor)$, for $l \le \min(n, m)$. Typical sums: $\sum_{i \le n} \lfloor n/i \rfloor$ is the total number of divisors of $1, \ldots, n$, and $\sum_{i \le n} i \lfloor n/i \rfloor$ is the total sum of divisors.

```cpp
// sum_{i=1}^{n} i*floor(n/i) = sum of divisors of 1..n (CSES 1082). O(sqrt n).
long long divisor_sum_all(long long n, long long mod) {
    long long ans = 0;
    for (long long l = 1, r; l <= n; l = r + 1) {
        long long q = n / l; r = n / q; // floor(n/i) == q on [l, r]
        __int128 s = (__int128)(l + r) * (r - l + 1) / 2; // sum of i on block
        ans = (ans + (__int128)(q % mod) * (s % mod)) % mod;
    }
    return ans;
}
```

Exponent reduction

Fermat, for a prime p and $\gcd(a, p) = 1$:

$$a^e \equiv a^{e \bmod (p-1)} \pmod{p}.$$

Generalised Euler, for any modulus m and any a, valid once $e \ge \varphi(m)$:

$$a^e \equiv a^{(e \bmod \varphi(m)) + \varphi(m)} \pmod{m}.$$

If $e < \varphi(m)$ use e itself. The added $\varphi(m)$ is what keeps the rule true when $\gcd(a, m) > 1$. Power towers (a_1 to the power of the tower $a_2, a_3, \ldots$) modulo m: compute the exponent tower modulo $\varphi(m)$ recursively, storing every intermediate value as x if $x < m$ and as $(x \bmod m) + m$ otherwise, including inside fast power. The chain $m, \varphi(m), \varphi(\varphi(m)), \ldots$ reaches 1 in $O(\log m)$ steps.

```cpp
// a^(b^c) mod prime p with 0^0 = 1 (CSES 1712). Needs modpow (NT essentials).
long long power_tower(long long a, long long b, long long c, long long p) {
    if (a % p == 0) return b == 0 && c > 0 ? 1 : 0; // exponent b^c is 0 or > 0
    return modpow(a, modpow(b, c, p - 1), p);
}
```

Binomials

Parity. $\binom{n}{k}$ is odd exactly when every set bit of k is also set in n, i.e. `(k & n) == k`. XOR pyramid: replacing $a_0, \ldots, a_{n-1}$ by $a_i \oplus a_{i+1}$ until one value is left gives the XOR of the a_i with `(i & (n-1)) == i`.

Vandermonde. Choose k items from a red and b blue ones:

$$\sum_i \binom{a}{i}\binom{b}{k-i} = \binom{a+b}{k}, \qquad \sum_i \binom{n}{i}^2 = \binom{2n}{n}.$$

Hockey stick. A column of Pascal's triangle sums to the entry below and to the right; for example $\sum_{i \le n} i = \binom{n+1}{2}$.

$$\sum_{i=r}^{n} \binom{i}{r} = \binom{n+1}{r+1}.$$

Stars and bars (CSES 1716). Solutions of $x_1 + \cdots + x_k = n$, the same as multisets of size n from k kinds:

$$\binom{n+k-1}{k-1} \ \text{with } x_i \ge 0, \qquad \binom{n-1}{k-1} \ \text{with } x_i \ge 1 \ (n \ge 1).$$

Lower bounds $x_i \ge l_i$: substitute $x_i - l_i$. Upper bound $x_i \le u$ for all i, by inclusion–ex-

clusion over the variables that overflow (stop once $n - j(u+1) < 0$):

$$\sum_{j \geq 0} (-1)^j \binom{k}{j} \binom{n - j(u+1) + k - 1}{k - 1}.$$

Reflection (CSES 2187). Walks of L steps of ± 1 from height $h \geq 0$ down to 0 that never go below 0. With $u = (L-h)/2$ up-steps:

$$\binom{L}{u} - \binom{L}{u-1},$$

and 0 if $L - h$ is odd or $L < h$. For brackets, h is the balance of the given prefix and L the number of characters still to place. $h = 0$, $L = 2n$ gives Catalan $\frac{1}{n+1}\binom{2n}{n}$.

Number families

Stirling numbers of the 2nd kind $S(n,k)$: ways to split n labeled items into k nonempty unlabeled groups. Row $n = 4$ is $1, 7, 6, 1$.

$$S(n,k) = kS(n-1,k) + S(n-1,k-1), \qquad S(n,k) = \frac{1}{k!} \sum_{i=0}^{k} (-1)^i \binom{k}{i} (k-i)^n.$$

$S(0,0) = 1$ and $S(n,0) = 0$ for $n > 0$. Onto maps from n labeled items to k labeled boxes: $k! \cdot S(n,k)$.

Bell numbers $B_n = \sum_k S(n,k)$: all partitions of an n-set.

$$B_{n+1} = \sum_{k=0}^{n} \binom{n}{k} B_k, \qquad B_0, B_1, \cdots = 1, 1, 2, 5, 15, 52, 203, 877, 4140.$$

Stirling numbers of the 1st kind $c(n,k)$ (unsigned): permutations of n items with exactly k cycles. Row $n = 4$ is $6, 11, 6, 1$.

$$c(n,k) = (n-1)c(n-1,k) + c(n-1,k-1), \qquad \sum_k c(n,k) x^k = x(x+1)\cdots(x+n-1).$$

So $\sum_k c(n,k) = n!$, and sorting a permutation with arbitrary swaps takes exactly $n -$ (number of cycles) swaps.

Eulerian numbers $A(n,k)$: permutations of n items with k descents ($p_i > p_{i+1}$). Rows $1, 1$ and $1, 4, 1$ and $1, 11, 11, 1$.

$$A(n,k) = (k+1)A(n-1,k) + (n-k)A(n-1,k-1), \qquad A(1,0) = 1.$$

Collecting $1, \ldots, n$ in left-to-right passes (CSES 2216) takes $d+1$ passes, where d counts the values x such that $x+1$ appears before x. Over all permutations, $A(n,d)$ of them need $d+1$ passes.

Derangements D_n (CSES 1717): permutations with no fixed point, $p_i \neq i$ for every i.

$$D_n = (n-1)(D_{n-1} + D_{n-2}) = nD_{n-1} + (-1)^n, \qquad D_0 = 1,\ D_1 = 0.$$

Values $1, 0, 1, 2, 9, 44, 265, 1854$. Permutations with exactly k fixed points: $\binom{n}{k} D_{n-k}$.

Trees and symmetry

Cayley. There are n^{n-2} labeled trees on n vertices (1 when $n = 1$). With prescribed degrees $d_1, \ldots, d_n \geq 1$ summing to $2n-2$:

$$\frac{(n-2)!}{\prod_i (d_i - 1)!}.$$

Forests on n labeled vertices made of k trees, with k given vertices in different trees: kn^{n-k-1}. Joining $k \geq 2$ fixed components of sizes $s_1, \ldots, s_k$ (n vertices in all) into one tree with $k-1$ new edges: $n^{k-2} s_1 s_2 \cdots s_k$ ways.

Prüfer code. Labeled trees on $n \geq 2$ vertices correspond one-to-one to sequences of length $n-2$ over the n labels. Encode: remove the smallest leaf and write down its neighbour, $n-2$ times. Vertex v appears $\deg v - 1$ times, so leaves never appear. Decode: set $d_v = \deg v$ from the counts; for each code value x in order, join x to the smallest v with $d_v = 1$ and decrease d_v and d_x by one; finally join the two vertices that still have $d_v = 1$.

Burnside. The number of colourings up to symmetry is the average number of colourings that a symmetry leaves unchanged (identity included):

$$\text{orbits} = \frac{1}{|G|} \sum_{g \in G} \text{fix}(g).$$

Necklaces of n beads in k colours up to rotation (CSES 2209): rotating by i splits the beads into $\gcd(i,n)$ cycles, each one colour.

$$N = \frac{1}{n} \sum_{i=0}^{n-1} k^{\gcd(i,n)} = \frac{1}{n} \sum_{d \mid n} \varphi(d) k^{n/d}.$$

Bracelets (rotations and reflections) number $(N+R)/2$, where R is the average count fixed by a reflection: $R = k^{(n+1)/2}$ for odd n and $R = \frac{1}{2}(k^{n/2} + k^{n/2+1})$ for even n. An $n \times n$ grid up to rotation (CSES 2210), from the identity, the half turn and the two quarter turns:

$$\frac{1}{4}\left(k^{n^2} + k^{\lceil n^2/2 \rceil} + 2k^{\lceil n^2/4 \rceil}\right).$$

Lattice and distance

Manhattan to Chebyshev. Rotate by 45° with $u = x + y$, $v = x - y$:

$$|\Delta x| + |\Delta y| = \max(|\Delta u|, |\Delta v|), \qquad \max(|\Delta x|, |\Delta y|) = \frac{|\Delta u| + |\Delta v|}{2}.$$

The farthest Manhattan pair is the larger of $\max u - \min u$ and $\max v - \min v$. The points within Manhattan distance d of a point form an axis-parallel square in (u, v), so 2D prefix sums and sweeps apply.

Pick. For a simple polygon with integer vertices, area A, I lattice points strictly inside and B on the boundary:

$$2A = 2I + B - 2, \qquad B = \sum_{\text{edges}} \gcd(|\Delta x|, |\Delta y|).$$

Get $2A$ from the shoelace formula, so $I = (2A - B + 2)/2$ stays in integers.

Pitfalls: reduce the exponent modulo $p-1$, never modulo p; keep $\varphi(m)$ added back when $\gcd(a, m) > 1$; Burnside averages over the whole group, identity included; $S(n, 0) = 0$ for $n > 0$ but $S(0, 0) = 1$; n^{n-2} needs the $n = 1$ special case.

5.10 Matrix Power

Use: Linear recurrences, path counting, DP transitions.
Complexity: `mul` $O(n^3)$; `mpow` $O(n^3 \log e)$.
Pitfalls: Change `MMOD` as needed; matrices must be square for `mpow`.
Assumptions/deps: Fibonacci example in header.

```cpp
// Matrix multiply/power mod. mul O(n^3), mpow O(n^3 log e).
// mul needs compatible dimensions; mpow needs a square matrix and e>=0.
// Usage (Fibonacci): mpow({{1,1},{1,0}}, n)[0][1] == F(n).
using ll = long long;
const ll MMOD = 1e9 + 7;
using Mat = vector<vector<ll>>;

Mat mul(const Mat& A, const Mat& B) {
    int n = A.size(), m = B[0].size(), K = B.size();
    Mat C(n, vector<ll>(m, 0));
    for (int i = 0; i < n; i++)
        for (int k = 0; k < K; k++) if (A[i][k])
            for (int j = 0; j < m; j++)
                C[i][j] = (C[i][j] + A[i][k] * B[k][j]) % MMOD;
    return C;
}

Mat mpow(Mat A, ll e) {
    int n = A.size();
    Mat R(n, vector<ll>(n, 0));
    for (int i = 0; i < n; i++) R[i][i] = 1;
    for (; e; e >>= 1, A = mul(A, A))
        if (e & 1) R = mul(R, A);
    return R;
}
```

5.11 Zeta and Mobius Transforms

Use: Subset/superset/divisor/multiple sums and AND/OR/gcd/lcm convolutions.
Complexity: Subset/superset $O(n \log n)$; divisor/multiple $O(n \log \log n)$.
Pitfalls: Subset versions need power-of-two size; divisor versions are indexed `1..n`.
Assumptions/deps: Self-contained (inline prime sieve). Header lists convolution recipes.

```cpp
// Zeta/Mobius transforms. Subset/superset: v.size() must be a power of 2,
// O(n log n). AND-convolution: supersetZeta both, multiply, supersetMobius.
// OR-convolution: subsetZeta both, multiply, subsetMobius.
// Divisor/multiple: v indexed 1..n (v[0] unused), O(n log log n).
// divisorZeta = F(i) = sum_{d|i} f(d); multipleZeta = F(i) = sum_{i|m} f(m).
// Mobius versions invert their zeta. gcd-convolution: multipleZeta both,
// multiply, multipleMobius (lcm-conv: divisor versions).
template<class T> void subsetZeta(vector<T>& v) {
    int n = v.size();
    for (int j = 1; j < n; j <<= 1)
        for (int i = 0; i < n; i++) if (i & j) v[i] += v[i ^ j];
}
template<class T> void subsetMobius(vector<T>& v) {
    int n = v.size();
    for (int j = 1; j < n; j <<= 1)
        for (int i = 0; i < n; i++) if (i & j) v[i] -= v[i ^ j];
}
template<class T> void supersetZeta(vector<T>& v) {
    int n = v.size();
    for (int j = 1; j < n; j <<= 1)
        for (int i = 0; i < n; i++) if (i & j) v[i ^ j] += v[i];
}
template<class T> void supersetMobius(vector<T>& v) {
    int n = v.size();
    for (int j = 1; j < n; j <<= 1)
        for (int i = 0; i < n; i++) if (i & j) v[i ^ j] -= v[i];
}
vector<int> primesUpTo(int n) {
    vector<int> pr; vector<bool> comp(n + 1);
    for (int p = 2; p <= n; p++) if (!comp[p]) {
        pr.push_back(p);
        for (int j = 2 * p; j <= n; j += p) comp[j] = true;
    }
    return pr;
}
template<class T> void divisorZeta(vector<T>& v) {
    int n = (int)v.size() - 1;
    for (int p : primesUpTo(n))
        for (int i = 1; i * p <= n; i++) v[i * p] += v[i];
}
template<class T> void divisorMobius(vector<T>& v) {
    int n = (int)v.size() - 1;
    for (int p : primesUpTo(n))
        for (int i = n / p; i; i--) v[i * p] -= v[i];
}
template<class T> void multipleZeta(vector<T>& v) {
    int n = (int)v.size() - 1;
    for (int p : primesUpTo(n))
        for (int i = n / p; i; i--) v[i] += v[i * p];
```

```
}
template<class T> void multipleMobius(vector<T>& v) {
    int n = (int)v.size() - 1;
    for (int p : primesUpTo(n))
        for (int i = 1; i * p <= n; i++) v[i] -= v[i * p];
}
```

5.12 Sieve

Use: Enumerate primes below limit.
Complexity: $O(n \log \log n)$.
Pitfalls: Returns primes `< lim`, not `<= lim`. `MAX_PR` fixed.
Assumptions/deps: Self-contained.

```
// Sieve of Eratosthenes; returns primes < lim. Requires lim <= MAX_PR.
// Time: lim=1e9 ~ 1.5s if MAX_PR is raised; 5e6 is instant.
const int MAX_PR = 5'000'000;
bitset<MAX_PR> isprime;
vector<int> eratosthenesSieve(int lim) {
  isprime.set(); isprime[0] = isprime[1] = 0;
  for (int i = 4; i < lim; i += 2) isprime[i] = 0;
  for (int i = 3; i*i < lim; i += 2) if (isprime[i])
    for (int j = i*i; j < lim; j += i*2) isprime[j] = 0;
  vector<int> pr;
  for (int i = 2; i < lim; i++) if (isprime[i]) pr.push_back(i);
  return pr;
}
```

5.13 Gaussian Elimination mod p

Use: Solve $Ax = b$ over prime field; get one solution + solution count.
Complexity: $O(nm \min(n, m))$.
Pitfalls: Returns -1 if inconsistent, else #free variables (p^{free} solutions); free vars set to 0. Prime modulus only.
Assumptions/deps: Self-contained (includes `gpow`).

```
// Solve A x = b mod PRIME p. a = n rows of m+1 entries (last column is b).
// Returns -1 if no solution, else the number of FREE variables (0 = unique).
// sol gets one valid solution (free variables set to 0). O(n m min(n,m)).
// Rank of A alone: pass b = 0 column; rank = m - free. Self-contained.
long long gpow(long long a, long long e, long long mod) {
    long long r = 1;
    for (a %= mod; e; e >>= 1, a = a * a % mod)
        if (e & 1) r = r * a % mod;
    return r;
}

int gauss(vector<vector<long long>> a, long long mod, vector<long long>& sol) {
    int n = a.size(), m = (int)a[0].size() - 1, row = 0;
    for (auto& r : a) for (auto& x : r) x = (x % mod + mod) % mod;
    vector<int> where(m, -1);
    for (int col = 0; col < m && row < n; col++) {
        int sel = row;
        while (sel < n && !a[sel][col]) sel++;
        if (sel == n) continue;
        swap(a[sel], a[row]);
        long long invp = gpow(a[row][col], mod - 2, mod);
        for (int j = col; j <= m; j++) a[row][j] = a[row][j] * invp % mod;
        for (int i = 0; i < n; i++) if (i != row && a[i][col]) {
            long long f = a[i][col];
            for (int j = col; j <= m; j++)
                a[i][j] = ((a[i][j] - f * a[row][j]) % mod + mod) % mod;
        }
        where[col] = row++;
    }
    for (int i = row; i < n; i++) // leftover rows are all-zero except maybe b
        if (a[i][m]) return -1;
    sol.assign(m, 0);
    for (int c = 0; c < m; c++)
        if (where[c] != -1) sol[c] = a[where[c]][m];
    return m - row; // row = rank
}
```

5.14 XOR Linear Basis

Use: Max subset xor, membership, count of distinct xors (2^{rank}).
Complexity: $O(B)$ per insert, $B = 60$.
Pitfalls: Reset basis per test (`b = Basis()`); raise `B` for values $\geq 2^{60}$.
Assumptions/deps: 64-bit safe; `add` returns false if already representable.

```
// XOR linear basis over 64-bit values. add O(B), B = bits.
// rank() = basis size; number of DISTINCT subset xors = 2^rank
// (each achieved by exactly 2^(n-rank) subsets, empty subset gives 0).
// Pitfalls: reset (b = Basis()) between test cases; raise B for values >= 2^60.
// add inserts an independent vector and reports whether rank grew; contains
// tests representability; maxXor(start) maximizes start xor a subset xor.
// Example: add(3), add(5) => rank()==2, contains(6), maxXor()==6.
struct Basis {
    static const int B = 60;
    long long b[B] = {};
    bool add(long long x) { // false if x already representable
        for (int i = B - 1; i >= 0; i--) if (x >> i & 1) {
            if (!b[i]) { b[i] = x; return true; }
            x ^= b[i];
```

```
        }
        return false;
    }
    bool contains(long long x) {
        for (int i = B - 1; i >= 0; i--) if (x >> i & 1) x ^= b[i];
        return x == 0;
    }
    long long maxXor(long long start = 0) {
        long long r = start;
        for (int i = B - 1; i >= 0; i--) r = max(r, r ^ b[i]);
        return r;
    }
    int rank() {
        int r = 0;
        for (int i = 0; i < B; i++) r += b[i] != 0;
        return r;
    }
};
```

5.15 Floor Sum

Use: Evaluate $\sum_{i=0}^{n-1} \lfloor (ai+b)/m \rfloor$.
Complexity: $O(\log \max(a, m))$.
Pitfalls: Nonnegative arguments only, $m > 0$; returns `__int128`.
Assumptions/deps: Euclidean recurrence; see derivation below.

```
// Sum floor((a*i+b)/m) for i=0..n-1, all arguments nonnegative, m>0.
// Complexity: O(log(max(a,m))) time, O(1) memory (Euclidean recurrence).
// Pitfalls: this is the nonnegative version; answer/products need i128.
// Usage: i128 ans=floor_sum(n,m,a,b);
__int128 floor_sum(long long n,long long m,long long a,long long b) {
    __int128 ans=0;
    while(true) {
        if(a>=m) {
            ans+=(__int128)(n-1)*n*(a/m)/2;
            a%=m;
        }
        if(b>=m) {
            ans+=(__int128)n*(b/m);
            b%=m;
        }
        __int128 y=(__int128)a*n+b;
        if(y<m) return ans;
        n=y/m;
        b=y%m;
        swap(a,m);
    }
}
```

5.16 Floor-Sum Notes

Use: Derivation and signed-input warning.
Complexity: $O(\log \max(a, m))$.
Pitfalls: C++ division is not mathematical floor for negative inputs.
Assumptions/deps: Pairs with the nonnegative implementation above.

For $n, a, b \geq 0$ and $m > 0$,

$$F(n, m, a, b) = \sum_{0 \leq i < n} \left\lfloor \frac{ai+b}{m} \right\rfloor.$$

First remove whole multiples:

- $a = q_a m + r_a$ contributes $q_a n(n-1)/2$;
- $b = q_b m + r_b$ contributes $q_b n$.

Now $0 \leq a, b < m$. Let $y = an + b$. If $y < m$, the remainder is zero. Otherwise reflect the lattice points and swap a, m:

$$n' = \left\lfloor \frac{y}{m} \right\rfloor, \qquad b' = y \bmod m,$$

then continue with (n', a, m, b'). This is Euclidean-algorithm-like, hence logarithmic. For signed inputs, normalize with mathematical floor division; C++ integer division truncates toward zero.

5.17 Catalan Numbers

Use: Quick formulas for Catalan counts.
Complexity: $O(1)$ formula after binomial precompute.
Pitfalls: Division requires modular inverse; modulus must allow it.
Assumptions/deps: Use factorial/binomial table separately.

Counts balanced-parenthesis strings, rooted ordered trees, and triangulations:

$$C_n = \frac{1}{n+1}\binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1}.$$

In modular arithmetic, the division needs an inverse of $n+1$. The difference form can be safer when that inverse does not exist.

5.18 Mobius Sieve

Use: Linear sieve for Mobius function.
Complexity: $O(n)$.
Pitfalls: `N` fixed; reset arrays before each build. `mu[1]=1`.
Assumptions/deps: Globals `mu,primes,is_comp`.

```cpp
const int N = 1e6;
int mu[N + 1], primes[N + 1], pcnt;
bool is_comp[N + 1];

void mobius_sieve(int n) { // linear sieve; each composite is visited once
    pcnt = 0;
    fill(mu, mu + n + 1, 0);
    fill(is_comp, is_comp + n + 1, false);
    mu[1] = 1;
    for (int i = 2; i <= n; i++) {
        if (!is_comp[i]) primes[pcnt++] = i, mu[i] = -1;
        for (int j = 0; j < pcnt && i * primes[j] <= n; j++) {
            is_comp[i * primes[j]] = true;
            if (i % primes[j] == 0) break; // mu stays 0: square factor
            mu[i * primes[j]] = -mu[i];
        }
    }
}
```

5.19 Mobius Inversion Notes

Use: Formula reminder for divisor-sum inversion.
Complexity: Reference notes.
Pitfalls: Apply only when the divisor relation really matches.
Assumptions/deps: Pair with the sieve below.

Möbius function

The Möbius function $\mu(n)$ is defined as

$$\mu(n) = \begin{cases} 1 & \text{if } n = 1, \\ (-1)^k & \text{if } n \text{ is a product of } k \text{ distinct primes}, \\ 0 & \text{if } n \text{ has a squared prime factor.} \end{cases}$$

Key identity:

$$\sum_{d|n} \mu(d) = \begin{cases} 1 & \text{if } n = 1, \\ 0 & \text{if } n > 1. \end{cases}$$

Inversion formula

If

$$F(n) = \sum_{d|n} f(d),$$

then

$$f(n) = \sum_{d|n} \mu(d)\, F\left(\frac{n}{d}\right).$$

Equivalently, in Dirichlet convolution form:

$$F = f * 1 \quad \Longleftrightarrow \quad f = F * \mu.$$

Common application

The number of ordered pairs $1 \le i, j \le n$ with $\gcd(i, j) = 1$ is

$$\sum_{d=1}^{n} \mu(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

Use Möbius inversion to:

- remove overcounting over divisors;
- transform sums constrained by gcd;
- invert divisor summations.

Implementation

`mobius_sieve(n)` fills `mu[1..n]` in $O(n)$.

5.20 Sprague–Grundy

Use: Solve finite impartial normal-play games on a DAG.
Complexity: $O(n + m)$ plus mex work.
Pitfalls: Returns empty on a cycle; game moves must be finite and impartial.
Assumptions/deps: Xor Grundy values of independent starting positions.

```cpp
// Grundy values of a finite DAG; xor values to combine impartial games.
// Complexity: O(n+m) plus mex work bounded by total outdegree.
// Pitfalls: returns {} on a directed cycle; moves must define a finite DAG.
// Usage: auto sg=grundy_dag(moves); answer xor of starting sg values.
vector<int> grundy_dag(const vector<vector<int>>& g) {
    int n = (int)g.size();
    vector<int> sg(n), color(n);
    bool ok = true;
    function<void(int)> dfs = [&](int v) {
        color[v] = 1;
        for (int to : g[v]) {
```

```
            if (color[to] == 0) dfs(to);
            else if (color[to] == 1) ok = false;
        }
        vector<int> seen(g[v].size() + 1);
        for (int to : g[v]) if (sg[to] < (int)seen.size()) seen[sg[to]] = 1;
        while (sg[v] < (int)seen.size() && seen[sg[v]]) ++sg[v];
        color[v] = 2;
    };
    for (int v = 0; v < n; ++v) if (!color[v]) dfs(v);
    return ok ? sg : vector<int>{};
}
```

5.21 Lucas Theorem

Use: $C(n,k) \bmod p$ for large n and small prime p.
Complexity: Build $O(p)$; query $O(\log_p n)$.
Pitfalls: Prime p must be small enough for factorial tables.
Assumptions/deps: Digit products in base p; see Kummer note below.

```
// Lucas theorem: C(n,k) modulo a small prime p, even when n>=p.
// Complexity: build O(p), query O(log_p n); memory O(p).
// Pitfalls: p must be prime and small enough to allocate; n,k nonnegative.
// Usage: Lucas lucas(p); long long value=lucas.C(n,k);
struct Lucas {
    long long p;
    vector<long long>fact,ifact;
    long long power(long long a,long long e) const {
        long long r=1;
        for(;e;e>>=1,a=a*a%p) if(e&1) r=r*a%p;
        return r;
    }
    Lucas(int prime):p(prime),fact(prime),ifact(prime) {
        fact[0]=1;for(int i=1;i<p;++i)fact[i]=fact[i-1]*i%p;
        ifact[p-1]=power(fact[p-1],p-2);
        for(int i=p-1;i;--i)ifact[i-1]=ifact[i]*i%p;
    }
    long long small(int n,int k) const {
        if(k<0||k>n)return 0;
        return fact[n]*ifact[k]%p*ifact[n-k]%p;
    }
    long long C(long long n,long long k) const {
        if(k<0||k>n)return 0;
        long long ans=1;
        while(n||k) {
            int ni=n%p,ki=k%p;
            if(ki>ni)return 0;
            ans=ans*small(ni,ki)%p;n/=p;k/=p;
        }
        return ans;
    }
};
```

5.22 Lucas and Kummer

Use: Binomial digit formula and p-adic carry interpretation.
Complexity: Reference formulas.
Pitfalls: Lucas code is impractical when p is too large to precompute.
Assumptions/deps: Pairs with the implementation above.

Lucas

For prime p, write n and k in base p with digits n_i, k_i:

$$\binom{n}{k} \equiv \prod_i \binom{n_i}{k_i} \pmod{p}.$$

If any $k_i > n_i$, the result is zero.

Kummer

The exponent of prime p in $\binom{n}{k}$ equals the number of carries when adding k and $n-k$ in base p. Use this for divisibility or p-adic valuation.

The code precomputes through $p-1$, so it needs $O(p)$ memory. For large p and few queries, compute each digit-level binomial multiplicatively.

5.23 Primitive Root

Use: Find generator modulo prime.
Complexity: $O(\sqrt{p}\log p)$ roughly.
Pitfalls: Prime modulus only (factors `p-1`). 998244353 has root 3.
Assumptions/deps: Requires `modpow` from NT Essentials. Used by kth roots below.

```
// Smallest primitive root modulo PRIME p (factors phi = p-1).
// Requires modpow from NT_essentials.cpp. O(sqrt p + ans * log^2 p).
// For NTT: root of mod 998244353 is 3. Used by discrete_mod.cpp.
long long generator(long long p) {
    if (p == 2) return 1;
    vector<long long> fact;
    long long phi = p - 1, n = phi;
    for (long long i = 2; i * i <= n; i++)
        if (n % i == 0) {
            fact.push_back(i);
```

```
            while (n % i == 0) n /= i;
        }
    if (n > 1) fact.push_back(n);
    for (long long res = 2; res <= p; res++) {
        bool ok = true;
        for (long long f : fact)
            ok &= modpow(res, phi / f, p) != 1;
        if (ok) return res;
    }
    return -1;
}
```

5.24 Discrete Log

Use: Smallest $x \geq 0$ with $a^x = b \pmod{m}$, any a, b, m.
Complexity: $O(\sqrt{m})$ time/memory.
Pitfalls: Returns -1 if none. Non-coprime handled by factor stripping.
Assumptions/deps: Requires `chash` (misc/custom_hash).

```
// Discrete log: smallest x >= 0 with a^x = b (mod m), or -1 if none.
// Works for ANY a, b, m >= 1 (no coprimality/primality needed).
// O(sqrt(m)) time and memory. Requires chash from misc/custom_hash.cpp
// (identity-hash unordered_map can be degraded to O(m) by chosen m).
// Source: cp-algorithms extended BSGS.
long long discrete_log(long long a, long long b, long long m) {
    a %= m; b %= m;
    if (a < 0) a += m;
    if (b < 0) b += m;
    long long k = 1 % m, add = 0, g;
    while ((g = __gcd(a, m)) > 1) {
        if (b == k) return add;
        if (b % g) return -1;
        b /= g; m /= g; add++;
        k = (__int128)k * (a / g) % m;
    }
    // now gcd(a, m) = 1: find a^(n*p) * k = b * a^q
    long long n = (long long)sqrtl(m) + 1;
    unordered_map<long long, long long, chash> vals;
    long long cur = b;
    for (long long q = 0; q <= n; q++) {
        vals[cur] = q; // keep the LARGEST q per value -> smallest answer
        cur = (__int128)cur * a % m;
    }
    long long an = 1;
    for (long long i = 0; i < n; i++) an = (__int128)an * a % m;
    cur = k;
    for (long long p = 1; p <= n; p++) {
        cur = (__int128)cur * an % m;
        auto it = vals.find(cur);
        if (it != vals.end()) return n * p - it->second + add;
    }
    return -1;
}
```

5.25 Discrete kth Roots mod Prime

Use: Solve $x^k = a \pmod{p}$.
Complexity: $O(\sqrt{p} \log p)$.
Pitfalls: `p` must be prime. Returns distinct sorted roots; `a=0` returns `{0}`.
Assumptions/deps: Requires NT Essentials, Primitive Root, and `chash`.

```
// Solve x^k = a (mod p) for prime p, via primitive root + BSGS index log.
// Requires NT_essentials.cpp (modpow, inv_any), primitive_root.cpp, and
// chash from misc/custom_hash.cpp.
// Complexity: O(sqrt(p) log p). Returns sorted distinct roots; a=0 gives {0}.
// Usage: vector<long long> xs = kth_roots_mod_prime(a, k, p);
long long discrete_log_prime_root(long long g, long long a, long long p) {
    // g must be a primitive root modulo prime p, and a != 0.
    long long m = (long long)sqrtl(p - 1) + 1;
    unordered_map<long long, long long, chash> baby;
    long long cur = 1;
    for (long long j = 0; j < m; j++) {
        if (!baby.count(cur)) baby[cur] = j;
        cur = (__int128)cur * g % p;
    }
    long long step = modpow(modpow(g, m, p), p - 2, p);
    cur = a % p;
    for (long long i = 0; i <= m; i++) {
        auto it = baby.find(cur);
        if (it != baby.end()) return i * m + it->second;
        cur = (__int128)cur * step % p;
    }
    return -1;
}

vector<long long> kth_roots_mod_prime(long long a, long long k, long long p) {
    a %= p;
    if (a < 0) a += p;
    if (a == 0) return {0};
    if (p == 2) return {1};

    long long g = generator(p);
    long long ind = discrete_log_prime_root(g, a, p); // a = g^ind
    if (ind == -1) return {};

    long long mod = p - 1, d = __gcd(k, mod);
    if (ind % d) return {};

```

```
    long long kk = ((k / d) % (mod / d) + (mod / d)) % (mod / d);
    long long b = ind / d, md = mod / d;
    long long y0 = (__int128)b * inv_any(kk, md) % md;

    vector<long long> ans;
    for (long long t = 0; t < d; t++) ans.push_back(modpow(g, y0 + t * md, p));
    sort(ans.begin(), ans.end());
    ans.erase(unique(ans.begin(), ans.end()), ans.end());
    return ans;
}
```

5.26 Mod Inverse Table

Use: Inverses, factorials, inverse factorials modulo prime.
Complexity: $O(n)$.
Pitfalls: `MOD` must be prime and `n<MOD`. `ifact` code is cumulative inverse factorial.
Assumptions/deps: Change `MOD` before use; binomial is `nCr(n,k)`.

```
// Precompute modular inverses and factorial inverses modulo prime MOD.
// Complexity: O(n). Use when 0 <= n < MOD.
// Pitfalls: inv[i] uses inv[MOD % i], not inv[i-1]; MOD must be prime.
// Usage: build_inv(1000000); then invv[i], fact[i], ifact[i], nCr(n,k).
const long long MOD = 1000000007;
vector<long long> invv, fact, ifact;

void build_inv(int n) {
    invv.assign(n + 1, 0);
    fact.assign(n + 1, 1);
    ifact.assign(n + 1, 1);
    if (n >= 1) invv[1] = 1;
    for (int i = 2; i <= n; i++)
        invv[i] = MOD - (MOD / i) * invv[MOD % i] % MOD;
    for (int i = 1; i <= n; i++) {
        fact[i] = fact[i - 1] * i % MOD;
        ifact[i] = ifact[i - 1] * invv[i] % MOD; // this one uses previous value
    }
}

long long nCr(int n, int k) {
    if (k < 0 || k > n) return 0;
    return fact[n] * ifact[k] % MOD * ifact[n - k] % MOD;
}
```

5.27 Miller Rabin and Pollard Rho

Use: 64-bit primality and factorization.
Complexity: Primality $O(\log n)$; factorization expected about $O(n^{1/4})$.
Pitfalls: Probabilistic factor search but deterministic bases for 64-bit primality. Factors unsorted.
Assumptions/deps: Uses unsigned 64-bit and `__uint128_t`.

```
// Deterministic Miller-Rabin and Pollard Rho factorization for unsigned 64-bit.
// Source: KACTL MillerRabin/Factor, using __int128 mod multiplication.
// Complexity: primality O(7 log n); factorization expected about O(n^(1/4)).
// Pitfalls: call factor(n) only for n >= 1; returns unsorted prime factors; factor
    (1) is empty.
// Usage: isPrime(n); auto f = factor(n); sort(f.begin(), f.end());
using ull = unsigned long long;
using u128 = __uint128_t;

ull mod_mul(ull a, ull b, ull mod) {
    return (ull)((u128)a * b % mod);
}

ull mod_pow(ull a, ull e, ull mod) {
    ull r = 1;
    while (e) {
        if (e & 1) r = mod_mul(r, a, mod);
        a = mod_mul(a, a, mod);
        e >>= 1;
    }
    return r;
}

bool isPrime(ull n) {
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    ull d = n - 1, s = 0;
    while ((d & 1) == 0) d >>= 1, s++;
    for (ull a : {2ULL, 325ULL, 9375ULL, 28178ULL, 450775ULL, 9780504ULL, 1795265022
        ULL}) {
        ull x = mod_pow(a % n, d, n), i = s;
        while (x != 1 && x != n - 1 && a % n && i--) x = mod_mul(x, x, n);
        if (x != n - 1 && i != s) return false;
    }
    return true;
}

ull pollard(ull n) {
    if (n % 2 == 0) return 2;
    static mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());
    while (true) {
        ull c = uniform_int_distribution<ull>(1, n - 1)(rng);
        ull x = uniform_int_distribution<ull>(0, n - 1)(rng), y = x, d = 1;
        auto f = [&](ull v) { return (ull)(((u128)v * v + c) % n); };
```

```
        while (d == 1) {
            x = f(x);
            y = f(f(y));
            ull diff = x > y ? x - y : y - x;
            d = gcd(diff, n);
        }
        if (d != n) return d;
    }
}

vector<ull> factor(ull n) {
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    ull d = pollard(n);
    auto a = factor(d), b = factor(n / d);
    a.insert(a.end(), b.begin(), b.end());
    return a;
}
```

5.28 Lagrange Interpolation

Use: Evaluate a polynomial from values at $0, 1, \ldots, n-1$.
Complexity: $O(n + \log MOD)$ per evaluation.
Pitfalls: Prime modulus, $n < MOD$; degree must be below n.
Assumptions/deps: Change `LAGRANGE_MOD`; consecutive-point optimized form.

```
// Evaluate degree < n polynomial from y[i]=f(i), modulo prime LAGRANGE_MOD.
// Complexity: O(n + log MOD) time, O(n) memory per evaluation.
// Pitfalls: n<MOD; values/x are interpreted modulo MOD; MOD must be prime.
// Usage: long long value=lagrangeConsecutive(y,x);
const long long LAGRANGE_MOD=1000000007;
long long lagPow(long long a,long long e) {
    long long r=1;
    for(;e;e>>=1,a=a*a%LAGRANGE_MOD) if(e&1) r=r*a%LAGRANGE_MOD;
    return r;
}
long long lagrangeConsecutive(vector<long long> y,long long x) {
    int n=y.size(); if(!n) return 0;
    x=(x%LAGRANGE_MOD+LAGRANGE_MOD)%LAGRANGE_MOD;
    for(auto& v:y) v=(v%LAGRANGE_MOD+LAGRANGE_MOD)%LAGRANGE_MOD;
    if(x<n) return y[x];
    vector<long long> pre(n+1,1),suf(n+1,1),fact(n),ifact(n);
    for(int i=0;i<n;++i) pre[i+1]=pre[i]*(x-i+LAGRANGE_MOD)%LAGRANGE_MOD;
    for(int i=n-1;i>=0;--i) suf[i]=suf[i+1]*(x-i+LAGRANGE_MOD)%LAGRANGE_MOD;
    fact[0]=1;for(int i=1;i<n;++i)fact[i]=fact[i-1]*i%LAGRANGE_MOD;
    ifact[n-1]=lagPow(fact[n-1],LAGRANGE_MOD-2);
    for(int i=n-1;i;--i)ifact[i-1]=ifact[i]*i%LAGRANGE_MOD;
    long long ans=0;
    for(int i=0;i<n;++i) {
        long long term=y[i]*pre[i]%LAGRANGE_MOD*suf[i+1]%LAGRANGE_MOD;
        term=term*ifact[i]%LAGRANGE_MOD*ifact[n-1-i]%LAGRANGE_MOD;
        if((n-1-i)&1) ans=(ans-term+LAGRANGE_MOD)%LAGRANGE_MOD;
        else ans=(ans+term)%LAGRANGE_MOD;
    }
    return ans;
}
```

5.29 Lagrange Formula

Use: Consecutive-point denominator and prefix/suffix products.
Complexity: $O(n)$ after one inverse.
Pitfalls: Return samples directly when x is a known point.
Assumptions/deps: Pairs with interpolation implementation above.

Given $y_i = f(i)$ for $0 \le i < n$ and $\deg f < n$,

$$f(x) = \sum_{i=0}^{n-1} y_i \frac{\prod_{j \ne i}(x-j)}{\prod_{j \ne i}(i-j)}.$$

At consecutive sample points,

$$\prod_{j \ne i}(i-j) = i!\,(-1)^{n-1-i}(n-1-i)!.$$

Prefix/suffix products of $(x-j)$ plus factorials and inverse factorials make each term $O(1)$, hence $O(n)$ total after one modular inverse.

Pitfalls: return y_x immediately when x is a sample index; otherwise the general numerator contains zero. Modular division normally needs prime MOD and $n < MOD$. This reconstructs only polynomials of degree below n.

5.30 CRT

Use: Merge two congruences, non-coprime allowed.
Complexity: $O(\log \min(m_1, m_2))$.
Pitfalls: Works only if residues compatible. LCM can overflow `long long`.
Assumptions/deps: Depends on `egcd` from number theory essentials.

```
// Solve x = a1 (mod m1), x = a2 (mod m2); returns {x, lcm(m1,m2)} with
// 0 <= x < lcm, or {-1,-1} if impossible. Chain calls for >2 congruences.
// O(log max(m1,m2)). Requires egcd, positive moduli and lcm fitting long long.
pair<long long,long long> crt(long long a1, long long m1,
                              long long a2, long long m2) {
```

```
    long long x, y;
    long long g = egcd(m1, m2, x, y);

    __int128 diff = (__int128)a2 - a1;
    if (diff % g != 0) return {-1, -1};

    long long lcm = m1 / g * m2;
    __int128 t = diff / g * x;
    t %= m2 / g;

    long long ans = (a1 + (__int128)m1 * t) % lcm;
    if (ans < 0) ans += lcm;

    return {ans, lcm};
}
```

5.31 Floating Simplex

Use: Maximize $c^T x$ subject to $Ax \le b$, $x \ge 0$.
Complexity: $O(nm \cdot pivots)$; exponential worst case.
Pitfalls: Numerical stability is not guaranteed; distinguish infeasible and unbounded.
Assumptions/deps: Two-phase solver with explicit status; high-risk fallback only.

```
// Two-phase simplex: maximize c^T x subject to A*x<=b and x>=0.
// Adapted to an explicit-result API from the Stanford/KACTL simplex (MIT).
// Complexity: O(nm * pivots), exponential worst case; memory O(nm).
// Pitfalls: floating numerical stability is NOT guaranteed; prefer x=0 feasible
// formulations. Status: -1 infeasible, 0 optimum, +1 unbounded.
// Usage: auto r=Simplex(A,b,c).solve(); r.status,r.value,r.x.
struct LPResult {int status;long double value;vector<long double>x;};
struct Simplex {
    using T=long double;
    static constexpr T EPS=1e-12L;
    int m,n;
    vector<int>N,B;
    vector<vector<T>>D;
    Simplex(const vector<vector<T>>&A,const vector<T>&b,const vector<T>&c):
        m(b.size()),n(c.size()),N(n+1),B(m),D(m+2,vector<T>(n+2)) {
        for(int i=0;i<m;++i)for(int j=0;j<n;++j)D[i][j]=A[i][j];
        for(int i=0;i<m;++i)B[i]=n+i,D[i][n]=-1,D[i][n+1]=b[i];
        for(int j=0;j<n;++j)N[j]=j,D[m][j]=-c[j];
        N[n]=-1;D[m+1][n]=1;
    }
    void pivot(int r,int s){
        T inv=1/D[r][s];
        for(int i=0;i<m+2;++i)if(i!=r&&fabsl(D[i][s])>EPS){T factor=D[i][s]*inv;for(
            int j=0;j<n+2;++j)D[i][j]-=D[r][j]*factor;D[i][s]=D[r][s]*factor;}
        for(int j=0;j<n+2;++j)if(j!=s)D[r][j]*=inv;
        for(int i=0;i<m+2;++i)if(i!=r)D[i][s]*=-inv;
        D[r][s]=inv;swap(B[r],N[s]);
    }
    bool phase(int which){
        int row=m+which-1;
        while(true){
            int s=-1;
            for(int j=0;j<=n;++j)if(N[j]!=-which&&(s==-1||make_pair(D[row][j],N[j])<
                make_pair(D[row][s],N[s])))s=j;
            if(s==-1||D[row][s]>=-EPS)return true;
            int r=-1;
            for(int i=0;i<m;++i)if(D[i][s]>EPS&&(r==-1||make_pair(D[i][n+1]/D[i][s],B[
                i])<make_pair(D[r][n+1]/D[r][s],B[r])))r=i;
            if(r==-1)return false;
            pivot(r,s);
        }
    }
    LPResult solve(){
        if(!n){for(int i=0;i<m;++i)if(D[i][n+1]<-EPS)return {-1,0,{}};return
            {0,0,{}};}
        if(m){int r=min_element(D.begin(),D.begin()+m,[&](auto&a,auto&b){return a[n
            +1]<b[n+1];})-D.begin();
            if(D[r][n+1]<-EPS){pivot(r,n);if(!phase(2)||D[m+1][n+1]<-EPS)return
                {-1,0,{}};for(int i=0;i<m;++i)if(B[i]==-1){int s=0;for(int j=1;j<=n
                ;++j)if(make_pair(D[i][j],N[j])<make_pair(D[i][s],N[s]))s=j;pivot(i,s
                );}}
        }
        bool bounded=phase(1);vector<T>x(n);for(int i=0;i<m;++i)if(B[i]<n)x[B[i]]=D[i
            ][n+1];
        return {bounded?0:1,bounded?D[m][n+1]:numeric_limits<T>::infinity(),x};
    }
};
```

5.32 Simplex Modeling

Use: Canonical-form conversions and numerical checklist.
Complexity: Reference notes.
Pitfalls: Prefer combinatorial formulations when available.
Assumptions/deps: Verify every returned constraint.

Canonical input

$$\max c^T x \quad \text{subject to } Ax \le b,\ x \ge 0.$$

Phase I adds an artificial variable to find a feasible basis; failure means infeasible. Phase II uses the real objective; an entering column with no leaving row means unbounded.

Modeling conversions

- Equality $a^T x = b$: add both $a^T x \le b$ and $-a^T x \le -b$.
- Free variable: $y = y^+ - y^-$ with $y^+, y^- \ge 0$.
- Lower bound $y \ge L$: substitute $y = L + z$, $z \ge 0$.
- Minimization: maximize the negated objective.

Floating simplex is risky: scale coefficients, avoid nearly dependent constraints, and verify every returned constraint. Prefer a combinatorial flow/matching formulation when one exists.

5.33 XOR FWHT

Use: XOR convolution.
Complexity: $O(n \log n)$.
Pitfalls: Size must be power of two. Modular inverse needed instead of division for modular values.
Assumptions/deps: Pointwise multiply between forward and inverse transforms.

```cpp
// XOR Fast Walsh-Hadamard Transform.
// n must be a power of two. Use inverse=true after pointwise multiply.
// For modular T, replace division by n with multiplication by inv(n).
// AND/OR convolutions: use superset/subset zeta+mobius (zeta_and_mobius.cpp).
// Time: O(n log n).
template<class T>
void fwht(vector<T>& a, bool inverse = false) {
    int n = (int)a.size();
    for (int len = 1; 2 * len <= n; len <<= 1)
        for (int i = 0; i < n; i += 2 * len)
            for (int j = i; j < i + len; j++) {
                T u = a[j], v = a[j + len];
                a[j] = u + v, a[j + len] = u - v;
            }
    if (inverse) for (T& x : a) x /= n;
}

template<class T>
vector<T> xor_convolution(vector<T> a, vector<T> b) {
    fwht(a);
    fwht(b);
    for (int i = 0; i < (int)a.size(); i++) a[i] *= b[i];
    fwht(a, true);
    return a;
}
```

5.34 Fraction Finder

Use: Binary search over rationals with bounded numerator/denominator.
Complexity: $O(\log N)$ calls.
Pitfalls: Predicate must be monotone and true at `hi`; overflow possible in medians.
Assumptions/deps: Uses `ll`.

```cpp
/**
 * Description: Given $f$ and $N$, finds the smallest fraction $p/q \in [0, 1]$
 * such that $f(p/q)$ is true, and $p, q \le N$.
 * You may want to throw an exception from $f$ if it finds an exact solution,
 * in which case $N$ can be removed.
 * Usage: fracBS([](Frac f) { return 3*f.p>=f.q; }, 10); // {1,3}
 * Time: O(\log(N))
 * Status: stress-tested for n <= 300
 */

using ll = long long;
struct Frac { ll p, q; };

template<class F>
Frac fracBS(F f, ll N) {
  bool dir = 1, A = 1, B = 1;
  Frac lo{0, 1}, hi{1, 1}; // Set hi to 1/0 to search (0, N]
  if (f(lo)) return lo;
  assert(f(hi));
  while (A || B) {
    ll adv = 0, step = 1; // move hi if dir, else lo
    for (int si = 0; step; (step *= 2) >>= si) {
      adv += step;
      Frac mid{lo.p * adv + hi.p, lo.q * adv + hi.q};
      if (abs(mid.p) > N || mid.q > N || dir == !f(mid)) {
        adv -= step; si = 2;
      }
    }
    hi.p += lo.p * adv;
    hi.q += lo.q * adv;
    dir = !dir;
    swap(lo, hi);
    A = B; B = !!adv;
  }
  return dir ? hi : lo;
}
```

6 Geometry

Default for integer input: use the self-contained Exact Integer Geometry Kit below. Use its linear polygon test unless query volume requires a faster convex-only method. Never sort a polygon's vertices; hull takes an unordered point set. Boundary counts as inside exactly when the containment result is ≥ 0. Floating routines below are for constructions/distances and require the separate floating base.

Checklist: integer or floating? EPS? collinear kept or removed? boundary included? polygon order? coordinates up to 10^9 may need `__int128`. Circles need tangent/same-center cases.

6.1 Geometry Base

Use: Shared floating 2D point/vector primitives.
Complexity: Each primitive $O(1)$.
Pitfalls: Exact `operator<` but EPS equality; avoid mixing with integer exact logic.
Assumptions/deps: Copy before other floating geometry snippets.

```
/*
GEOMETRY CHECKLIST
1. int or floating?
2. Need EPS?
3. Coordinates up to 1e9 => integer cross may need __int128.
4. Segment intersection: endpoint? overlap? collinear?
5. Convex hull: keep or remove collinear points?
6. Polygon vertices clockwise or counterclockwise?
7. Area is signed; use abs(area2)/2.
8. For angle/sqrt, clamp values if needed.
9. For circles, handle tangent and same-center cases.
*/

// Shared floating-point geometry base.
// Source: KACTL Point style, simplified for notebook use.
// Complexity: each primitive is O(1).
// Pitfalls: operator< is exact for sort/set; geometric equality uses EPS.
// Usage: copy this before other floating geometry snippets.
using T = long double;
const T EPS = 1e-12;

int sgn(T x) { return (x > EPS) - (x < -EPS); }

struct P {
    T x, y;
    bool operator<(P p) const {
        if (x != p.x) return x < p.x;
        return y < p.y;
    }
    bool operator==(P p) const {
        return sgn(x - p.x) == 0 && sgn(y - p.y) == 0;
    }
    P operator+(P p) const { return {x + p.x, y + p.y}; }
    P operator-(P p) const { return {x - p.x, y - p.y}; }
    P operator*(T k) const { return {x * k, y * k}; }
    P operator/(T k) const { return {x / k, y / k}; }
};

T dot(P a, P b) { return a.x * b.x + a.y * b.y; }
T cross(P a, P b) { return a.x * b.y - a.y * b.x; }
T cross(P a, P b, P c) { return cross(b - a, c - a); }
T norm2(P a) { return dot(a, a); }
T norm(P a) { return sqrtl(norm2(a)); }
P perp(P a) { return {-a.y, a.x}; }

int ori(P a, P b, P c) { return sgn(cross(a, b, c)); }

bool onSegment(P a, P b, P p) {
    return ori(a, b, p) == 0 && sgn(dot(p - a, p - b)) <= 0;
}
```

6.2 Exact Integer Geometry Kit

Use: Segments, strict triangle test, polygon area/containment, convex hull.
Complexity: Predicates $O(1)$; polygon $O(n)$; hull $O(n \log n)$.
Pitfalls: Safe for $|coordinate| \leq 10^{15}$ and $n \leq 10^6$. Simple polygons stay in boundary order; either orientation works.
Assumptions/deps: Self-contained: `IP`, `i128`; no floating base/EPS. Containment: 1 inside, 0 boundary, -1 outside. Area is signed twice-area in `i128`.

```
// Exact integer geometry kit; no EPS or external geometry dependencies.
// Safe common bound: |coordinate| <= 10^15, polygon size <= 10^6.
// Wider inputs require every determinant/area sum to fit signed i128.
// Cast BEFORE subtraction/multiplication. Never multiply raw determinants.
// Polygon vertices stay in boundary order; only hull sorts a point SET.
using ll = long long;
__extension__ typedef __int128 i128;
struct IP {
    ll x, y;
    bool operator<(IP p) const { return tie(x,y) < tie(p.x,p.y); }
    bool operator==(IP p) const { return x == p.x && y == p.y; }
};
```

```cpp

// Signed determinant and turn (-1 right, 0 straight, +1 left). O(1).
i128 cross_i(IP a, IP b, IP c) {
    return ((i128)b.x-a.x)*((i128)c.y-a.y) -
           ((i128)b.y-a.y)*((i128)c.x-a.x);
}
int ori_i(IP a, IP b, IP c) {
    i128 v = cross_i(a,b,c);
    return (v > 0) - (v < 0);
}

// Closed segment membership, including a==b. O(1).
bool onSeg_i(IP a, IP b, IP p) {
    return ori_i(a,b,p) == 0 &&
        min(a.x,b.x) <= p.x && p.x <= max(a.x,b.x) &&
        min(a.y,b.y) <= p.y && p.y <= max(a.y,b.y);
}

// Closed segments intersect? Touching/overlap/point segments count. O(1).
bool segInter_i(IP a, IP b, IP c, IP d) {
    int x = ori_i(a,b,c), y = ori_i(a,b,d);
    int z = ori_i(c,d,a), w = ori_i(c,d,b);
    if (x*y < 0 && z*w < 0) return true; // signs, not determinants
    return onSeg_i(a,b,c) || onSeg_i(a,b,d) ||
           onSeg_i(c,d,a) || onSeg_i(c,d,b);
}

// Strictly inside triangle, either orientation. Degenerate => false. O(1).
bool inTriStrict_i(IP a, IP b, IP c, IP q) {
    int x = ori_i(a,b,q), y = ori_i(b,c,q), z = ori_i(c,a,q);
    return x != 0 && x == y && y == z;
}

// Twice signed polygon area: CCW positive, CW negative. O(n), O(1) extra.
// Empty/point/segment => 0. Simple polygon required for geometric area.
i128 area2_i(const vector<IP>& p) {
    i128 sum = 0;
    for (int i = 0, n = p.size(); i < n; ++i) {
        IP a = p[i], b = p[(i+1)%n];
        sum += (i128)a.x*b.y - (i128)a.y*b.x;
    }
    return sum;
}

// Simple polygon, either orientation: 1 inside, 0 boundary, -1 outside.
// O(n), O(1) extra. Empty => -1; point/segment => boundary or outside.
// Repeated closing vertex is OK. Do NOT sort polygon vertices.
int inPolygon_i(const vector<IP>& p, IP q) {
    bool inside = false;
    for (int i = 0, n = p.size(); i < n; ++i) {
        IP a = p[i], b = p[(i+1)%n];
        if (onSeg_i(a,b,q)) return 0;
        if (a.y > b.y) swap(a,b);
        if (a.y <= q.y && q.y < b.y && ori_i(a,b,q) > 0)
            inside = !inside;
    }
    return inside ? 1 : -1;
}

// Strict CCW hull of a point SET, starting at smallest (x,y).
// O(n log n), O(n) extra. Drops duplicates/collinear interior points.
// Empty => {}; all collinear => endpoints; no repeated closing point.
vector<IP> hull_i(vector<IP> p) {
    sort(p.begin(),p.end());
    p.erase(unique(p.begin(),p.end()),p.end());
    if (p.size() <= 2) return p;
    vector<IP> h;
    for (int pass = 0; pass < 2; ++pass) {
        int start = h.size();
        for (IP q : p) {
            while ((int)h.size() >= start+2 &&
                   ori_i(h[h.size()-2],h.back(),q) <= 0) h.pop_back();
            h.push_back(q);
        }
        h.pop_back();
        reverse(p.begin(),p.end());
    }
    return h;
}
// Example: auto h = hull_i({{0,0},{2,0},{0,2},{0,0}});
// area2_i(h)==4; inPolygon_i(h,{1,1})==0 (on the hypotenuse).
// Keep area as i128; do not narrow it just to print (use an i128 printer).
```

6.3 Convex Hull and Geometry Routines

Use: Segments, polygon tests, hull, diameter, circle intersections.
Complexity: Most $O(1)$; polygon/hull $O(n)$ or $O(n \log n)$.
Pitfalls: Hull removes collinear boundary points with `<=`. Line intersection assumes nonparallel lines.
Assumptions/deps: Depends on `geometry_base.cpp`; hull output has no duplicate last point.

```cpp
// Core 2D geometry routines. Depends on geometry_base.cpp.
// Sources: KACTL OnSegment/LineIntersection/InsidePolygon/ConvexHull/HullDiameter/
     CircleLine/CircleIntersection style.
// Complexity: listed per function below. Uses 0-indexed vectors.
// Usage: copy geometry_base.cpp first.

// segment intersection. O(1).
```

```cpp
// Pitfalls: segInter only says yes/no; overlapping intersection needs separate handling.
bool segInter(P a, P b, P c, P d) {
    int oa = ori(c, d, a), ob = ori(c, d, b);
    int oc = ori(a, b, c), od = ori(a, b, d);
    if (oa == 0 && onSegment(c, d, a)) return true;
    if (ob == 0 && onSegment(c, d, b)) return true;
    if (oc == 0 && onSegment(a, b, c)) return true;
    if (od == 0 && onSegment(a, b, d)) return true;
    return oa * ob < 0 && oc * od < 0;
}

// line intersection/projection/distances. O(1).
// Pitfalls: lineInter assumes non-parallel non-zero-length lines.
P lineInter(P a, P b, P c, P d) {
    P r = b - a, s = d - c;
    return a + r * (cross(c - a, s) / cross(r, s));
}

P projLine(P a, P b, P p) {
    P ab = b - a;
    return a + ab * (dot(p - a, ab) / norm2(ab));
}

T distLine(P a, P b, P p) {
    return abs(cross(b - a, p - a)) / norm(b - a);
}

T distSegment(P a, P b, P p) {
    if (a == b) return norm(p - a);
    if (sgn(dot(p - a, b - a)) <= 0) return norm(p - a);
    if (sgn(dot(p - b, a - b)) <= 0) return norm(p - b);
    return distLine(a, b, p);
}

// polygon signed double-area. O(n).
// Pitfalls: clockwise order gives negative area.
T area2(const vector<P>& p) {
    T s = 0;
    for (int i = 0, n = (int)p.size(); i < n; i++) s += cross(p[i], p[(i + 1) % n]);
    return s;
}

// point in polygon: 0 outside, 1 inside, 2 boundary. O(n).
// Pitfalls: works for simple polygons; boundary is checked first.
int inPoly(const vector<P>& poly, P q) {
    bool in = false;
    int n = (int)poly.size();
    for (int i = 0, j = n - 1; i < n; j = i++) {
        P a = poly[i], b = poly[j];
        if (onSegment(a, b, q)) return 2;
        if ((a.y > q.y) != (b.y > q.y)) {
            T x = a.x + (b.x - a.x) * (q.y - a.y) / (b.y - a.y);
            if (sgn(x - q.x) > 0) in = !in;
        }
    }
    return in;
}

// convex hull in CCW order. O(n log n).
// Pitfalls: <= removes collinear boundary points. To keep them, use <
// and handle all-collinear input separately so points are not duplicated.
vector<P> convexHull(vector<P> p) {
    sort(p.begin(), p.end());
    p.erase(unique(p.begin(), p.end()), p.end());
    if ((int)p.size() <= 1) return p;
    vector<P> h;
    for (int pass = 0; pass < 2; pass++) { // lower chain, then upper chain
        int start = (int)h.size();
        for (P pt : p) {
            while ((int)h.size() >= start + 2 && sgn(cross(h[h.size() - 2], h.back(), pt)) <= 0)
                h.pop_back();
            h.push_back(pt);
        }
        h.pop_back();
        reverse(p.begin(), p.end());
    }
    return h;
}

// squared diameter of a convex polygon in CCW order. O(n).
// Pitfalls: run convexHull first; hull should have no duplicate last point.
T diameter2(const vector<P>& p) {
    int n = (int)p.size();
    if (n <= 1) return 0;
    if (n == 2) return norm2(p[0] - p[1]);
    T ans = 0;
    int j = 1;
    for (int i = 0; i < n; i++) {
        int ni = (i + 1) % n;
        while (abs(cross(p[ni] - p[i], p[(j + 1) % n] - p[i])) >
               abs(cross(p[ni] - p[i], p[j] - p[i])))
            j = (j + 1) % n;
        ans = max(ans, norm2(p[i] - p[j]));
    }
    return ans;
}

// circle-line intersection. O(1).
// Pitfalls: a and b must be distinct; returns 0/1/2 points.
vector<P> circleLine(P c, T r, P a, P b) {
    P h = projLine(a, b, c), dir = (b - a) / norm(b - a);
    T d2 = norm2(h - c);
```

```
    if (sgn(d2 - r * r) > 0) return {};
    if (sgn(d2 - r * r) == 0) return {h};
    T len = sqrtl(max((T)0, r * r - d2));
    return {h - dir * len, h + dir * len};
}

// circle-circle intersection. O(1).
// Pitfalls: same center returns empty for both infinite and no intersections.
vector<P> circleCircle(P a, T r, P b, T R) {
    P ab = b - a;
    T d2 = norm2(ab), d = sqrtl(d2);
    if (sgn(d) == 0) return {};
    T x = (d2 + r * r - R * R) / (2 * d);
    T h2 = r * r - x * x;
    if (sgn(h2) < 0) return {};
    P v = ab / d, p = a + v * x, q = perp(v);
    if (sgn(h2) == 0) return {p};
    T h = sqrtl(max((T)0, h2));
    return {p - q * h, p + q * h};
}
```

6.4 Point in Convex Polygon

Use: Fast containment query in a convex polygon.
Complexity: $O(\log n)$ per query.
Pitfalls: Polygon must be CCW and no duplicate last point; `strict` excludes boundary.
Assumptions/deps: Depends on `geometry_base.cpp`.

```
// Point in convex polygon in O(log n). Depends on geometry base.
// Source: KACTL PointInsideHull style.
// Complexity: O(log n) per query after CCW convex hull is built.
// Pitfalls: polygon must be CCW and have no duplicate last point; strict excludes
    boundary.
// Usage: bool ok = inConvex(poly, q, false);
bool inConvex(const vector<P>& p, P q, bool strict = false) {
    int n = (int)p.size();
    if (n == 0) return false;
    if (n == 1) return !strict && p[0] == q;
    if (n == 2) return !strict && onSegment(p[0], p[1], q);
    int a = ori(p[0], p[1], q), b = ori(p[0], p[n - 1], q);
    if (a < 0 || b > 0) return false;
    if (strict && (a == 0 || b == 0)) return false;
    int l = 1, r = n - 1;
    while (r - l > 1) {
        int m = (l + r) / 2;
        if (ori(p[0], p[m], q) >= 0) l = m;
        else r = m;
    }
    int o = ori(p[l], p[(l + 1) % n], q);
    return strict ? o > 0 : o >= 0;
}
```

6.5 Half-Plane Intersection

Use: Intersect directed left half-planes into a bounded polygon.
Complexity: $O(n \log n)$.
Pitfalls: Returns empty for unbounded or empty result; add a bounding box when required; EPS matters.
Assumptions/deps: Depends on Geometry Base; zero direction invalid.

```
// Intersection of left half-planes p + t*v. Depends on geometry_base.cpp.
// Returns the bounded convex polygon in CCW order; unbounded/empty -> {}.
// Complexity: O(n log n) time, O(n) memory.
// Pitfalls: zero direction vectors are invalid. Scale directions so EPS
// comparisons make sense. Add a box if you want a clipped region.
// Usage: halfPlaneIntersection({{{0,0},{1,0}}, ...});
struct HalfPlane {
    P p,v;
    bool outside(P q) const { return sgn(cross(v,q-p))<0; }
};
P hpIntersection(const HalfPlane& a,const HalfPlane& b) {
    return a.p+a.v*(cross(b.p-a.p,b.v)/cross(a.v,b.v));
}
int hpHalf(P v) { return v.y>0 || (v.y==0 && v.x>=0) ? 0 : 1; }

vector<P> halfPlaneIntersection(vector<HalfPlane> h) {
    sort(h.begin(),h.end(),[](const HalfPlane& a,const HalfPlane& b) {
        int ha=hpHalf(a.v),hb=hpHalf(b.v);
        if(ha!=hb) return ha<hb;
        return cross(a.v,b.v)>0;
    });
    // Merge equal-angle constraints, retaining the more restrictive one.
    vector<HalfPlane> lines;
    for(auto line:h) {
        if(!lines.empty() && sgn(cross(lines.back().v,line.v))==0 &&
           dot(lines.back().v,line.v)>0) {
            if(line.outside(lines.back().p)) lines.back()=line;
        } else lines.push_back(line);
    }
    // A cyclic direction gap of at least pi permits a recession direction.
    for(int i=0;i<(int)lines.size();++i)
        if(sgn(cross(lines[i].v,lines[(i+1)%lines.size()].v))<=0) return {};
    deque<HalfPlane> q;
    for(auto line:lines) {
```

```
        while(q.size()>1 && line.outside(hpIntersection(q[q.size()-2],q.back()))) q.
            pop_back();
        while(q.size()>1 && line.outside(hpIntersection(q[0],q[1]))) q.pop_front();
        if(!q.empty() && sgn(cross(q.back().v,line.v))==0) return {};
        q.push_back(line);
    }
    while(q.size()>2 && q.front().outside(hpIntersection(q[q.size()-2],q.back()))) q
        .pop_back();
    while(q.size()>2 && q.back().outside(hpIntersection(q[0],q[1]))) q.pop_front();
    if(q.size()<3) return {};
    vector<P> poly;
    for(int i=0;i<(int)q.size();++i) {
        if(sgn(cross(q[i].v,q[(i+1)%q.size()].v))<=0) return {};
        poly.push_back(hpIntersection(q[i],q[(i+1)%q.size()]));
    }
    return poly;
}
```

6.6 Circle Tangents

Use: External/internal tangent points between two circles or point-circle.
Complexity: $O(1)$.
Pitfalls: Use `r2=0` for point tangents; negate radius for internal tangents. Same center returns empty.
Assumptions/deps: Depends on `geometry_base.cpp`.

```
// Tangent points between two circles. Depends on geometry base.
// Source: KACTL CircleTangents style.
// Complexity: O(1).
// Pitfalls: use r2 = 0 for tangents from point c2 to circle c1; negate r2 for
    internal tangents.
// Usage: auto t = circleTangents(c, r, p, 0); // pairs {on circle, p}
vector<pair<P, P>> circleTangents(P c1, T r1, P c2, T r2) {
    P d = c2 - c1;
    T dr = r1 - r2, d2 = norm2(d), h2 = d2 - dr * dr;
    if (sgn(d2) == 0 || sgn(h2) < 0) return {};
    vector<pair<P, P>> out;
    for (T sign : {-1.0L, 1.0L}) {
        P v = (d * dr + perp(d) * sqrtl(max((T)0, h2)) * sign) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    }
    if (sgn(h2) == 0) out.pop_back();
    return out;
}
```

6.7 Minkowski Sum

Use: Sum two strictly convex integer polygons.
Complexity: $O(n+m)$ after normalization.
Pitfalls: Remove collinear hull points first; coordinate sums must fit `long long`.
Assumptions/deps: Depends on Integer Geometry; accepts CW/rotated input.

```
// Minkowski sum of two nonempty strictly-convex integer polygons.
// Input polygons may be CW/rotated; output is CCW, without repeated endpoint.
// Complexity: O(n+m) after normalization, O(n+m) memory.
// Pitfalls: remove collinear hull points first; products use i128, coordinates
// of the resulting sums must still fit long long. Depends on IP/i128.
// Usage: vector<IP> c=minkowskiSum(a,b);
i128 mpCross(IP a,IP b) { return (i128)a.x*b.y-(i128)a.y*b.x; }
i128 mpDot(IP a,IP b) { return (i128)a.x*b.x+(i128)a.y*b.y; }
IP mpAdd(IP a,IP b) { return {a.x+b.x,a.y+b.y}; }
IP mpSub(IP a,IP b) { return {a.x-b.x,a.y-b.y}; }
int mpHalf(IP a) { return a.y>0 || (a.y==0 && a.x>=0) ? 0 : 1; }
bool mpAngleLess(IP a,IP b) {
    if(mpHalf(a)!=mpHalf(b)) return mpHalf(a)<mpHalf(b);
    return mpCross(a,b)>0;
}

vector<IP> mpNormalize(vector<IP> p) {
    if(p.size()>1 && p.front()==p.back()) p.pop_back();
    i128 area=0;
    for(int i=0;i<(int)p.size();++i) area+=mpCross(p[i],p[(i+1)%p.size()]);
    if(area<0) reverse(p.begin(),p.end());
    int at=min_element(p.begin(),p.end(),[](IP a,IP b){return tie(a.y,a.x)<tie(b.y,b
        .x);})-p.begin();
    rotate(p.begin(),p.begin()+at,p.end());
    return p;
}
vector<IP> minkowskiSum(vector<IP> a,vector<IP> b) {
    a=mpNormalize(a); b=mpNormalize(b);
    if(a.size()==1) { for(auto& p:b)p=mpAdd(p,a[0]); return b; }
    if(b.size()==1) { for(auto& p:a)p=mpAdd(p,b[0]); return a; }
    vector<IP> ea(a.size()),eb(b.size());
    for(int i=0;i<(int)a.size();++i) ea[i]=mpSub(a[(i+1)%a.size()],a[i]);
    for(int i=0;i<(int)b.size();++i) eb[i]=mpSub(b[(i+1)%b.size()],b[i]);
    vector<IP> ans={mpAdd(a[0],b[0])};
    int i=0,j=0;
    while(i<(int)ea.size() || j<(int)eb.size()) {
        IP step;
        if(i<(int)ea.size() && j<(int)eb.size() && mpCross(ea[i],eb[j])==0 && mpDot(
            ea[i],eb[j])>0)
            step=mpAdd(ea[i++],eb[j++]);
        else if(j==(int)eb.size() || (i<(int)ea.size() && mpAngleLess(ea[i],eb[j])))
            step=ea[i++];
        else step=eb[j++];
        ans.push_back(mpAdd(ans.back(),step));
```

```
    }
    ans.pop_back();
    return ans;
}
```

6.8 Closest Pair

Use: Minimum squared distance among points.
Complexity: $O(n \log n)$.
Pitfalls: Returns squared distance; needs at least 2 points; duplicates return 0.
Assumptions/deps: Depends on `geometry_base.cpp`.

```
// Closest pair of points. Depends on geometry base.
// Source: standard divide-and-conquer closest pair.
// Complexity: O(n log n).
// Pitfalls: returns squared distance; duplicate points give 0; needs n >= 2.
// Usage: auto [d2, pr] = closestPair(points);
pair<T, pair<P, P>> closestPair(vector<P> p) {
    assert((int)p.size() >= 2);
    sort(p.begin(), p.end()); // P::operator<: exact (x, y)
    for (int i = 1; i < (int)p.size(); ++i)
        if (norm2(p[i] - p[i-1]) == 0) return {0, {p[i-1], p[i]}};
    vector<P> tmp(p.size());
    pair<T, pair<P, P>> ans = {norm2(p[0] - p[1]), {p[0], p[1]}};

    auto upd = [&](P a, P b) {
        T d = norm2(a - b);
        if (d < ans.first) ans = {d, {a, b}};
    };

    function<void(int, int)> solve = [&](int l, int r) {
        if (r - l <= 3) {
            for (int i = l; i < r; i++)
                for (int j = i + 1; j < r; j++) upd(p[i], p[j]);
            sort(p.begin() + l, p.begin() + r, [](P a, P b) { return a.y < b.y; });
            return;
        }
        int m = (l + r) / 2;
        T mx = p[m].x;
        solve(l, m);
        solve(m, r);
        merge(p.begin() + l, p.begin() + m, p.begin() + m, p.begin() + r,
              tmp.begin(), [](P a, P b) { return a.y < b.y; });
        copy(tmp.begin(), tmp.begin() + (r - l), p.begin() + l);

        int sz = 0;
        for (int i = l; i < r; i++) {
            T dx = p[i].x - mx;
            if (dx * dx >= ans.first) continue;
            for (int j = sz - 1; j >= 0; j--) {
                T dy = p[i].y - tmp[j].y;
                if (dy * dy >= ans.first) break;
                upd(p[i], tmp[j]);
            }
            tmp[sz++] = p[i];
        }
    };
    solve(0, (int)p.size());
    return ans;
}
```

6.9 Rectangle Union Area

Use: Sweep-line union area of axis-aligned rectangles.
Complexity: $O(n \log n)$.
Pitfalls: Half-open rectangles; degenerate rectangles ignored; answer is `__int128`.
Assumptions/deps: Internal compressed cover tree; equal-x events grouped.

```
// Sweep-line area of the union of axis-aligned half-open rectangles.
// Complexity: O(n log n) time, O(n) memory.
// Pitfalls: rectangles are [x1,x2)x[y1,y2); degenerate ones are ignored;
// spans and area use i128. The total area must fit signed i128.
// Usage: i128 area=rectangleUnionArea(rectangles);
struct Rectangle { long long x1,y1,x2,y2; };

__int128 rectangleUnionArea(const vector<Rectangle>& rectangles) {
    struct Event { long long x,y1,y2; int delta; };
    vector<Event> events;
    vector<long long> ys;
    for(auto r:rectangles) if(r.x1<r.x2 && r.y1<r.y2) {
        events.push_back({r.x1,r.y1,r.y2,1});
        events.push_back({r.x2,r.y1,r.y2,-1});
        ys.push_back(r.y1);ys.push_back(r.y2);
    }
    if(events.empty()) return 0;
    sort(events.begin(),events.end(),[](auto a,auto b){return a.x<b.x;});
    sort(ys.begin(),ys.end());ys.erase(unique(ys.begin(),ys.end()),ys.end());
    int m=ys.size()-1;
    vector<int> cover(4*m);
    vector<__int128> length(4*m);
    function<void(int,int,int)> pull=[&](int x,int l,int r){
        if(cover[x]) length[x]=(__int128)ys[r]-ys[l];
        else if(r-l==1) length[x]=0;
        else length[x]=length[2*x]+length[2*x+1];
    };
```

```
    function<void(int,int,int,int,int,int)> add=[&](int x,int l,int r,int ql,int qr,
         int d){
        if(qr<=l || r<=ql) return;
        if(ql<=l && r<=qr) cover[x]+=d;
        else {int mid=(l+r)/2;add(2*x,l,mid,ql,qr,d);add(2*x+1,mid,r,ql,qr,d);}
        pull(x,l,r);
    };
    __int128 area=0;
    long long prev=events[0].x;
    for(int i=0;i<(int)events.size();) {
        long long x=events[i].x;
        area+=((__int128)x-prev)*length[1];
        while(i<(int)events.size() && events[i].x==x) {
            int l=lower_bound(ys.begin(),ys.end(),events[i].y1)-ys.begin();
            int r=lower_bound(ys.begin(),ys.end(),events[i].y2)-ys.begin();
            add(1,0,m,l,r,events[i].delta);++i;
        }
        prev=x;
    }
    return area;
}
```

6.10 Sweep-Line Event Ordering

Use: Covered-length invariant and tie-order checklist.
Complexity: $O(n \log n)$ for rectangle union.
Pitfalls: Event order changes boundary semantics; group equal coordinates where possible.
Assumptions/deps: Pairs with rectangle-union implementation above.

Maintain a data structure for the active cross-section while events are visited in coordinate order. Compute the contribution from x_{prev} to x using the **old** active state, then apply all events at x as one group.

Rectangle union

$$area \mathrel{+}= covered_y \, (x - x_{prev}).$$

- Start at x_1: add $[y_1, y_2)$.
- End at x_2: remove $[y_1, y_2)$.

Coordinate-compress all y endpoints. A segment-tree node stores a cover count:

- `cover > 0`: covered length is $ys_r - ys_l$.
- `cover == 0`: sum its children, or use zero at a leaf.

Grouping equal x avoids arbitrary start/end tie order. In sweeps with point queries, tie order is semantic: decide the open/closed boundaries before placing add, query, and remove events.

Skip zero-area rectangles, keep half-open intervals consistent, and use `__int128` if coordinate difference times covered length may overflow.

6.11 Minimum Enclosing Circle

Use: Smallest circle covering all points.
Complexity: Expected $O(n)$.
Pitfalls: Randomized; circumcenter fails for collinear triples but algorithm should call only when needed. EPS matters.
Assumptions/deps: Depends on `geometry_base.cpp`; uses `shuffle`, `mt19937`.

```
// Minimum enclosing circle for points in the plane.
// Source: KACTL MinEnclosingCircle, adapted to the shared geometry P.
// Complexity: expected O(n).
// Pitfalls: randomized order; copy geometry base first; use EPS when checking
     containment.
// Usage: auto [c, r] = minimum_enclosing_circle(points);
P circumcenter(P a, P b, P c) {
    b = b - a, c = c - a;
    T d = 2 * cross(b, c);
    return a + P{
        (c.y * (b.x * b.x + b.y * b.y) - b.y * (c.x * c.x + c.y * c.y)) / d,
        (b.x * (c.x * c.x + c.y * c.y) - c.x * (b.x * b.x + b.y * b.y)) / d
    };
}

pair<P, T> minimum_enclosing_circle(vector<P> p) {
    if (p.empty()) return {{0, 0}, 0};
    shuffle(p.begin(), p.end(), mt19937(chrono::steady_clock::now().time_since_epoch
         ().count()));
    P c = p[0];
    T r = 0, mult = 1 + 1e-10;
    for (int i = 0; i < (int)p.size(); i++) if (norm(c - p[i]) > r * mult) {
        c = p[i], r = 0;
        for (int j = 0; j < i; j++) if (norm(c - p[j]) > r * mult) {
            c = (p[i] + p[j]) / 2;
            r = norm(c - p[i]);
            for (int k = 0; k < j; k++) if (norm(c - p[k]) > r * mult) {
                c = circumcenter(p[i], p[j], p[k]);
                r = norm(c - p[i]);
            }
        }
    }
    return {c, r};
}
```

6.12 Concave Max-Plus Convolution

Use: Compute $c[k] = \max_i(a[i] + b[k-i])$ for discrete concave sequences.
Complexity: $O(n+m)$.
Pitfalls: Adjacent differences must be nonincreasing; empty input returns empty; output sums must fit `long long`.
Assumptions/deps: Uses `__int128` for differences/sums; ties are harmless.

```cpp
// Max-plus convolution of discrete concave sequences.
// c[k]=max(a[i]+b[k-i]); adjacent differences in each input are nonincreasing.
// Complexity: O(n+m) time and memory. Empty input returns {}.
// Pitfalls: output values must fit long long; invalid concavity hits assert.
// Uses __int128 for differences and sums. Usage: auto c=maxPlusConcave(a,b);
using ll = long long;
__extension__ typedef __int128 i128;

vector<ll> maxPlusConcave(const vector<ll>& a,const vector<ll>& b) {
    if(a.empty()||b.empty()) return {};
    auto concave=[](const vector<ll>& x) {
        for(int i=2;i<(int)x.size();++i)
            if((i128)x[i]-x[i-1]>(i128)x[i-1]-x[i-2]) return false;
        return true;
    };
    assert(concave(a)&&concave(b));
    vector<i128> da(a.size()-1),db(b.size()-1);
    for(int i=1;i<(int)a.size();++i) da[i-1]=(i128)a[i]-a[i-1];
    for(int i=1;i<(int)b.size();++i) db[i-1]=(i128)b[i]-b[i-1];
    vector<ll> c(a.size()+b.size()-1);
    i128 cur=(i128)a[0]+b[0];
    for(int k=0, i=0, j=0;k<(int)c.size();++k) {
        if(k) {
            if(i<(int)da.size()&&(j==(int)db.size()||da[i]>=db[j])) cur+=da[i++];
            else cur+=db[j++];
        }
        assert((i128)LLONG_MIN<=cur&&cur<=(i128)LLONG_MAX);
        c[k]=(ll)cur;
    }
    return c;
}
```

7 Dynamic Programming

7.1 Fast Knapsack and Subset Sum

Use: Bitset reachability, compressed bounded sums/min-items, bounded max-value.
Complexity: Bitset $O(nS/64)$; compressed $O(S\sqrt{S})$; bounded $O(types \cdot C)$.
Pitfalls: Weights must be nonnegative; zero weights/values need the documented handling.
Assumptions/deps: Codeforces square-root residue-window method; fixed-size bitset needs compile-time sum.

```cpp
// Fast bounded knapsack and subset-sum variants.
// Complexity: bitset O(items*SUM/64); compressed DP O(S*D), D <= sqrt(2S).
// Pitfalls: all weights are nonnegative; zero weights need special handling.
// Usage: subset_sum_sqrt(a), subset_sum_min_items_sqrt(a), bounded_knapsack(C,it).
const int SUBSET_INF = 1e9;

template<size_t MAX_SUM>
bitset<MAX_SUM + 1> subset_sum_bitset(const vector<int>& a) {
    bitset<MAX_SUM + 1> can;
    can[0] = 1;
    for (int x : a) if (0 <= x && x <= (int)MAX_SUM) can |= can << x;
    return can;
}

vector<pair<int, int>> compress_positive(const vector<int>& a, int& sum) {
    sum = 0;
    for (int x : a) if (x > 0) sum += x;
    vector<int> freq(sum + 1);
    for (int x : a) if (x > 0) ++freq[x];
    vector<pair<int, int>> items;
    for (int w = 1; w <= sum; ++w) if (freq[w]) items.push_back({w, freq[w]});
    return items;
}

vector<char> subset_sum_sqrt(const vector<int>& a) {
    int S;
    auto items = compress_positive(a, S);
    vector<char> dp(S + 1), ndp(S + 1);
    dp[0] = 1;
    for (auto [w, cnt] : items) {
        fill(ndp.begin(), ndp.end(), 0);
        for (int r = 0; r < w && r <= S; ++r) {
            int window = 0;
            for (int s = r, t = 0; s <= S; s += w, ++t) {
                window += dp[s];
                if (t > cnt) window -= dp[s - (cnt + 1) * w];
                ndp[s] = window > 0;
            }
        }
        dp.swap(ndp);
    }
    return dp;
}

vector<int> subset_sum_min_items_sqrt(const vector<int>& a) {
    int S;
    auto items = compress_positive(a, S);
    vector<int> dp(S + 1, SUBSET_INF), ndp(S + 1);
    dp[0] = 0;
    for (auto [w, cnt] : items) {
        fill(ndp.begin(), ndp.end(), SUBSET_INF);
        for (int r = 0; r < w && r <= S; ++r) {
            deque<pair<int, int>> q; // (dp[s]-t, t)
            for (int s = r, t = 0; s <= S; s += w, ++t) {
                while (!q.empty() && q.front().second < t - cnt) q.pop_front();
                if (dp[s] < SUBSET_INF) {
                    int val = dp[s] - t;
                    while (!q.empty() && q.back().first >= val) q.pop_back();
                    q.push_back({val, t});
                }
                if (!q.empty()) ndp[s] = q.front().first + t;
            }
        }
        dp.swap(ndp);
    }
    return dp;
}

struct BoundedItem { int weight, count; long long value; };

long long bounded_knapsack(int cap, const vector<BoundedItem>& items) {
    vector<long long> dp(cap + 1), ndp(cap + 1);
    for (auto [w, cnt, val] : items) {
        if (w == 0) {
            if (val > 0) for (long long& x : dp) x += val * cnt;
            continue;
        }
        ndp = dp;
        for (int r = 0; r < w && r <= cap; ++r) {
            deque<pair<long long, int>> q;
            for (int c = r, t = 0; c <= cap; c += w, ++t) {
                while (!q.empty() && q.front().second < t - cnt) q.pop_front();
                long long cur = dp[c] - 1LL * t * val;
                while (!q.empty() && q.back().first <= cur) q.pop_back();
                q.push_back({cur, t});
                ndp[c] = q.front().first + 1LL * t * val;
            }
```

```
        }
        dp.swap(ndp);
    }
    return dp[cap];
}
```

7.2 Fast Knapsack Formulas

Use: Residue-class sliding-window recurrences.
Complexity: As above.
Pitfalls: Compress equal positive values; deque direction differs for min-items and max-value.
Assumptions/deps: Read before adapting the code.

Bitset reachability

The 0/1 transition is `can |= can << weight`, taking $O(items \cdot SUM/wordsize)$.

Few distinct positive weights

If positive weights total S and there are D distinct values, then

$$1 + 2 + \cdots + D \le S, \qquad D = O(\sqrt{S}).$$

Compress equal weights into (w, k). Within each residue modulo w, a window of length $k+1$ processes one weight in $O(S)$, hence $O(S\sqrt{S})$ total.

Minimum item count for sum $r + tw$:

$$new_t = t + \min_{\max(0,t-k) \le j \le t} (old_j - j).$$

For k copies of an item with weight w and value v:

$$new_t = tv + \max_{\max(0,t-k) \le j \le t} (old_j - jv).$$

Maintain the min/max with a deque. Bounded max-value knapsack is $O(types \cdot capacity)$. Zero subset-sum weights do not help; zero-weight positive-value items contribute every available copy.

7.3 Bitmask DP

Use: Submask enumeration and Held–Karp Hamiltonian path.
Complexity: Submasks $O(2^{popcount})$; path $O(n^2 2^n)$.
Pitfalls: Loop includes zero; memory is often limiting; example starts at vertex 0.
Assumptions/deps: Usually $n \le 22$; costs use `long long`.

```
// Bitmask DP helpers: submask enumeration and Held-Karp Hamiltonian path.
// Complexity: all submasks of one mask O(2^popcount); Held-Karp O(n^2 2^n).
// Pitfalls: the submask loop includes 0; n must be small (usually <= 20-22);
// this path starts at 0, visits every vertex, and may end anywhere.
// Usage: for(int s=m;;s=(s-1)&m){... if(!s)break;} tsp_path(cost);
vector<int> submasks(int mask) {
    vector<int> out;
    for(int s=mask;;s=(s-1)&mask) {
        out.push_back(s);
        if(!s) break;
    }
    return out;
}

long long tsp_path(const vector<vector<long long>>& cost) {
    int n=cost.size();
    if(!n) return 0;
    const long long INF=(1LL<<62);
    vector<vector<long long>> dp(1<<n,vector<long long>(n,INF));
    dp[1][0]=0;
    for(int mask=1;mask<(1<<n);++mask) for(int v=0;v<n;++v) if(mask>>v&1) {
        if(dp[mask][v]==INF) continue;
        for(int u=0;u<n;++u) if(!(mask>>u&1))
            dp[mask|1<<u][u]=min(dp[mask|1<<u][u],dp[mask][v]+cost[v][u]);
    }
    return *min_element(dp.back().begin(),dp.back().end());
}
```

7.4 Bitmask DP Formulas

Use: Submask $O(3^n)$ proof and Held–Karp recurrence.
Complexity: Reference notes.
Pitfalls: Confirm path versus cycle and mask integer width.
Assumptions/deps: Pairs with the example implementation above.

Bit i belongs to subset S when `(S >> i) & 1`. Add, remove, or toggle it with `|`, `&`, or `^` using `1 << i`.

Enumerate all submasks

```
for (int T = S; ; T = (T - 1) & S) {
    use(T);
    if (T == 0) break;
}
```

Across every S, this is $O(3^n)$: each bit is outside S, in $S \setminus T$, or in T. For nonempty proper submasks, start at `(S - 1) & S` and stop before zero.

Held-Karp path DP

$dp[S][v]$ is the minimum cost of a path starting at 0, visiting exactly S, and ending at v:

$$dp[S \cup \{u\}][u] \leftarrow \min\big(dp[S \cup \{u\}][u],\ dp[S][v] + cost[v][u]\big).$$

Pitfalls: `1 << n` overflows `int` near $n = 31$; use `1LL << n` when needed. Memory $O(n2^n)$ is often the real limit. Decide path vs. cycle and whether the start is fixed.

7.5 Digit DP

Use: Count values up to a bound with a target digit sum.
Complexity: $O(digits^2 \cdot 10)$.
Pitfalls: Leading zeros represent shorter values; zero is counted for target zero; reset memo per bound.
Assumptions/deps: Canonical bound function for range subtraction.

```cpp
// Digit DP example: count x in [0,limit] with digit sum exactly target.
// Complexity: O(digits^2 * 10) time, O(digits^2) memory per call.
// Pitfalls: leading zeroes represent shorter numbers; 0 is counted when
// target=0. This version assumes -1 <= limit <= 1e18.
// Usage: count_digit_sum(r,s)-count_digit_sum(l-1,s);
long long count_digit_sum(long long limit,int target) {
    if(limit<0 || target<0 || target>171) return 0;
    string digits=to_string(limit);
    long long memo[20][172];
    memset(memo,-1,sizeof memo);
    function<long long(int,int,bool)> dfs=[&](int pos,int sum,bool tight)->long long
        {
        if(sum>target) return 0;
        if(pos==(int)digits.size()) return sum==target;
        if(!tight && memo[pos][sum]!=-1) return memo[pos][sum];
        int hi=tight?digits[pos]-'0':9;
        long long ans=0;
        for(int d=0;d<=hi;++d) ans+=dfs(pos+1,sum+d,tight && d==hi);
        if(!tight) memo[pos][sum]=ans;
        return ans;
    };
    return dfs(0,0,true);
}
```

7.6 Digit DP State Design

Use: Tight/started flags and common property states.
Complexity: State-dependent.
Pitfalls: Decide zero semantics and answer width before coding.
Assumptions/deps: Use the code above as a small concrete example.

Canonical state

Scan most-significant digit first with `(position, problem_state, tight, started)`.

- `tight`: the prefix still equals the bound, so the next digit is bounded.
- `started`: separates leading zeroes from real zero digits when length, adjacency, or the number zero matters.

For $[L, R]$, compute $solve(R) - solve(L-1)$. Memoize only states with `tight == false`; tight states depend on the bound prefix. Omit `started` when leading zeroes cannot change the property, as with digit sum.

Common problem states

- digit sum or sum modulo k;
- previous digit for adjacency constraints;
- automaton node for forbidden/required substrings;
- used-digit mask;
- remainder modulo m.

Decide whether zero is included, reset memo between bounds/test cases, and estimate answer overflow before choosing `long long`.

7.7 Longest Increasing Subsequence

Use: Reconstruct one strict LIS as original indices.
Complexity: $O(n \log n)$.
Pitfalls: `lower_bound` is strict; use `upper_bound` for nondecreasing.
Assumptions/deps: 0-indexed; empty input returns empty.

```cpp
// Reconstruct one strict longest increasing subsequence (indices).
// Complexity: O(n log n).
// Pitfalls: lower_bound gives strict LIS; use upper_bound for nondecreasing LIS.
// Usage: vector<int> ids = lis_indices(a);
vector<int> lis_indices(const vector<long long>& a) {
    vector<long long> tail;
    vector<int> at, parent(a.size(), -1);
    for (int i = 0; i < (int)a.size(); ++i) {
```

```
        int p = lower_bound(tail.begin(), tail.end(), a[i]) - tail.begin();
        if (p == (int)tail.size()) tail.push_back(a[i]), at.push_back(i);
        else tail[p] = a[i], at[p] = i;
        if (p) parent[i] = at[p - 1];
    }
    vector<int> ans;
    if (!at.empty()) for (int v = at.back(); v != -1; v = parent[v]) ans.push_back(v
        );
    reverse(ans.begin(), ans.end());
    return ans;
}
```

7.8 Meet in the Middle

Use: Maximum subset sum not exceeding a limit.
Complexity: $O(2^{n/2} \log 2^{n/2})$.
Pitfalls: Returns `LLONG_MIN` if no subset fits; additions can overflow.
Assumptions/deps: Useful around $n \approx 40$–44.

```
// Maximum subset sum <= limit by meet in the middle.
// Complexity: O(2^(n/2) log 2^(n/2)); practical for n about 40-44.
// Pitfalls: returns LLONG_MIN if no subset fits (possible when limit < 0).
// Usage: long long best=max_subset_sum_leq(a,limit).
vector<long long> half_sums(const vector<long long>& a, int l, int r) {
    vector<long long> sums(1, 0);
    for (int i = l; i < r; ++i) {
        int old = sums.size();
        sums.resize(2 * old);
        for (int j = 0; j < old; ++j) sums[old + j] = sums[j] + a[i];
    }
    return sums;
}

long long max_subset_sum_leq(const vector<long long>& a, long long limit) {
    int m = a.size() / 2;
    auto left = half_sums(a, 0, m), right = half_sums(a, m, a.size());
    sort(right.begin(), right.end());
    long long ans = LLONG_MIN;
    for (long long x : left) {
        auto it = upper_bound(right.begin(), right.end(), limit - x);
        if (it != right.begin()) ans = max(ans, x + *prev(it));
    }
    return ans;
}
```

7.9 Slope Trick

Use: Maintain convex piecewise-linear DP functions with two heaps.
Complexity: $O(\log n)$ per hinge; $O(1)$ shift/minimum.
Pitfalls: Convex functions only; offsets and function values can overflow.
Assumptions/deps: Supports constants, one-sided hinges, absolute value, and sliding minimum.

```
// Slope trick for convex piecewise-linear functions with integer breakpoints.
// Supports adding constants, max(a-x,0), max(x-a,0), |x-a|, and sliding min.
// Complexity: O(log n) per hinge, O(1) shift/minimum; memory O(operations).
// Pitfalls: values/offsets can overflow long long; shift(a,b) requires a<=b.
// addAMinusX/addXMinusA add one-sided hinges; addAbs adds both. shift(a,b)
// changes f to min_{x-b<=y<=x-a} f(y). minimum/argmin read the optimum.
// Example: addAbs(2); addAbs(5) gives minimum()==3 and argmin()=={2,5}.
struct SlopeTrick {
    using ll=long long;
    const ll INF=(1LL<<62);
    priority_queue<ll>L;
    priority_queue<ll,vector<ll>,greater<ll>>R;
    ll addL=0,addR=0,minF=0;

    ll topL() const{return L.top()+addL;}
    ll topR() const{return R.top()+addR;}
    void pushL(ll x){L.push(x-addL);}
    void pushR(ll x){R.push(x-addR);}
    void addConstant(ll c){minF+=c;}
    void addAMinusX(ll a) {
        if(R.empty()){pushL(a);return;}
        ll r=topR();if(a>r)minF+=a-r;
        pushR(a);r=topR();R.pop();pushL(r);
    }
    void addXMinusA(ll a) {
        if(L.empty()){pushR(a);return;}
        ll l=topL();if(l>a)minF+=l-a;
        pushL(a);l=topL();L.pop();pushR(l);
    }
    void addAbs(ll a){addAMinusX(a);addXMinusA(a);}
    void shift(ll a,ll b){assert(a<=b);addL+=a;addR+=b;} // f(x)=min f(y), y in [x-b,
        x-a]
    ll minimum() const{return minF;}
    pair<ll,ll> argmin() const{return {L.empty()?-INF:topL(),R.empty()?INF:topR()};}
    ll value(ll x) const { // O(k log k) for k breakpoints, mainly for debugging
        ll ans=minF;auto l=L;auto r=R;
        while(!l.empty()){ans+=max(0LL,l.top()+addL-x);l.pop();}
        while(!r.empty()){ans+=max(0LL,x-(r.top()+addR));r.pop();}
        return ans;
    }
};
```

7.10 Slope Trick Formulas

Use: Breakpoint representation and sliding-min transform.
Complexity: As above.
Pitfalls: Derive the DP transition as supported convex operations first.
Assumptions/deps: Pairs with the two-heap implementation.

Represent a convex piecewise-linear f by its minimum and two heaps of breakpoints. The left max-heap contributes $\max(l - x, 0)$; the right min-heap contributes $\max(x - r, 0)$.

- Add $\max(a - x, 0)$: insert a on the left, rebalancing through the right.
- Add $\max(x - a, 0)$: insert a on the right, rebalancing through the left.
- Add $|x - a|$: perform both operations.

The minimum is stored directly. Its minimizer interval is $[\max(left), \min(right)]$.

Sliding-window minimum

For $a \le b$,

$$g(x) = \min_{x-b \le y \le x-a} f(y).$$

Shift every left breakpoint by a and every right breakpoint by b; lazy offsets avoid touching the heaps.

This structure represents **convex functions only**. Derive the DP transition as supported convex operations before copying code.

7.11 Lagrangian Relaxation (Aliens/WQS)

Use: Replace an exact-count dimension by a per-component penalty.
Complexity: $O(\log range \cdot oracle)$.
Pitfalls: Monotone count alone is insufficient; prove discrete convexity/strong duality and tie rules.
Assumptions/deps: Generic exact-k minimum wrapper around a pure penalized oracle.

```cpp
// Lagrangian relaxation (WQS/Aliens trick) for an exact-k penalized oracle.
// solve(lambda) -> {min(base_cost + lambda*count), chosen_count}.
// Complexity: O(log(hi-lo) * oracle cost).
// Pitfalls: count must be nonincreasing in lambda and the exact-count cost must
// have the required discrete-convex/strong-duality property.
// Usage: answer=lagrangian_exact_k(k,lo,hi,solve);
template<class Solve>
long long lagrangian_exact_k(int k,long long lo,long long hi,Solve solve) {
    long long originalLo=lo;
    assert(solve(lo).second>=k && solve(hi).second<=k);
    while(lo<hi) {
        long long mid=lo+(hi-lo)/2;
        if(solve(mid).second<=k)hi=mid;
        else lo=mid+1;
    }
    auto adjusted=[&](long long lambda){return solve(lambda).first-lambda*k;};
    long long ans=adjusted(lo);
    if(lo>originalLo)ans=max(ans,adjusted(lo-1));
    return ans;
}
```

7.12 Lagrangian Relaxation Proof

Use: Penalty monotonicity, dual recovery, and oracle checklist.
Complexity: As above.
Pitfalls: Penalty bounds must straddle k; cost arithmetic can overflow.
Assumptions/deps: Also known as Aliens trick or WQS binary search.

Let $C(k)$ be the optimum base cost using exactly k components. Add penalty λ per component and ask an oracle for

$$P(\lambda) = \min_t \big(C(t) + \lambda t\big).$$

As λ increases, the chosen component count is nonincreasing. For optima a at λ_1 and b at $\lambda_2 > \lambda_1$, add the two optimality inequalities to get

$$(\lambda_2 - \lambda_1)(b - a) \le 0 \quad \Longrightarrow \quad b \le a.$$

Binary-search where the oracle count crosses k. Under the required discrete-convex/strong-duality condition,

$$C(k) = \max_\lambda \big(P(\lambda) - \lambda k\big).$$

Oracle checklist

- Return both penalized cost and chosen count.
- Break equal-cost ties consistently to preserve monotonicity.
- Prove penalty bounds whose endpoint counts straddle k.
- Monotone count is not enough: justify exact-k dual recovery.

Also called Aliens trick or WQS binary search.

7.13 Divide and Conquer DP

Use: Optimize DP with monotone optimal split.
Complexity: Typically $O(mn \log n)$ here; tighter variants can be $O(mn)$.
Pitfalls: Prove monotone optimal splits. Only nonempty groups are considered.
Assumptions/deps: `divide_and_conquer_dp(n,groups,cost)` with half-open costs.

```cpp
// Minimize cost of exactly groups nonempty intervals partitioning [0,n).
// cost(k,j) is the cost of [k,j). Smallest optimal k must be monotone in j.
// Example: squared segment sum with nonnegative elements, using prefix sums.
// O(groups * n log n) time for O(1) cost, O(n) space. Sums must fit long long.
template<class Cost>
long long divide_and_conquer_dp(int n, int groups, Cost cost) {
    if (!n && !groups) return 0;
    assert(1 <= groups && groups <= n);
    vector<long long> prev(n+1), cur(n+1);
    for (int j = 1; j <= n; ++j) prev[j] = cost(0,j);
    auto comp = [&](auto&& self, int l, int r, int lo, int hi) -> void {
        if (l > r) return;
        int mid = (l+r)/2, opt = lo;
        long long best = LLONG_MAX;
        for (int k = lo; k <= min(hi,mid-1); ++k) {
            long long cand = prev[k] + cost(k,mid);
            if (cand < best) best = cand, opt = k;
        }
        cur[mid] = best;
        self(self,l,mid-1,lo,opt);
        self(self,mid+1,r,opt,hi);
    };
    for (int g = 2; g <= groups; ++g) {
        comp(comp,g,n,g-1,n-1);
        prev.swap(cur);
    }
    return prev[n];
}
```

7.14 Divide and Conquer DP Notes

Use: Proof checklist for monotone DP optimization.
Complexity: Reference notes.
Pitfalls: The note is a guide, not a proof for a specific problem.
Assumptions/deps: Read before using the template.

Recurrence and requirement

For one DP layer,

$$dp_i(j) = \min_{i-1 \le k < j} \left(dp_{i-1}(k) + C(k,j) \right), \qquad i \ge 2.$$

$dp_i(j)$ is the cost of partitioning $[0,j)$ into exactly i nonempty groups. $C(k,j)$ costs $[k,j)$ and $dp_1(j) = C(0,j)$ for $j \ge 1$. Let $opt_i(j)$ be the smallest minimizing k. Prove

$$opt_i(j) \le opt_i(j+1).$$

A common sufficient condition is the quadrangle inequality

$$C(a,c) + C(b,d) \le C(a,d) + C(b,c) \quad (a \le b \le c \le d),$$

but this must be checked for the actual cost function.

Divide-and-conquer step

Compute the midpoint mid while searching only $[opt_L, \min(mid-1, opt_R)]$. If its optimum is $best$, recurse on the two halves.

- the left half with bounds $[opt_L, best]$;
- the right half with bounds $[best, opt_R]$.

With $O(1)$ cost evaluation, one layer is $O(n \log n)$ and m layers are $O(mn \log n)$, versus $O(mn^2)$ naively.

Usage and pitfalls

Call `divide_and_conquer_dp(n, groups, cost)` with a half-open cost function. For layer `g` the code fills endpoints from `g` to `n` and starts the split search at `g-1`. This keeps impossible prefixes out of the search.

- Use a wide type for both C and `dp + C`.
- Tie-breaking must preserve a valid monotone optimum.

7.15 k Smallest Subset Sums

Use: Enumerate the first k sums with a min-heap.
Complexity: $O(n \log n + k \log(k+1))$ time and $O(n+k)$ space.
Pitfalls: Keep equal sums with multiplicity. The empty subset counts. An oversized k returns all sums.
Assumptions/deps: Toggle elements from the minimum-sum subset. Each heap step adds the next index or replaces the largest index with the next one. Uses GNU `__int128`.

```cpp
// First k subset sums in sorted order (CSES 3108, entry 13897226).
// Include the empty subset and keep one sum per subset of indices.
// Usage: k_smallest_subset_sums({1, -3, 3}, 4) -> {-3, -2, 0, 0}.
// O(n log n + k log(k+1)) time and O(n+k) space.
vector<__int128> k_smallest_subset_sums(const vector<long long>& a, int k) {
    if (k <= 0) return {};
    vector<__int128> w(a.begin(), a.end());
    __int128 base = 0;
    for (auto& x : w) if (x < 0) {
        base += x;
        x = -x;
    }
    sort(w.begin(), w.end());

    // Start with all negatives selected. Toggling index i costs w[i].
    // A toggle set with max j has one parent. Remove j if j == 0 or
    // j-1 is present. Otherwise replace j with j-1.
    using State = pair<__int128, int>; // sum, largest toggled index
    priority_queue<State, vector<State>, greater<State>> pq;
    pq.push({base, -1});
    vector<__int128> ans;
    int n = w.size();
    for (; k > 0 && !pq.empty(); --k) {
        auto [sum, i] = pq.top();
        pq.pop();
        ans.push_back(sum);
        if (i + 1 == n) continue;
        pq.push({sum + w[i + 1], i + 1}); // Add i+1.
        if (i >= 0) pq.push({sum + w[i + 1] - w[i], i + 1});
    }
    return ans;
}
```

7.16 Knuth Optimization

Use: Interval DP with monotone split bounds.
Complexity: $O(n^2)$ after prefix/cost setup.
Pitfalls: Requires monotone optimal splits. Cost takes `[l,r)`.
Assumptions/deps: `knuth(n,cost)` stores triangular costs and one row of splits.

```cpp
// Knuth optimization for merging intervals. cost(l,r) uses [l,r).
// Require monotone optimal splits: opt(l,r-1) <= opt(l,r) <= opt(l+1,r).
// Example: knuth(n, [&](int l,int r){return pref[r]-pref[l];}) for
// adjacent pile merging with nonnegative weights. Singleton cost is zero.
// O(n^2) time for O(1) cost, n(n+1)/2 stored sums plus O(n) split indices.
// At n=5000 the sums alone take about 100 MB. All costs/sums must fit ll.
template<class Cost>
long long knuth(int n, Cost cost) {
    if (!n) return 0;
    vector<vector<long long>> dp(n); // dp[r][l] represents [l,r+1)
    for (int r = 0; r < n; ++r) dp[r].resize(r+1);
    vector<int> opt(n);
    iota(opt.begin(),opt.end(),0);
    for (int len = 2; len <= n; ++len) {
        for (int l = 0, r = len-1; r < n; ++l, ++r) {
            // Left-to-right: opt[l] and opt[l+1] still describe length len-1.
            long long best = LLONG_MAX;
            int split = opt[l];
            for (int k = opt[l]; k <= min(opt[l+1],r-1); ++k) {
                long long cand = dp[k][l] + dp[r][k+1];
                if (cand < best) best = cand, split = k;
            }
            dp[r][l] = best + cost(l,r+1);
            opt[l] = split;
        }
    }
    return dp[n-1][0];
}
```

8 Misc

8.1 Quick Local Test Script

Use: Compile `SOL.cpp`, run it on `input`, save at most 10000 lines to `output`.
Complexity: Program-dependent.
Pitfalls: Run from the directory containing the source and input file; compile failure stops execution.
Input/output: `bash tools/test.sh SOL`; diagnostics go to terminal, program output to `output`.

```
#!/usr/bin/env bash
# Usage: bash tools/test.sh SOL, where SOL.cpp and file "input" exist.
# Input: stdin is read from ./input.
# Output: compiler errors/warnings on the terminal; first 10000 program lines in ./output.
set -u
: "${1:?Usage: bash tools/test.sh SOL}"
if ! g++ -std=c++17 -O2 -Wall -Wextra "$1.cpp" -o "$1" \
       2> >(grep -E "error:|warning:" >&2); then
    exit 1
fi
"./$1" < input | head -10k > output
```

8.2 Stress Test Kit

Use: Compare a fast solution with a brute force on random tiny tests until they differ; write it *before* the first run of any unproven greedy, formula or casework.
Complexity: Tests × (brute time + process start, about 10–30 ms each).
Pitfalls: The generator decides what is found: tiny values for ties, zeros, edge parameters, several test cases, a few maximal values. Seed from the argument so a failing seed reproduces.
Input/output: `bash stress.sh ./a ./brute "python3 gen.py" [N]`; prints `WA/RE/TLE seed`, the test and the diff. `stress.py` is the same loop with the generator inside, for machines without bash.

```
#!/usr/bin/env bash
# Usage: bash stress.sh FAST BRUTE GEN [N] e.g. bash stress.sh ./a ./brute "python3 gen.py"
# GEN gets the seed as its last argument, so a failing seed reproduces the same test.
for ((i = 1; i <= ${4:-1000}; i++)); do
  $3 $i > in
  timeout 2 $1 < in > o1 || { echo "RE/TLE seed $i"; cat in; exit 1; }
  $2 < in > o2
  diff -w o1 o2 > /dev/null || { echo "WA seed $i"; cat in; diff -w o1 o2; exit 1; }
done
echo "OK $((i - 1)) tests"
```

```
import random, sys
random.seed(int(sys.argv[1])) # seed from stress.sh: same seed, same test
R = random.randint
n = R(1, 6) # tiny n: the failing test stays readable
print(n)
print(*[R(-3, 3) for _ in range(n)]) # tiny values: ties, zeros, negatives
```

```
"""stress.py FAST BRUTE [N] -- compare two commands on N random tests from gen()."""
import random, subprocess, sys

def gen(): # EDIT per problem; mix tiny values, edge sizes, several test cases
    n = random.randint(1, 6)
    return f"{n}\n{' '.join(str(random.randint(-3, 3)) for _ in range(n))}\n"

def run(cmd, s):
    return subprocess.run(cmd, shell=True, input=s, capture_output=True,
                          text=True, timeout=5).stdout.split()

for seed in range(int(sys.argv[3]) if len(sys.argv) > 3 else 1000):
    random.seed(seed); s = gen()
    x, y = run(sys.argv[1], s), run(sys.argv[2], s)
    if x != y: sys.exit(f"WA seed {seed}\n{s}fast: {' '.join(x)}\nbrute: {' '.join(y)}")
print("OK")
```

8.3 Python Brute Force Recipes

```
# Python brute-force recipes for tiny stress-test oracles.
from itertools import combinations, combinations_with_replacement
from itertools import permutations, product


# Executable examples: python3 brute.py --examples
# N length-k tuples: O(N*(k+1)) time, plus checking each candidate.
# Iterators keep input pools; list() below also stores ALL output.
# k >= 0; k=0 gives one empty tuple; k>n gives none without reuse.
# Equal values at different positions stay distinct. Iterators are single-use.
def examples():
    a, k = [10, 20, 30], 2
    pairs = list(combinations(a, k)) # C(n,k), order ignored
    assert pairs == [(10, 20), (10, 30), (20, 30)]
    indices = list(combinations(range(len(a)), k))
    assert indices == [(0, 1), (0, 2), (1, 2)]

```

```python
    orders = list(permutations(a)) # n! full orders
    assert len(orders) == 6
    ordered_pairs = list(permutations(a, k)) # n!/(n-k)!
    assert ordered_pairs == [(10, 20), (10, 30), (20, 10),
                             (20, 30), (30, 10), (30, 20)]
    repeated = list(combinations([1, 1, 2], 2))
    assert repeated == [(1, 1), (1, 2), (1, 2)]
    unique = sorted(set(permutations([1, 1, 2]))) # still generates n! tuples!
    assert unique == [(1, 1, 2), (1, 2, 1), (2, 1, 1)]

    bits = list(product(range(2), repeat=3)) # 2**3 bit strings
    assert len(bits) == 8 and bits[-1] == (1, 1, 1)
    words = [''.join(s) for s in product('ab', repeat=2)]
    assert words == ['aa', 'ab', 'ba', 'bb']
    grid = list(product(range(2), range(3))) # different domain per slot
    assert grid == [(0, 0), (0, 1), (0, 2), (1, 0), (1, 1), (1, 2)]

    multisets = list(combinations_with_replacement(a, k)) # C(n+k-1,k)
    assert multisets == [(10, 10), (10, 20), (10, 30),
                         (20, 20), (20, 30), (30, 30)]
    subsets = [s for k in range(len(a) + 1) for s in combinations(a, k)]
    assert len(subsets) == 8 and subsets[0] == ()
    assert list(mask_subsets(a))[3] == [10, 20]
    assert list(submasks(0b1010)) == [0b1010, 0b1000, 0b0010, 0]
    assert brute([-1, 0, 1], 0) == 4
    assert knapsack([(2, 5), (3, 7), (4, 8)], 5) == 12
    assert assignment([[9, 2], [3, 8]]) == 5
    assert colorings(3, [(0, 1), (1, 2)], 2) == 2
    assert coin_ways([1, 2, 3], 2, 4) == 2
    tree = [[1], [0, 2], [1]]
    assert set(tree_paths(tree)) == {(0,), (1,), (2,), (0, 1), (1, 2), (0, 1, 2)}
    assert list(simple_paths(tree, 0, 2)) == [(0, 1, 2)]
    assert list(partitions([1, 2])) == [((1, 2),), ((1,), (2,))]
    assert tsp([[None, 2, 5], [2, None, 3], [5, 3, None]]) == 10
    assert mst(3, [(0, 1, 2), (1, 2, 3), (0, 2, 5)]) == 5


# All index subsets, including empty. O(n*2**n) time, O(n) extra space.
# Duplicate values are separate choices; iterate instead of storing all subsets.
def mask_subsets(a):
    for mask in range(1 << len(a)):
        yield [a[i] for i in range(len(a)) if mask >> i & 1]


# All submasks, descending, INCLUDING zero. O(2**popcount(mask)), O(1) space.
# mask must be nonnegative; stop at zero or (s-1)&mask cycles forever.
def submasks(mask):
    assert mask >= 0
    s = mask
    while True:
        yield s
        if s == 0:
            break
        s = (s - 1) & mask


# Count index subsets summing to target, INCLUDING empty; negatives are OK.
# O(n*2**n) time, O(n) extra space. Do not prune sum > target with negatives.
def brute(a, target):
    answer = 0
    for k in range(len(a) + 1):
        for chosen in combinations(a, k):
            if sum(chosen) == target:
                answer += 1
    return answer


# 0/1 knapsack: each (weight,value) used at most once; empty is allowed.
# O(n*2**n) time, O(n) space. Nonnegative weights and capacity required.
def knapsack(items, capacity):
    best = 0
    for take in product((0, 1), repeat=len(items)):
        weight = sum(w for (w, v), yes in zip(items, take) if yes)
        value = sum(v for (w, v), yes in zip(items, take) if yes)
        if weight <= capacity:
            best = max(best, value)
    return best


# Minimum assignment: cost[worker][job], square n*n matrix, all jobs distinct.
# O(n*n!) time, O(n) extra space. Empty assignment costs 0; negatives are OK.
def assignment(cost):
    n = len(cost)
    return min(sum(cost[i][p[i]] for i in range(n))
               for p in permutations(range(n)))


# Count proper colorings with q LABELED colors; edges use 0-based vertices.
# O(q**n * (n+m+1)) time, O(n+q) space. Self-loop => 0; empty graph => 1.
# Require n,q >= 0. Repeated edges are harmless; color names are NOT identified.
def colorings(n, edges, q):
    answer = 0
    for color in product(range(q), repeat=n):
        if all(color[u] != color[v] for u, v in edges):
            answer += 1
    return answer


# Count unordered ways to choose exactly k coins summing to target, with reuse.
# Enumeration: O((k+1)*C(d+k-1,k)) time, O(d+k) space for d distinct coins (d>0).
# Preprocessing: expected O(len(coins) + d*log(d)) time to deduplicate/sort.
# k >= 0. Deduplicate denominations; (1,2) and (2,1) are the same way.
def coin_ways(coins, k, target):
    coins = sorted(set(coins))
```

```
    return sum(sum(chosen) == target
               for chosen in combinations_with_replacement(coins, k))


# Every simple path in an UNDIRECTED TREE (also works for a forest).
# adj has both directions, no loops/parallel edges/cycles; vertices are 0-based.
# Yield vertex tuples, including singletons; reverse paths counted only once.
# O(n**2 + total output length) time, O(n) space; O(n**3) time on a chain.
# Tiny trees only: recursive DFS uses O(n) Python call depth.
def tree_paths(adj):
    path = []

    def dfs(u, parent, start):
        path.append(u)
        if start <= u:
            yield tuple(path)
        for v in adj[u]:
            if v != parent:
                yield from dfs(v, u, start)
        path.pop()

    for start in range(len(adj)):
        yield from dfs(start, -1, start)


# All simple source->target paths in a directed or undirected graph.
# No repeated vertices; source==target yields only (source,), not cycles.
# Unique neighbors per adjacency list; valid endpoints required.
# O(n*n!) worst-case time, O(n) space on simple graphs; tiny n only.
# Backtrack visited state: a global 'visited forever' would miss paths.
def simple_paths(adj, source, target):
    used = [False] * len(adj)
    path = []

    def dfs(u):
        used[u] = True
        path.append(u)
        if u == target:
            yield tuple(path)
        else:
            for v in adj[u]:
                if not used[v]:
                    yield from dfs(v)
        path.pop()
        used[u] = False

    yield from dfs(source)


# Split a sequence into every possible list of nonempty CONTIGUOUS blocks.
# O(n*2**(n-1)) time, O(n) space for n>=1; empty input has one partition ().
# Cuts are between positions, not values; useful for checking partition DP.
def partitions(a):
    n = len(a)
    if n == 0:
        yield ()
        return
    for mask in range(1 << (n - 1)):
        blocks, start = [], 0
        for end in range(1, n + 1):
            if end == n or mask >> (end - 1) & 1:
                blocks.append(tuple(a[start:end]))
                start = end
        yield tuple(blocks)


# Cheapest tour from vertex 0, visiting every other vertex once, back to 0.
# Square cost matrix: None means missing edge; directed/negative costs OK.
# O(n*(n-1)!) time, O(n) space. Return None if impossible; n<=1 costs 0.
# Fixing the start removes rotations. A 2-vertex tour traverses both directions.
def tsp(cost):
    n = len(cost)
    if n <= 1:
        return 0
    best = None
    for order in permutations(range(1, n)):
        tour = (0,) + order + (0,)
        weights = [cost[u][v] for u, v in zip(tour, tour[1:])]
        if all(w is not None for w in weights):
            value = sum(weights)
            best = value if best is None else min(best, value)
    return best


# Minimum spanning tree by choosing n-1 edges and checking connectivity.
# Undirected edge list (u,v,w); loops, parallel edges, negative weights OK.
# O(m + n*C(m,n-1)) time, O(m+n) space for n>=1; tiny m only.
# Connected + exactly n-1 edges implies a tree. None if disconnected; n=0 => 0.
def mst(n, edges):
    if n == 0:
        return 0
    best = None
    for chosen in combinations(edges, n - 1):
        adj = [[] for _ in range(n)]
        for u, v, w in chosen:
            adj[u].append(v)
            adj[v].append(u)
        seen, stack = {0}, [0]
        while stack:
            for v in adj[stack.pop()]:
                if v not in seen:
                    seen.add(v)
                    stack.append(v)
        if len(seen) == n:
```

```
            value = sum(w for u, v, w in chosen)
            best = value if best is None else min(best, value)
    return best


# Default oracle input: n target, then n integers; output: subset count.
# EDIT input/check and stress.py's gen() together; Python integers don't overflow.
# python3 stress.py './fast' 'python3 brute.py' 100
if __name__ == '__main__':
    import sys
    if sys.argv[1:] == ['--examples']:
        examples()
        print('OK')
    else:
        n, target, *a = map(int, sys.stdin.buffer.read().split())
        assert len(a) == n
        print(brute(a, target))
```

8.4 In-Process Stress Test

Use: Fast/brute as functions in one file: no scripts, about 10^5 tests/s.
Complexity: Tests × brute time.
Pitfalls: `fast()` runs many times: it must reset its own globals (this also catches multi-test reset bugs). Fixed seed reproduces failures.
Assumptions/deps: Standalone file with `main`; example is max subarray sum.

```
// In-process stress test: no scripts or files, about 1e5 tests/s.
// Paste the solution as fast(), write an obviously correct brute(), edit the generator.
// Build: g++ -O2 -fsanitize=address,undefined stress.cpp && ./a.out
// Fixed seed: a failing test reproduces on every run. fast() runs many times,
// so a global it forgets to reset fails here exactly as on a multi-test judge.
#include <bits/stdc++.h>
using namespace std;
using ll = long long;
mt19937 rng(1);
ll rnd(ll l, ll r) { return uniform_int_distribution<ll>(l, r)(rng); }

ll fast(vector<ll> a) { // example: max nonempty subarray sum (Kadane)
    ll best = a[0], cur = 0;
    for (ll x : a) cur = max(cur + x, x), best = max(best, cur);
    return best;
}
ll brute(vector<ll> a) {
    ll best = LLONG_MIN;
    for (int l = 0; l < (int)a.size(); l++)
        for (ll r = l, s = 0; r < (ll)a.size(); r++) s += a[r], best = max(best, s);
    return best;
}
int main() {
    for (int it = 0; it < 100000; it++) {
        int n = rnd(1, 6); // tiny n and values: readable test, many ties
        vector<ll> a(n);
        for (ll &x : a) x = rnd(-5, 5);
        ll x = fast(a), y = brute(a);
        if (x != y) {
            cout << "test " << it << ": n = " << n << "\n";
            for (ll v : a) cout << v << ' ';
            cout << "\nfast " << x << ", brute " << y << "\n";
            return 1;
        }
    }
    cout << "OK\n";
}
```

8.5 Interactive Grader Helper

Use: Compile a solution and local interactive judge, then pipe them together.
Complexity: Protocol-dependent.
Pitfalls: Both programs must flush complete lines; no judge timeout.
Input/output: `grader.py [-v] SOL [JUDGE]`; returns judge status, `-v` logs dialogue.

```
#!/usr/bin/env python3
"""grader.py [-v] SOL [JUDGE] -compile both and pipe SOL<->JUDGE; -v echoes the talk.
    """
# Input: SOL.cpp and JUDGE.cpp (default judge.cpp), using line-flushed protocols.
# Effect: compiles both, then pipes each program's stdout to the other's stdin.
# Output: judge exit status; -v copies the conversation to stderr.
# Pitfalls: no timeout while the judge runs; a program that does not flush may deadlock.
import sys, subprocess, threading

def g(s): return subprocess.run(["g++", "-std=c++17", "-O2", s + ".cpp", "-o", s]).returncode

def pump(a, b, tag):
    for line in a:
        if tag: sys.stderr.write(tag + line)
        b.write(line); b.flush()
    b.close()

a = sys.argv[1:]
v = "-v" in a
a = [x for x in a if x != "-v"]
if not a: print(__doc__); sys.exit()

```

```python
sol = a[0].removesuffix(".cpp")
judge = (a[1] if len(a) > 1 else "judge").removesuffix(".cpp")
if g(sol) or g(judge): sys.exit(1)

s = subprocess.Popen(["./" + sol], stdin=subprocess.PIPE, stdout=subprocess.PIPE, text=True)
j = subprocess.Popen(["./" + judge], stdin=subprocess.PIPE, stdout=subprocess.PIPE, text=True)
threading.Thread(target=pump, args=(j.stdout, s.stdin, "JUDGE> " if v else 0), daemon=True).start()
threading.Thread(target=pump, args=(s.stdout, j.stdin, "SOL> " if v else 0), daemon=True).start()
j.wait()
try: s.wait(.5)
except subprocess.TimeoutExpired: s.kill()
sys.exit(j.returncode)
```

8.6 mt19937 RNG

Use: Random 32-bit generator, correct usage demo.
Complexity: $O(1)$ per value.
Pitfalls: `int x = rng()` can be negative – use `unsigned`. Never `rand()`/`random_shuffle`.
Assumptions/deps: Shows `uniform_int_distribution` and `shuffle`.

```cpp
#include <bits/stdc++.h>
using namespace std;

mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());

int main() {
    unsigned x = rng(); // random 32-bit (int x = rng() can be negative!)
    int y = rng() % 100; // 0..99, slight modulo bias (fine for CP)
    int z = uniform_int_distribution<int>(5, 10)(rng); // exact uniform in [5,10]
    long long big = ((long long)rng() << 31) ^ rng(); // or use mt19937_64
    vector<int> v = {1, 2, 3};
    shuffle(v.begin(), v.end(), rng); // NEVER random_shuffle (uses rand())
    cout << x << " " << y << " " << z << " " << big << "\n";
}
```

8.7 mt19937_64 RNG

Use: Random 64-bit generator.
Complexity: $O(1)$ per value.
Pitfalls: Seed once; do not reseed inside tight loops.
Assumptions/deps: Requires `chrono`, `mt19937_64`.

```cpp
mt19937_64 rng64(chrono::steady_clock::now().time_since_epoch().count());
unsigned long long x = rng64();
```

8.8 Random Hashing

Use: Assign random xor keys to values.
Complexity: Expected $O(1)$ map operations.
Pitfalls: Hash is probabilistic. Requires stable rng and clearing map when state universe changes.
Assumptions/deps: Depends on `rng64` above and uses `uint64_t`.

```cpp
// Set-equality hashing: hash of a set = xor of random keys of its elements.
// Requires: mt19937_64 rng64 (rand_mt19937_faster.cpp). Compare multisets with
// sums instead of xor (xor cancels duplicate pairs).
// Expected O(1) per lookup. Collisions are possible.
unordered_map<int, uint64_t> h;
uint64_t getHash(int x) {
    if (!h.count(x)) h[x] = rng64();
    return h[x];
}
// Usage: cur ^= getHash(x); // toggle x
```

8.9 Zobrist Hashing

Use: Incremental xor hash for states.
Complexity: Build $O(positions \cdot values)$, update/hash $O(1)$ or $O(n)$.
Pitfalls: Probabilistic collisions; state values must be valid indices.
Assumptions/deps: Uses `mt19937_64`; `uint64_t`.

```cpp
// Zobrist hashing: xor random keys for incremental state hashes.
// Source: standard Zobrist/tabulation hashing.
// Build O(positions * values), toggle O(1), full hash O(state.size()).
// Pitfalls: probabilistic collisions; state values must be in range.
// Usage: h ^= key[pos][old]; h ^= key[pos][now];
struct Zobrist {
    vector<vector<uint64_t>> key;

    Zobrist(int positions, int values, uint64_t seed = chrono::steady_clock::now().time_since_epoch().count()) {
        mt19937_64 rng(seed);
        key.assign(positions, vector<uint64_t>(values));
```

```
        for (auto& row : key)
            for (uint64_t& x : row) x = rng();
    }

    uint64_t hash(const vector<int>& state) const {
        uint64_t h = 0;
        for (int i = 0; i < (int)state.size(); i++)
            if (state[i] >= 0) h ^= key[i][state[i]];
        return h;
    }
};
```

8.10 Quick Select

Use: Get kth element / partition order statistic.
Complexity: Average linear for `nth_element`.
Pitfalls: After call, only kth is fixed; sides are partitioned, not sorted.
Assumptions/deps: `k` is 0-indexed iterator offset.

```
nth_element(a.begin(), a.begin()+k, a.end());
```

8.11 GNU Extensions

Use: PBDS ordered sets/maps and rope snippets.
Complexity: $O(\log n)$ usual PBDS/rope ops.
Pitfalls: Put extension headers before the integer macro. Use the pair trick for multisets.
Assumptions/deps: GNU C++ only.

```
// Place extension headers before #define int long long.
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
// NOTE: examples below are not one compilable file; paste only the needed block.
using namespace __gnu_pbds;

template<class T> using ordered_set = tree<T, null_type, less<T>,
    rb_tree_tag, tree_order_statistics_node_update>;
template<class K, class V> using ordered_map = tree<K, V, less<K>,
    rb_tree_tag, tree_order_statistics_node_update>;

ordered_set<int> s;

s.insert(x);
s.erase(x);

// number of elements strictly smaller than x
int k = s.order_of_key(x);

// iterator to k-th (0-indexed) element
auto it = s.find_by_order(k);

// multiset trick: store (value, unique id) pairs. Do NOT use less_equal<> as
// comparator instead: it silently breaks erase(key) and lower_bound.
using pii = pair<int,int>;

ordered_set<pii> ms;
int id = 0;

ms.insert({value, id++});

// erase one occurrence
auto occurrence = ms.lower_bound({value, 0});
if (occurrence != ms.end() && occurrence->first == value) ms.erase(occurrence);

// order_of_key({value, 0}) = # elements < value

// rope: O(log n) insert/erase of chunks (editor-style problems)
#include <ext/rope>
using namespace __gnu_cxx;

rope<char> r;

r.insert(pos, "abc");
r.erase(pos, len);
r.replace(pos, len, "xyz");

char c = r[i];
```

8.12 Parallel Binary Search

Use: Find each query's first true event prefix by batched replays.
Complexity: $O(\log(E+2))$ complete event sweeps.
Pitfalls: Predicate must be prefix-monotone. Reset must fully clear replay state.
Assumptions/deps: Callbacks for reset/apply/check. Returns $E+1$ when never true.

```
// Parallel binary search for predicates monotone over an event prefix.
// Returns smallest prefix length t in [0,events], or events+1 if never true.
// Complexity: O(log(events+2)) full replays; memory O(q+events).
// Pitfalls: apply events in fixed order; reset must fully clear state; check(id)
// must stay true after becoming true.
// Usage: ans=parallel_bs(q,event_count,reset,apply_event,check_query);
```

```cpp
template<class Reset,class Apply,class Check>
vector<int> parallel_bs(int q,int events,Reset reset,Apply apply,Check check) {
    vector<int>lo(q,-1),hi(q,events+1);
    while(true) {
        bool active=false;
        vector<vector<int>>bucket(events+1);
        for(int id=0;id<q;++id) if(lo[id]+1<hi[id]) {
            int mid=(lo[id]+hi[id])/2;
            if(mid<=events) bucket[mid].push_back(id);
            active=true;
        }
        if(!active) return hi;
        reset();
        for(int t=0;t<=events;++t) {
            for(int id:bucket[t]) {
                if(check(id)) hi[id]=t;
                else lo[id]=t;
            }
            if(t<events) apply(t);
        }
    }
}
```

Usage with edge additions

Copy Disjoint Set Union and find the first prefix where each pair is connected.

```cpp
DSU dsu(4);
vector<pair<int,int>> edges = {{0,1}, {1,2}};
vector<pair<int,int>> ask = {{0,0}, {0,1}, {0,2}, {0,3}};
auto ans = parallel_bs(ask.size(), edges.size(),
    [&] { dsu.init(4); },
    [&](int t) { dsu.unite(edges[t].first, edges[t].second); },
    [&](int id) { return dsu.same(ask[id].first, ask[id].second); });
// ans = {0,1,2,3}
```

Prefix `t` contains the first `t` edges, so `0` means connected before any addition and `edges.size() + 1` means never connected. Edge additions keep connectivity monotone. Reset the DSU at the start of every replay.

8.13 Custom Hash for unordered_map

Use: Defeat anti-hash tests against gcc's identity hash.
Complexity: $O(1)$ per op restored.
Pitfalls: Default integer hash is identity: chosen keys collide into one bucket ($O(n)$ per op).
Assumptions/deps: `unordered_map<ll,int,chash>`; random offset at runtime.

```cpp
// Safe hash for unordered_map/set. libstdc++'s default hash for integers is
// the IDENTITY: a setter can pick keys colliding mod the bucket prime and
// degrade the map to O(n) per op (same anti-test class as mod-2^64 string
// hashing). splitmix64 + runtime-random offset defeats fixed test data.
// Usage: unordered_map<long long, int, chash> mp;
struct chash {
    static uint64_t splitmix64(uint64_t x) {
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }
    size_t operator()(uint64_t x) const {
        static const uint64_t R =
            chrono::steady_clock::now().time_since_epoch().count();
        return splitmix64(x + R);
    }
};
```

8.14 Deep Recursion Stack

Use: Request a larger stack limit for recursive DFS.
Complexity: $O(1)$ setup.
Pitfalls: Call before DFS and check the result. Stack use counts toward the memory limit. Put the include above `#define int long long`.
Assumptions/deps: Linux `setrlimit`.

```cpp
// Raise the stack limit for deep recursion (Linux). Call FIRST in main.
// O(1). Returns false on failure. Stack use counts toward memory limits.
// The default request is 256 MiB. Check depth and stack size for your DFS.
#include <sys/resource.h> // put ABOVE #define int long long
bool raise_stack(rlim_t bytes = 256 << 20) {
    rlimit rl;
    if (getrlimit(RLIMIT_STACK, &rl) != 0) return false;
    if (rl.rlim_cur == RLIM_INFINITY || rl.rlim_cur >= bytes) return true;
    if (rl.rlim_max != RLIM_INFINITY && rl.rlim_max < bytes) return false;
    rl.rlim_cur = bytes;
    return setrlimit(RLIMIT_STACK, &rl) == 0;
}
```

9 Hacks

Copy the shared C++17 setup once before the snippets that include `common.hpp`. Use the ordinary `int` type here. Seed `mt19937_64` once and pass it by reference. Use `mt19937_64 rng(42);` to reproduce the examples. Probability bounds assume independent trials. For budgeted witness searches, exhaustion means *not found*. For consecutive-point Lagrange, see §5.28 in Math.

9.1 Shared Setup

Save this as `common.hpp` beside the selected source, or paste it once above the snippets and omit their local includes and the pragma.

```cpp
// Shared C++17 setup; copy once before the selected snippets.
// Modular helpers: O(log e) power, O(1) normalization; fixed prime only.
// Signed 64-bit products are safe for this modulus. Do not increase blindly.
#pragma once
#include <bits/stdc++.h>
using namespace std;
using ll = long long;
using ull = unsigned long long;
const ll HMOD = 1000000007;
ll hnorm(ll x) { x %= HMOD; return x < 0 ? x + HMOD : x; }
ll hpow(ll a, ll e) {
    ll r = 1; a = hnorm(a);
    for (; e; e >>= 1, a = a * a % HMOD)
        if (e & 1) r = r * a % HMOD;
    return r;
}
// Seed once in main; use a fixed seed while debugging.
// mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());
ll pick(mt19937_64& rng, ll lo, ll hi) {
    return uniform_int_distribution<ll>(lo, hi)(rng);
}
```

9.2 Berlekamp–Massey and Nth Term

Use: Recover a modular linear recurrence and evaluate its zero-based Nth term.
Complexity: $O(s^2 + s \log P)$ for s samples, then $O(L^2 \log(N+1))$ for order L.
Pitfalls: Prove an order bound and supply twice that many samples. Give the evaluator at least L initial terms.
Assumptions/deps: Uses the shared prime P. An empty recurrence denotes the zero sequence.

```cpp
// Infer recurrence mod HMOD, then evaluate its N-th term (0-indexed).
// Time: BM O(s^2 + s log HMOD); evaluation O(L^2 log N). Space O(s+L).
// Need a proven order bound L and >=2L samples; prefix fits alone prove nothing.
// Empty recurrence means zero sequence. initial must contain >=rec.size() terms.
// Usage: nthTerm({0,1}, {1,1}, 10) == 55.
#include "common.hpp"

vector<ll> berlekampMassey(vector<ll> s) {
    for (ll& x : s) x = hnorm(x);
    vector<ll> C{1}, B{1};
    int L = 0, shift = 1; ll last = 1;
    for (int i = 0; i < (int)s.size(); ++i) {
        ll d = s[i];
        for (int j = 1; j <= L; ++j)
            d = (d + C[j] * s[i-j]) % HMOD;
        if (!d) { ++shift; continue; }
        auto old = C;
        ll coef = d * hpow(last, HMOD-2) % HMOD;
        if (C.size() < B.size()+shift) C.resize(B.size()+shift);
        for (int j = 0; j < (int)B.size(); ++j)
            C[j+shift] = hnorm(C[j+shift] - coef*B[j]%HMOD);
        if (2*L <= i) {
            L = i+1-L; B = old; last = d; shift = 1;
        } else ++shift;
    }
    C.resize(L+1); C.erase(C.begin());
    for (ll& x : C) x = hnorm(-x);
    return C; // s[i] = sum rec[j] * s[i-1-j]
}
ll nthTerm(vector<ll> initial, vector<ll> rec, ull N) {
    int L = rec.size(); assert(initial.size() >= rec.size());
    for (ll& x : initial) x = hnorm(x);
    for (ll& x : rec) x = hnorm(x);
    if (N < initial.size()) return initial[N];
    if (!L) return 0;
    auto mul = [&](vector<ll> a, vector<ll> b) {
        vector<ll> c(2*L-1);
        for (int i = 0; i < L; ++i)
            for (int j = 0; j < L; ++j)
                c[i+j] = (c[i+j] + a[i]*b[j]) % HMOD;
        for (int i = 2*L-2; i >= L; --i)
            for (int j = 1; j <= L; ++j)
                c[i-j] = (c[i-j] + c[i]*rec[j-1]) % HMOD;
        c.resize(L); return c;
    };
    vector<ll> ans(L), x(L); ans[0] = 1;
    if (L == 1) x[0] = rec[0]; else x[1] = 1;
    for (; N; N >>= 1, x = mul(x, x))
        if (N & 1) ans = mul(ans, x);
    ll value = 0;
    for (int i = 0; i < L; ++i)
        value = (value + ans[i]*initial[i]) % HMOD;
    return value;
```

```
}
```

Example usage. `auto r = berlekampMassey({0,1,1,2});` then `nthTerm({0,1}, r, 10)` returns 55.

9.3 Tutte Matrix Matching Size

Use: Estimate maximum matching size in a general undirected graph.
Complexity: $O(tn^3)$ time and $O(n^2)$ space for t trials.
Pitfalls: Result is a lower bound. For $n < P$, the miss probability is at most $(n/P)^t$.
Assumptions/deps: Use a simple vertex index range $[0, n)$ and omit self-loops. The output is a size.

```
// Maximum matching SIZE of an undirected graph, via randomized Tutte rank.
// Time O(trials*n^3), memory O(n^2); answer is always a lower bound.
// Failure <= (n/HMOD)^trials for independent uniform field samples, n<HMOD.
// Vertices 0..n-1; no loops. Parallel input edges are harmless. No edge recovery.
// Usage: tutteSize(3, {{0,1},{1,2},{2,0}}, 3, rng) == 1 with high probability.
#include "common.hpp"

int tutteSize(int n, const vector<pair<int,int>>& edges,
              int trials, mt19937_64& rng) {
    assert(n >= 0 && n < HMOD && trials > 0);
    int best = 0;
    while (trials--) {
        vector<vector<ll>> a(n, vector<ll>(n));
        for (auto [u,v] : edges) {
            assert(0 <= u && u < n && 0 <= v && v < n && u != v);
            ll r = pick(rng, 0, HMOD-1);
            a[u][v] = r; a[v][u] = hnorm(-r);
        }
        int rank = 0;
        for (int col = 0; col < n; ++col) {
            int row = rank;
            while (row < n && !a[row][col]) ++row;
            if (row == n) continue;
            swap(a[row], a[rank]);
            ll inv = hpow(a[rank][col], HMOD-2);
            for (int i = rank+1; i < n; ++i) {
                ll f = a[i][col]*inv % HMOD;
                for (int j = col; j < n; ++j)
                    a[i][j] = hnorm(a[i][j] - f*a[rank][j]%HMOD);
            }
            ++rank;
        }
        assert(rank % 2 == 0);
        best = max(best, rank/2);
    }
    return best;
}
```

Example usage. `tutteSize(3, {{0,1},{1,2},{2,0}}, 3, rng)` returns 1 with high probability.

9.4 Small-Budget Vertex Cover

Use: Find a cover of size at most k by branching on an uncovered edge.
Complexity: $O(2^k(n+m))$ time and $O((k+1)(n+m))$ space.
Pitfalls: Use a simple graph. Duplicate edges break the forced-degree rule.
Assumptions/deps: Exact search. An empty vector covers an edgeless graph.

```
// Find a vertex cover of size <=k, or nullopt if none exists (EXACT).
// Time O(2^k*(n+m)), stack/copies O((k+1)*(n+m)) for nonnegative k.
// Simple undirected graph: no loops/parallel edges (degree rule requires this).
// All state is local, so repeated calls are independent. k is a small budget.
// Usage: vertexCover(3, {{0,1},{1,2}}, 1) returns {1}.
#include "common.hpp"

optional<vector<int>> vertexCover(int n, vector<pair<int,int>> edges, int k) {
    vector<int> chosen;
    function<bool(const vector<pair<int,int>>&,int)> dfs =
    [&](const vector<pair<int,int>>& e, int left) {
        if (left < 0) return false;
        if (e.empty()) return true;
        if (!left) return false;
        vector<int> degree(n);
        for (auto [u,v] : e) { ++degree[u]; ++degree[v]; }
        int forced = max_element(degree.begin(), degree.end())-degree.begin();
        vector<int> branch{e[0].first, e[0].second};
        if (degree[forced] > left) branch = {forced};
        for (int v : branch) {
            vector<pair<int,int>> next;
            for (auto [a,b] : e)
                if (a != v && b != v) next.push_back({a,b});
            chosen.push_back(v);
            if (dfs(next, left-1)) return true;
            chosen.pop_back();
        }
        return false;
    };
    if (dfs(edges, k)) return chosen;
    return nullopt;
}
```

Example usage. `vertexCover(3, {{0,1},{1,2}}, 1)` returns a cover contain-

ing vertex 1.

9.5 Color-Coding for Short Paths

Use: Find a simple path with exactly k vertices via random colors and subset DP.
Complexity: $O(t2^k(n+m))$ time and $O(2^k n)$ space for t trials.
Pitfalls: k counts vertices. Budget both memory and trials. Miss probability is at most $(1-k!/k^k)^t$ for $k>0$.
Assumptions/deps: Directed or undirected adjacency lists. A returned path is a witness.

```cpp
// Find a simple path with k VERTICES, or nullopt if trials found none.
// Directed or undirected adjacency lists; returned path is always valid.
// Time O(trials*2^k*(n+m)); memory O(2^k*n). Intended k<=15 (often much less).
// Miss probability <=(1-k!/k^k)^trials when a k-vertex path exists.
// Usage: colorfulPath(g, 4, 200, rng); nullopt does not prove impossibility.
#include "common.hpp"

optional<vector<int>> colorfulPath(const vector<vector<int>>& g,
                                   int k, int trials, mt19937_64& rng) {
    int n = g.size(); assert(0 <= k && k <= 15 && trials >= 0);
    if (!k) return vector<int>{};
    if (k > n) return nullopt;
    int masks = 1 << k;
    while (trials--) {
        vector<int> color(n);
        for (int& c : color) c = pick(rng, 0, k-1);
        vector<vector<int>> par(masks, vector<int>(n, -2));
        for (int v = 0; v < n; ++v) par[1<<color[v]][v] = -1;
        for (int mask = 1; mask < masks; ++mask)
            for (int v = 0; v < n; ++v) if (par[mask][v] != -2)
                for (int u : g[v]) if (!(mask >> color[u] & 1))
                    par[mask | (1<<color[u])][u] = v;
        for (int v = 0; v < n; ++v) if (par[masks-1][v] != -2) {
            vector<int> path; int mask = masks-1;
            while (v != -1) {
                path.push_back(v); int u = par[mask][v];
                mask ^= 1 << color[v]; v = u;
            }
            reverse(path.begin(), path.end()); return path;
        }
    }
    return nullopt;
}
```

Example usage. `colorfulPath({{1},{2},{}}, 3, 100, rng)` searches for the path $0, 1, 2$.

9.6 Bit-Parallel LCS Length

Use: Find the exact LCS length of two byte strings.
Complexity: $O((|a|+256)w+|b|)$ time and $O(256w)$ space for $w=\lceil |b|/64 \rceil$.
Pitfalls: Keep unsigned arithmetic and carry/borrow propagation across words.
Assumptions/deps: Use the shorter string as `b` to reduce storage.

```cpp
// Exact LCS length of two byte strings; no subsequence reconstruction.
// Time O((|a|+256)*ceil(|b|/64)+|b|), memory O(256*ceil(|b|/64)).
// Unsigned arithmetic is intentional: borrow and shift carry cross words.
// Usage: bitLCS("banana", "ananas") == 5. Includes embedded zero/high bytes.
#include "common.hpp"

int bitLCS(const string& a, const string& b) {
    int words = (b.size()+63)/64;
    vector<vector<ull>> match(256, vector<ull>(words));
    for (int j = 0; j < (int)b.size(); ++j)
        match[(unsigned char)b[j]][j/64] |= 1ULL << (j%64);
    vector<ull> s(words);
    for (unsigned char c : a) {
        ull carry = 1, borrow = 0;
        for (int j = 0; j < words; ++j) {
            ull old = s[j], x = old | match[c][j];
            ull y = (old << 1) | carry;
            carry = old >> 63;
            ull z = x-y, next = (x < y) | (z < borrow);
            z -= borrow; borrow = next;
            s[j] = x & ~z;
        }
    }
    int ans = 0;
    for (ull x : s) ans += __builtin_popcountll(x);
    return ans;
}
```

Example usage. `bitLCS("banana", "ananas")` returns 5.

9.7 Bitmask Exact Cover

Use: Use Algorithm X to select rows that cover every column exactly once.
Complexity: Exponential search with $O(cr)$ work per node for c columns and r rows.
Pitfalls: At most 64 columns. Row masks must fit the declared columns.
Assumptions/deps: Exact search. A present result contains original row indices.

```cpp
// Algorithm X with bitmasks: select rows covering every column EXACTLY once.
// <=64 columns; rows are masks. Returns row indices or nullopt (EXACT).
// Worst case exponential; O(columns*rows) per search node, O(columns) stack.
// Zero rows can be ignored; this is exact cover, not ordinary set cover.
// Usage: exactCover(3, {3,4,5}) returns row indices {0,1}.
#include "common.hpp"

optional<vector<int>> exactCover(int columns, const vector<ull>& rows) {
    assert(0 <= columns && columns <= 64);
    ull full = columns == 64 ? ~0ULL : (1ULL << columns)-1;
    for (ull r : rows) assert(!(r & ~full));
    vector<int> chosen;
    function<bool(ull)> dfs = [&](ull covered) {
        if (covered == full) return true;
        int best = -1, count = INT_MAX;
        for (int c = 0; c < columns; ++c) if (!(covered >> c & 1)) {
            int ways = 0;
            for (ull r : rows)
                ways += !(r & covered) && (r >> c & 1);
            if (ways < count) { count = ways; best = c; }
        }
        if (!count) return false;
        for (int i = 0; i < (int)rows.size(); ++i)
            if (!(rows[i] & covered) && (rows[i] >> best & 1)) {
                chosen.push_back(i);
                if (dfs(covered | rows[i])) return true;
                chosen.pop_back();
            }
        return false;
    };
    if (dfs(0)) return chosen;
    return nullopt;
}
```

Example usage. `exactCover(3, {3,4,5})` can select rows 0 and 1. Their masks are disjoint and cover all three columns.

9.8 Posa Rotations

Use: Search for a Hamiltonian path by extending and rotating a candidate path.
Complexity: $O(R(B+1)n)$ time and $O(n)$ space for R restarts and B steps per restart.
Pitfalls: Heuristic for simple undirected graphs. Check the closing edge separately for a cycle.
Assumptions/deps: Validate any returned path against the original graph.

```cpp
// Hamiltonian PATH heuristic for simple UNDIRECTED graphs; nullopt = not found.
// Time O(restarts*(steps+1)*n), memory O(n); steps counts extensions/rotations.
// A found path is valid; there is no general success/time guarantee.
// Reverse suffix after a pivot adjacent to endpoint. Cycles need an extra check.
// Usage: posaPath(g, 50, 20*g.size(), rng); adjacency must be symmetric.
#include "common.hpp"

optional<vector<int>> posaPath(const vector<vector<int>>& g,
                               int restarts, int steps, mt19937_64& rng) {
    int n = g.size(); assert(restarts >= 0 && steps >= 0);
    if (!n) return vector<int>{};
    while (restarts--) {
        vector<int> path{(int)pick(rng, 0, n-1)}, pos(n, -1);
        pos[path[0]] = 0;
        for (int it = 0; ; ++it) {
            if ((int)path.size() == n) return path;
            if (it == steps) break;
            int last = path.back(); vector<int> next, pivots;
            for (int u : g[last]) {
                if (pos[u] == -1) next.push_back(u);
                else if (pos[u]+2 < (int)path.size())
                    pivots.push_back(pos[u]);
            }
            if (!next.empty()) {
                int u = next[pick(rng, 0, next.size()-1)];
                pos[u] = path.size(); path.push_back(u);
            } else if (!pivots.empty()) {
                int p = pivots[pick(rng, 0, pivots.size()-1)];
                reverse(path.begin()+p+1, path.end());
                for (int i = p+1; i < (int)path.size(); ++i) pos[path[i]] = i;
            } else break;
        }
    }
    return nullopt;
}
```

Example usage. `posaPath({{1},{0,2},{1}}, 20, 100, rng)` searches for $0, 1, 2$ or its reverse.

9.9 Shuffled Window Subset Sum

Use: Search for a reachable target with packed DP on a bounded window.
Complexity: $O(tn\lceil(2W+1)/64\rceil)$ time and $O(n+W/64)$ space for t trials.
Pitfalls: Clipping at window radius W can lose solutions. A false result means not found.
Assumptions/deps: Nonnegative weights and target. A true result certifies reachability.

```cpp
// Heuristic subset-sum DECISION for nonnegative weights/target.
// true proves reachable; false means NOT FOUND (clipping may lose solutions).
```

```cpp
// Time O(trials*n*ceil((2W+1)/64)), memory O(W/64+n), with packed bitsets.
// States are signed corrections in [-W,W]. Weights/target fit signed 64-bit.
// Usage: windowSubset({4,7,9}, 11, 20, 10, rng). No witness reconstruction.
#include "common.hpp"

bool windowSubset(const vector<ll>& a, ll target, int W,
                  int trials, mt19937_64& rng) {
    assert(target >= 0 && W >= 0 && W <= (INT_MAX-1)/2 && trials >= 0);
    if (!target) return true;
    vector<ll> delta; ll base = 0;
    for (ll x : a) {
        assert(x >= 0);
        if (x <= target-base) { base += x; delta.push_back(-x); }
        else delta.push_back(x);
    }
    ll goal = target-base;
    if (!goal) return true;
    if (goal > W) return false;
    int size = 2*W+1;
    while (trials--) {
        shuffle(delta.begin(), delta.end(), rng);
        int words = (size+63LL)/64;
        vector<ull> dp(words); dp[W/64] = 1ULL << (W%64);
        for (ll x : delta) {
            if (x > 2LL*W || x < -2LL*W) continue;
            int q = abs(x)/64, b = abs(x)%64;
            if (x > 0) {
                for (int i = words-1; i >= q; --i) {
                    ull v = dp[i-q] << b;
                    if (b && i > q) v |= dp[i-q-1] >> (64-b);
                    dp[i] |= v;
                }
            } else if (x < 0) {
                for (int i = 0; i+q < words; ++i) {
                    ull v = dp[i+q] >> b;
                    if (b && i+q+1 < words) v |= dp[i+q+1] << (64-b);
                    dp[i] |= v;
                }
            }
            if (size%64) dp.back() &= (1ULL << (size%64))-1;
        }
        int at = W+(int)goal;
        if (dp[at/64] >> (at%64) & 1) return true;
    }
    return false;
}
```

Example usage. `windowSubset({4,7,9}, 11, 20, 10, rng)` finds that $4+7=11$ is reachable.

9.10 Schoning Randomized 3-SAT

Use: Search for a satisfying assignment with random restarts and literal flips.
Complexity: $O(Rnm)$ time and $O(n)$ space for R restarts.
Pitfalls: A failed search gives no UNSAT certificate. Use signed 1-based literals.
Assumptions/deps: At most three literals per clause. Check the returned assignment.

```cpp
// Randomized 3-SAT witness search; nullopt = NOT FOUND, never an UNSAT proof.
// Literal +(v+1) means x[v], -(v+1) means !x[v]; clauses have 1..3 literals.
// Time O(restarts*n*m), memory O(n). Each restart makes <=3n random flips.
// For satisfiable inputs, expected O((4/3)^n) restarts; budget may be too small.
// Usage: schoning(2, {{1,2},{-1,2}}, 100, rng); empty formula is satisfiable.
#include "common.hpp"

optional<vector<int>> schoning(int n, const vector<vector<int>>& clauses,
                               int restarts, mt19937_64& rng) {
    assert(n >= 0 && restarts >= 0);
    for (const auto& c : clauses) {
        assert(c.size() <= 3);
        if (c.empty()) return nullopt;
        for (int lit : c) assert(lit != 0 && abs((ll)lit) <= n);
    }
    if (clauses.empty()) return vector<int>(n);
    while (restarts--) {
        vector<int> a(n);
        for (int& x : a) x = pick(rng, 0, 1);
        for (ll step = 0; step <= 3LL*n; ++step) {
            int bad = -1;
            for (int i = 0; i < (int)clauses.size(); ++i) {
                bool ok = false;
                for (int lit : clauses[i])
                    ok |= a[abs(lit)-1] == (lit > 0);
                if (!ok) { bad = i; break; }
            }
            if (bad == -1) return a;
            if (step == 3LL*n) break;
            const auto& c = clauses[bad];
            int lit = c[pick(rng, 0, c.size()-1)];
            a[abs(lit)-1] ^= 1;
        }
    }
    return nullopt;
}
```

Example usage. `schoning(2, {{1,2},{-1,2}}, 100, rng)` searches for an assignment with `x[1]` true.

9.11 General Lagrange Interpolation

Use: Evaluate a polynomial of degree below n from arbitrary sample coordinates.
Complexity: $O(n^2 + n \log P)$ time and $O(n)$ extra space.
Pitfalls: Sample coordinates must be distinct modulo P. Check the optional result.
Assumptions/deps: Uses the shared prime P. Inputs are normalized before subtraction.

```cpp
// Evaluate degree < n polynomial from arbitrary samples y[i]=f(x[i]) mod HMOD.
// Time O(n^2 + n log HMOD), memory O(n) for normalized input copies.
// x coordinates must be distinct modulo HMOD; prime is fixed at 1000000007.
// Returns nullopt for empty/mismatched input or repeated x residues (even equal y).
// Usage: lagrangeGeneral({-1,2,4}, {1,4,16}, 3).value() == 9.
#include "common.hpp"

optional<ll> lagrangeGeneral(vector<ll> x, vector<ll> y, ll at) {
    if (x.empty() || x.size() != y.size()) return nullopt;
    int n = x.size(); at = hnorm(at);
    for (ll& v : x) v = hnorm(v);
    for (ll& v : y) v = hnorm(v);
    ll ans = 0;
    for (int i = 0; i < n; ++i) {
        ll num = y[i], den = 1;
        for (int j = 0; j < n; ++j) if (j != i) {
            if (x[i] == x[j]) return nullopt;
            num = num * hnorm(at-x[j]) % HMOD;
            den = den * hnorm(x[i]-x[j]) % HMOD;
        }
        ans = (ans + num*hpow(den, HMOD-2)) % HMOD;
    }
    return ans;
}
```

Example usage. `lagrangeGeneral({-1,2,4}, {1,4,16}, 3)` returns an optional containing 9.

9.12 Connected Subsets with One Centroid

Use: Count nonempty connected vertex subsets with exactly one centroid.
Complexity: $O(n^2)$ time and space. Fixed tables use about 145 MB.
Pitfalls: Standalone 1-indexed tree solution for $n \leq 3000$. Keep the reset order and stream synchronization.
Assumptions/deps: Modulo 998244353.

```cpp
// Count nonempty connected vertex subsets with exactly one centroid.
// User-supplied complete solution; formatting only. Input: t, then n and n-1 edges.
// Time O(n^2), memory O(n^2); fixed arrays use about 145 MB even for small n.
// Pitfalls: 1-indexed tree, 1<=n<=3000; recursive DFS may need more stack.
// Modulus is 998244353. g is cleared after each test; DP reset logic is retained.
#include <bits/stdc++.h>
using namespace std;
constexpr long long mod = 998244353;
int t, n, si[3005];
long long dp1[3005][3005], dp2[3005][3005], ans;
vector<int> g[3005];
void dfs1(int v, int fa) {
    for (int i = 0; i <= si[v]; i++) dp1[v][i] = dp2[v][i] = 0;
    si[v] = 1, dp1[v][1] = 1;
    for (int i : g[v]) {
        if (i == fa) continue;
        dfs1(i, v);
        for (int j = si[v]; ~j; j--) for (int k = 1; k <= si[i]; k++)
            dp1[v][j+k] = (dp1[v][j+k] + dp1[v][j]*dp1[i][k]) % mod;
        si[v] += si[i];
    }
    dp1[v][0] = 1;
    for (int i = 1; i <= si[v]; i++) ans += dp1[v][i];
}
void dfs2(int v, int fa) {
    for (int i = 1; i <= si[v]; i++) ans = (ans - dp1[v][i]*dp2[v][i]) % mod;
    for (int i : g[v]) {
        if (i == fa) continue;
        for (int j = 1; j <= si[i]; j++) dp2[i][j] = dp2[v][j-1];
        for (int j : g[v]) {
            if (j == i || j == fa) continue;
            for (int k = si[i]; ~k; k--)
                for (int l = min(si[j], si[i]-k); l; l--)
                    dp2[i][k+l] = (dp2[i][k+l] + dp2[i][k]*dp1[j][l]) % mod;
        }
        dp2[i][0] = 1, dfs2(i, v);
    }
    g[v].clear();
}
int main() {
    cin >> t;
    while (t--) {
        scanf("%d", &n);
        for (int i = 1, x, y; i < n; i++)
            scanf("%d%d", &x, &y), g[x].emplace_back(y), g[y].emplace_back(x);
        ans = 0, dfs1(1, 0), dp2[1][0] = 1, dfs2(1, 0);
        printf("%lld\n", (ans+mod) % mod);
    }
    return 0;
}
```

Example usage. Enter `1`, `3`, `1 2`, and `2 3` on separate lines. The program prints 4.

10 Appendix

10.1 Binomial (auto-extend)

Use: $C(n,k)$ with lazily grown factorial tables.
Complexity: Amortized $O(1)$ per query after growth.
Pitfalls: `mod` must be prime and `n < mod`.
Assumptions/deps: Alternative to Mod Inverse Table; pick one.

```cpp
// Factorials/inverses mod prime, auto-extending. C(n,k) is O(1) after extend.
using ll = long long;
const ll mod = 1e9 + 7;
struct Binom {
    vector<ll> fact{1}, inv{1}, invfact{1};

    void extend(ll n) {
        ll cur = fact.size() - 1;
        if (cur >= n) return;

        fact.resize(n + 1);
        inv.resize(n + 1);
        invfact.resize(n + 1);

        for (ll i = cur + 1; i <= n; i++) {
            fact[i] = fact[i - 1] * i % mod;

            if (i == 1) inv[i] = 1;
            else inv[i] = mod - mod / i * inv[mod % i] % mod;

            invfact[i] = invfact[i - 1] * inv[i] % mod;
        }
    }

    ll C(ll n, ll k) {
        if (k < 0 || k > n) return 0;
        extend(n);
        return fact[n] * invfact[k] % mod * invfact[n - k] % mod;
    }
} binom;
```

10.2 Block-Cut Tree Query Driver

Use: Answer vertex-deletion connectivity queries.
Complexity: $O(\log n)$ per query after preprocessing.
Pitfalls: Uses 0-indexed input.
Assumptions/deps: Copy with Block-Cut Tree, DSU and LCA.

```cpp
// Input: n m q; m undirected edges u v; q independent queries u v x. 0-indexed.
// Output: YES iff u and v remain connected after deleting vertex x.
// Let N = bc.tree.size()+1. Build: O(n+m log(m+1)+N log N).
// Query: O(log N); memory: O(n+m+N log N). Depends on BlockCutTree, DSU, LCA.
void solve_vertex_removal() {
    int n,m,q; cin >> n >> m >> q;
    BlockCutTree bc(n);
    DSU d(n);
    for(int i=0,u,v;i<m;++i) {
        cin >> u >> v;
        bc.addEdge(u,v); d.unite(u,v);
    }
    bc.build();
    int root=bc.tree.size();
    LCA lca(root+1);
    lca.g=bc.tree; lca.g.resize(root+1);
    for(int v=0;v<n;++v)
        if(d.find(v)==v) lca.addEdge(root,v);
    lca.build(root);
    while(q--) {
        int u,v,x; cin >> u >> v >> x;
        bool ok=d.same(u,v);
        if(ok && d.same(u,x))
            ok=lca.dist(u,x)+lca.dist(x,v)!=lca.dist(u,v);
        cout << (ok ? "YES\n" : "NO\n");
    }
}
```

10.3 Critical Cities Dominator

Use: Dominator-style critical vertices from source to sink in directed graph.
Complexity: About $O((n+m)\log n)$.
Pitfalls: Standalone problem solution, not a reusable library. Assumes sink reachable from source.
Assumptions/deps: Includes its own `main`; 1-indexed input converted to 0-index.

```cpp
#include <algorithm>
#include <cassert>
#include <cmath>
#include <cstdint>
#include <functional>
#include <iostream>
#include <vector>

// Input: n m, then m directed 1-indexed edges; assumes n is reachable from 1.
```

```cpp
// Output: count and sorted 1-indexed vertices on every directed path from 1 to n.

using std::cout;
using std::endl;
using std::vector;

// BeginCodeSnip{Tree Class for rdom}
template <typename T> class Tree {
 private:
 const int root = 0;
 const vector<int> &parents;
 const vector<T> &vals;
 const int log2dist;
 vector<vector<int>> pow2ends;
 vector<vector<T>> pow2mins;
 vector<int> depth;

 public:
 Tree(const vector<int> &parents, const vector<T> &vals)
     : parents(parents), vals(vals),
       log2dist(std::ceil(std::log2(parents.size() + 1))),
       pow2ends(parents.size(), vector<int>(log2dist + 1)),
       pow2mins(parents.size(), vector<T>(log2dist + 1)) {
   assert(parents[root] == -1);

   vector<vector<int>> children(parents.size());
   for (int n = 0; n < parents.size(); n++) {
     if (parents[n] != -1) { children[parents[n]].push_back(n); }
   }
   depth = vector<int>(parents.size());
   vector<int> frontier{root};
   while (!frontier.empty()) {
     int curr = frontier.back();
     frontier.pop_back();
     for (int n : children[curr]) {
       depth[n] = depth[curr] + 1;
       frontier.push_back(n);
     }
   }

   for (int n = 0; n < parents.size(); n++) {
     pow2mins[n][0] = vals[n];
     pow2ends[n][0] = parents[n];
   }
   for (int p = 1; p <= log2dist; p++) {
     for (int n = 0; n < parents.size(); n++) {
       int halfway = pow2ends[n][p - 1];
       if (halfway == -1) {
         pow2ends[n][p] = -1;
         pow2mins[n][p] = pow2mins[n][p - 1];
       } else {
         pow2ends[n][p] = pow2ends[halfway][p - 1];
         pow2mins[n][p] =
             std::min(pow2mins[n][p - 1], pow2mins[halfway][p - 1]);
       }
     }
   }
 }

 /**
  * @return the min value on the path from the ancestor to its descendant,
  * not including the ancestor.
  */
 T min_val(int ancestor, int desc) {
   int dist = depth[desc] - depth[ancestor];
   T ret = vals[desc];
   int at = desc;
   for (int pow = 0; pow <= log2dist; pow++) {
     if ((dist & (1 << pow)) != 0) {
       ret = std::min(ret, pow2mins[at][pow]);
       at = pow2ends[at][pow];
     }
   }
   assert(at == ancestor);
   return ret;
 }
};
// EndCodeSnip

int main() {
 int city_num;
 int flight_num;
 std::cin >> city_num >> flight_num;
 vector<vector<int>> adj(city_num);
 vector<vector<int>> rev_adj(city_num);
 for (int f = 0; f < flight_num; f++) {
   int a, b;
   std::cin >> a >> b;
   adj[--a].push_back(--b);
   rev_adj[b].push_back(a);
 }

 // Variables used for the Euler Tour
 vector<int> visit_order;
 // visit_time is initialized with INF so nodes that aren't reachable
 // during the DFS won't mess up our sdom calculation
 vector<int> visit_time(city_num, INT32_MAX);
 vector<int> visit_parent(city_num, -1);
 vector<bool> visited(city_num, false);
 std::function<void(int, int)> dfs;
 dfs = [&](int at, int prev) {
   if (visited[at]) { return; }
   visited[at] = true;
```

```
  visit_time[at] = visit_order.size();
  visit_order.push_back(at);
  visit_parent[at] = prev;
  for (int to : adj[at]) { dfs(to, at); }
};
dfs(0, -1);

// We use a function-based interface instead of a class-based one due to
// heavy reliance on previously calculated values
vector<int> dsu_parent(city_num, -1);
vector<int> dsu_min(city_num, INT32_MAX);
std::function<int(int)> find;
find = [&](int x) {
  if (dsu_parent[x] == -1) { return x; }
  if (dsu_parent[dsu_parent[x]] != -1) {
    int parent_res = find(dsu_parent[x]);
    if (visit_time[parent_res] < visit_time[dsu_min[x]]) {
      dsu_min[x] = parent_res;
    }
    dsu_parent[x] = dsu_parent[dsu_parent[x]];
  }
  assert(dsu_min[x] != INT32_MAX);
  return dsu_min[x];
};

vector<int> sdom(city_num, -1);
for (int i = visit_order.size() - 1; i > 0; i--) {
  int c = visit_order[i];
  // Iterate over all nodes with a directed edge to c
  for (int from : rev_adj[c]) {
    int find_res = find(from);
    // Take the node with the earliest visit time in the traversal
    if (sdom[c] == -1 || visit_time[find_res] < visit_time[sdom[c]]) {
      sdom[c] = find_res;
    }
  }

  // Link c to its parent in the DFS tree
  dsu_parent[c] = visit_parent[c];
  dsu_min[c] = sdom[c];
}

// Initialize the values in the tree
vector<std::pair<int, int>> sdom_times(city_num, {INT32_MAX, -1});
for (int c : visit_order) {
  if (c != 0) {
    // The tree takes the minimum of these pairs, but what we
    // really want is the node itself- therefore, we store both
    sdom_times[c] = {visit_time[sdom[c]], c};
  }
}
Tree tree(visit_parent, sdom_times);

vector<int> rdom(city_num, -1);
for (int c : visit_order) {
  if (c != 0) {
    // Use the definition of the rdom
    rdom[c] = tree.min_val(sdom[c], c).second;
  }
}

// Use the properties previously given to compute the idom
vector<int> idom(city_num, -1);
for (int c : visit_order) {
  if (c != 0) { idom[c] = rdom[c] == c ? sdom[c] : idom[rdom[c]]; }
}

// Trace the idom tree from the finish node to the start node,
// finding all dominators along the way
// NOTE: assumes city_num-1 is reachable from 0; otherwise idom[-1] UB.
vector<int> critical{0};
int at = city_num - 1;
while (at != 0) {
  critical.push_back(at);
  at = idom[at];
}

std::sort(critical.begin(), critical.end());

cout << critical.size() << '\n';
for (int i = 0; i < critical.size() - 1; i++) { cout << critical[i] + 1 << ' '; }
cout << critical.back() + 1 << endl;
}
```

10.4 Randomized Hill Climbing Skeleton

Use: Approximate optimization when exact method is hard.
Complexity: Heuristic.
Pitfalls: Risky in ICPC: tune step, time limit, random direction, and score. No correctness guarantee.
Assumptions/deps: Depends on geometry point `P` and user functions.

```
// Local search with shrinking step (hill climbing / pattern search).
// Good for: approximate geometric optimization (e.g. point minimizing max
// distance), unimodal-ish continuous functions. Tune step count to time limit.
// For true simulated annealing also accept worse moves with probability
// exp((score(cur)-score(nxt))/temp), temp decaying like step.
P cur = start;
double step = initial_step; // e.g. max coordinate range

```

```
while (step > 1e-9) {
    P nxt = cur + random_direction() * step;
    if (score(nxt) < score(cur))
        cur = nxt;
    step *= 0.98; // slower decay (0.999) = better quality, more time
}
```