

BV50 Automated Ball Valve Assembly

SKU / Model Number: BV50-DN100-SS

Manufacturer: TruFlow Valves Ltd

Category: Valves | ETIM Code: EC002440

PRODUCT OVERVIEW

The BV50 is a full-bore 2-piece ball valve with electric quarter-turn actuator for on/off isolation service in process piping. Features anti-blowout stem, fire-safe design, and fail-safe spring return.

TECHNICAL SPECIFICATIONS

Valve Type	Full-bore, 2-piece ball
Size	DN100 (4 inch)
Bore Diameter	100 mm
Pressure Class	PN 25 / ANSI 150
Cv	760
Leakage	Zero leakage (Class VI)
Actuator Torque	200 Nm

ELECTRICAL RATINGS

Actuator Supply	24 V DC or 230 V AC
Motor Power	40 W
Operating Time	15 seconds (90 deg)
Limit Switches	2x SPDT, adjustable
Heater	Optional anti-condensation

DIMENSIONS & MECHANICAL

Face-to-Face	229 mm
Flange Diameter	229 mm (EN 1092-1)
Height with Actuator	380 mm
Shaft	ISO 5211 F10
Weight	28 kg (with actuator)

OPERATING CONDITIONS

Temperature Range	-20 to 200 deg C
Max Pressure	25 bar at 20 deg C
Ambient Temperature	-20 to 60 deg C
Cycle Life	> 100,000 cycles
IP Rating	IP67

MATERIALS OF CONSTRUCTION

Body	CF8M (316 Stainless Steel)
Ball	316 SS, chrome plated
Seats	Reinforced PTFE
Stem	316 SS with blowout proof
Actuator Housing	Powder-coated Aluminum

PERFORMANCE DATA / SELECTION TABLE

Size	Cv	Torque (Nm)	Weight (kg)	Face-to-Face (mm)
DN25	135	20	6.5	108
DN50	320	50	12.0	178
DN80	570	120	20.5	203
DN100	760	200	28.0	229

CERTIFICATIONS & APPROVALS

CE (PED) | ATEX | API 608 | API 607 Fire-safe | TA-Luft | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

This document is the property of TruFlow Valves Ltd. Specifications are subject to change without notice. For the latest revision, visit www.truflowvalvesltd.com. Document revision: Rev. B | Date: 2025-01