

CB400 Molded Case Circuit Breaker

SKU / Model Number: CB400-3P-250A

Manufacturer: ElectroPower Systems

Category: Electrical | ETIM Code: EC000082

PRODUCT OVERVIEW

The CB400 is an IEC 60947-2 compliant MCCB for protection of electrical circuits against overload and short-circuit currents. Features thermal-magnetic trip unit with adjustable settings and front-accessible wiring.

TECHNICAL SPECIFICATIONS

Frame Size	400 A
Rated Current (In)	250 A (adjustable 200-250 A)
Poles	3-pole
Breaking Capacity (Icu)	50 kA at 415 V AC
Service Breaking (Ics)	100% Icu
Trip Unit	Thermal-Magnetic, adjustable
Utilization Category	A (non-selective)

ELECTRICAL RATINGS

Rated Voltage (Ue)	690 V AC
Insulation Voltage (Ui)	800 V
Impulse Voltage (Uimp)	8 kV
Frequency	50/60 Hz
Auxiliary Contacts	1 NO + 1 NC (standard)

DIMENSIONS & MECHANICAL

Width	140 mm (3P)
Height	260 mm
Depth	103 mm
Mounting	DIN rail / direct
Weight	3.8 kg

OPERATING CONDITIONS

Ambient Temperature	-25 to 70 deg C
Storage Temperature	-40 to 85 deg C
Altitude	Up to 2000 m
Mechanical Life	20,000 operations
Electrical Life	10,000 operations

MATERIALS OF CONSTRUCTION

Housing	Glass-reinforced Polyamide PA6.6
Contacts	Silver alloy
Arc Chamber	Ceramic plates
Terminals	Tinned copper
Operating Mechanism	Toggle, stored energy

PERFORMANCE DATA / SELECTION TABLE

Voltage	Icu (kA)	Ics (kA)	Icw (1s)
230 V AC	65	65	---
415 V AC	50	50	---
500 V AC	36	36	---
690 V AC	20	20	---

CERTIFICATIONS & APPROVALS

IEC 60947-2 | CE | UL 489 | CSA C22.2 | CCC | KEMA

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of ElectroPower Systems. Specifications are subject to change without notice. For the latest revision, visit www.electropowersystems.com.
Document revision: Rev. B | Date: 2025-01*