

CP300 Horizontal Centrifugal Process Pump

SKU / Model Number: CP300-65-40-200

Manufacturer: HydroFlow Engineering

Category: Pumps | ETIM Code: EC002620

PRODUCT OVERVIEW

The CP300 is an ISO 5199 / ISO 2858 compliant end-suction centrifugal pump for chemical processing, water treatment, and HVAC applications. Back pull-out design for easy maintenance without disturbing piping.

TECHNICAL SPECIFICATIONS

Pump Type	End-suction, single stage
Flow Rate	65 m3/h (at BEP)
Total Head	40 m
Impeller Diameter	200 mm
Efficiency	78% at BEP
NPSH Required	2.5 m
Specific Speed	32 (metric)

ELECTRICAL RATINGS

Motor Power	15 kW
Motor Speed	2960 RPM (2-pole, 50 Hz)
Motor Voltage	400 V AC, 3-phase
Motor Efficiency	IE3 (93.0%)
Starting Method	DOL / Star-Delta / VFD

DIMENSIONS & MECHANICAL

Suction	DN80 (PN16 flange)
Discharge	DN65 (PN16 flange)
Baseplate Length	1200 mm
Overall Height	450 mm
Weight (dry)	180 kg (pump + motor)

OPERATING CONDITIONS

Fluid Temperature	-30 to 140 deg C
Max Working Pressure	16 bar
Ambient Temperature	-20 to 45 deg C
Min Flow	25% of BEP
Max Solids	< 5% by weight

MATERIALS OF CONSTRUCTION

Casing	GGG-40.3 Ductile Iron
Impeller	316L Stainless Steel
Shaft	AISI 4140 alloy steel
Wear Rings	Duplex SS 2205
Mechanical Seal	SiC/SiC/FKM (EN 12756)

PERFORMANCE DATA / SELECTION TABLE

Flow (m3/h)	Head (m)	Power (kW)	NPSH-r (m)	Eff. (%)
20	48	6.5	1.5	55
40	45	10.2	2.0	72
65	40	14.5	2.5	78
80	35	15.0	3.2	74
100	26	14.8	4.5	65

CERTIFICATIONS & APPROVALS

CE | ATEX Zone 2 | ISO 5199 | ISO 2858 | API 610 11th Ed. | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of HydroFlow Engineering. Specifications are subject to change without notice. For the latest revision, visit www.hydroflowengineering.com.
Document revision: Rev. B | Date: 2025-01*