

CV200 Globe Control Valve

SKU / Model Number: CV200-DN80-PN40
Manufacturer: ValveTech International
Category: Valves | ETIM Code: EC002450

PRODUCT OVERVIEW

The CV200 is a pneumatically actuated globe control valve for precision throttling of steam, water, and chemical process fluids. Features equal percentage or linear flow characteristics, and integral positioner.

TECHNICAL SPECIFICATIONS

Valve Type	Single-seat Globe
Nominal Size	DN80 (3 inch)
Pressure Rating	PN 40 / ANSI 300
Cv (Flow Coefficient)	120
Rangeability	50:1
Leakage Class	ANSI/FCI 70-2 Class IV
Flow Characteristic	Equal Percentage

ELECTRICAL RATINGS

Positioner Input	4-20 mA
Positioner Feedback	4-20 mA
Supply Air	1.4 to 7 bar
Communication	HART / Foundation Fieldbus
Solenoid Valve	24 V DC, ATEX approved

DIMENSIONS & MECHANICAL

Face-to-Face	310 mm (EN 558-1)
Flange Type	EN 1092-1, Form B1
Overall Height	580 mm (with actuator)
Actuator Size	Size 60 diaphragm
Weight	85 kg (complete assembly)

OPERATING CONDITIONS

Temperature Range	-29 to 425 deg C
Max Differential Pressure	25 bar
Ambient Temperature	-20 to 60 deg C
Shutoff Pressure	40 bar
Cycle Life	> 1,000,000 cycles

MATERIALS OF CONSTRUCTION

Body	WCB Carbon Steel (A216)
Trim	316 Stainless Steel
Seat Ring	Stellite 6 overlay
Packing	PTFE V-ring
Gasket	Spiral Wound SS/Graphite

PERFORMANCE DATA / SELECTION TABLE

Travel %	Cv	Flow %	Gain
10%	2.4	2%	0.20
25%	9.5	8%	0.32
50%	38	32%	0.63
75%	76	63%	1.00
100%	120	100%	1.58

CERTIFICATIONS & APPROVALS

CE (PED 2014/68/EU) | ATEX | SIL 3 | NACE MR0175 | Fire-safe API 607

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of ValveTech International. Specifications are subject to change without notice. For the latest revision, visit www.valvetechinternational.com.
Document revision: Rev. B | Date: 2025-01*