

DP80 Air-Operated Double Diaphragm Pump

SKU / Model Number: DP80-2IN-PP

Manufacturer: PumpWorks Industrial

Category: Pumps | ETIM Code: EC002630

PRODUCT OVERVIEW

The DP80 AODD pump is a self-priming, seal-less pump for handling abrasive, viscous, and shear-sensitive fluids. Dry-run capable with no damage. Ideal for chemical transfer, paint, slurries, and waste handling.

TECHNICAL SPECIFICATIONS

Max Flow Rate	570 L/min
Max Head	70 m
Max Suction Lift	6 m (dry)
Solids Handling	Up to 6 mm
Max Viscosity	50,000 cP
Self-Priming	Yes, dry & wet
Deadhead Capable	Yes

ELECTRICAL RATINGS

Air Supply	1 to 7 bar compressed air
Air Consumption	Max 800 NL/min
Air Inlet	G 1/2 BSP
Air Valve Type	Spool valve, unlubricated
(No electrical power required)	---

DIMENSIONS & MECHANICAL

Inlet / Outlet	2 inch BSP / Flanged
Height	620 mm
Width	380 mm
Depth	280 mm
Weight (dry)	22 kg

OPERATING CONDITIONS

Fluid Temperature	-40 to 120 deg C
Ambient Temperature	-40 to 60 deg C
Max Cycles	350 CPM
Noise Level	< 78 dB(A)
IP Rating	Inherently safe (no electricity)

MATERIALS OF CONSTRUCTION

Fluid Housing	Polypropylene (PP)
Diaphragms	Santoprene (standard)
Ball Valves	Polypropylene
Ball Seats	Polypropylene
Air Section	Aluminum alloy

PERFORMANCE DATA / SELECTION TABLE

Air Pressure	Flow (L/min)	Cycles/min	Air Use (NL/min)
1 bar	95	50	150
3 bar	280	150	400
5 bar	430	250	620
7 bar	570	350	800

CERTIFICATIONS & APPROVALS

CE | ATEX II 2G/D | FDA 21 CFR 177 | 3-A Sanitary | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of PumpWorks Industrial. Specifications are subject to change without notice. For the latest revision, visit www.pumpworksindustrial.com.
Document revision: Rev. B | Date: 2025-01*