

FS50 Electromagnetic Flow Meter

SKU / Model Number: FS50-DN50-FL

Manufacturer: FlowMaster Corp

Category: Sensors | ETIM Code: EC001892

PRODUCT OVERVIEW

The FS50 electromagnetic flow meter provides precise volumetric flow measurement of conductive liquids. Features integral or remote-mount transmitter, empty pipe detection, and bi-directional flow measurement capability.

TECHNICAL SPECIFICATIONS

Nominal Size	DN50 (2 inch)
Flow Range	0.5 to 10 m/s
Accuracy	+/- 0.2% of reading
Repeatability	+/- 0.1%
Conductivity Minimum	> 5 microS/cm
Liner Material	PTFE
Electrode Material	Hastelloy C-276

ELECTRICAL RATINGS

Supply Voltage	100 to 240 V AC, 50/60 Hz
Power Consumption	15 W
Output 1	4-20 mA / HART
Output 2	Pulse / Frequency
Communication	Modbus RTU (RS485)

DIMENSIONS & MECHANICAL

Face-to-Face Length	200 mm (ISO 13359)
Flange Rating	PN 16 / ANSI 150
Overall Height	310 mm
Transmitter Housing	Aluminum, IP67
Weight	12.5 kg

OPERATING CONDITIONS

Process Temperature	-20 to 150 deg C
Ambient Temperature	-25 to 60 deg C
Max Pressure	16 bar
Ingress Protection	IP67 / IP68
Vibration	IEC 60068-2-6

MATERIALS OF CONSTRUCTION

Tube	316L Stainless Steel
Liner	PTFE
Flanges	Carbon Steel, epoxy coated
Electrodes	Hastelloy C-276
Housing	Powder-coated Aluminum

PERFORMANCE DATA / SELECTION TABLE

DN Size	Flow Range (m3/h)	Length (mm)	Weight (kg)
DN25	0.35 - 35	200	8.2
DN50	1.4 - 140	200	12.5
DN80	3.6 - 360	200	18.0
DN100	5.6 - 565	250	24.5
DN150	12.7 - 1270	300	38.0

CERTIFICATIONS & APPROVALS

CE | MCERTS | OIML R49 | ATEX Zone 1 | RoHS | REACH

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

This document is the property of FlowMaster Corp. Specifications are subject to change without notice. For the latest revision, visit www.flowmastercorp.com. Document revision: Rev. B | Date: 2025-01