

GP20 External Gear Pump

SKU / Model Number: GP20-16-CI
Manufacturer: FluidPower Systems
Category: Pumps | ETIM Code: EC002625

PRODUCT OVERVIEW

The GP20 is a positive displacement external gear pump for hydraulic power units, lubrication systems, and fuel transfer. Features hardened steel gears, pressure-loaded bearings, and bi-directional operation capability.

TECHNICAL SPECIFICATIONS

Displacement	16 cc/rev
Max Flow	24 L/min at 1500 RPM
Max Continuous Pressure	250 bar
Max Intermittent Pressure	280 bar
Speed Range	500 to 3500 RPM
Volumetric Efficiency	> 95% at 200 bar
Noise Level	68 dB(A) at 200 bar

ELECTRICAL RATINGS

Drive Type	Shaft-driven (external motor)
Shaft Rotation	CW or CCW (bi-directional)
Shaft Coupling	SAE A 2-bolt
Recommended Motor	5.5 kW at 250 bar
---	---

DIMENSIONS & MECHANICAL

Port Size	G 3/4 SAE
Shaft Diameter	18 mm (keyed)
Length	132 mm
Width	89 mm
Weight	5.8 kg

OPERATING CONDITIONS

Fluid Temperature	-25 to 80 deg C
Viscosity Range	10 to 300 cSt
Fluid Type	Mineral Oil ISO VG 32-68
Filtration	25 micron recommended
Max Inlet Vacuum	-0.3 bar

MATERIALS OF CONSTRUCTION

Housing	Grey Cast Iron GG25
Gears	20MnCr5 carburized steel
Bearings	Aluminum bronze
Shaft Seal	FKM lip seal
Ports	SAE O-ring boss

PERFORMANCE DATA / SELECTION TABLE

Displacement (cc)	Max Flow (L/min)	Max Pressure (bar)	Weight (kg)
8	12	250	4.2
12	18	250	4.8
16	24	250	5.8
20	30	250	6.5
25	37.5	230	7.2

CERTIFICATIONS & APPROVALS

CE | ISO 4413 | DNV-GL | RINA | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of FluidPower Systems. Specifications are subject to change without notice. For the latest revision, visit www.fluidpowersystems.com.
Document revision: Rev. B | Date: 2025-01*