

HC16 Heavy-Duty Industrial Connector

SKU / Model Number: HC16-24P-M25
Manufacturer: ConnectPro Industries
Category: Connectors | ETIM Code: EC001024

PRODUCT OVERVIEW

The HC16 is a modular heavy-duty rectangular connector system for machine-to-cabinet connections. Combines power, signal, and data contacts in a single housing with quick-lock mechanism. EN 61984 compliant.

TECHNICAL SPECIFICATIONS

Contact Configuration	24 poles (16A)
Rated Current	16 A per contact
Rated Voltage	500 V AC / 600 V DC
Insulation Resistance	> 10 ⁹ ohm
Dielectric Strength	3000 V AC / 1 min
Mating Cycles	> 500
Wire Range	0.5 to 2.5 mm ²

ELECTRICAL RATINGS

Contact Resistance	< 2 mohm
Max Frequency	Up to 10 MHz (data contacts)
Creepage Distance	> 8 mm
Clearance	> 6 mm
Grounding	PE contact, first-make/last-break

DIMENSIONS & MECHANICAL

Housing Size	10B (single lever)
Insert Size	Han 24B
Cable Entry	M25
Hood Dimensions	104 x 54 mm
Weight	450 g (complete set)

OPERATING CONDITIONS

Temperature Range	-40 to 125 deg C
IP Rating	IP65 (mated)
Humidity	100% RH
Salt Spray	500 hours (IEC 60068-2-52)
Vibration	IEC 60068-2-6 (10g)

MATERIALS OF CONSTRUCTION

Housing	Die-cast Aluminum, powder coated
Inserts	PC + GF, UL94 V-0
Contacts	CuSn with Ag plating
Gasket	Silicone
Locking	Single lever, SS spring

PERFORMANCE DATA / SELECTION TABLE

Pin Count	Current (A)	Housing Size	Cable Entry
6 poles	16 A	6B	M20
16 poles	16 A	16B	M25
24 poles	16 A	24B	M25
6+12+PE	40A+16A	16B	M32

CERTIFICATIONS & APPROVALS

IEC 61984 | CE | UL | CSA | EAC | CCC | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of ConnectPro Industries. Specifications are subject to change without notice. For the latest revision, visit www.connectproindustries.com.
Document revision: Rev. B | Date: 2025-01*