

IM750 Three-Phase Induction Motor

SKU / Model Number: IM750-IE4-160M

Manufacturer: EuroMotors AG

Category: Motors | ETIM Code: EC001840

PRODUCT OVERVIEW

The IM750 is an IE4 Super Premium Efficiency three-phase squirrel cage induction motor conforming to IEC 60034. Designed for continuous duty operation in fans, pumps, and compressor applications with maximum energy savings.

TECHNICAL SPECIFICATIONS

Rated Power	7.5 kW
Efficiency Class	IE4 (IEC 60034-30-1)
Efficiency at Full Load	93.6%
Power Factor	0.87
Slip	1.7%
Starting Torque	2.5x rated
Starting Current	6.8x rated

ELECTRICAL RATINGS

Rated Voltage	400 V AC, 3-phase, 50 Hz
Rated Current	14.2 A
Frequency Range	0 to 87 Hz (with VFD)
Winding Connection	Delta 400 V / Star 690 V
Insulation	Class F, thermal Class B rise

DIMENSIONS & MECHANICAL

Frame Size	160M (IEC)
Shaft Height	160 mm
Shaft Diameter	42 mm
Overall Length	560 mm
Weight	68 kg

OPERATING CONDITIONS

Ambient Temperature	-20 to 40 deg C
Altitude	Up to 1000 m
Duty Cycle	S1 (Continuous)
Noise Level	< 65 dB(A)
IP Rating	IP55

MATERIALS OF CONSTRUCTION

Frame	Cast Iron GG25
Rotor	Copper die-cast
Bearings	6309-2Z / 6209-2Z
Fan Cover	Sheet Steel
Terminal Box	Cast Iron, IP55

PERFORMANCE DATA / SELECTION TABLE

Load %	Current (A)	Efficiency %	Power Factor	Speed (RPM)
25%	6.8	89.2	0.52	1490
50%	8.9	92.8	0.71	1485
75%	11.5	93.5	0.82	1478
100%	14.2	93.6	0.87	1470
125%	17.8	93.0	0.89	1460

CERTIFICATIONS & APPROVALS

CE | IEC 60034 | EISA | NEMA Premium | CSA | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

This document is the property of EuroMotors AG. Specifications are subject to change without notice. For the latest revision, visit www.euromotorsag.com. Document revision: Rev. B | Date: 2025-01