

LS20 Heavy-Duty Limit Switch

SKU / Model Number: LS20-RL-SPDT
Manufacturer: SwitchMaster Industrial
Category: Switches | ETIM Code: EC000524

PRODUCT OVERVIEW

The LS20 is a heavy-duty enclosed limit switch for position detection in conveyors, cranes, presses, and machine tools. Features adjustable roller lever, snap-action contacts, and IP67 die-cast aluminum housing.

TECHNICAL SPECIFICATIONS

Contact Configuration	1 NO + 1 NC (SPDT)
Rated Current (AC-15)	10 A at 240 V AC
Rated Current (DC-13)	4 A at 24 V DC
Mechanical Life	> 30 million operations
Electrical Life	> 2 million at rated load
Operating Force	3.5 N
Over-travel	60 degrees

ELECTRICAL RATINGS

Max Voltage	500 V AC / 300 V DC
Min Switching Load	10 mA at 5 V DC
Short-circuit Rating	1000 A (with 10 A fuse)
Pollution Degree	3
Impulse Voltage	4 kV

DIMENSIONS & MECHANICAL

Body Size	40 x 44 x 120 mm
Lever Length	Adjustable 37-92 mm
Roller Diameter	20 mm
Cable Entry	M20 x 1.5
Weight	350 g

OPERATING CONDITIONS

Temperature Range	-25 to 70 deg C
IP Rating	IP67
Vibration	IEC 60068-2-6 (10g)
Shock	IEC 60068-2-27 (30g)
Corrosion	Salt spray 200 hours

MATERIALS OF CONSTRUCTION

Body	Die-cast Aluminum, chromate coated
Cover	Die-cast Aluminum
Lever	Stainless Steel
Roller	Glass-filled Nylon
Gasket	Silicone rubber

PERFORMANCE DATA / SELECTION TABLE

Actuator	Travel (deg)	Force (N)	Application
Roller lever	25-90	3.5	Conveyor end-stop
Adjustable rod	25-90	2.5	Door interlock
Spring wire	25-90	1.5	Flexible detection
Cross roller	25-90	5.0	Heavy-duty cam

CERTIFICATIONS & APPROVALS

IEC 60947-5-1 | CE | UL | CSA | CCC | ATEX Zone 22 | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of SwitchMaster Industrial. Specifications are subject to change without notice. For the latest revision, visit www.switchmasterindustrial.com.
Document revision: Rev. B | Date: 2025-01*