

PB22 Industrial Pushbutton Switch

SKU / Model Number: PB22-22MM-ILL-GR

Manufacturer: PanelPro Components

Category: Switches | ETIM Code: EC000505

PRODUCT OVERVIEW

The PB22 is a 22 mm metal-body illuminated pushbutton for industrial control panels. Features modular contact blocks, multiple LED colors, and IP67 front-face protection. Conforms to IEC 60947-5-1.

TECHNICAL SPECIFICATIONS

Cutout Diameter	22.3 mm (22 mm standard)
Contact Configuration	1 NO + 1 NC (modular)
Rated Current	10 A at 240 V AC
Illumination	Integrated LED, multi-voltage
LED Colors	Green, Red, Amber, Blue, White
Mechanical Life	> 10 million operations
Operating Force	5 N

ELECTRICAL RATINGS

LED Voltage	12-240 V AC/DC (universal)
LED Current	< 20 mA
Max Voltage	600 V AC
Min Switching Load	5 mA at 12 V
Terminal Type	Screw (M3.5) or spring-cage

DIMENSIONS & MECHANICAL

Bezel Diameter	30 mm
Depth behind panel	42 mm (with contacts)
Panel Thickness	1 to 6 mm
Mounting	Threaded ring, rear mount
Weight	45 g

OPERATING CONDITIONS

Temperature Range	-25 to 70 deg C
IP Rating	IP67 (front), IP20 (rear)
Vibration	IEC 60068-2-6
Shock	IEC 60068-2-27
UV Resistance	UL 746C

MATERIALS OF CONSTRUCTION

Bezel	Stainless Steel 304, brushed
Actuator	PA66, chrome plated
Lens	Polycarbonate, diffused
Body	PA66, UL94 V-0
Contacts	Silver alloy (AgNi)

PERFORMANCE DATA / SELECTION TABLE

Type	Color	Contacts	Function
Momentary	Green	1 NO	Start / Acknowledge
Momentary	Red	1 NC	Stop / E-Stop
Maintained	Amber	1 NO+1 NC	Selector
Illuminated	Blue	1 NO	Status indicator

CERTIFICATIONS & APPROVALS

IEC 60947-5-1 | CE | UL | CSA | CCC | ATEX | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

This document is the property of PanelPro Components. Specifications are subject to change without notice. For the latest revision, visit www.panelprocomponents.com. Document revision: Rev. B | Date: 2025-01