

PLC200 Compact Programmable Logic Controller

SKU / Model Number: PLC200-16DI-12DO
Manufacturer: AutoLogic Technologies
Category: Controllers | ETIM Code: EC001185

PRODUCT OVERVIEW

The PLC200 is a compact PLC for small to medium automation applications including packaging machines, material handling, and building automation. Features integrated I/O, Ethernet/IP, and web-based programming.

TECHNICAL SPECIFICATIONS

CPU	ARM Cortex-A9, 800 MHz
Program Memory	4 MB
Data Memory	2 MB
Digital Inputs	16 x 24 V DC (sink/source)
Digital Outputs	12 x relay (2 A)
Analog Inputs	4 x 0-10 V / 4-20 mA
Scan Time	< 1 ms per 1000 instructions

ELECTRICAL RATINGS

Supply Voltage	24 V DC (18-32 V DC)
Power Consumption	12 W max
Communication	2x Ethernet/IP, 1x RS-485
Protocols	Modbus TCP/RTU, EtherNet/IP, MQTT
USB	Mini-USB for programming

DIMENSIONS & MECHANICAL

Width	110 mm (6 modules)
Height	100 mm
Depth	75 mm
Mounting	35 mm DIN rail
Weight	320 g

OPERATING CONDITIONS

Operating Temperature	-20 to 60 deg C
Storage Temperature	-40 to 85 deg C
Humidity	5 to 95% RH
Vibration	IEC 60068-2-6
IP Rating	IP20

MATERIALS OF CONSTRUCTION

Housing	PC/ABS blend, UL94 V-0
Connectors	Pluggable spring terminals
PCB	Multi-layer FR4
LED Indicators	Per-channel status LEDs
RTC Battery	CR2032 lithium (replaceable)

PERFORMANCE DATA / SELECTION TABLE

I/O Type	Channels	Voltage	Response Time
DI	16	24 V DC	< 1 ms
DO (relay)	12	250 V AC / 30 V DC	8 ms
AI (voltage)	4	0-10 V	1 ms / ch
AI (current)	4	4-20 mA	1 ms / ch

CERTIFICATIONS & APPROVALS

IEC 61131-2 | CE | UL 508 | CSA | KC | RoHS | cULus

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of AutoLogic Technologies. Specifications are subject to change without notice. For the latest revision, visit www.autologicttechnologies.com.
Document revision: Rev. B | Date: 2025-01*