

PS100 Industrial Pressure Transmitter

SKU / Model Number: PS100-420-SS

Manufacturer: SensorTech Industries

Category: Sensors | ETIM Code: EC001184

PRODUCT OVERVIEW

The PS100 is a high-accuracy piezoelectric pressure transmitter designed for demanding industrial process control applications. It features a flush-mount stainless steel diaphragm, 4-20 mA output, and HART protocol compatibility.

TECHNICAL SPECIFICATIONS

Measurement Range	0 to 600 bar
Output Signal	4-20 mA (2-wire)
Accuracy	+/- 0.1% of full scale
Response Time	< 5 ms
Overpressure Limit	1.5x rated pressure
Long-term Stability	< 0.1% FS / year
Turn-down Ratio	100:1

ELECTRICAL RATINGS

Supply Voltage	10 to 36 V DC
Power Consumption	< 0.8 W
Loop Resistance	0 to 1300 ohm
Isolation Voltage	500 V AC
EMC Protection	EN 61326-1

DIMENSIONS & MECHANICAL

Body Diameter	27 mm
Overall Length	142 mm
Process Connection	G 1/2 male
Electrical Connection	M12x1 4-pin connector
Weight	240 g

OPERATING CONDITIONS

Operating Temperature	-40 to 125 deg C
Storage Temperature	-50 to 150 deg C
Humidity	0 to 100% RH
Vibration Resistance	20 g (10 to 2000 Hz)
Shock Resistance	100 g / 11 ms

MATERIALS OF CONSTRUCTION

Wetted Parts	316L Stainless Steel
Diaphragm	Hastelloy C-276
Seals	FKM (Viton)
Housing	316 Stainless Steel
Cable Gland	Nickel-plated Brass

PERFORMANCE DATA / SELECTION TABLE

Parameter	Min	Typical	Max	Unit
Zero Offset	-0.05	0	0.05	% FS
Span Error	-0.1	0	0.1	% FS
Linearity	-0.05	---	0.05	% FS
Hysteresis	---	0.02	0.05	% FS
Temp. Effect Zero	-0.02	---	0.02	%FS/K

CERTIFICATIONS & APPROVALS

CE | ATEX Zone 0 | IECEx | SIL 2/3 | RoHS | REACH

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of SensorTech Industries. Specifications are subject to change without notice. For the latest revision, visit www.sensortechindustries.com.
Document revision: Rev. B | Date: 2025-01*