

PSW40 Electronic Pressure Switch

SKU / Model Number: PSW40-400B-G14
Manufacturer: PresSafe Technologies
Category: Switches | ETIM Code: EC001312

PRODUCT OVERVIEW

The PSW40 is a programmable electronic pressure switch with analog output and IO-Link for hydraulic and pneumatic systems. Features OLED display, 2 switch outputs, and teach-in function.

TECHNICAL SPECIFICATIONS

Pressure Range	0 to 400 bar
Switching Output	2x PNP/NPN (programmable)
Analog Output	4-20 mA (scalable)
Accuracy	+/- 0.5% FS (BFSL)
Burst Pressure	1200 bar
Communication	IO-Link V1.1
Response Time	< 2 ms

ELECTRICAL RATINGS

Supply Voltage	15 to 36 V DC
Current Consumption	< 100 mA
Switch Output Current	250 mA max
Short-circuit Protection	Yes (auto-recovery)
Connector	M12 x 1, 5-pin

DIMENSIONS & MECHANICAL

Process Connection	G 1/4 male
Body Diameter	30 mm
Length	76 mm
Display	OLED, 128x64 pixel
Weight	85 g

OPERATING CONDITIONS

Medium Temperature	-25 to 85 deg C
Ambient Temperature	-25 to 70 deg C
IP Rating	IP65 / IP67
EMC	EN 61326-1
Shock / Vibration	100g / 20g

MATERIALS OF CONSTRUCTION

Body	316L Stainless Steel
Diaphragm	316L Stainless Steel
Process Seal	FKM (Viton)
Display Window	PMMA
Connector	PA66, nickel-plated brass

PERFORMANCE DATA / SELECTION TABLE

Range (bar)	Accuracy	Burst (bar)	Process Connection
-1 to 10	+/- 0.5%	30	G 1/4
0 to 25	+/- 0.5%	75	G 1/4
0 to 100	+/- 0.5%	300	G 1/4
0 to 250	+/- 0.5%	750	G 1/4
0 to 400	+/- 0.5%	1200	G 1/4

CERTIFICATIONS & APPROVALS

CE | UL | CSA | IO-Link certified | RoHS | REACH

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of PresSafe Technologies. Specifications are subject to change without notice. For the latest revision, visit www.pressafetechnologies.com.
Document revision: Rev. B | Date: 2025-01*