

RL50 Universal Industrial Relay

SKU / Model Number: RL50-4CO-24DC

Manufacturer: SwitchTech Automation

Category: Electrical | ETIM Code: EC000560

PRODUCT OVERVIEW

The RL50 is a compact plug-in industrial relay with 4 changeover contacts for PLC output switching, control panel design, and safety interlock circuits. Features LED indicator, test button, and lockable test position.

TECHNICAL SPECIFICATIONS

Contact Configuration	4 CO (4PDT)
Rated Current	6 A (resistive, 250 V AC)
Max Switching Voltage	400 V AC / 60 V DC
Contact Material	AgNi + Au flash
Mechanical Life	> 10 million operations
Electrical Life	> 100,000 at rated load
Operate Time	< 15 ms

ELECTRICAL RATINGS

Coil Voltage	24 V DC
Coil Power	1.0 W
Pick-up Voltage	> 70% of Un
Drop-out Voltage	< 10% of Un
Coil Suppression	Integral free-wheel diode

DIMENSIONS & MECHANICAL

Relay Width	27 mm
Height	79 mm
Depth	35 mm
Socket	14-pin, DIN rail mount
Weight	65 g (relay + socket)

OPERATING CONDITIONS

Ambient Temperature	-40 to 60 deg C
Humidity	35 to 85% RH
Vibration	10 to 55 Hz, 0.75 mm
Shock	30 g / 11 ms
Pollution Degree	2

MATERIALS OF CONSTRUCTION

Housing	Transparent PA66, UL94 V-0
Contacts	AgNi with gold flash
Coil Former	PBT, UL94 V-0
Base Socket	PA66, black
Terminals	Tin-plated brass

PERFORMANCE DATA / SELECTION TABLE

Load Type	Voltage	Current	Cycles
Resistive	250 V AC	6 A	100,000
Inductive (cos 0.4)	250 V AC	3 A	100,000
Motor (AC-3)	400 V AC	2 A	50,000
Lamp	250 V AC	6 A	10,000
DC Resistive	30 V DC	6 A	100,000

CERTIFICATIONS & APPROVALS

IEC 61810-1 | CE | UL | CSA | CCC | VDE | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of SwitchTech Automation. Specifications are subject to change without notice. For the latest revision, visit www.switchtechautomation.com.
Document revision: Rev. B | Date: 2025-01*