

RV25 Spring-Loaded Safety Relief Valve

SKU / Model Number: RV25-DN40-FL

Manufacturer: SafeGuard Valves Inc

Category: Valves | ETIM Code: EC002470

PRODUCT OVERVIEW

The RV25 is an ASME certified spring-loaded safety relief valve for overpressure protection in steam, gas, and liquid service. Features full nozzle design, top-guided disc, and blowdown ring adjustment.

TECHNICAL SPECIFICATIONS

Type	Full Nozzle, Spring Loaded
Inlet Size	DN40 (1-1/2 inch)
Outlet Size	DN65 (2-1/2 inch)
Set Pressure Range	0.5 to 40 bar
Overpressure	10% (gas) / 25% (liquid)
Blowdown	Adjustable, 5-15%
Capacity Factor	Kd = 0.975 (gas), 0.65 (liquid)

ELECTRICAL RATINGS

(No electrical components)	---
Lifting Lever	Plain or packed, optional
Position Indicator	Available as option
---	---
---	---

DIMENSIONS & MECHANICAL

Inlet Flange	DN40 PN 40 (EN 1092-1)
Outlet Flange	DN65 PN 16 (EN 1092-1)
Overall Height	380 mm
Lift	12 mm
Weight	18 kg

OPERATING CONDITIONS

Temperature Range	-196 to 560 deg C
Max Backpressure	10% of set pressure
Service	Steam, Gas, Liquid
Seat Tightness	API 527 / EN ISO 4126-1
Spring Range	Adjustable +/- 5%

MATERIALS OF CONSTRUCTION

Body	A216 WCB Carbon Steel
Nozzle	A182 F316 Stainless Steel
Disc	A182 F316 + Stellite facing
Spring	A231 Chrome Vanadium Steel
Bonnet	A216 WCB Carbon Steel

PERFORMANCE DATA / SELECTION TABLE

Set Pressure	Orifice	Capacity (kg/h)	Spring Color
5 bar	D (orifice)	2400	Yellow
10 bar	D (orifice)	4800	Blue
20 bar	D (orifice)	9600	Red
40 bar	D (orifice)	19200	Silver

CERTIFICATIONS & APPROVALS

ASME Section VIII | CE (PED) | API 526 | NACE MR0175 | ATEX | National Board Certified

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

This document is the property of SafeGuard Valves Inc. Specifications are subject to change without notice. For the latest revision, visit www.safeguardvalvesinc.com. Document revision: Rev. B | Date: 2025-01