

SV100 Direct-Acting Solenoid Valve

SKU / Model Number: SV100-G14-NC
Manufacturer: FluidControl GmbH
Category: Valves | ETIM Code: EC002465

PRODUCT OVERVIEW

The SV100 is a 2/2-way direct-acting solenoid valve for general purpose fluid control. Normally closed configuration with zero minimum operating pressure differential. Suitable for water, air, light oils, and inert gases.

TECHNICAL SPECIFICATIONS

Valve Type	2/2-way, direct acting
Function	Normally Closed (NC)
Orifice Size	6 mm
Kv Value	0.8 m3/h
Response Time (open)	< 30 ms
Response Time (close)	< 50 ms
Min. Pressure Differential	0 bar

ELECTRICAL RATINGS

Coil Voltage	24 V DC
Power Consumption	8 W (holding: 4.5 W)
Coil Class	Class H (180 deg C)
Protection	Integrated TVS diode
Connector	DIN 43650 Form A

DIMENSIONS & MECHANICAL

Port Size	G 1/4 female
Body Width	32 mm
Body Height	76 mm
Overall Height	95 mm (with coil)
Weight	280 g

OPERATING CONDITIONS

Medium Temperature	-10 to 80 deg C
Ambient Temperature	-10 to 55 deg C
Max Pressure	10 bar
Duty Cycle	100% ED
IP Rating	IP65 (with connector)

MATERIALS OF CONSTRUCTION

Body	Brass CW617N
Seal	NBR (Buna-N)
Plunger	430F Stainless Steel
Spring	302 Stainless Steel
Coil Housing	PA66 glass-filled nylon

PERFORMANCE DATA / SELECTION TABLE

Medium	Temp Range	Max Pressure	Seal Material
Water	-10 to 80 C	10 bar	NBR
Compressed Air	-10 to 60 C	10 bar	NBR
Light Oil	-10 to 60 C	6 bar	FKM
Steam	0 to 180 C	6 bar	EPDM

CERTIFICATIONS & APPROVALS

CE | RoHS | REACH | DVGW | UL Listed

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

This document is the property of FluidControl GmbH. Specifications are subject to change without notice. For the latest revision, visit www.fluidcontrolgmbh.com. Document revision: Rev. B | Date: 2025-01