

TB100 Spring-Cage DIN Rail Terminal Block

SKU / Model Number: TB100-4MM-GY
Manufacturer: TerminalTech Solutions
Category: Connectors | ETIM Code: EC000380

PRODUCT OVERVIEW

The TB100 is a push-in spring-cage terminal block for fast, tool-free wiring in control panels and distribution boards. Features vibration-proof connection, clear labeling area, and test-tap access point.

TECHNICAL SPECIFICATIONS

Connection Type	Push-in spring cage
Cross Section	0.14 to 4 mm ² (AWG 26-12)
Rated Current	32 A
Rated Voltage	800 V
Stripping Length	10 mm
Number of Connections	2 (through-type)
Pitch	6.2 mm

ELECTRICAL RATINGS

Contact Resistance	< 5 mohm
Insulation Resistance	> 10 ⁹ ohm
Dielectric Strength	3 kV AC / 1 min
Impulse Voltage	8 kV (1.2/50 us)
Temperature Rise	< 45 K at rated current

DIMENSIONS & MECHANICAL

Width	6.2 mm
Height	47 mm
Depth	35 mm
Mounting	35 mm DIN rail (TS35)
Weight	8 g per terminal

OPERATING CONDITIONS

Temperature Range	-60 to 130 deg C
Flammability	UL94 V-0
Humidity	100% RH
Vibration	IEC 60068-2-6 (5g)
Pollution Degree	3

MATERIALS OF CONSTRUCTION

Housing	PA66, UL94 V-0, halogen-free
Current Bar	Tin-plated copper
Spring	Stainless Steel CrNi
Marking Strip	PC, laser-printable
End Plate	PA66, snap-on

PERFORMANCE DATA / SELECTION TABLE

Wire Size	Current (A)	Voltage (V)	Stripping (mm)
0.14 mm2	---	---	10
0.5 mm2	10	800	10
1.5 mm2	17.5	800	10
2.5 mm2	24	800	10
4.0 mm2	32	800	10

CERTIFICATIONS & APPROVALS

IEC 60947-7-1 | CE | UL 1059 | CSA | ATEX Zone 2 | GL Marine | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

*This document is the property of TerminalTech Solutions. Specifications are subject to change without notice. For the latest revision, visit www.terminaltechsolutions.com.
Document revision: Rev. B | Date: 2025-01*