

VB30 Industrial Vibration Sensor

SKU / Model Number: VB30-100G-ICP
Manufacturer: DynaSense Technologies
Category: Sensors | ETIM Code: EC001299

PRODUCT OVERVIEW

The VB30 is a piezoelectric IEPE/ICP accelerometer for continuous vibration monitoring of rotating machinery. Features hermetically sealed titanium housing, wide frequency range, and 4-20 mA vibration transmitter output.

TECHNICAL SPECIFICATIONS

Sensitivity	100 mV/g (+/- 10%)
Measurement Range	+/- 50 g peak
Frequency Range	0.5 to 15000 Hz (+/- 3 dB)
Resonant Frequency	> 28 kHz
Dynamic Range	> 108 dB
Output Type	IEPE / ICP
Noise Floor	< 15 micro-g/sqrt(Hz)

ELECTRICAL RATINGS

Excitation	2-20 mA constant current
Compliance Voltage	18 to 30 V DC
Output Impedance	< 100 ohm
Bias Voltage	8 to 14 V DC
Connector	MIL-C-5015, 2-pin

DIMENSIONS & MECHANICAL

Diameter	22 mm
Height	35 mm
Mounting	1/4-28 UNF stud
Cable Length	Integral 5 m
Weight	50 g

OPERATING CONDITIONS

Operating Temperature	-55 to 120 deg C
Storage Temperature	-65 to 150 deg C
Humidity	100% RH, non-condensing
Shock Limit	5000 g peak
IP Rating	IP68

MATERIALS OF CONSTRUCTION

Housing	Titanium Grade 2
Sensing Element	PZT Ceramic
Connector Body	Stainless Steel
Cable Jacket	PTFE
Adhesive Mount	Ceramic filled epoxy

PERFORMANCE DATA / SELECTION TABLE

Mounting	Freq Range	Sensitivity Dev	Typical Use
Stud	0.5-15000 Hz	+/- 5%	Permanent install
Adhesive	0.5-8000 Hz	+/- 10%	Temporary monitoring
Magnetic	0.5-5000 Hz	+/- 15%	Route-based surveys
Probe Tip	0.5-2000 Hz	+/- 20%	Spot checks

CERTIFICATIONS & APPROVALS

CE | ATEX Zone 2 | IECEx | MIL-STD-810G | RoHS

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

This document is the property of DynaSense Technologies. Specifications are subject to change without notice. For the latest revision, visit www.dynasensetechnologies.com. Document revision: Rev. B | Date: 2025-01