

VFD150 Variable Frequency Drive

SKU / Model Number: VFD150-15KW-3P

Manufacturer: InverterTech Corp

Category: Controllers | ETIM Code: EC001210

PRODUCT OVERVIEW

The VFD150 is a sensorless vector control variable frequency drive for induction and PM motors up to 15 kW. Features STO (Safe Torque Off), built-in EMC filter, dynamic braking, and Modbus communication.

TECHNICAL SPECIFICATIONS

Rated Power	15 kW / 20 HP
Output Current	32 A (continuous)
Overload	150% for 60s, 200% for 3s
Control Mode	V/F, Sensorless Vector, FOC
Output Frequency	0 to 590 Hz
Carrier Frequency	2 to 16 kHz
Speed Regulation	+/- 0.5% (sensorless vector)

ELECTRICAL RATINGS

Input Voltage	380-480 V AC, 3-phase
Input Frequency	47-63 Hz
Input Current	35 A
DC Bus Voltage	540-680 V DC
Braking Transistor	Built-in

DIMENSIONS & MECHANICAL

Width	200 mm
Height	380 mm
Depth	190 mm
Mounting	Wall / Panel mount
Weight	8.5 kg

OPERATING CONDITIONS

Ambient Temperature	-10 to 50 deg C
Derating	1% per deg C above 40 deg C
Altitude	Up to 1000 m (4000 m with derating)
Humidity	5 to 95% RH
IP Rating	IP20 (IP55 optional enclosure)

MATERIALS OF CONSTRUCTION

Housing	Sheet Steel, powder coated
Heatsink	Extruded Aluminum
PCB	Multi-layer, conformal coated
Power Modules	IGBT (Infineon)
Fan	DC fan, field replaceable

PERFORMANCE DATA / SELECTION TABLE

Motor Power (kW)	Output Current (A)	Frame Size	Weight (kg)
0.75	2.5	A	1.2
4.0	10	B	3.5
7.5	18	C	5.8
15	32	D	8.5
22	45	E	12.0

CERTIFICATIONS & APPROVALS

IEC 61800-5-1 | CE | UL 508C | CSA | RoHS | STO: IEC 61800-5-2 SIL 3

Note: Specific certification documents and test reports are available upon request. All products are manufactured under ISO 9001:2015 quality management system.

This document is the property of InverterTech Corp. Specifications are subject to change without notice. For the latest revision, visit www.invertechcorp.com. Document revision: Rev. B | Date: 2025-01