

Name:Deeksha S
USN: 1BM21CS048

AIRLINE FLIGHT DATABASE

Week 8

```
create database 1bm21cs048_airline;  
use 1bm21cs048_airline;
```

Create Tables

```
create table flights(  
  flno int,  
  ffrom varchar(20),  
  tto varchar(20),  
  distance int,  
  departs time,  
  arrives time,  
  price int,  
  primary key(flno)  
);
```

```
create table aircraft(  
  aid int,  
  aname varchar(20),  
  cruising_range int,  
  primary key(aid)  
);
```

```
create table employee(  
  eid int,  
  ename varchar(20),  
  salary int,  
  primary key(eid)  
);
```

```
create table certified(  
  eid int,  
  aid int,  
  foreign key (eid) references employee(eid) on delete cascade on update cascade,  
  foreign key (aid) references aircraft(aid) on delete cascade on update cascade  
);
```

Insert Values

```
insert into employee values (101,'Avinash',50000);
insert into employee values (102,'Lokesh',60000);
insert into employee values (103,'Rakesh',70000);
insert into employee values (104,'Santhosh',82000);
insert into employee values (105,'Tilak',5000);
```

```
insert into aircraft values (1,'Airbus',2000);
insert into aircraft values (2,'Boeing',700);
insert into aircraft values (3,'Jetairways',550);
insert into aircraft values (4,'Indigo',5000);
insert into aircraft values (5,'Boeing',4500);
insert into aircraft values (6,'Airbus',2200);
```

```
insert into certified values(101,2);
insert into certified values(101,4);
insert into certified values(101,5);
insert into certified values(101,6);
insert into certified values(102,1);
insert into certified values(102,3);
insert into certified values(102,5);
insert into certified values(103,2);
insert into certified values(103,3);
insert into certified values(103,5);
insert into certified values(103,6);
insert into certified values(104,6);
insert into certified values(104,1);
insert into certified values(104,3);
insert into certified values(105,3);
```

```
insert into flights values(1,'Bengaluru','New Delhi',500,'6:00','9:00',5000);
insert into flights values(2,'Bengaluru','Chennai',300,'7:00','8:30',3000);
insert into flights values(3,'Trivandrum','New Delhi',800,'8:00','11:30',6000);
insert into flights values(4,'Bengaluru','Frankfurt',1000,'6:00','23:30',50000);
insert into flights values(5,'Kolkata','New Delhi',2400,'11:00','3:30',9000);
insert into flights values(6,'Bengaluru','Frankfurt',8000,'9:00','23:00',40000);
```

select * from employee;

Result Grid			
	eid	ename	salary
▶	101	Avinash	50000
	102	Lokesh	60000
	103	Rakesh	70000
	104	Santhosh	82000
	105	Tilak	5000
*	NULL	NULL	NULL

employee 18 × aircraft 19 certified 20 flights 21

select * from aircraft;

Result Grid			
	aid	aname	cruising_range
▶	1	Airbus	2000
	2	Boeing	700
	3	Jetairways	550
	4	Indigo	5000
	5	Boeing	4500
	6	Airbus	2200
*	NULL	NULL	NULL

employee 18 aircraft 19 × certified 20 flights 21

select * from certified;

Result Grid		
	eid	aid
▶	101	2
	101	4
	101	5
	101	6
	102	1
	102	3
	102	5
	103	2
	103	3
	103	5
	103	6
	104	6
	104	1
	104	3
	105	3

employee 18 aircraft 19 certified 20 × flights 21

select * from flights;

Result Grid							
Filter Rows:							
	fno	ffrom	tto	distance	departs	arrives	price
▶	1	Bengaluru	New Delhi	500	06:00:00	09:00:00	5000
	2	Bengaluru	Chennai	300	07:00:00	08:30:00	3000
	3	Trivandrum	New Delhi	800	08:00:00	11:30:00	6000
	4	Bengaluru	Frankfurt	1000	06:00:00	23:30:00	50000
	5	Kolkata	New Delhi	2400	11:00:00	03:30:00	9000
	6	Bengaluru	Frankfurt	8000	09:00:00	23:00:00	40000
*	NULL	NULL	NULL	NULL	NULL	NULL	NULL
employee 18 aircraft 19 certified 20 flights 21 ×							

TO DO

i. Find the name of the aircraft such that all pilots certified to operate them have salaries more than 80,000

select a.aname

from aircraft a, certified c, employee e

where c.aid = a.aid and e.eid = c.eid and e.salary>80000;

Result Grid	
aname	
▶	Airbus
	Airbus
	Jetairways
Result 22 ×	

ii. For each pilot who is certified for more than three aircrafts, find the eid and the maximum cruising range of the aircraft for which she or he is certified.

select c.eid ,max(a.cruising_range)

from certified c, aircraft a

where c.aid=a.aid

group by c.eid

having count(c.aid)>=3;

Result Grid		
Filter Rows:		
	eid	max(a.cruising_range)
▶	101	5000
	102	4500
	103	4500
	104	2200
Result 23 ×		

iii. Find the names of pilots whose salary is less than the price of the cheapest route from Bengaluru to Frankfurt.

```
select ename
from employee
where salary < (
select min(price)
from flights
where ffrom='Bengaluru' and tto='Frankfurt');
```




The screenshot shows a 'Result Grid' window. It contains a single row with the column header 'ename' and the value 'Tilak'. At the bottom, there is a tab labeled 'employee 24' with a close button.

ename
Tilak

iv. For all aircraft with cruising range over 1000 Kms, find the name of the aircraft and the average salary of all pilots certified for this aircraft.

```
select a.aid, a.aname, avg(e.salary)
from aircraft a, employee e, certified c
where c.aid = a.aid and e.eid = c.eid and a.cruising_range > 1000
group by c.aid;
```



The screenshot shows a 'Result Grid' window with a table containing 4 rows. The columns are 'aid', 'aname', and 'avg(e.salary)'. The rows are: (1, Airbus, 71000.0000), (4, Indigo, 50000.0000), (5, Boeing, 60000.0000), and (6, Airbus, 67333.3333). At the bottom, there is a tab labeled 'Result 25' with a close button.

aid	aname	avg(e.salary)
1	Airbus	71000.0000
4	Indigo	50000.0000
5	Boeing	60000.0000
6	Airbus	67333.3333

v. Find the names of pilots certified for some Boeing aircraft

```
select distinct(e.ename)
from aircraft a, employee e, certified c
where c.aid = a.aid and e.eid = c.eid and aname = 'Boeing';
```

Result Grid	
	ename
▶	Avinash
	Rakesh
	Lokesh

Result 26 x

vi. Find the aids of all aircraft that can be used on routes from Bengaluru to New Delhi.

```
select a.aid
from aircraft a
where a.cruising_range>=
(select distance
from flights
where ffrom='Bengaluru' and tto='New Delhi');
```

Result Grid	
	aid
▶	1
	2
	3
	4
	5
	6
	NULL

aircraft 27 x