CSE 556: Natural Language Processing Assignment 04: CKY Parser

Total Points: 50

Instructions:

- Please don't copy from the internet or any other student. Plagiarism will thoroughly be checked on all the submitted files.
- Allowed Programming language: Python
- Use classroom discussion for any doubt.

In this assignment, you will implement the CKY algorithm for English and apply it to the word recognition and parsing problem. You can use the NLTK modules for representing context-free grammars and parse trees, but you should implement the parser from scratch.

Ingredients: We provide the grammar and test sentences. The grammar stems from the Airline Travel Information System (ATIS), a project working on spoken dialog systems for air travel. The ATIS CFG is available in the NLTK data package, together with 98 test sentences. You can initialize the resources this way:

load the grammar

grammar = nltk.data.load("grammars/large grammars/atis.cfg")

load the raw sentences

s = nltk.data.load("grammars/large grammars/atis sentences.txt", "raw")

extract the test sentences

t = nltk.parse.util.extract test sentences(s)

NLTK already implements a number of parsing algorithms (see nltk.parse for the list). You can try one to see if you loaded the grammar correctly:

initialize the parser

parser = nltk.parse.BottomUpChartParser(grammar) # parse all test sentences

for sentence in t:

parser.chart parse(sentence[0])

However, the NLTK version of the ATIS grammar is not in Chomsky normal form (CNF), which you will need for your CKY parser. Feel free to implement a conversion module. You can then read the grammar from the file using nltk.data.load() and utilize the nice features of the nltk.grammar module on the resulting object.

[Note that chart parse() throws an error when it encounters an unknown word, which is undesirable behavior for any parser. If you want to test the grammars with the pre implemented parser (for example, to check whether the CNF version is in fact weakly equivalent), you may need to catch this error]

Problem Statement: Parsing

Implement the CKY algorithm for parsing. Also, implement a function that extracts the set of all parse trees from the backpointers in the chart. Feel free to use the NLTK module nltk.tree for this purpose; notice that only Immutable Trees can be used as elements of Python sets, whereas raw Trees cannot.

Please submit your code, outputs, and a README file containing instructions for running your recognizer and parser. The outputs should consist of at least:

- (1) the list of ATIS test sentences with tab-separated numbers of parse trees
- (2) pictures of the parse trees for an ATIS test sentence of your choice with a number of parses p such that 1 .

You can visualize an NLTK tree using its draw method.