

```

import java.util.Scanner;
class student{
    String Name,USN;

void accept()
{
    Scanner sc = new Scanner(System.in);
    System.out.println("Enter student name:");
    Name = sc.nextLine();
    System.out.println("Enter student USN:");
    USN = sc.nextLine();
}
void display()
{
    System.out.println("student name:"+Name);
    System.out.println("student USN:"+USN);
}
}
class studentRun
{
    public static void main(String args[]){
        int i;
        student s[] = new student[3];
        for (i = 0; i < 3;i++){
            {
                s[i]=new student();
                s[i].accept();
            }
            for (i = 0; i < 3;i++){

                s[i].display();}[]

        }
    }
}

```

student.java

Compile Messages jGRASP Messages Run I/O Interactions / REPL

```

----jGRASP exec: java -Xint -Xrunjdp:transport=dt_socket,suspend=y,server=y studentRun
----jGRASP: Connected to debugger.
Enter student name:
deekshitha
Enter student USN:

```



student.java

Compile Messages

jGRASP Messages

Run I/O

Interactions / REF



Enter student name:

arun



Enter student USN:

1bm26cs008

Enter student name:


 student.java

Compile Messages

jGRASP Messages

Run I/O

Interactions / REPL



```
▶▶ 1bm26cs008
    Enter student name:
▶▶ chethan
    Enter student USN:
▶▶ 1bm26cs014
```

student.java

Compile Messages

jGRASP Messages

Run I/O

Interactions / REPL





```
student USN:1bm26cs605
student name:arun
student USN:1bm26cs008
student name:chethan
student USN:1bm26cs014
```

```
class Grocery
{
    double qDal, qPul, qSugar;

    // Default constructor
    Grocery()
    {
        qDal = 2;
        qPul = 2;
        qSugar = 1;
    }

    // Parameterized constructor
    Grocery(double price)
    {
        qDal = price;
        qPul = price;
        qSugar = price;
    }

    // Copy constructor
    Grocery(Grocery ob)
    {
        qDal = ob.qDal;
        qPul = ob.qPul;
        qSugar = ob.qSugar;
    }

    // Parameterized constructor with 3 values
    Grocery(double dal, double pul, double sugar)
    {
        qDal = dal;
        qPul = pul;
        qSugar = sugar;
    }

    double calcPrice()
    {
        return qDal + qPul + qSugar;
    }
}

class Main
{
```

```
public static void main(String[] args)
{
    Grocery q1 = new Grocery();
    Grocery q2 = new Grocery(120);
    Grocery q3 = new Grocery(150, 120, 70);
    Grocery q4 = new Grocery(43);

    System.out.println("Q1 price = " + q1.calcPrice());
    System.out.println("Q2 price = " + q2.calcPrice());
    System.out.println("Q3 price = " + q3.calcPrice());
    System.out.println("Q4 price = " + q4.calcPrice());
}
}
```

```
class Grocery
{
    double qDal, qPul, qSugar;

    // Default constructor
    Grocery()
    {
        qDal = 2;
    }
}
```

G Grocery.java

Compile Messages

jGRASP Messages

Run I/O

Interactions / REPL

Q1 price = 5.0
Q2 price = 360.0
Q3 price = 340.0
Q4 price = 129.0

----jGRASP: Operation complete.

▶▶ L