20104016

DEENA

Importing Libraries

In [1]:
```
import numpy as np
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
```

Importing Datasets

In [2]:
```
df=pd.read_csv("rainfall_gangetic west bengal.csv")
df
```

Out[2]:

	index	SUBDIVISION	YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OC
0	552	GANGETIC WEST BENGAL	1901	37.1	58.4	3.9	64.1	121.7	198.0	280.8	275.7	313.5	51
1	553	GANGETIC WEST BENGAL	1902	0.0	1.2	44.2	103.8	161.6	140.9	347.8	264.8	230.5	32
2	554	GANGETIC WEST BENGAL	1903	17.5	24.6	37.3	30.6	78.5	201.7	179.6	277.6	300.7	198
3	555	GANGETIC WEST BENGAL	1904	0.1	23.9	35.6	17.5	160.2	286.7	435.3	241.7	142.8	35
4	556	GANGETIC WEST BENGAL	1905	30.9	49.6	84.7	84.9	156.8	70.9	525.5	263.6	287.6	107
...	...	...	...	...	...	...	...	...	...	...	...	...	
110	662	GANGETIC WEST BENGAL	2011	2.5	2.7	40.5	75.0	132.6	434.5	219.9	443.2	295.9	36
111	663	GANGETIC WEST BENGAL	2012	40.7	15.3	4.4	57.7	44.2	146.6	315.0	261.4	246.9	64
112	664	GANGETIC WEST BENGAL	2013	2.5	10.0	4.8	45.6	195.9	233.4	263.2	401.4	254.0	353
113	665	GANGETIC WEST BENGAL	2014	0.9	42.2	19.9	1.9	124.4	193.6	298.7	292.6	229.5	56
114	666	GANGETIC WEST BENGAL	2015	12.9	5.5	19.3	88.7	57.6	247.2	633.1	260.6	164.0	32

115 rows × 20 columns

Data Cleaning and Data Preprocessing

In [3]:
```
df=df.dropna()
```

In [4]:
```
df.columns
```

Out[4]:
```
Index(['index', 'SUBDIVISION', 'YEAR', 'JAN', 'FEB', 'MAR', 'APR', 'MAY',
       'JUN', 'JUL', 'AUG', 'SEP', 'OCT', 'NOV', 'DEC', 'ANNUAL', 'Jan-Feb',
       'Mar-May', 'Jun-Sep', 'Oct-Dec'],
      dtype='object')
```

In [5]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 115 entries, 0 to 114
Data columns (total 20 columns):
 #   Column       Non-Null Count  Dtype  
---  ------       --------------  -----  
 0   index        115 non-null    int64  
 1   SUBDIVISION  115 non-null    object 
 2   YEAR         115 non-null    int64  
 3   JAN          115 non-null    float64
 4   FEB          115 non-null    float64
 5   MAR          115 non-null    float64
 6   APR          115 non-null    float64
 7   MAY          115 non-null    float64
 8   JUN          115 non-null    float64
 9   JUL          115 non-null    float64
 10  AUG          115 non-null    float64
 11  SEP          115 non-null    float64
 12  OCT          115 non-null    float64
 13  NOV          115 non-null    float64
 14  DEC          115 non-null    float64
 15  ANNUAL       115 non-null    float64
 16  Jan-Feb      115 non-null    float64
 17  Mar-May      115 non-null    float64
 18  Jun-Sep      115 non-null    float64
 19  Oct-Dec      115 non-null    float64
dtypes: float64(17), int64(2), object(1)
memory usage: 18.9+ KB
```

Line chart

In [6]:
```
df.plot.line(subplots=True)
```

Out[6]:
```
array([<AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>,
       <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>,
       <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>,
       <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>,
       <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>], dtype=object)
```



Line chart

In [7]:

Out[7]: <AxesSubplot:>



Bar chart

In [8]:

Out[8]: <AxesSubplot:>



Histogram

In [9]:
```
df.plot.hist()
```

Out[9]: <AxesSubplot:ylabel='Frequency'>



Area chart

In [10]:
```
df.plot.area()
```

Out[10]: <AxesSubplot:>



Box chart

In [11]:
```
df.plot.box()
```

Out[11]: <AxesSubplot:>



Pie chart

In [12]:
```
df.plot.pie(y='ANNUAL')
```

Out[12]:
```
<AxesSubplot:ylabel='ANNUAL'>
```



Scatter chart

In [13]:
```
df.plot.scatter(x='SUBDIVISION', y='ANNUAL')
```

Out[13]: <AxesSubplot:xlabel='SUBDIVISION', ylabel='ANNUAL'>



In [14]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 115 entries, 0 to 114
Data columns (total 20 columns):
 #   Column       Non-Null Count  Dtype
---  ------       --------------  -----
 0   index        115 non-null    int64
 1   SUBDIVISION  115 non-null    object
 2   YEAR         115 non-null    int64
 3   JAN          115 non-null    float64
 4   FEB          115 non-null    float64
 5   MAR          115 non-null    float64
 6   APR          115 non-null    float64
 7   MAY          115 non-null    float64
 8   JUN          115 non-null    float64
 9   JUL          115 non-null    float64
 10  AUG          115 non-null    float64
 11  SEP          115 non-null    float64
 12  OCT          115 non-null    float64
 13  NOV          115 non-null    float64
 14  DEC          115 non-null    float64
```

In [15]:
```
df.describe()
```

Out[15]:

	index	YEAR	JAN	FEB	MAR	APR	MAY	
count	115.000000	115.000000	115.000000	115.000000	115.000000	115.000000	115.000000	11
mean	609.000000	1958.000000	12.595652	22.452174	29.090435	44.885217	107.787826	24
std	33.341666	33.341666	14.741821	24.165919	30.754415	31.812974	51.001443	9
min	552.000000	1901.000000	0.000000	0.000000	0.100000	0.900000	16.400000	6
25%	580.500000	1929.500000	1.250000	5.200000	7.200000	21.000000	71.900000	18
50%	609.000000	1958.000000	6.800000	13.600000	18.900000	39.200000	98.900000	22
75%	637.500000	1986.500000	18.350000	30.650000	42.250000	61.050000	131.400000	30
max	666.000000	2015.000000	60.000000	123.600000	152.500000	174.200000	250.900000	59

EDA AND VISUALIZATION

In [16]:
```
sns.pairplot(df)
```

Out[16]:
```
<seaborn.axisgrid.PairGrid at 0x26137171e20>
```



In [17]:
```
sns.distplot(df['ANNUAL'])
```

```
C:\ProgramData\Anaconda3\lib\site-packages\seaborn\distributions.py:2557: Fut
ureWarning: `distplot` is a deprecated function and will be removed in a futu
re version. Please adapt your code to use either `displot` (a figure-level fu
nction with similar flexibility) or `histplot` (an axes-level function for hi
stograms).
  warnings.warn(msg, FutureWarning)
```

Out[17]: <AxesSubplot:xlabel='ANNUAL', ylabel='Density'>



In [18]:
```
sns.heatmap(df.corr())
```

Out[18]: <AxesSubplot:>