20104016

DEENA

Importing Libraries

In [1]:
```
import numpy as np
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
```

Importing Datasets

In [2]:
```
df=pd.read_csv("rainfall_saurashtra _ kutch.csv")
df
```

Out[2]:

	index	SUBDIVISION	YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
0	2392	SAURASHTRA & KUTCH	1901	1.9	0.0	0.1	0.2	3.2	9.1	87.8	62.5	12.0	3.8
1	2393	SAURASHTRA & KUTCH	1902	0.1	0.0	0.0	0.5	1.1	14.4	92.9	160.0	123.9	1.5
2	2394	SAURASHTRA & KUTCH	1903	0.5	0.0	1.7	0.0	3.1	10.5	337.9	96.1	61.9	11.1
3	2395	SAURASHTRA & KUTCH	1904	1.4	5.8	17.5	0.0	0.0	9.5	111.2	9.4	28.9	0.3
4	2396	SAURASHTRA & KUTCH	1905	1.5	1.0	0.6	0.4	0.0	6.4	254.5	12.3	12.8	0.4
...	...	...	...	...	...	...	...	...	...	...	...	...	...
110	2502	SAURASHTRA & KUTCH	2011	0.0	1.4	0.0	0.0	0.0	26.0	212.7	290.9	210.1	1.2
111	2503	SAURASHTRA & KUTCH	2012	0.0	0.0	0.0	0.2	0.1	22.4	34.7	34.5	228.5	2.4
112	2504	SAURASHTRA & KUTCH	2013	1.7	0.2	0.1	8.5	0.1	127.7	171.2	83.3	260.2	28.6
113	2505	SAURASHTRA & KUTCH	2014	0.3	0.0	0.1	0.5	2.1	17.3	137.7	118.8	99.2	5.2
114	2506	SAURASHTRA & KUTCH	2015	0.9	0.0	4.4	2.1	0.8	112.6	226.7	10.6	79.9	3.3

115 rows × 20 columns

Data Cleaning and Data Preprocessing

In [3]:
```
df.dropna()
```

In [4]:
```
df.columns
```

Out[4]:
```
Index(['index', 'SUBDIVISION', 'YEAR', 'JAN', 'FEB', 'MAR', 'APR', 'MAY',
       'JUN', 'JUL', 'AUG', 'SEP', 'OCT', 'NOV', 'DEC', 'ANNUAL', 'Jan-Feb',
       'Mar-May', 'Jun-Sep', 'Oct-Dec'],
      dtype='object')
```

In [5]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 115 entries, 0 to 114
Data columns (total 20 columns):
 #   Column       Non-Null Count  Dtype  
---  ------       --------------  -----  
 0   index        115 non-null    int64  
 1   SUBDIVISION  115 non-null    object 
 2   YEAR         115 non-null    int64  
 3   JAN          115 non-null    float64
 4   FEB          115 non-null    float64
 5   MAR          115 non-null    float64
 6   APR          115 non-null    float64
 7   MAY          115 non-null    float64
 8   JUN          115 non-null    float64
 9   JUL          115 non-null    float64
 10  AUG          115 non-null    float64
 11  SEP          115 non-null    float64
 12  OCT          115 non-null    float64
 13  NOV          115 non-null    float64
 14  DEC          115 non-null    float64
 15  ANNUAL       115 non-null    float64
 16  Jan-Feb      115 non-null    float64
 17  Mar-May      115 non-null    float64
 18  Jun-Sep      115 non-null    float64
 19  Oct-Dec      115 non-null    float64
dtypes: float64(17), int64(2), object(1)
memory usage: 18.9+ KB
```

Line chart

In [6]:
```
df.plot.line(subplots=True)
```

Out[6]:
```
array([<AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>,
       <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>,
       <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>,
       <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>,
       <AxesSubplot:>, <AxesSubplot:>, <AxesSubplot:>], dtype=object)
```



Line chart

In [7]:
```
df.plot.line()
```

Out[7]:
```
<AxesSubplot:>
```



Bar chart

In [8]:
```
df.plot.bar()
```

Out[8]: <AxesSubplot:>



Histogram

In [9]:
```
df.plot.hist()
```

Out[9]: <AxesSubplot:ylabel='Frequency'>



Area chart

In [10]:
```
df.plot.area()
```

Out[10]: <AxesSubplot:>



Box chart

In [11]:
```
df.plot.box()
```

Out[11]: <AxesSubplot:>



Pie chart

In [12]:
```
df.plot.pie(y='ANNUAL')
```

Out[12]:
```
<AxesSubplot:ylabel='ANNUAL'>
```



Scatter chart

In [13]:
```
df.plot.scatter(x='SUBDIVISION', y='ANNUAL')
```

Out[13]: <AxesSubplot:xlabel='SUBDIVISION', ylabel='ANNUAL'>



In [14]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 115 entries, 0 to 114
Data columns (total 20 columns):
 #   Column       Non-Null Count  Dtype
---  ------       --------------  -----
 0   index        115 non-null    int64
 1   SUBDIVISION  115 non-null    object
 2   YEAR         115 non-null    int64
 3   JAN          115 non-null    float64
 4   FEB          115 non-null    float64
 5   MAR          115 non-null    float64
 6   APR          115 non-null    float64
 7   MAY          115 non-null    float64
 8   JUN          115 non-null    float64
 9   JUL          115 non-null    float64
 10  AUG          115 non-null    float64
 11  SEP          115 non-null    float64
 12  OCT          115 non-null    float64
 13  NOV          115 non-null    float64
 14  DEC          115 non-null    float64
```

In [15]:
```
df.describe()
```

Out[15]:

	index	YEAR	JAN	FEB	MAR	APR	MAY	
count	115.000000	115.000000	115.000000	115.000000	115.000000	115.000000	115.000000	11
mean	2449.000000	1958.000000	1.139130	1.615652	1.296522	1.183478	4.662609	7
std	33.341666	33.341666	2.374709	4.270576	5.691544	6.158847	16.587231	6
min	2392.000000	1901.000000	0.000000	0.000000	0.000000	0.000000	0.000000	
25%	2420.500000	1929.500000	0.000000	0.000000	0.000000	0.000000	0.000000	1
50%	2449.000000	1958.000000	0.200000	0.000000	0.000000	0.000000	0.500000	6
75%	2477.500000	1986.500000	1.000000	0.550000	0.400000	0.500000	2.700000	11
max	2506.000000	2015.000000	12.500000	28.200000	46.200000	64.400000	131.900000	32

EDA AND VISUALIZATION

In [16]:
```
sns.pairplot(df)
```

Out[16]:
```
<seaborn.axisgrid.PairGrid at 0x1b5e4a2c610>
```



In [17]:
```
sns.distplot(df['ANNUAL'])
```

```
C:\ProgramData\Anaconda3\lib\site-packages\seaborn\distributions.py:2557: Fut
ureWarning: `distplot` is a deprecated function and will be removed in a futu
re version. Please adapt your code to use either `displot` (a figure-level fu
nction with similar flexibility) or `histplot` (an axes-level function for hi
stograms).
  warnings.warn(msg, FutureWarning)
```

Out[17]: <AxesSubplot:xlabel='ANNUAL', ylabel='Density'>



In [18]:
```
sns.heatmap(df.corr())
```

Out[18]: <AxesSubplot:>