UNIVERSITY INSTITUTE OF ENGINEERING

Department of Computer Science & Engineering

Subject Name: WEB AND MOBILE SECURITY LAB

Subject Code: 20ITP-378

Submitted to:

MARIAM KHAN

Submitted by:

 Name: Tushar Singh

UID: 20BET1094

Section: 20BET601

Group: B

Experiment-2.1

Student Name: Tushar Singh   **UID: 20BET1094**
Branch: BE-IT   **Section/Group: 20BET_WM_601-B**
Semester: FIFTH   **Date of Performance: 09/11/22**
Subject Name: WMS LAB   **Subject Code: ITP-378**

Aim:

Write a program to generate message digest for the given message using the SHA/MD5 algorithm and verify the integrity of message.

Software/Hardware Requirements:

window 7 and above version **Tools**

to be used:

1. Eclipse IDE
2. JDK (Java Development kit)
3. IntelliJ IDEA

Steps/Method/Coding:

To calculate cryptographic hashing value in Java, **MessageDigest** Class is used, under the package java.security.

MessageDigest Class provides following cryptographic hash function to find hash value of a text as follows:

- MD2
- MD5
- SHA-1
- SHA-224
- SHA-256
- SHA-384
- SHA-512

1.This Algorithms are initialize in static method called **getInstance()**.

2.   After selecting the algorithm it calculate the **digest** value and return the results in byte array.

3.   BigInteger class is used, which converts the resultant byte array into its **sign-magnitude representation**.

4.This representation is then converted into a hexadecimal format to get the expected MessageDigest.

Code (MD5 algorithm):

```
package com.company;

import java.math.BigInteger; import
java.security.MessageDigest;
import java.security.NoSuchAlgorithmException;
// Java program to calculate MD5 hash value public
class MD5 {
   public static String getMd5(String input)
   {
try {
        // Static getInstance method is called with hashing MD5
        MessageDigest md = MessageDigest.getInstance("MD5");
        // digest() method is called to calculate message digest
        // of an input digest() return array of byte
byte[] messageDigest = md.digest(input.getBytes());
// Convert byte array into signum representation
        BigInteger no = new BigInteger(1, messageDigest);
        // Convert message digest into hex value
String hashtext = no.toString(16);          while
(hashtext.length() < 32) {
          hashtext = "0" + hashtext;
        }
        return hashtext;
      }
```

```
        // For specifying wrong message digest algorithms
catch (NoSuchAlgorithmException e) {
        throw new RuntimeException(e);
    }
  }
  // Driver code
  public static void main(String args[]) throws NoSuchAlgorithmException
  {
    String s = "GeeksForGeeks";
    System.out.println("Your HashCode Generated by MD5 is: " +   getMd5(s));
  }
}
```

Output: (Screenshots)


```
C:\Users\Win10\.jdks\azul-15.0.5\bin\java.exe "-javaagent:C:\Program
Your HashCode Generated by MD5 is: e39b9c178b2c9be4e99b141d956c6ff6


Process finished with exit code 0
```

Code (SHA Algorithm):

package com.company;

import java.math.BigInteger; import
java.security.MessageDigest; import
java.security.NoSuchAlgorithmException; public
class GFG {
  public static String encryptThisString(String input)
  {
try {
        // getInstance() method is called with algorithm SHA-1
        MessageDigest md = MessageDigest.getInstance("SHA-1");

        // digest() method is called
        // to calculate message digest of the input string

```java
        // returned as array of byte            byte[]
messageDigest = md.digest(input.getBytes());            //
Convert byte array into signum representation
        BigInteger no = new BigInteger(1, messageDigest);
        // Convert message digest into hex value
        String hashtext = no.toString(16);
// Add preceding 0s to make it 32 bit
while (hashtext.length() < 32) {
        hashtext = "0" + hashtext;
        }
        // return the HashText
return hashtext;
    }
    // For specifying wrong message digest algorithms
catch (NoSuchAlgorithmException e) {
        throw new RuntimeException(e);
    }
  }
  // Driver code
  public static void main(String args[]) throws
        NoSuchAlgorithmException
  {
    System.out.println("HashCode Generated by SHA-1 for: ");

    String s1 = "GeeksForGeeks";
    System.out.println("\n" + s1 + " : " + encryptThisString(s1));
    String s2 = "hello world";
    System.out.println("\n" + s2 + " : " + encryptThisString(s2));
  }
}
```

Output (Screenshots):

```
C:\Users\Win10\.jdks\azul-15.0.5\bin\java.exe "-javaagent:C
HashCode Generated by SHA-1 for:

GeeksForGeeks : addf120b430021c36c232c99ef8d926aea2acd6b

hello world : 2aae6c35c94fcfb415dbe95f408b9ce91ee846ed

Process finished with exit code 0
```

Learning Outcomes:

Output is often known as hash values, hash codes, message digest. The length of output hashes is generally less than its corresponding input message length.