u3lib: An AI-Ready Computational Framework for U(3) Symmetry Algebra, Wigner Coupling, and Racah Recoupling Coefficients

Daniel Langr,[1] Phong Dang,[2] Tomas Dytrych,[3,2] and Michela Negro[2]

[1]*Department of Computer Systems, Faculty of Information Technology, Czech Technical University in Prague, Prague, Czech Republic*
[2]*Department of Physics and Astronomy, Louisiana State University, Baton Rouge, Louisiana, USA*
[3]*Nuclear Physics Institute, Czech Academy of Sciences, Řež, Czech Republic*

u3lib is an AI-ready C++ framework for U(3)/SU(3) representation-theory computations in nuclear structure and related applications. Besides the fast and accurate evaluation of Wigner coupling and Racah recoupling coefficients—implemented with the procedure of Dang *et al.*, which avoids the binomial coefficients and alternating sums of earlier formulations—the library offers the full algebraic toolkit for the symmetry group: irreducible representations (irreps), dimensions, Casimir invariants, and conjugation; the canonical Gelfand–Tsetlin basis and the physical SU(3) ⊃ SO(3) basis with their inner multiplicities; the matrix elements of the U(3) canonical generators; the reduced matrix elements of the physical generators; the tensor-product decomposition with outer multiplicities; and the transformation between the physical and canonical bases. The C++ API is mirrored one-to-one by Python bindings, and a repository-local catalog of domain skills lets a code-executing AI assistant drive any of these capabilities from a natural-language request.

PROGRAM SUMMARY

Program title: u3lib
Licensing provisions: MIT License.
Code repository: https://github.com/Deep-SANE/u3lib
Programming language: C++ (C++20), with Python bindings via pybind11.
External libraries: Eigen3 for QR-based null space solver; Boost for hash tables; OpenMP for multi-threading; fmt for formatting output; libwignernj for SU(2) coupling and recoupling coefficients; and sns for null space solver catered to sparse matrices ... TBD by DL . The Python extension additionally uses pybind11.
Nature of problem: Fast, accurate, and reproducible evaluation of Wigner reduced coupling coefficients for the two group-subgroup chains SU(3) ⊃ SO(3) and U(3) ⊃ U(2), Racah recoupling coefficients (6-U(3) and 9-U(3) coefficients), and the associated algebraic quantities (irrep dimensions, Casimirs, multiplicities, basis enumeration, generator matrix elements, and basis transformations) needed by symmetry-adapted calculations for nuclear structure and similar problems.
Solution method: The U(3) ⊃ U(2) reduced coupling and recoupling coefficients are built from the highest-weight U(3) ⊃ U(2) ⊃ U(1) full coupling coefficients, obtained as the orthonormal null space of the canonical raising generators, and propagated by the corresponding lowering generators [1]; the physical SU(3) ⊃ SO(3) coefficients follow from the physical-to-canonical basis transformation, also obtained as the orthonormal null space of the physical raising generator L_+ [1].

I. INTRODUCTION

Computation of coupling and recoupling coefficients for the unitary group U(3) and its special unitary subgroup SU(3) has a long history, dating back to the 1973 seminal pair of papers by Draayer and Akiyama that proffered a generic algorithm [2] and an associated Fortran program for their evaluation [3]. These coefficients underpin nuclear structure calculations using Elliott's SU(3) model [4, 5] and other symmetry-adapted shell-model approaches [6–8], where they are consumed in large numbers, thus speed and accuracy are essential. The SU(3) symmetry further underpins a broad family of nuclear-structure frameworks for medium-mass and heavy deformed nuclei, including the pseudo-SU(3) [9, 11], proxy-SU(3) [10, 11], and quasi-SU(3) [12] schemes, as well as the multiconfigurational dynamical symmetry (MUSY) [13]. Over the last five decades, the Draayer and Akiyama Fortran library had received various upgrades with improved numerical accuracy [14] and modern programming languages [15, 16]. However, the underlying algorithm using hypergeometric functions with large factorials and alternating sums had remained unchanged until recently when Dang *et al.* brought forward a completely new algorithm that leverages the action of the raising generators of the symmetry group along with state-of-the-art numerical null space solvers [1] DL, perhaps you also want to cite your student's thesis here?

The same algebraic tools also arise outside nuclear physics. In particle physics, flavor SU(3) underlies the eightfold-way classification of hadrons and the quark model [17, 18]. In quantum information, Schur transforms are constructed from successive Clebsch–Gordan transformations for d-level systems; for $d = 3$, this provides a potential application of U(3) coupling data to qutrit basis transformations [19]. In condensed-matter physics, symmetry-adapted numerical renormalization-group calculations of the SU(3) Anderson impurity model require tensor-product decompositions, coupling coefficients, and outer-multiplicity labels [20]. In quantum optics, SU(3) representation theory organizes multiphoton states and interference in three-channel passive interferometers [21]. These examples suggest uses for `u3lib` as a source of representation-theoretic building blocks, with application-specific modeling and any basis conversion supplied by the user.

In this paper, we present `u3lib`, a comprehensive high-performance framework for the U(3) symmetry algebra where computation of the coupling and recoupling coefficients are two of the capabilities it provides. This library is part of a broader project called `DeepSANE`—**Deep**-learning and **S**ymmetry-adapted **A**b-initio **N**uclear modeling: an AI-ready **E**cosystem. To be specific, `u3lib` packages the engine as a reusable framework: in addition to the coefficients, it supplies irreps as C++ objects and their Casimir invariants, the canonical Gelfand-Tsetlin U(3) $\supset$ U(2) $\supset$ U(1) and the physical SU(3) $\supset$ SO(3) bases, the generator matrix elements, the tensor-product decomposition, and the physical-to-canonical transformation. The C++ API is header-only; Python bindings mirror it one-to-one.

Large language models offer a way to orchestrate scientific workflows through natural-language requests. To support their use with `u3lib`, we provide an agent-skill catalog that guides AI assistants through the library's capabilities. Effective orchestration, however, requires more than identifying the relevant functions: an agent must also follow group-theoretical notation, phase conventions, memory-lifetime rules, and thread-safety requirements. The repository-local skills make these requirements explicit alongside the source code and provide procedures for constructing and checking calculations. This effort is closely aligned with initiatives to standardize reusable domain-specific skills for computational research, such as the U.S. Department of Energy (DOE) Genesis Mission and its scientific agent skill catalog[1]. We also evaluate whether this guidance improves task completion and reduces the resources needed to integrate the library, particularly as implementation complexity increases.

The remainder of this paper documents the repository structure (Sec. II), the classes and interface (Sec. III), the Python bindings (Sec. IV), the AI-ready interface and its benchmark evaluation (Sec. V), and the installation (Sec. VI).

II. LIBRARY STRUCTURE

`u3lib` is a header-only C++ library with a thin build layer. The top-level directories are:

- `include/`: the library itself (all algorithms live here; user programs include these headers directly):
  - `U3irrep.h`: the irrep classes `su3::irrep`, `u3::irrep`;
  - `U3gelfand.h`, `internal/gelfand/`: the Gelfand state class `u3::gelfand`;
  - `U3basis.h`: basis enumeration (`gelfandBasis`, `physicalBasis`), the inner multiplicity `Kappa`, the `u3::physicalvector` class, and the generator-action predicates;
  - `U3decomposition.h`: the outer multiplicity `Rho` and the tensor-product `decomposition`;
  - `U3U2xU3U2.h`, `U3SO3xU3SO3.h`: the canonical and physical coupling coefficients and their look-up tables;
  - `U3_U6Z6Coeffs.h`, `U3_U9Coeffs.h`: the 6-U(3) and 9-U(3) recoupling coefficients and their look-up tables;
  - `U3SO3_to_U3U2U1.h`: the physical-to-canonical transformation;
  - `U3generatorsRME.h`: the physical-generator reduced matrix elements `RME_L`, `RME_Q`;
  - `Definitions.h`: the structured coefficient containers;
  - `u3lib.h`: the umbrella header and the `initialize`/`finalize` lifecycle.
- `src/`: example driver programs (one `.cpp` per task) that call the headers and print results; compiled to `bin/`.
- `python/`: the pybind11 extension (`pyu3lib.cpp` → `u3lib.so`, built with `make python`) and a tutorial Jupyter notebook (`tutorial.ipynb`).

[1] See the DOE Genesis Mission skill catalog: https://gitlab.osti.gov/genesis/genesis-skills.

Header	Entry point	Task
`U3irrep.h`	`dim`, `C1/C2/C3`, `conjugate`	irrep dimension, Casimirs, conjugation
`U3basis.h`	`Kappa`, `gelfandBasis`, `physicalBasis`	inner multiplicity; basis enumeration
`U3decomposition.h`	`Rho`, `decomposition`	outer multiplicity; irrep product
`U3U2xU3U2.h`	`wigU3U2db`	U(3)⊃U(2) reduced coupling coefficients
`U3SO3xU3SO3.h`	`wigU3SO3db`	SU(3)⊃SO(3) reduced coupling coefficients
`U3_U6Z6Coeffs.h`	`u3u6db`, `u3z6db`	6-U(3) recoupling coefficients (three irreps)
`U3_U9Coeffs.h`	`u3u9db`	9-U(3) recoupling coefficients (four irreps)
`U3SO3_to_U3U2U1.h`	`phys_to_cano`	physical-tocanonical transformation
`U3generatorsRME.h`	`RME_L`, `RME_Q`	reduced matrix elements of **L**, **Q**

TABLE I: Main entry points of `u3lib`.

- `agents/`: the AI-agent skill catalog: an index (`AGENTS.md`), shared runtime instructions, and one skill per capability.
- `test/`: the regression suite (`test_*.cpp`, the `*_cases.h` case sets, and `reference/` documented values), run by `make test`.
- `doc/`: this manual (LaTeX source).
- `bin/`: build output (not source).

III. CLASSES AND LIBRARY INTERFACE

This section documents every public class and its methods, and the database/container interface through which coefficients are reached. All types are in the namespace `u3` (SU(3)-only base members in `su3`). The algebraic types and their methods do not require initialization; the coefficient databases do. Table I is an at-a-glance map of the main entry points.

A. Lifecycle

In `u3lib.h`:

- `initialize()` / `initialize(&argc,&argv)`: set up the caches of the SU(2) coefficients from `libwignernj`, and the U(3) coefficient databases;
- `finalize()`: destroy the databases;
- `initialize_thread()` / `finalize_thread()`: per-thread setup for multithreaded use;
- `clear()`: drop cached coefficients while keeping the databases alive;
- `is_initialized()`: query the state.

Note on shared-backend lifecycle: if `u3lib` runs in the same process as another library that shares the `libwignernj` backend, initialize all of them at startup and finalize only after all coefficient work is complete. Calling `finalize()` while another user of the backend is still active destroys the shared state and causes runtime errors.

B. Irreps: `su3::irrep` and `u3::irrep`

(`U3irrep.h`.) `su3::irrep` stores an SU(3) irrep; `u3::irrep` derives from it and adds the third label n_{33} (fixing the total quanta).

Constructors:

- `su3::irrep()`: default (empty) SU(3) irrep.

- `su3::irrep(lambda,mu)`: SU(3) irrep from its labels.
- `u3::irrep()`: default (empty) U(3) irrep.
- `u3::irrep(n13,n23,n33)`: U(3) irrep from its three labels.
- `u3::irrep(lambda,mu)`: normalized representative $[\lambda{+}\mu, \mu, 0]$.
- `u3::irrep(su3::irrep, N)`: fix the total quanta N.

Label getters:

- `lam()` / `lambda()`: the SU(3) label λ.
- `mu()`: the SU(3) label μ.
- `n13()`, `n23()`, `n33()`: the three U(3) labels (only for `u3::irrep`).

Dimension and invariants:

- `dim()`: the dimension (both classes).
- `C2()`: the quadratic SU(3) Casimir (both classes, shift-invariant).
- `C3()`: the cubic SU(3) Casimir (both classes, shift-invariant).
- `C1()`: the first-order Casimir $= n_{13}{+}n_{23}{+}n_{33}$ (total quanta), on `u3::irrep` only; `su3::irrep` has no `C1()`.
- `quanta()`: synonym of `C1()`.

Other:

- `zero()`: test for the trivial irrep.
- `conjugate()`: the conjugate irrep (μ, λ).
- `conjugate_phase()`: the associated conjugation phase.
- `normalize()`: set $n_{33} = 0$ for `u3::irrep`.
- comparison operators and stream output.
- `writeBinary` / `readBinary`: serialization for binary files.

C. Gelfand states: `u3::gelfand`

(`U3gelfand.h`.) The canonical basis state $|n_{13}, n_{23}, n_{33};\, n_{12}, n_{22};\, n_{11}\rangle$.
Constructor:

- `u3::gelfand(n13,n23,n33,n12,n22,n11)`: build a Gelfand state from its labels.

Label getters and validity check:

- `n13()` ... `n11()`: the six Gelfand-pattern labels.
- `check()`: test the betweenness condition.
- `normalize()`: shift all quantum numbers by n_{33}.

Subgroup labels:

- `lam()` / `lambda()`: the SU(3) label λ.
- `mu()`: the SU(3) label μ.
- `epsilon()`: the U(1) weight.
- `Lambdax2()`: $2\times$ the embedded SU(2) angular momentum.

- `MLambdax2()`: $2\times$ its projection.

Conjugation:

- `conjugate()`: the conjugate Gelfand state.
- `conjugate_phase()`: the associated conjugation phase.

Generator matrix elements: Each returns the matrix element of a U(3) canonical generator E_{ij} acting on a Gelfand state; a `_12`/`_22` suffix selects the target branch (either on n_{12} or n_{22}, see [1]).

- `e11()`, `e22()`, `e33()`: the diagonal weight generators.
- `e12()`: the E_{12} element.
- `e21()`: the E_{21} element.
- `e23_12()`, `e23_22()`: the E_{23} element, per target branch.
- `e32_12()`, `e32_22()`: the E_{32} element, per target branch.
- `e13_12()`, `e13_22()`: the E_{13} element, per target branch.
- `e31_12()`, `e31_22()`: the E_{31} element, per target branch.

The raising-action predicates `E12`, `E23_12`, `E23_22`, `E13_12`, `E13_22` (in `U3basis.h`) identify the target state of each generator.

D. Physical states: `u3::physicalvector`

(`U3basis.h`.) The SU(3) $\supset$ SO(3) reduced state $|(\lambda\mu)\,\kappa\,L\rangle$.
Constructor:

- `u3::physicalvector(irrep, L)`: a physical state of angular momentum L.

Accessors:

- `irr()`: the underlying irrep.
- `lam()` / `lambda()`: the SU(3) label λ.
- `mu()`: the SU(3) label μ.
- `n13()`, `n23()`, `n33()`: the U(3) labels.
- `L()`: the angular momentum.
- `kappa()`, `kappamax()`: the inner multiplicity of L.

E. Free functions

Multiplicities:

- `u3::Kappa(irrep,L)`: inner multiplicity $\kappa_{\max}$ (also `kmax`, `mult`).
- `u3::Rho(A,B,C)`: outer multiplicity $\rho_{\max}$ of irrep C in $A \otimes B$ product (`U3decomposition.h`).

Bases:

- `u3::gelfandBasis(irrep)`: all Gelfand states of the irrep.
- `u3::physicalBasis(irrep)`: all physical states with nonzero κ.
- `u3::findGelfand(g,gArr)`: the index of a state within the `gArr` Gelfand basis.

Decomposition:

- `u3::decomposition(A,B)`: the full Kronecker series, returning (list of C, list of $\rho_{\max}$) with $\sum_C \rho_{\max}(C) \dim C = \dim A \dim B$.

Physical generator reduced matrix elements: Each takes two `physicalvector` states (bra, ket) and two `std::vector<int>` out-parameters (which receive the zero-based multiplicity labels), and returns an `Eigen::MatrixXd` of shape $\kappa'_{\max} \times \kappa_{\max}$.

- `RME_L`: the angular-momentum RME, $\langle (\lambda\mu)\kappa' L' \| \mathbf{L} \| (\lambda\mu)\kappa L \rangle = \delta_{L'L}\sqrt{L(L{+}1)(2L{+}1)}$.
- `RME_Q`: the quadrupole RME, carrying an extra $\sqrt{2L'+1}$ (Sec. III H).

Transformation: Both expand a physical state `p` in the Gelfand basis `gArr`, returning the canonical-state indices and an amplitude matrix with one orthonormal column per κ.

- `u3::phys_to_cano(p,M,gArr)`: the expansion at a single projection M.
- `u3::phys_to_cano_allM(p,gArr)`: the expansion over all M.

F. Coefficient containers

(`Definitions.h`.) Every container provides `operator()(...)`, `operator[](i)`, a member `print()` method, and stream insertion via `operator<<`. The indexing operators return a writable reference for a non-const C++ container and a value for a const container. They access the same coefficients using different indexing schemes:

- `block(i0,...,id)` selects a coefficient by its multiplicity indices, in the order listed for each container below. Each index starts at zero and is smaller than its corresponding `*max()` count.
- `block[i]` selects a coefficient by a single flat index, $0 \le i <$ `block.size()`. For axis sizes $d_0, \ldots, d_{m-1}$, the equivalent flat index is $i = \sum_{j=0}^{m-1} i_j \prod_{k=j+1}^{m-1} d_k$, where an empty product is one. Thus, for a four-axis container, $i = ((i_0 d_1 + i_1)d_2 + i_2)d_3 + i_3$.
- `data()` exposes the underlying flat buffer; `size()` gives its number of coefficients; and `empty()` tests whether it contains no coefficients.
- `print(s)` and `s << block`: output a formatted table of all multiplicity indices and their corresponding values to the stream `s` (defaulting to `std::cout` for `print()`).

In the equations below, A, B, C, D denote U(3) irreps, and AB, BC, AC, BD, CD denote selected intermediate irreps in the indicated tensor products, rather than the tensor products themselves. The total irrep is denoted by T for three- and four-irrep recoupling. Each ρ labels a particular occurrence of an output irrep in its coupling channel; κ resolves repeated angular momenta within an SU(3) irrep. The multiplicity indices in these equations use the library's zero-based indexing.

`U3U2`: canonical coupling of $A \otimes B \to C$, reduced with respect to U(2): $\langle Aa; Bb \| Cc \rangle_\rho$, where a, b, c are their fixed U(2) sublabels $[n_{12}, n_{22}]$. Only the outer multiplicity varies within the container, so `block(rho)` and `block[rho]` are identical.

- `rhomax()`: the outer multiplicity $\rho_{\max}$.
- `operator()(rho)`: indexed by ρ.
- `print(s = std::cout)`: prints the coefficient row over ρ.

`U3SO3`: physical coupling of $A \otimes B \to C$, reduced with respect to SO(3): $\langle A\,\kappa_A L_A;\, B\,\kappa_B L_B \| C\,\kappa_C L_C \rangle_\rho$, where L_A, L_B, L_C are fixed angular momenta. The three inner multiplicities and the outer multiplicity are the four container axes.

- `kappaAmax()`: inner multiplicity $\kappa_{A,\max}$.
- `kappaBmax()`: inner multiplicity $\kappa_{B,\max}$.
- `kappaCmax()`: inner multiplicity $\kappa_{C,\max}$.

- `rhomax()`: the outer multiplicity $\rho_{\max}$.
- `operator()(kappaA,kappaB,kappaC,rho)`.
- `print(s = std::cout)`: tabular print over $(\kappa_A, \kappa_B, \kappa_C, \rho)$.

`U3U6`: U-recoupling: $U(A, B, T, C;\ AB, \rho_{AB}, \rho_{AB_C};\ BC, \rho_{BC}, \rho_{A_BC})$. The labels ρ_{AB_C} and ρ_{A_BC} resolve the final couplings $AB \otimes C \to T$ and $A \otimes BC \to T$, respectively.

- `rhoABmax()`: multiplicity of the $A \otimes B \to AB$ coupling.
- `rhoAB_Cmax()`: multiplicity of the $AB \otimes C$ coupling.
- `rhoBCmax()`: multiplicity of the $B \otimes C \to BC$ coupling.
- `rhoA_BCmax()`: multiplicity of the $A \otimes BC$ coupling.
- `operator()(rhoAB,rhoAB_C,rhoBC,rhoA_BC)`.
- `print(s = std::cout)`: tabular print over $(\rho_{AB}, \rho_{AB_C}, \rho_{BC}, \rho_{A_BC})$.

`U3Z6`: Z-recoupling: $Z(B, A, T, C;\ AB, \rho_{AB}, \rho_{AB_C};\ AC, \rho_{AC}, \rho_{AC_B})$. The labels ρ_{AB_C} and ρ_{AC_B} resolve the couplings $AB \otimes C \to T$ and $AC \otimes B \to T$, respectively.

- `rhoABmax()`: multiplicity of the $A \otimes B \to AB$ coupling.
- `rhoAB_Cmax()`: multiplicity of the $AB \otimes C$ coupling.
- `rhoACmax()`: multiplicity of the $A \otimes C \to AC$ channel.
- `rhoAC_Bmax()`: multiplicity of the $AC \otimes B$ channel.
- `operator()(rhoAB,rhoAB_C,rhoAC,rhoAC_B)`.
- `print(s = std::cout)`: tabular print over $(\rho_{AB}, \rho_{AB_C}, \rho_{AC}, \rho_{AC_B})$.

`U3U9`: 9-U(3) recoupling:

$$\begin{bmatrix} A & B & AB & \rho_{AB} \\ C & D & CD & \rho_{CD} \\ AC & BD & T & \rho_{AC_BD} \\ \rho_{AC} & \rho_{BD} & \rho_{AB_CD} & \end{bmatrix}. \tag{1}$$

The rightmost entries label the row couplings, and the bottom entries label the column couplings. In particular, ρ_{AB_CD} labels $AB \otimes CD \to T$ and is named `rhoABCD` in the code; ρ_{AC_BD} labels $AC \otimes BD \to T$ and is named `rhoACBD`. The container's axis order is $(\rho_{AC}, \rho_{BD}, \rho_{AB_CD}, \rho_{AB}, \rho_{CD}, \rho_{AC_BD})$.

- `rhoACmax()`: multiplicity of the $A \otimes C \to AC$ coupling.
- `rhoBDmax()`: multiplicity of the $B \otimes D \to BD$ coupling.
- `rhoABCDmax()`: multiplicity of the $AB \otimes CD \to T$ route.
- `rhoABmax()`: multiplicity of the $A \otimes B \to AB$ coupling.
- `rhoCDmax()`: multiplicity of the $C \otimes D \to CD$ coupling.
- `rhoACBDmax()`: multiplicity of the $AC \otimes BD \to T$ route.
- `operator()(rhoAC,rhoBD,rhoABCD,rhoAB,rhoCD,rhoACBD)`.
- `print(s = std::cout)`: tabular print over all six recoupling multiplicity axes.

In C++ the `U3U9` result is a view into a thread-local scratch buffer that the next database call overwrites; copy it before the next call. The other four own their buffers.

G. Coefficient databases

All coupling and recoupling coefficients are computed on demand and cached inside singleton database instances: `u3::wigU3U2db()`, `u3::wigU3SO3db()`, `u3::u3u6db()`, `u3::u3z6db()`, and `u3::u3u9db()`. The library exposes two complementary access tiers:

- **Structured container getters** (`get_U3U2`, `get_U3SO3`, `get_U3U6`, `get_U3Z6`, `get_U3U9`): return the dedicated multidimensional containers described above (`U3U2`, `U3SO3`, `U3U6`, `U3Z6`, `U3U9`). These containers support multi-index coordinate access via `operator()`, linear flat indexing via `operator[]`, shape accessors (`*max()`), and formatted stream printing.
- **Direct and flat-buffer getters** (`get`): return contiguous buffers without container wrapper overhead.

The available getters across the five databases are:

- **Canonical coupling database** (`u3::wigU3U2db()`):
  - `get_U3U2(` $n^a_{13}, n^a_{23}, n^a_{33}, n^a_{12}, n^a_{22},\ \ldots^b,\ \ldots^c$ `)` → `U3U2`: structured container over ρ.
  - `get(` $n^a_{13}, n^a_{23}, n^a_{33}, n^a_{12}, n^a_{22},\ \ldots^b,\ \ldots^c$ `)` → `Eigen::RowVectorXd`: direct row vector of reduced coupling coefficients $\langle Aa; Bb || Cc \rangle_\rho$ across all outer multiplicities $\rho = 0, \ldots, \rho_{\max} - 1$. Returns an empty vector if the coupling is forbidden or outside branching rules.
- **Physical coupling database** (`u3::wigU3SO3db()`):
  - `get_U3SO3(` $\lambda_1, \mu_1, L_1,\ \ \lambda_2, \mu_2, L_2,\ \ \lambda_3, \mu_3, L_3$ `)` → `U3SO3`: structured 4D container indexed by $(\kappa_A, \kappa_B, \kappa_C, \rho)$.
  - `get(` $\lambda_1, \mu_1, L_1,\ \lambda_2, \mu_2, L_2,\ \lambda_3, \mu_3, L_3$ `)` → `std::vector<double>`: flat coefficient buffer laid out in row-major order of $(\kappa_A, \kappa_B, \kappa_C, \rho)$, with size $\kappa_{A,\max}\kappa_{B,\max}\kappa_{C,\max}\rho_{\max}$.
- **U-recoupling database** (`u3::u3u6db()`):
  - `get_U3U6(` $A, B, ABC, C, AB,\ \rho_{AB}, \rho_{AB_C},\ BC, \rho_{BC}, \rho_{A_BC}$ `)` → `U3U6`: structured container indexed by $(\rho_{AB}, \rho_{AB_C}, \rho_{BC}, \rho_{A_BC})$.
  - `get(` $A, B, ABC, C, AB,\ \rho_{AB}, \rho_{AB_C},\ BC, \rho_{BC}, \rho_{A_BC}$ `)` → `std::vector<double>`: flat buffer of length $\rho_{AB}\rho_{AB_C}\rho_{BC}\rho_{A_BC}$.
  - `get(` $n^a_{13}, n^a_{23}, n^a_{33},\ \ldots,\ n^{bc}_{13}, n^{bc}_{23}, n^{bc}_{33}$ `)` (18 integers) → `std::vector<double>`: raw-integer overload taking the partition labels of A, B, ABC, C, AB, BC directly, computing intermediate ρ maxima internally.
- **Z-recoupling database** (`u3::u3z6db()`):
  - `get_U3Z6(` $B, A, ABC, C, AB,\ \rho_{AB}, \rho_{AB_C},\ AC, \rho_{AC}, \rho_{AC_B}$ `)` → `U3Z6`: structured container indexed by $(\rho_{AB}, \rho_{AB_C}, \rho_{AC}, \rho_{AC_B})$ (note the leading B, A exchanging the first pair).
  - `get(` $B, A, ABC, C, AB,\ \rho_{AB}, \rho_{AB_C},\ AC, \rho_{AC}, \rho_{AC_B}$ `)` → `std::vector<double>`: flat buffer of length $\rho_{AB}\rho_{AB_C}\rho_{AC}\rho_{AC_B}$.
  - `get(` $n^b_{13}, n^b_{23}, n^b_{33},\ \ldots,\ n^{ac}_{13}, n^{ac}_{23}, n^{ac}_{33}$ `)` (18 integers) → `std::vector<double>`: raw-integer overload taking the partition labels of B, A, ABC, C, AB, AC directly.
- **9-**U(3) **recoupling database** (`u3::u3u9db()`):
  - `get_U3U9(` $A, B, C, D, AB, CD, AC, BD, ABCD,\ \rho_{AC}, \rho_{BD}, \rho_{ABCD}, \rho_{AB}, \rho_{CD}, \rho_{ACBD}$ `)` → `U3U9`: structured container view. Multiplicity parameters follow the container's axis order: column intermediate channels $(\rho_{AC}, \rho_{BD}, \rho_{ABCD})$ followed by row intermediate channels $(\rho_{AB}, \rho_{CD}, \rho_{ACBD})$.
  - `get(` $A, B, C, D, AB, CD, AC, BD, ABCD,\ \rho_{AB}, \rho_{CD}, \rho_{ABCD}, \rho_{AC}, \rho_{BD}, \rho_{ACBD}$ `)` → `std::span<const double>` (or `std::vector<double>`): flat buffer of length $\rho_{AC}\rho_{BD}\rho_{ABCD}\rho_{AB}\rho_{CD}\rho_{ACBD}$. **Note the multiplicity ordering difference**: in `get`, intermediate row channels $(\rho_{AB}, \rho_{CD}, \rho_{ABCD})$ precede column channels $(\rho_{AC}, \rho_{BD}, \rho_{ACBD})$, whereas in `get_U3U9` the column channels appear first to match internal storage strides.
  - `get(` $n^a_{13}, n^a_{23}, n^a_{33},\ \ldots,\ n^{abcd}_{13}, n^{abcd}_{23}, n^{abcd}_{33}$ `)` (27 integers) → `std::vector<double>`: raw-integer overload taking the partition labels of all 9 participating irreps.

The multiplicity maxima passed to recoupling routines must match the exact `Rho` values for the corresponding channels; a mismatch trips an internal assertion. A forbidden or empty coupling returns an empty container or buffer (safe to query for shape, not to index).

Each database singleton provides a `clear()` member function (and `u3::clear()` flushes all five) to purge cached coefficient blocks while retaining allocated thread workspaces.

H. Conventions and normalization

Phase and normalization conventions follow Ref. [1]; documented values and the generation procedure are in `test/reference/`.

- **Multiplicity indexing:** Counts come from `Kappa`/`Rho`; container accessors use zero-based indices.
- **Canonical-coupling phase:** For each ρ block the phase and normalization are fixed by the highest-weight reduced coefficients—the orthonormal null space of the system imposed by E_{23} and E_{12} annihilating the highest-weight coupled state. For $\rho_{\max} > 1$ (and self-conjugate irreps) the solver fixes *a* valid orthonormal ρ basis (Row Reduced Echelon Form + Gram-Schmidt + positive leading sign); any alternative must be applied consistently to every ρ-carrying coefficient. Conjugation of a Gelfand state satisfies $C\,|g\rangle = (-1)^{n_{23}-n_{12}-n_{22}-n_{11}}\,|g.\text{conjugate}()\rangle$ (`gelfand::conjugate_phase()`).
- **Physical-to-canonical transformation:** A physical SO(3) state $|(\lambda\mu)\,\kappa\,L\,M\rangle$ is expanded in canonical Gelfand states $|g\rangle$ with $M = e_{11} - e_{22} = 2n_{11} - (n_{12} + n_{22})$. The highest-weight state $M = L$ belongs to the null space of L_+; L_- fixes the lower-M phases within a κ multiplet. Distinct conjugate irreps obey $C\,|(\lambda\mu)\,\kappa\,L\,M\rangle = (-1)^{\lambda+\mu-L+M}\,|(\mu\lambda)\,\kappa\,L,-M\rangle$ (for $\lambda > \mu$ the transformation is built from the conjugate irrep with the phase factor $(-1)^{n_{22}+n_{11}-L}$). For a self-conjugate irrep (λ,λ) conjugation acts as an M-independent symmetric matrix D ($D^2 = \mathbb{1}$) that may mix κ.
- **Generator reduced matrix element factor:** `RME_L`/`RME_Q` carry an extra $\sqrt{2L'+1}$, so $\langle\kappa L\|\mathbf{Q}\|\kappa' L'\rangle = (-1)^{L-L'}\langle\kappa' L'\|\mathbf{Q}\|\kappa L\rangle$.
- **Assertions are on.** Invalid labels or out-of-range indices abort via assertion.

IV. PYTHON BINDINGS

The module `u3lib` mirrors the C++ API one-to-one; build it with `make python` and the interpreter whose ABI matches the extension. Irreps (`su3.irrep`, `irrep`), `gelfand`, `physicalvector`, the free functions `Rho`, `Kappa`, `decomposition`, `gelfandBasis`, `physicalBasis`, the physical-generator reduced matrix elements `RME_L`/`RME_Q`, the transformation `phys_to_cano`/`phys_to_cano_allM`, and the five database accessors are all exposed with the same names and semantics as Sec. III. The structured containers provide `__call__` (multiplicity-indexed), flat `data()` as a NumPy array, and formatted printing via `print()` and `__str__`; database access before `initialize()` or after `finalize()` raises `RuntimeError` rather than aborting. The `U3U9` container, a scratch-buffer view in C++, is copied into owning storage automatically in Python. A worked introduction covering irreps, bases, coupling, and recoupling is provided as a Jupyter notebook, `python/tutorial.ipynb`; build and toolchain details are in the top-level `README.md`.

V. AI-READY INTERFACE

A. Skill catalog and orchestration

`u3lib` ships a repository-local catalog of agent-ready skills under `agents/`: an index (`agents/AGENTS.md`), shared runtime instructions, and one skill per capability. Each skill states its inputs, the exact library call, the convention, and a built-in numerical check. A code-executing AI assistant pointed at the catalog carries out the requested computation using the configured local library; no network service is involved. The catalog also provides an `install` skill (`agents/install/SKILL.md`). On a fresh checkout the agent builds the library first—`make config` to resolve or download the dependencies, then `make` and `make test`—before running any calculation skill. Table II lists each skill with a representative prompt; the parenthetical results were checked against the library, so each prompt doubles as a self-test.

Skill	Example prompt (expected result)
`dim`	"Dimension of the SU(3) irrep $(2,1)$ – equivalently the U(3) irrep $[3,1,0]$ or any shift such as $[4,2,1]$?" (15; shift-invariant)
`casimirs`	"C_2, C_3 for the SU(3) irrep $(3,1)$, and C_1, C_2, C_3 for the U(3) irrep $[4,2,1]$." (SU(3): 50/3, 160/9; U(3): C_1=7, 32/3, 56/9, U(3)-only)
`cano-list`	"Enumerate the canonical Gelfand basis of $(2,0)$ with each state's $\epsilon, 2\Lambda, 2M$ labels." (6 states)
`phys-list`	"List the physical SO(3) basis (κ, L) of $(4,2)$ and verify the dimension sum rule." (L=6, 5, 4, 3, 2, 0 with κ=1, 1, 2, 1, 2, 1; $\sum \kappa(2L{+}1)$=60)
`cano-generators`	"Act with E_{12} on the Gelfand state $\lvert 2,0,0;2,0;1\rangle$ of $(2,0)$; give the resulting state and matrix element." ($\lvert 2,0,0;2,0;2\rangle$ with $\sqrt{2}$)
`phys-generators`	"Compute $\langle (2,0)\,\kappa{=}1\,L{=}2 \Vert \mathbf{Q} \Vert (2,0)\,\kappa{=}1\,L{=}2\rangle$ and $\langle \Vert \mathbf{L} \Vert \rangle$." ($\sqrt{35/3} \approx 3.416$ and $\sqrt{30} \approx 5.477$)
`phys-to-cano`	"Express $\lvert (2,0)\,\kappa{=}1\,L{=}2\,M{=}0\rangle$ in the canonical Gelfand basis." (amplitudes $\sqrt{1/3}, \sqrt{2/3}$)
`inner-mult`	"SO(3) multiplicity κ of L=2 in $(4,2)$?" (2)
`outer-mult`	"Outer multiplicity ρ of $(1,1)$ in $(1,1)\otimes(1,1)$?" (2)
`decomposition`	"Full decomposition of $(2,0)\otimes(0,2)$ with outer multiplicities; check the dimension sum rule." ($(2,2){+}(1,1){+}(0,0)$)
`cano-coupling`	"U(3)⊃U(2) reduced coupling for highest-weight states $[2,0,0]\,[2,0]\times[2,0,0]\,[2,0] \to [4,0,0]\,[4,0]$ of $(2,0)\times(2,0)\to(4,0)$; verify it equals 1."
`phys-coupling`	"SO(3)-reduced coupling $(2,0)\,\kappa{=}1\,L{=}2 \times (2,0)\,\kappa{=}1\,L{=}2 \to (4,0)\,\kappa{=}1\,L{=}2$; check against $-\sqrt{2/9}$."
`u6recoupling`	"U-recoupling for $(1,0)\otimes(1,0)\otimes(1,0)\to(3,0)$ through intermediate irreps $AB=(2,0)$ and $BC=(2,0)$." (1)
`z6recoupling`	"Z-recoupling between $(AB)C$ and $(AC)B$ routes for $(1,0)\otimes(1,0)\otimes(1,0)\to(3,0)$ with intermediate irreps $AB=(2,0)$ and $AC=(2,0)$." (1)
`u9recoupling`	"9-$(\lambda\mu)$ recoupling for four fundamentals $(1,0)$ coupling to $(4,0)$ with intermediate irreps $AB=CD=AC=BD=(2,0)$." (1)
`conjugation`	"Conjugate the SU(3) irrep $(2,1)$ and its Gelfand states, reporting the phases." (irrep $\to(1,2)$, phase power -1)

TABLE II: The `u3lib` agent skills with a representative prompt for each.

It is important to be precise about what the agent does and does not do. The agent performs no physics and no mathematics itself. Its role is orchestration: from a natural-language request it selects the matching skill, constructs valid inputs in the library's conventions, invokes the compiled C++/Python routine, and reports the returned numbers with their labels and the check that was run. All numerical work is done by the library; the agent is an interface that routes a request to the correct tool and formats the result, and it declines or asks for clarification when a request is ill-posed (e.g., a request for the first-order Casimir of an SU(3) irrep, which is not defined).

B. Evaluation objectives

To evaluate the practical value of the skill catalog, we compare autonomous coding agents with and without access to the skills. The central question is whether they improve task completion efficiency and correctness, and whether their benefit varies with the implementation complexity of the task. We examine two hypotheses:

1. Resource efficiency: Domain skills reduce token consumption, execution time, and API cost by supplying conventions and usage patterns that the agent would otherwise need to discover from the source.

2. Dependence on task complexity: The benefit increases as tasks move from Python integration to C++ workspace management and parallel execution, where memory ownership and thread-safety requirements introduce additional constraints.

C. Experimental methodology

1. Benchmark Tasks

To examine how the benefit of domain skills varies with task complexity, we formulated three benchmark tasks spanning Python integration, C++ workspace management, and parallel execution:

- Task 1: Python Racah recoupling (`consumer/recouple.py`). A standalone Python utility computing U- and Z-recoupling coefficients through the pybind11 interface and verifying unitary symmetry relations across fundamental representations (e.g. $(1,0)\times(1,0)\times(1,0) \to (3,0)$). *Architectural complexity: low* (declarative bindings, automatic memory, single-threaded).
- Task 2: C++ 9-U(3) batch exporter (`consumer/u9_batch.cpp`). A C++ executable evaluating 9-U(3) blocks via `u3::u3u9db()`: it parses the multi-irrep label specification, computes intermediate outer multiplicities, and serializes block and entry records, copying scratch-buffer views into owning storage to avoid aliasing across iterations. *Architectural complexity: medium* (C++ typing, headers, manual workspace lifecycle).
- Task 3: C++ multi-threaded coupling (`consumer/coupling_batch.cpp`). Parallel canonical- and physical-basis coupling with OpenMP (`#pragma omp parallel for`), requiring thread-private scratch workspaces to avoid races on the null-space solver, correct `-fopenmp` configuration, and deterministic output. *Architectural complexity: high* (shared-memory concurrency, thread-private state isolation).

2. Sandbox Isolation and Cleanroom Protocol

To ensure reproducibility and prevent cross-trial contamination, every benchmark run was conducted in a strictly isolated, disposable sandbox directory equipped with an independent consumer build environment. A zero-leak snapshot protocol was strictly enforced:

- Control (zero skills): a pristine checkout with all skills (`agents/`) removed—full source, headers, and build scripts, but no catalog, as an agent would meet an unfamiliar codebase.
- Treatment (domain skills): the same workspace plus the repository-local skill catalog indexed by `agents/AGENTS.md`, which the prompt directed the agent to consult.

3. Blinded Evaluation and Grader Mutation Validation

During trial execution, the agent operated autonomously with full bash tool capabilities (file viewing, file editing, directory inspection, and command execution). Upon the agent declaring task completion (or upon reaching a hard limit of 50 agent steps), the environment was locked, and an automated grading harness evaluated the consumer artifact against a hidden validation suite, which determined functional correctness by asserting numerical agreement (within 10^{-12} tolerance) against exact group-theoretical coupling and recoupling values across diverse irrep representations. To ensure the integrity of the evaluation harness itself, the grading suite was subjected to prior mutation testing: intentional phase inversions, memory leaks, uninitialized buffer reads, and artificial race conditions were injected into reference implementations. The grader achieved 100% sensitivity and specificity, confirming zero false positives and zero false negatives.

4. Model and Statistical Protocol

All experiments used Anthropic's Claude 3.5 Sonnet under an autonomous agentic harness. For each task, $N = 10$ matched Control/Treatment pairs were run (60 trajectories total), recording four metrics per run: functional pass rate; total token consumption (prompt, cache-read, and completion tokens); wall-clock latency; and API cost at official token pricing. Significance was assessed with two-tailed Welch's t-tests (unequal variance), reporting t, degrees of freedom, and p.

TABLE III: Empirical performance comparison between Control (Zero Skills) and Treatment (Domain Skills) across $N = 10$ independent matched pairs per task (60 runs total) using Claude 3.5 Sonnet. Tokens, execution duration, and costs are reported as Mean ± Standard Deviation. Statistical significance is assessed via two-tailed Welch's t-tests.

Task	Condition	Pass Rate	Total Tokens	Time (s)	Cost ($)	Token Δ	Time Δ
Task 1	Control (N=10)	100% (10/10)	$381,613 \pm 80,140$	58.90 ± 10.51	$0.2780	—	—
	Treatment (N=10)	100% (10/10)	$270,260 \pm 93,890$	46.61 ± 7.88	$0.2280	**−29.2%***	**−20.9%****
Task 2	Control (N=10)	100% (10/10)	$614,511 \pm 144,848$	105.21 ± 20.86	$0.3751	—	—
	Treatment (N=10)	100% (10/10)	$329,829 \pm 62,106$	71.42 ± 7.74	$0.2499	**−46.3%*****	**−32.1%*****
Task 3	Control (N=10)	90.0% (9/10)	$654,185 \pm 163,874$	110.73 ± 18.35	$0.3934	—	—
	Treatment (N=10)	100% (10/10)	$320,246 \pm 141,267$	65.89 ± 15.71	$0.2459	**−51.0%*****	**−40.5%*****
Aggregate	Control (N=30)	96.7% (29/30)	$550,103 \pm 178,309$	91.61 ± 28.85	$0.3488	—	—
	Treatment (N=30)	100% (30/30)	$306,778 \pm 104,076$	61.31 ± 15.21	$0.2413	**−44.2%*****	**−33.1%*****

$^{*}p < 0.05$ ($t = -2.85$); $^{**}p < 0.01$ ($t = -2.96$); $^{***}p < 0.001$ (Task 2: $t_{\text{tok}} = -5.71, t_{\text{time}} = -4.80$;
Task 3: $t_{\text{tok}} = -4.88, t_{\text{time}} = -5.87$; Grand Aggregate: $t_{\text{tok}} = -6.46, t_{\text{time}} = -5.09$; Welch's two-tailed t-test).

D. Results and discussion

1. Overall Quantitative Findings

The empirical results across all 60 benchmark evaluations are summarized in Table III and illustrated graphically in Fig. 1. Across the entire benchmark suite:

- Token Consumption: Providing domain skills reduced mean token consumption from $550,103 \pm 178,309$ tokens to $306,778 \pm 104,076$ tokens—an aggregate reduction of 44.2% ($t = -6.46$, $p = 6.0 \times 10^{-8}$, Welch's t-test).
- Execution Latency: Wall-clock execution time decreased from 91.61 ± 28.85 s to 61.31 ± 15.21 s, representing an aggregate speedup of 33.1% ($t = -5.09$, $p = 7.2 \times 10^{-6}$).
- API Cost: Direct inference costs fell from an average of $0.3488 to $0.2413 per task (−30.8%, $t = -7.16$, $p = 4.4 \times 10^{-9}$).
- Reliability: Treatment runs achieved a 100% pass rate across all 30 evaluations. In contrast, Control runs suffered a failure on Task 3 (9/10), resulting in an aggregate pass rate of 96.7%.

2. Dependence on task complexity

For the three tasks considered here, the relative reductions in token consumption and execution time increase with the intended progression in task complexity:

$$\Delta_{\text{tokens}} = -29.2\% \text{ (Task 1)} \longrightarrow -46.3\% \text{ (Task 2)} \longrightarrow -51.0\% \text{ (Task 3)},$$
$$\Delta_{\text{time}} = -20.9\% \text{ (Task 1)} \longrightarrow -32.1\% \text{ (Task 2)} \longrightarrow -40.5\% \text{ (Task 3)}.$$

This trend is consistent with the hypothesis that explicit guidance becomes more useful as implementation constraints increase. Three tasks alone do not establish a general scaling law; the following observations describe agent behavior within this benchmark:

1. Task 1 (exploration tax): Unassisted Control agents produced correct recoupling solutions but paid a heavy exploration tax—typically 3–6 shell turns (`grep`, `ls`, inspecting pybind11 modules) to discover the exposed bindings (`u3lib.u6recoupling`, `u3lib.z6recoupling`) and their argument order. Treatment agents retrieved the signatures directly from the catalog, finishing in 16.6 steps versus 22.8 for Control.
2. Task 2 (scratch-buffer aliasing): The 9-U(3) database (`u3::u3u9db()`) returns views into internal scratch buffers reused across queries. Without guidance, Control agents hit aliasing bugs (later queries overwriting stored blocks), struggled to locate `U3_U9Coeffs.h`, and misordered the multiplicity strides, inflating consumption to $614,511$ tokens on average (worst case exceeding $853,000$). Treatment agents followed the recipe—copying views into owning storage and indexing correctly—and ran cleanly in $329,829$ tokens with about half the variance.




FIG. 1: Benchmark results comparing autonomous agent performance between Control (Zero Skills) and Treatment (Domain Skills) across $N = 10$ independent trials per task. (a) Total token consumption (thousands) by task, showing monotonic savings of 29.2%, 46.3%, and 51.0%. (b) Wall-clock execution duration (seconds) by task, showing speedups of 20.9%, 32.1%, and 40.5%. Error bars indicate ±1 sample standard deviation.

3. Task 3 (concurrency): Because the C++ null-space solver mutates internal scratch memory during factorization, naively sharing a database across threads races. One Control run (`task3-control-2`) failed the hidden tests after chasing non-deterministic segfaults; even successful Control runs averaged 33.6 steps and 110.7 s to find the need for thread-private workspaces. Treatment agents applied the skill's OpenMP guidance from the first turn, finishing deterministically in 65.89 s and 320,246 tokens.

3. *Implications for scientific software*

These results support the use of repository-local domain skills to document the mathematical conventions and implementation constraints that an autonomous agent must follow. In this benchmark, the skills reduced aggregate token consumption by 44.2% and execution time by 33.1%, while all treatment runs passed the validation suite. The single control failure occurred in the parallel C++ task. These observations motivate further evaluation across models and tasks; they do not establish that skills guarantee correctness or eliminate concurrency errors in general.

VI. BUILD AND INSTALLATION

`u3lib` is header-only; user programs include the headers in `include/` directly. The source is hosted publicly at https://github.com/Deep-SANE/u3lib. The build resolves dependency paths from a configuration environment rather than hardcoded paths; after sourcing it from the repository root the make targets are `make` (example programs → `bin/`), `make test` (build and run the regression suite), and `make python` (the pybind11 extension). The regression tests check dimensions, Gelfand interlacing and ordering, SO(3) branching, canonical/physical coupling orthonormality across κ and ρ, conjugation identities, and documented analytic values; numerical agreement is tolerance-based rather than bitwise-identical across backends.

The external libraries are resolved by `make config` (which writes `config/config.generated.mk`); they are either downloaded from their pinned upstream sources and built locally under `external-libs/` (not part of the repository), or taken from an existing install:

- `libwignernj`: https://github.com/susilehtola/libwignernj
- `sns`: https://gitlab.fit.cvut.cz/krastale/dp-sparse-nullspace
- `Eigen3`: https://eigen.tuxfamily.org
- `Boost`: https://www.boost.org

- `OpenMP` (via the compiler runtime, e.g. GCC's libgomp): https://www.openmp.org
- `fmt`: https://github.com/fmtlib/fmt
- `pybind11`: https://github.com/pybind/pybind11

Acknowledgments

This work is dedicated to the memory of J. P. Draayer, who passed on September 13, 2026 and whose pioneering contributions to algebraic computational nuclear physics through Elliott's SU(3) model, the Symplectic Sp(3, R) model, the *ab initio* Symmetry-Adapted No-Core Shell Model, and his recent effort in Wigner's SU(4) model inspired this framework. The authors also gratefully acknowledge F. Pan and D. Kekejian for valuable discussions. PD was supported by the Institute of International Education through the Quad Fellowship, Louisiana State University, and Quantum CodeX. DL and TD were funded by Quantum CodeX.

[1] P. Dang, J. P. Draayer, F. Pan, and K. S. Becker, "New Procedure for Evaluation of U(3) Coupling and Recoupling Coefficients," Eur. Phys. J. Plus **139**, 704 (2024), doi:10.1140/epjp/s13360-024-05501-8.
[2] J. P. Draayer and Y. Akiyama, "Wigner and Racah coefficients for SU_3," J. Math. Phys. **14**, 1904 (1973), doi:10.1063/1.1666267.
[3] Y. Akiyama and J. P. Draayer, "A User's Guide to Fortran Programs for Wigner and Racah Coefficients of SU_3," Comp. Phys. Comms. **5**, 405 (1973), doi:10.1016/0010-4655(73)90077-5.
[4] J. P. Elliott, "Collective motion in the nuclear shell model. I. Classification schemes for states of mixed configurations," Proc. R. Soc. Lond. A **245**, 128–145 (1958), doi:10.1098/rspa.1958.0072.
[5] J. P. Elliott, "Collective motion in the nuclear shell model II. The introduction of intrinsic wave-functions," Proc. R. Soc. Lond. A **245**, 562–581 (1958), doi:10.1098/rspa.1958.0101.
[6] T. Dytrych, K. D. Launey, J. P. Draayer, P. Maris, J. P. Vary, E. Saule, U. Catalyurek, M. Sosonkina, D. Langr, and M. A. Caprio, "Collective Modes in Light Nuclei from First Principles," Phys. Rev. Lett. **111**, 252501 (2013), doi:10.1103/PhysRevLett.111.252501.
[7] T. Dytrych, K. D. Launey, J. P. Draayer, D. J. Rowe, J. L. Wood, G. Rosensteel, C. Bahri, D. Langr, and R. B. Baker, "Physics of Nuclei: Key Role of an Emergent Symmetry," Phys. Rev. Lett. **124**, 042501 (2020), doi:10.1103/PhysRevLett.124.042501.
[8] A. E. McCoy, M. A. Caprio, T. Dytrych, and P. J. Fasano, "Emergent Sp(3, $\mathbb{R}$) Dynamical Symmetry in the Nuclear Many-Body System from an Ab Initio Description," Phys. Rev. Lett. **125**, 102505 (2020), doi:10.1103/PhysRevLett.125.102505.
[9] V. K. B. Kota, "SU(3) Symmetry in Atomic Nuclei," Springer, Singapore (2020), doi:10.1007/978-981-15-3603-8.
[10] D. Bonatsos, A. Martinou, S. K. Peroulis, T. J. Mertzimekis, and N. Minkov, "The Proxy-SU(3) Symmetry in Atomic Nuclei," Symmetry **15**, 169 (2023), doi:10.3390/sym15010169.
[11] J. Cseh, "Shell-like quarteting in heavy nuclei: Algebraic approaches based on the pseudo- and proxy-SU(3) schemes," Phys. Rev. C **101**, 054306 (2020), doi:10.1103/PhysRevC.101.054306.
[12] A. P. Zuker, J. Retamosa, A. Poves, and E. Caurier, "Spherical shell model description of rotational motion," Phys. Rev. C **52**, R1741 (1995), doi:10.1103/PhysRevC.52.R1741.
[13] J. Cseh, "Microscopic structure and mathematical background of the multiconfigurational dynamical symmetry," Phys. Rev. C **103**, 064322 (2021), doi:10.1103/PhysRevC.103.064322.
[14] C. Bahri, D. J. Rowe and J. P. Draayer, "Programs for generating Clebsch–Gordan coefficients of SU(3) in SU(2) and SO(3) bases," Comp. Phys. Comms. **159**, 121 (2004), doi:10.1016/j.cpc.2004.01.005.
[15] T. Dytrych, D. Langr, J. P. Draayer, K. D. Launey and D. Gazda, "SU3lib: A C++ library for accurate computation of Wigner and Racah coefficients of SU(3)," Comp. Phys. Comms **269**, 108137 (2021), doi:10.1016/j.cpc.2021.108137.
[16] J. Herko, M. A. Caprio, A. E. McCoy and P. J. Fasano, "A modern Fortran library for SU(3) coupling and recoupling coefficients," Eur. Phys. J. A **62**, 95 (2026), doi:10.1140/epja/s10050-026-01845-0.
[17] M. Gell-Mann, "Symmetries of Baryons and Mesons," Phys. Rev. **125**, 1067 (1962), doi:10.1103/PhysRev.125.1067.
[18] Y. Ne'eman, "Derivation of strong interactions from a gauge invariance," Nucl. Phys. **26**, 222 (1961), doi:10.1016/0029-5582(61)90134-1.
[19] D. Bacon, I. L. Chuang, and A. W. Harrow, "Efficient Quantum Circuits for Schur and Clebsch–Gordan Transforms," Phys. Rev. Lett. **97**, 170502 (2006), doi:10.1103/PhysRevLett.97.170502.
[20] C. P. Moca, A. Alex, J. von Delft, and G. Zaránd, "SU(3) Anderson impurity model: A numerical renormalization group approach exploiting non-Abelian symmetries," Phys. Rev. B **86**, 195128 (2012), doi:10.1103/PhysRevB.86.195128.
[21] S.-H. Tan, Y. Y. Gao, H. de Guise, and B. C. Sanders, "SU(3) Quantum Interferometry with Single-Photon Input Pulses," Phys. Rev. Lett. **110**, 113603 (2013), doi:10.1103/PhysRevLett.110.113603.