



Reinforcement Learning

Computer Engineering Department
Sharif University of Technology

Mohammad Hossein Rohban, Ph.D.

Spring 2025

Courtesy: Some slides are adopted from CS 285 Berkeley, and CS 234 Stanford, and Pieter Abbeel's compact series on RL.

Disadvantages of Monte-Carlo Learning

- We have seen MC algorithms can be used to learn value predictions
- But when episodes are long, learning can be slow
 - we have to **wait until an episode ends** before we can learn...
 - return can have **high variance**
 - Which one is more? First-visit or every-visit
- Are there alternatives? (Spoiler: yes)

Monte Carlo Control

→ Prediction → V^π
 Q^π

Monte-Carlo Control

Repeat:

- Pred.*
- Sample **episode** $1, \dots, k, \dots$, using $\pi: \{S_1, A_1, R_2, \dots, S_T\} \sim \pi$
 - For each state S_t and action A_t in the episode:
$$q(S_t, A_t) \leftarrow q(S_t, A_t) + \alpha_t (G_t - q(S_t, A_t))$$
 - e.g.,

$$\alpha_t = \frac{1}{N(S_t, A_t)} \quad \text{of} \quad \alpha_t = 1/k$$

- Control*
- **Improve policy** based on new action-value function

$$\pi^{new}(s) = \operatorname{argmax}_{a \in A} q(s, a)$$

Any issue?

- Let's consider this example:
- Discount = 1, start in state H.

A	B	C	D	E	F	G	H	I	J
r=10	→	→	→	→	→	↑	→	→	r=1

$H, \rightarrow, 0, I, \rightarrow, 1, J$

$$Q(H, \rightarrow) = 1$$

$$Q(I, \rightarrow) = 1$$

$$\forall s, a \quad Q(s, a) = 0$$

$$\forall s \quad \pi(s) = \underset{a}{\operatorname{argmax}} Q(s, a)$$

Epsilon Greedy Policy

- Simple idea to balance exploration and achieving rewards
- Let $|A|$ be the number of actions
- Then an ϵ -greedy policy w.r.t a state action value $Q(s, a)$ is

$$\pi(a|s) =$$

- $\arg \max_a Q(s, a)$, w. prob $1 - \epsilon + \frac{\epsilon}{|A|}$
- $a' \neq \arg \max Q(s, a)$ w. prob $\frac{\epsilon}{|A|}$

Does this hurt improvement?

Theorem

For any ϵ -greedy policy π_i , the ϵ -greedy policy w.r.t. Q^{π_i} , π_{i+1} is a monotonic improvement $V^{\pi_{i+1}} \geq V^{\pi_i}$

Monte-Carlo Control (done right)

Repeat:

- Sample **episode** $1, \dots, k, \dots$, using $\pi: \{S_1, A_1, R_2, \dots, S_T\} \sim \pi$
- For each state S_t and action A_t in the episode:

$$q(S_t, A_t) \leftarrow q(S_t, A_t) + \alpha_t (G_t - q(S_t, A_t))$$

- e.g.,

$$\alpha_t = \frac{1}{N(S_t, A_t)} \quad \text{of} \quad \alpha_t = 1/k$$

- **Improve policy** based on new action-value function

$$\pi(a|s) =$$

- $\arg \max_a Q(s, a)$, w. prob $1 - \epsilon + \frac{\epsilon}{|A|}$
- $a' \neq \arg \max Q(s, a)$ w. prob $\frac{\epsilon}{|A|}$

Disadvantages of MC Learning

- We have seen MC algorithms can be used to learn value predictions
- But when episodes are long, learning can be slow
 - ...we have to **wait until an episode ends** before we can learn
 - ...return can have **high variance**
- Are there alternatives? (Yes)

Temporal Difference Learning

Prediction

TD Overview

TD methods learn directly from episodes of experience

TD is *model-free*: no knowledge of MDP transitions / rewards

TD learns from *incomplete* episodes, by *bootstrapping*

TD updates a guess towards a guess

$$\hat{V}^{\pi}(s) = \frac{1}{n} \sum_{i=1}^n [R(s, \pi(s), s'_i) + \gamma \hat{V}^{\pi}(s'_i)]$$

Temporal Difference Learning by Sampling Bellman Equations


- Bellman update equations:

$$v_{k+1}(s) = \mathbb{E} [R_{t+1} + \gamma v_k(S_{t+1}) \mid S_t = s, A_t \sim \pi(S_t)]$$

- We can sample this!

$$v_{t+1}(S_t) = R_{t+1} + \gamma v_t(S_{t+1})$$

- Samples could be averaged, in a similar way to MC:

$$v_{t+1}(S_t) = v_t(S_t) + \alpha_t \left(\underbrace{R_{t+1} + \gamma v_t(S_{t+1})}_{\text{target}} - v_t(S_t) \right)$$


temporal difference error δ_t

Temporal Difference Learning

- Prediction setting: learn v_π online from experience under policy π

- **Monte Carlo**

- Update value $v_n(S_t)$ towards sampled return G_t


$$v_{n+1}(S_t) = v_n(S_t) + \alpha (\mathbf{G}_t - v_n(S_t))$$

- **TD Learning**


- Update value $v_t(S_t)$ towards estimated return $R_{t+1} + \gamma v(S_{t+1})$

$$v_{t+1}(S_t) \leftarrow v_t(S_t) + \alpha \left(\underbrace{\overbrace{\mathbf{R}_{t+1} + \gamma v_t(S_{t+1})}^{\text{TD error}}}_{\text{target}} - v_t(S_t) \right)$$


Backup (Dynamic Programming)



Backup (Monte Carlo)



Backup (Temporal Difference)



Bootstrapping and Sampling

- Bootstrapping: update involves an **estimate**
 - MC does not bootstrap
 - DP bootstraps
 - TD bootstraps
- Sampling: update **samples an expectation**
 - MC samples
 - DP does not sample
 - TD samples

TD Learning for action values

- We can apply the same idea to action values
- Temporal-difference learning for action values:
 - Update value $q_t(S_t, A_t)$ towards estimated return $R_{t+1} + \gamma q(S_{t+1}, A_{t+1})$

$$q_{t+1}(S_t, A_t) \leftarrow q_t(S_t, A_t) + \alpha \left(\underbrace{R_{t+1} + \gamma q_t(S_{t+1}, A_{t+1})}_{\text{target}} - q_t(S_t, A_t) \right)$$

TD vs. MC

- **TD can learn *before* knowing the final outcome**
 - TD can learn online after every step
 - *MC must wait* until end of episode before return is known
- **TD can learn *without* the final outcome**
 - MC must wait until end of episode before return is known
 - MC can only learn from complete sequences
 - TD works in continuing (non-terminating) environments
 - *MC only works for episodic (terminating) environments*
- **TD is independent of the temporal span of the prediction**
 - TD can learn from single transitions
 - MC must store all predictions (or states) to update at the end of an episode
- **TD needs reasonable value estimates**

Temporal Difference Learning

Control

SARSA Algorithm for On-Policy Control



Initialize $Q(s, a), \forall s \in \mathcal{S}, a \in \mathcal{A}(s)$, arbitrarily, and $Q(\text{terminal-state}, \cdot) = 0$
Repeat (for each episode):
 Initialize S
 Choose A from S using policy derived from Q (e.g., ϵ -greedy)
 Repeat (for each step of episode):
 Take action A , observe R, S'
 Choose A' from S' using policy derived from Q (e.g., ϵ -greedy)
 $Q(S, A) \leftarrow Q(S, A) + \alpha[R + \gamma Q(S', A') - Q(S, A)]$
 $S \leftarrow S'; A \leftarrow A';$
 until S is terminal

Off-Policy TD and Q-Learning

On and Off-Policy Learning

- On-policy learning
 - "Learn on the job"
 - Learn about policy π from experience sampled from π
- Off-policy learning
 - "Look over someone's shoulder"
 - Learn about policy π from experience sampled from μ

Off-Policy Learning

- Evaluate target policy $\pi(a|s)$ to compute $v_\pi(s)$ or $q_\pi(s, a)$
- While using behavior policy $\mu(a, s)$ to generate actions
- Why is this important?
 - Learn from **observing humans** or other agents (e.g., from logged data)
 - **Re-use experience** from old policies (e.g., from your own past experience)
 - Learn about **multiple policies** while following one policy
 - Learn about greedy policy while **following exploratory policy**

Q-Learning

- Q-learning estimates the value of the greedy policy

$$q_{t+1}(s, a) = q_t(S_t, A_t) + \alpha_t \left(R_{t+1} + \gamma \max_{a'} q_t(S_{t+1}, a') - q_t(S_t, A_t) \right)$$

- Acting greedy all the time would not explore sufficiently

Theorem

Q-learning control converges to the optimal action-value function, $q \rightarrow q^$, as long as we take each action in each state infinitely often.*

- Note: no need for greedy behavior!
- Works for **any** policy that **eventually selects all actions sufficiently often**

Q-Learning for Off-Policy Control

```
Initialize  $Q(s, a), \forall s \in \mathcal{S}, a \in \mathcal{A}(s)$ , arbitrarily, and  $Q(\text{terminal-state}, \cdot) = 0$   
Repeat (for each episode):  
  Initialize  $S$   
  Repeat (for each step of episode):  
    Choose  $A$  from  $S$  using policy derived from  $Q$  (e.g.,  $\epsilon$ -greedy)  
    Take action  $A$ , observe  $R, S'$   
     $Q(S, A) \leftarrow Q(S, A) + \alpha [R + \gamma \max_a Q(S', a) - Q(S, A)]$   
     $S \leftarrow S'$ ;  
  until  $S$  is terminal
```