



Comment	Description	Designator	Footprint	LibRef	Quantity	Digi-Key Part Number
470	RESSMD 470 OHM 5% 1/10W 0402	R23, R24, R25, R26	SMD-0402-RES	ERJ-2GEJ471X	4	P470JCT-ND
100k	RESSMD 100K OHM 1%1/10W 0402	R4, R14	SMD-0402-RES	ERJ-2RKF1003X	2	P100KLCT-ND
10k	RESSWID 10K OHM 1% 1/10W 0402	R2, R3, R5, R7, R8, R9, R10, R11, R12, R15, R16, R17, R18, R19, R20, R21, R22	SWID-0402-RES	ERJ2RVF1002X	17	P10.0KLCT-ND
6.04k	RESSMD 6.04KOHM 1%1/10W 0402	R6	SMD-0402-RES	ERJ-2RKF6041X	1	P6.04KLCT-ND
5.1k	RESSMD 5.1K OHM 1% 1/10W 0603	R35, R36, R37	SMD-0603-RES	ERJ:3EKF5101V	3	P5.10KHCT-ND
4.7k	RESSMD 4.7K OHM 1% 1/10W 0402	R1, R13	SMD-0402-RES	ERJ-2RKF4701X	2	P4.70KLCT-ND
0.0	RESSIVID 0.00HIM JUMPER 1/10W 0603	R27, R28, R29, R30, R31, R32, R33, R34	SMD-0603-RES	ERJ-3GEY0R00V	8	P0.0GCT-ND
4.7µF	CAP CER 4.7UF 10V X5R 0402	C9	SMD-0402C	ZRB15XR61A475KE 01D	1	490-13252-1-ND
10µF	CAP CER 10UF 16V X6S 0805	C11	SMD-0805C	GRT21BC81C106KE 01L	1	490-12343-1-ND
2.2µF	CAPCER2.2UF16V	c 2	SMD-0603C	GRT188C81C225KE	1	490-12287-1-ND
10µF	X6S0603 CAP CER 10UF 16V X6S	C1, C5	SMD-0603C	13D GRT188C81C106ME	2	490-12286-1-ND
1μF	0603 CAPCER1UF25VX5R	C7, C12, C13	SMD-0402C	13D GRM155R61E105M		490-10018-1-ND
ıμı	0402	C3, C4, C6,	GVID-04020	A12D	3	450-10010-1-IND
0.10µF	CAPCERO.1UF16V X7R0402	C8, C10, C14, C15, C16, C17, C18, C19, C20, C21, C24, C25, C26, C27, C28, C29, C30, C31, C32, C33	SMD-0402C	GOW155R71C104K A55J	23	490-7998-1-ND
18pF	CAP CER 18PF 25V NPO 0402	C22, C23	SMD-0402C	GRM1555C1E180JA	2	490-6172-1-ND
4.7uH	Ind Power Chip Wirewound 4.7uH 20%7.96MHz Ferrite 1.1A 1007 T/R	L1	INDC2518X200 N	01D CB2518T4R7M	1	
10 O hm	WECBA SMT EMI Suppression Ferrite Bead, size 0402, 10Ohm, 1.5A	FB1	WE- CBA_0402_L1W 0.5H0.5_HC	782423100	1	
90Ohm	WECNSW SMT Common Mode Line Filter, size 1206, 900hm, 0.111uH, 50V	L2	WE- ONSW_1206	744232090	1	
691322110002	WR-TBL Serie 3221 Horizontal PCB Header, Pluggable, THT, pitch 3.5mm, 2p	М	691322110002	691322110002	1	
692122030100	WR-COM USB 3.0 Type A Horizontal SMT	Ji	692122030100	692122030100	1	
ABM8G-25.000MHZ-18- D-2-Y-T3	Crystal or Oscillator	Y1	ABM8G16000M HZB4YT	ABM8G-25.000MHZ 18-D-2-Y-T3	1	
DX079016JA1R1500	USB-C (USB TYPEC) USB 2.0 Receptacle Connector 24 (16+8 Dummy) Position Surface Mount, Right Angle; Through Hole	J6	JAE_DX07S016J A1R1500	DX07 S 016JA1R150 0	1	
Green	LED 0603 SMD Green 525nm 350mcd 20mA, LED 0603 SMD Green 570nm 50mcd 20mA	LED1, LED2, LED3, LED4, LED5	LED-0603- GREEN	LED_SMD_Green_0 603_525nm_350mc d, LED_SMD_Green_0 603_570nm	5	
SDR_Module		SDR1, SDR2,	SDR	SDR_Module	4	
SMA-J-P-H-ST-EM1	SMA Connector Jack, Female Socket 500hm Board Edge, End Launch Solder	SDR3, SDR4 J2, J3, J4, J5	SAMTEC_SMA-J- P-H-ST-EM1	SMA-J-P-H-ST-EM1	4	
SST25VF512A-33-4C- SAE	Integrated Circuit	102	SOIC127P600X1 75-8N	SST25VF512A-33- 4CSAE	1	
VL817-Q7_B0_	Integrated Orcuit	IC1	QFN40P900X90 0X90-77N-D	VL817-Q7 B0	1	