

The Treasure's in the Details

Jacques Carette, Musa Al-hassy, Wolfram Kahl

McMaster University, Hamilton

July 19, 2018

<https://github.com/JacquesCarette/TheoriesAndDataStructures>

WORK IN PROGRESS

DeepSpec 2018, Princeton University

A Relationship Between Mathematics and Computing Science

The Curry-Howard Correspondence

—“Propositions as Types”

Logic	Programming	Example Use in Programming
<i>true</i>	singleton type	return type of side-effect only methods
<i>false</i>	empty type	return type for non-terminating methods

A Relationship Between Mathematics and Computing Science

The Curry-Howard Correspondence

—“Propositions as Types”

Logic	Programming	Example Use in Programming
<i>true</i>	singleton type	return type of side-effect only methods
<i>false</i>	empty type	return type for non-terminating methods
\Rightarrow	function type	\rightarrow methods with an input and output type
\wedge	product type	\times simple records of data and methods
\vee	sum type	$+$ enumerations or tagged unions

A Relationship Between Mathematics and Computing Science

The Curry-Howard Correspondence

—“Propositions as Types”

Logic	Programming		Example Use in Programming
<i>true</i>	singleton type		return type of side-effect only methods
<i>false</i>	empty type		return type for non-terminating methods
\Rightarrow	function type	\rightarrow	methods with an input and output type
\wedge	product type	\times	simple records of data and methods
\vee	sum type	$+$	enumerations or tagged unions
\forall	dependent function type Π		return type varies according to input <i>value</i>
\exists	dependent product type Σ		record fields depend on each other's <i>values</i>

A Relationship Between Mathematics and Computing Science

The Curry-Howard Correspondence

—“Propositions as Types”

Logic	Programming		Example Use in Programming
<i>true</i>	singleton type		return type of side-effect only methods
<i>false</i>	empty type		return type for non-terminating methods
\Rightarrow	function type	\rightarrow	methods with an input and output type
\wedge	product type	\times	simple records of data and methods
\vee	sum type	$+$	enumerations or tagged unions
\forall	dependent function type Π		return type varies according to input <i>value</i>
\exists	dependent product type Σ		record fields depend on each other's <i>values</i>
natural deduction	type system		ensuring only “meaningful” programs
hypothesis	free variables		global variables, closures
implication elimination	function application		executing methods on arguments
implication introduction	λ -abstraction		parameters acting as local variables to method definitions

A Relationship Between Mathematics and Computing Science

Proposition *P is either true or false.*

The Curry-Howard Correspondence

—“Propositions as Types”

Logic	Programming	Example Use in Programming
<i>true</i>	singleton type	return type of side-effect only methods
<i>false</i>	empty type	return type for non-terminating methods
\Rightarrow	function type	\rightarrow methods with an input and output type
\wedge	product type	\times simple records of data and methods
\vee	sum type	$+$ enumerations or tagged unions
\forall	dependent function type Π	return type varies according to input <i>value</i>
\exists	dependent product type Σ	record fields depend on each other's <i>values</i>
natural deduction	type system	ensuring only “meaningful” programs
hypothesis	free variables	global variables, closures
implication elimination	function application	executing methods on arguments
implication introduction	λ -abstraction	parameters acting as local variables to method definitions

A Relationship Between Mathematics and Computing Science

Proposition *P is either true or false.*

The Curry-Howard Correspondence

—“Propositions as Types”

Logic	Programming	Example Use in Programming
<i>true</i>	singleton type	return type of side-effect only methods
<i>false</i>	empty type	return type for non-terminating methods
\Rightarrow	function type	\rightarrow methods with an input and output type
\wedge	product type	\times simple records of data and methods
\vee	sum type	$+$ enumerations or tagged unions
\forall	dependent function type Π	return type varies according to input <i>value</i>
\exists	dependent product type Σ	record fields depend on each other's <i>values</i>
natural deduction	type system	ensuring only “meaningful” programs
hypothesis	free variables	global variables, closures
implication elimination	function application	executing methods on arguments
Type <i>P may have more than 2 elements!</i>	λ -abstraction	parameters acting as local variables to method definitions
implication introduction		

A Relationship Between Mathematics and Computing Science

Proposition P is either true or false.

The Curry-Howard Correspondence

—“Propositions as Types”

Logic	Programming	Example Use in Programming
$true$	singleton type	return type of side-effect only methods
$false$	empty type	return type for non-terminating methods
\Rightarrow	function type	\rightarrow methods with an input and output type
\wedge	product type	\times simple records of data and methods
\vee	sum type	$+$ enumerations or tagged unions
\forall	dependent function type Π	return type varies according to input <i>value</i>
\exists	dependent product type Σ	record fields depend on each other's <i>values</i>
natural deduction	type system	ensuring only “meaningful” programs
hypothesis	free variables	global variables, closures
implication elimination	function application	executing methods on arguments
Type P may have more than 2 elements!	λ -abstraction	parameters acting as local variables to method definitions

Adjunctions, à la Prop

- 1 Try to understand *complex notion* via a transformation to a *simpler notion*.

Adjunctions, à la Prop

- ① Try to understand *complex notion* via a transformation to a *simpler notion*.
- ② Methodology: Transport *complex*-problems into *simple*-setting where they are **easier to solve**, then go back.

Adjunctions, à la Prop

- ① Try to understand *complex notion* via a transformation to a *simpler notion*.
- ② Methodology: Transport *complex*-problems into *simple*-setting where they are **easier to solve**, then go back.
- ③ Usually transformation is not invertible, but has a **best approximate inverse**:

Adjunctions, à la Prop

- ① Try to understand *complex notion* via a transformation to a *simpler notion*.
- ② Methodology: Transport *complex*-problems into *simple*-setting where they are **easier to solve**, then go back.
- ③ Usually transformation is not invertible, but has a **best approximate inverse**:

Galois Connections

$$f \dashv g \quad \equiv \quad \forall x, y \bullet f x \leq_1 y \equiv x \leq_2 g y$$

Adjunctions, à la Prop

- ① Try to understand *complex notion* via a transformation to a *simpler notion*.
- ② Methodology: Transport *complex*-problems into *simple*-setting where they are **easier to solve**, then go back.
- ③ Usually transformation is not invertible, but has a **best approximate inverse**:

Galois Connections

$$f \dashv g \quad \equiv \quad \forall x, y \bullet f x \leq_1 y \equiv x \leq_2 g y$$

For example, we can understand the complicated notion of supremum by the trivial notion of constant function:

$$\forall h, z \bullet \sup h \leq z \equiv h \dot{\leq} K z$$

- ① Try to understand *complex notion* via a transformation to a *simpler notion*.
- ② Methodology: Transport *complex*-problems into *simple*-setting where they are **easier to solve**, then go back.
- ③ Usually transformation is not invertible, but has a **best approximate inverse**:

Galois Connections

$$f \dashv g \quad \equiv \quad \forall x, y \bullet f x \leq_1 y \equiv x \leq_2 g y$$

For example, we can understand the complicated notion of supremum by the trivial notion of constant function:

$$\forall h, z \bullet \sup h \leq z \equiv h \dot{\leq} K z$$

Adjunctions, à la Prop

Easy now to show that supremum distributes over maximum

$$\sup(h \sqcup k) = \sup h \sqcup \sup k$$

- 1 Try to understand *complex notion* via a transformation to a *simpler notion*.
- 2 Methodology: Transport *complex*-problems into *simple*-setting where they are **easier to solve**, then go back.
- 3 Usually transformation is not invertible, but has a **best approximate inverse**:

Galois Connections

$$f \dashv g \quad \equiv \quad \forall x, y \bullet f x \leq_1 y \equiv x \leq_2 g y$$

For example, we can understand the complicated notion of supremum by the trivial notion of constant function:

$$\forall h, z \bullet \sup h \leq z \equiv h \dot{\leq} K z$$

Ubiquitous! Integer division: $(\times k) \dashv (\div n)$, floor: $\iota_{\mathbb{R}} \dashv \lfloor - \rfloor$,
Prefix extraction: $\text{length} \times \text{Id} \dashv \text{take}$, Binary joins: $\max \dashv \Delta$, Power sets: $\bigcup \vdash \mathbb{P}$,
Unit & empty types, residuals, colimits, Kan extensions, **Free** \vdash **Forgetful**

Adjunctions, Constructively

Proof relevance: We care about *which proof* witnesses the Galois Connection.

Adjunctions, Constructively

Proof relevance: We care about *which proof* witnesses the Galois Connection.
We make a few replacements,

Adjunctions, Constructively

Proof relevance: We care about *which proof* witnesses the Galois Connection.

We make a few replacements,

Order ' \leq ' \mapsto Morphism type constructor ' \longrightarrow '

Adjunctions, Constructively

Proof relevance: We care about *which proof* witnesses the Galois Connection.

We make a few replacements,

Order ' \leq '	\mapsto	Morphism type constructor ' \longrightarrow '
------------------	-----------	---

Equivalence ' \equiv '	\mapsto	Isomorphism ' \cong '
--------------------------	-----------	-------------------------

Adjunctions, Constructively

Proof relevance: We care about *which proof* witnesses the Galois Connection.

We make a few replacements,

Order ' \leq '	\mapsto	Morphism type constructor ' \longrightarrow '
Equivalence ' \equiv '	\mapsto	Isomorphism ' \cong '
Functions f, g between sets	\mapsto	Functors F, G between categories

Adjunctions, Constructively

Proof relevance: We care about *which proof* witnesses the Galois Connection.

We make a few replacements,

Order ' \leq '	\mapsto	Morphism type constructor ' \longrightarrow '
Equivalence ' \equiv '	\mapsto	Isomorphism ' \cong '
Functions f, g between sets	\mapsto	Functors F, G between categories

Adjunctions, Global Characterisation

$$F \dashv G \quad \equiv \quad \forall x, y \bullet (F x \longrightarrow_1 y) \cong (x \longrightarrow_2 G y)$$

Where the isomorphism is natural in x and y .

Adjunctions, Constructively

Proof relevance: We care about *which proof* witnesses the Galois Connection. We make a few replacements,

Order ‘ \leq ’	\mapsto	Morphism type constructor ‘ \longrightarrow ’
Equivalence ‘ \equiv ’	\mapsto	Isomorphism ‘ \cong ’
Functions f, g between sets	\mapsto	Functors F, G between categories

Adjunctions, Global Characterisation

$$F \dashv G \quad \equiv \quad \forall x, y \bullet (F x \longrightarrow_1 y) \cong (x \longrightarrow_2 G y)$$

Where the isomorphism is natural in x and y .

Adjunctions, Local Characterisation

$$\epsilon : FG \dashrightarrow \text{Id} \quad \text{and} \quad \eta : \text{Id} \dashrightarrow GF$$

such that the nonsensical “inverse equation $\text{Id} = \epsilon \circ \eta$ ” holds.

η is called the **unit** since FG is a monad; dually ϵ is the **counit** since GF is a comonad.

Adjunctions, Constructively

Proof relevance: We care about *which proof* witnesses the Galois Connection.
We make a few replacements,

Order ‘ \leq ’	\mapsto	Morphism type constructor ‘ \longrightarrow ’
Equivalence ‘ \equiv ’	\mapsto	Isomorphism ‘ \cong ’
Functions f, g between sets	\mapsto	Functors F, G between categories

Adjunctions, Global Characterisation

$$F \dashv G \quad \equiv \quad \forall x, y \bullet (F x \longrightarrow_1 y) \cong (x \longrightarrow_2 G y)$$

Where the isomorphism is natural in x and y .

Adjunctions, Local Characterisation

$$\epsilon : FG \dashrightarrow \text{Id} \quad \text{and} \quad \eta : \text{Id} \dashrightarrow GF$$

such that the nonsensical “inverse equation $\text{Id} = \epsilon \circ \eta$ ” holds.

η is called the **unit** since FG is a monad; dually ϵ is the **counit** since GF is a comonad.

η embeds, or *inserts*, “elements” as “singleton structures”;
whereas ϵ *extracts* “elements” from “singleton structures.”

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	NEList A	Type	Propositional

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	NEList A	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times$ List A	Type	Propositional

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	NEList A	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times$ List A	Type	Propositional
Commutative Monoid	Bag	Setoid	Proof-relevant permutations
Group	?	?	?
Abelian Group	Hybrid Sets	Setoid	Proof-relevant permutations
Idemp. Comm. Monoid	Set	Setoid	Logical equivalence

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	NEList A	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times$ List A	Type	Propositional
Commutative Monoid	Bag	Setoid	Proof-relevant permutations
Group	?	?	?
Abelian Group	Hybrid Sets	Setoid	Proof-relevant permutations
Idemp. Comm. Monoid	Set	Setoid	Logical equivalence

◇ **Free Structure** is “the” **term language in normal form** associated to the theory.

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	NEList A	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times$ List A	Type	Propositional
Commutative Monoid	Bag	Setoid	Proof-relevant permutations
Group	?	?	?
Abelian Group	Hybrid Sets	Setoid	Proof-relevant permutations
Idemp. Comm. Monoid	Set	Setoid	Logical equivalence

◇ **Free Structure** is “the” **term language in normal form** associated to the theory.

◇ \perp , \top , \mathbb{B} , \mathbb{N} , \mathbb{Z} show up as *initial objects*.

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	NEList A	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times$ List A	Type	Propositional
Commutative Monoid	Bag	Setoid	Proof-relevant permutations
Group	?	?	?
Abelian Group	Hybrid Sets	Setoid	Proof-relevant permutations
Idemp. Comm. Monoid	Set	Setoid	Logical equivalence

◇ **Free Structure** is “the” **term language in normal form** associated to the theory.

◇ \perp , \top , \mathbb{B} , \mathbb{N} , \mathbb{Z} show up as *initial objects*.

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	NEList A	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times$ List A	Type	Propositional
Commutative Monoid \Leftarrow	Bag	Setoid	Proof-irrelevant permutations
Group	?	?	?
Abelian Group	Hybrid Sets	Setoid	Proof-relevant permutations
Idemp. Comm. Monoid	Set	Setoid	Logical equivalence

◇ **Free Structure** is “the” **term language in normal form** associated to the theory.

◇ \perp , \top , \mathbb{B} , \mathbb{N} , \mathbb{Z} show up as *initial objects*.

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	$\text{NEList } A$	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times \text{List } A$	Type	Propositional
Commutative Monoid	Bag	Setoid	Proof-relevant permutations

Implementation issues!

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	$\text{NEList } A$	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times \text{List } A$	Type	Propositional
Commutative Monoid	Bag	Setoid	Proof-irrelevant permutations

Implementation issues!

◇ Inductive type \Rightarrow Ordering! Thus not free!

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	NEList A	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times$ List A	Type	Propositional
Commutative Monoid \Leftarrow	Bag	Setoid	Proof-irrelevant permutations

Implementation issues!

- ◇ Inductive type \Rightarrow Ordering! Thus not free!
- ◇ $A \rightarrow \mathbb{N} \Rightarrow$ No finite support

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	$\mathbb{N} \text{List } A$	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times \text{List } A$	Type	Propositional
Commutative Monoid	Bag	Setoid	Proof-irrelevant permutations

Implementation issues!

- ◊ Inductive type \Rightarrow Ordering! Thus not free!
- ◊ $A \rightarrow \mathbb{N} \Rightarrow$ No finite support
- \Rightarrow Finiteness hard to express constructively!

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	$\mathbb{N}\text{List } A$	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times \text{List } A$	Type	Propositional
Commutative Monoid	Bag	Setoid	Proof-relevant permutations

Implementation issues!

- ◊ Inductive type \Rightarrow Ordering! Thus not free!
- ◊ $A \rightarrow \mathbb{N}$ \Rightarrow No finite support
- \Rightarrow Finiteness hard to express constructively!
- \Rightarrow Decidable equality on A ! Thus not free!

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unary	$\mathbb{N} \times A$	Type	Propositional
Involutive	$A \uplus A$	Type	Propositional
Magma	Tree A	Type	Propositional
Semigroup	$\mathbb{N}\text{List } A$	Type	Propositional
Monoid	List A	Type	Propositional
Left Unital Semigroup	List $A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times \text{List } A$	Type	Propositional
Commutative Monoid \Leftarrow	Bag	Setoid	Proof-relevant permutations

Implementation issues!

- ◇ Inductive type \Rightarrow Ordering! Thus not free!
- ◇ $A \rightarrow \mathbb{N} \Rightarrow$ No finite support
 - \Rightarrow Finiteness hard to express constructively!
 - \Rightarrow Decidable equality on A ! Thus not free!
- ◇ List A with permutations! **Works!**

Computing Science \dashv Mathematics

Given an arbitrary type A ,

Theory	Structure	Over	Equality
Carrier	Identity A	Type	Propositional
Pointed	Maybe A	Type	Propositional
Unital Semigroup	$\text{List } A$	Type	Propositional
Monoid	$\text{List } A$	Type	Propositional
Left Unital Semigroup	$\text{List } A \times \mathbb{N}$	Type	Propositional
Right Unital Semigroup	$\mathbb{N} \times \text{List } A$	Type	Propositional
Commutative Monoid	$\text{Bag } A$	Setoid	Proof-irrelevant permutations

Theorem :: Within Martin-Löf Type Theory, there's no *free* functor from *Types* to *Commutative Monoids* using propositional equality.

Implementation issues!

- ◇ Inductive type \Rightarrow Ordering! Thus not free!
- ◇ $A \rightarrow \mathbb{N}$
 - \Rightarrow No finite support
 - \Rightarrow Finiteness hard to express constructively!
 - \Rightarrow Decidable equality on A ! Thus not free!
- ◇ $\text{List } A$ with permutations! **Works!**

Why the Mechanisation

~ 1000 lines of Agda code

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.
- Unicode and mixfix operators \Rightarrow Mechanisation is readable and not significantly more effort than a conventional presentation in LaTeX.

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.
- Unicode and mixfix operators \Rightarrow Mechanisation is readable and not significantly more effort than a conventional presentation in LaTeX.
- Agda as a type checker for doing mathematics —manipulating symbols according to specified rules. Mechanised mathematical notation \Rightarrow **Confidence in results!** Dispell silly conjectures/errors!

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.
- Unicode and mixfix operators \Rightarrow Mechanisation is readable and not significantly more effort than a conventional presentation in LaTeX.
- Agda as a type checker for doing mathematics —manipulating symbols according to specified rules. Mechanised mathematical notation \Rightarrow **Confidence in results!** Dispell silly conjectures/errors!
- Agda enables a natural treatment of theories and their direct use as modules of executable programs.

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.
- Unicode and mixfix operators \Rightarrow Mechanisation is readable and not significantly more effort than a conventional presentation in LaTeX.
- Agda as a type checker for doing mathematics —manipulating symbols according to specified rules. Mechanised mathematical notation \Rightarrow **Confidence in results!** Dispell silly conjectures/errors!
- Agda enables a natural treatment of theories and their direct use as modules of executable programs.
- Finally, formal proofs are fool-proof! **No “an exercise to the reader”!**

Why the Mechanisation

~ 1000 lines of Agda code

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.
- Unicode and mixfix operators \Rightarrow Mechanisation is readable and not significantly more effort than a conventional presentation in LaTeX.
- Agda as a type checker for doing mathematics —manipulating symbols according to specified rules. Mechanised mathematical notation \Rightarrow **Confidence in results!** Dispell silly conjectures/errors!
- Agda enables a natural treatment of theories and their direct use as modules of executable programs.
- Finally, formal proofs are fool-proof! **No “an exercise to the reader”!**

By working out the details we discovered

- Common recursion principles ; “Evaluate” the **syntax** under a given **semantics**.

Why the Mechanisation

~ 1000 lines of Agda code

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.
- Unicode and mixfix operators \Rightarrow Mechanisation is readable and not significantly more effort than a conventional presentation in LaTeX.
- Agda as a type checker for doing mathematics —manipulating symbols according to specified rules. Mechanised mathematical notation \Rightarrow **Confidence in results!** Dispell silly conjectures/errors!
- Agda enables a natural treatment of theories and their direct use as modules of executable programs.
- Finally, formal proofs are fool-proof! **No “an exercise to the reader”!**

By working out the details we discovered

- Common recursion principles ; “Evaluate” the **syntax** under a given **semantics**.
- `map` operators and their optimisation rewrites: $\text{map } \text{id} \mapsto \text{id}$; $\text{map } f \circ \text{map } g \mapsto \text{map } (f \circ g)$

Why the Mechanisation

~ 1000 lines of Agda code

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.
- Unicode and mixfix operators \Rightarrow Mechanisation is readable and not significantly more effort than a conventional presentation in LaTeX.
- Agda as a type checker for doing mathematics —manipulating symbols according to specified rules. Mechanised mathematical notation \Rightarrow **Confidence in results!** Dispell silly conjectures/errors!
- Agda enables a natural treatment of theories and their direct use as modules of executable programs.
- Finally, formal proofs are fool-proof! **No “an exercise to the reader”!**

By working out the details we discovered

- Common recursion principles ; “Evaluate” the **syntax** under a given **semantics**.
- **map** operators and their optimisation rewrites: $\text{map } \text{Id} \mapsto \text{Id}$; $\text{map } f \circ \text{map } g \mapsto \text{map } (f \circ g)$
- (Haskell’s **return**) Unit transformations take on familiar forms: $[-]$, **Leaf**, **Just**, ...
Along with proven optimisation laws: $\text{map } f(\text{return } x) \mapsto \text{return } (f x)$

Why the Mechanisation

~ 1000 lines of Agda code

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.
- Unicode and mixfix operators \Rightarrow Mechanisation is readable and not significantly more effort than a conventional presentation in LaTeX.
- Agda as a type checker for doing mathematics —manipulating symbols according to specified rules. Mechanised mathematical notation \Rightarrow **Confidence in results!** Dispell silly conjectures/errors!
- Agda enables a natural treatment of theories and their direct use as modules of executable programs.
- Finally, formal proofs are fool-proof! **No “an exercise to the reader”!**

By working out the details we discovered

- Common recursion principles ; “Evaluate” the **syntax** under a given **semantics**.
- **map** operators and their optimisation rewrites: $\text{map } \text{Id} \mapsto \text{Id}$; $\text{map } f \circ \text{map } g \mapsto \text{map } (f \circ g)$
- (Haskell’s **return**) Unit transformations take on familiar forms: $[-]$, **Leaf**, **Just**, ...
Along with proven optimisation laws: $\text{map } f(\text{return } x) \mapsto \text{return } (f x)$
- **Boom Hierarchy does not necessarily work for type theory!**

Why the Mechanisation

~ 1000 lines of Agda code

Benefits of the formal approach

- Give solid grounding to folklore; e.g., there are no associative extensions of non-associative operators: There is no free functor from magmas to semigroups.
- Unicode and mixfix operators \Rightarrow Mechanisation is readable and not significantly more effort than a conventional presentation in LaTeX.
- Agda as a type checker for doing mathematics —manipulating symbols according to specified rules. Mechanised mathematical notation \Rightarrow **Confidence in results!** Dispell silly conjectures/errors!
- Agda enables a natural treatment of theories and their direct use as modules of executable programs.
- Finally, formal proofs are fool-proof! **No “an exercise to the reader”!**

By working out the details we discovered

- Common recursion principles ; “Evaluate” the **syntax** under a given **semantics**.
- **map** operators and their optimisation rewrites: $\text{map } \text{Id} \mapsto \text{Id}$; $\text{map } f \circ \text{map } g \mapsto \text{map } (f \circ g)$
- (Haskell’s **return**) Unit transformations take on familiar forms: `[-]`, `Leaf`, `Just`, ...
Along with proven optimisation laws: $\text{map } f(\text{return } x) \mapsto \text{return } (f x)$
- **Boom Hierarchy does not necessarily work for type theory!**
- New-ish relationships: Lists may be specified as a *free monoid* but may also be specified as *initial pointed indexed unary algebra*. Single-sorted unary algebras also have a surprising relationship with temporal logic.

Adventurous Avenues To Explore

—Where do these show up?

Adventurous Avenues To Explore —Where do these show up?

Math theories yielding potential data structures

left-zero monoid (Prolog's cut!?), pointed unary (natural numbers!?), idempotent unary, commutative magma, pointed magma, quasigroup, loop, semilattice, medial magma, left semimedial magma, left distributive magma, idempotent magma, zeropotent magma, left unary magma, Steiner magma, null semigroup, BCI algebra, BCK algebra, squag, sloop, Moufang quasigroup, loop, left shelf, shelf, rack, spindle, quandle, Kei, involutive semigroup, band, rectangular band, hemigroup, pseudo inverse algebra, ringoid, left near semiring, near semiring, semifield, semiring, semirng, pre-dioid, dioid, star semiring, idempotent dioid, ring, commutative ring, idempotent semiring, Stone algebra, Kleene lattice, Kleene algebra, Heyting algebra, Goedel algebra, ortho lattice, directoid, semiheap, idempotent semiheap, heap, meadow, wheel.

Adventurous Avenues To Explore —Where do these show up?

Math theories yielding potential data structures

left-zero monoid (**Prolog's cut!**?), pointed unary (**natural numbers!**?), idempotent unary, commutative magma, pointed magma, quasigroup, loop, semilattice, medial magma, left semimedial magma, left distributive magma, idempotent magma, zeropotent magma, left unary magma, Steiner magma, null semigroup, BCI algebra, BCK algebra, squag, sloop, Moufang quasigroup, loop, left shelf, shelf, rack, spindle, quandle, Kei, involutive semigroup, band, rectangular band, hemigroup, pseudo inverse algebra, ringoid, left near semiring, near semiring, semifield, semiring, semirng, pre-dioid, dioid, star semiring, idempotent dioid, ring, commutative ring, idempotent semiring, Stone algebra, Kleene lattice, Kleene algebra, Heyting algebra, Goedel algebra, ortho lattice, directoid, semiheap, idempotent semiheap, heap, meadow, wheel.

Structures possibly arising from mathematical theories

Difference list (**Yoneda on Monoids!**?), stack, queue, finite map, rose tree, digraph, multigraph, partitions, oriented cycles, colorings, tri-colorings, hedges, derangements, ballots, commutative parenthesizations, linear order, permutations, even permutations, chains, oriented sets, even sets, octopus, vertebrae, automata (**pointed indexed algebras!**?).