

1) index=botsv2 dest_ip="172.31.7.2" sourcetype="stream:http" (status=500 OR status=403 OR status=401)

| stats count by src_ip, http_method, uri_path, status, user_agent

| sort - count

[To verify if an attacker targeted the Backend Admin panel]

2) index=botsv2 dest_ip="172.31.7.2" sourcetype="stream:http" (status=500 OR status=403 OR status=401)

| stats count by src_ip, http_method, uri_path, status, user_agent

| sort - count

[To uncover any exploit attempts, scanning activity, or application crashes on 172.31.7.2, filter for HTTP error status codes (500, 403, 401)]

3) index=botsv2 sourcetype="stream:smtp"

| table _time, src_ip, mailfrom, email_to, subject, content_type

| sort _time

[To search for incoming emails]

4) index=botsv2 sourcetype="xmlwineventlog:microsoft-windows-sysmon/operational" "<EventID>1</EventID>" earliest=0

| rex field=_raw "<Data Name='Image'>(?!<Process_Image>[^\<]+)</Data>"

| rex field=_raw "<Data Name='CommandLine'>(?!<Command_Line>[^\<]+)</Data>"

| rex field=_raw "<Data Name='User'>(?!<User>[^\<]+)</Data>"

| search NOT Process_Image="*SplunkUniversalForwarder*" NOT

Process_Image="*SearchFilterHost*" NOT Process_Image="*dllhost.exe*" NOT

Process_Image="*taskhost.exe*" NOT Command_Line="*win_listening_ports.bat"

| stats count by Process_Image, Command_Line, User

| sort - count

[To filter out the background Splunk agent noise and surface suspicious administrator or attacker process activity (like powershell.exe, cmd.exe, mshta.exe, or encoded

commands)]

5) index=botsv2 sourcetype="xmlwineventlog:microsoft-windows-sysmon/operational" "
<EventID>1</EventID>" "kevin.lagerfield" earliest=0

| rex field=_raw "<Data Name='Image'>(?!<Process_Image>[^\<]+)</Data>"

| rex field=_raw "<Data Name='User'>(?!<User>[^\<]+)</Data>"

| rex field=_raw "<Computer>(?!<Computer>[^\<]+)</Computer>"

| table _time, Computer, User, Process_Image

[To find which specific host machine Kevin was using, run this query to pull the Computer Name and IP]

6) index=botsv2 "wrk-klagerf" sourcetype="stream:dns" earliest=0

| table _time, src_ip, query, reply

[Run this query to parse the SourceIp directly from DNS lookups performed for or by wrk-klagerf]

7) index=botsv2 src_ip="10.0.2.107" sourcetype="stream:dns" earliest=0

| rename "query{" as domain_requested, "host_addr{" as resolved_ip

| table _time, src_ip, domain_requested, resolved_ip

| sort - _time

[Run this query to view the actual DNS requests made by Kevin's workstation (10.0.2.107)]

8) index=botsv2 src_ip="10.0.2.107" sourcetype="stream:dns" earliest=0

| rename "query{" as domain_requested

| search NOT domain_requested="*.in-addr.arpa" NOT
domain_requested="*.frothly.local"

| stats count by domain_requested

| sort - count

[To find phishing links, C2 servers, or external tracking domains queried by 10.0.2.107, filter out routine local lookups]

```
9) index=botsv2 src_ip="10.0.2.109" (sourcetype="stream:tcp" OR  
sourcetype="stream:http") earliest=0  
| stats sum(bytes_out) as total_bytes_sent, count by dest_ip, dest_port  
| eval MB_sent = round(total_bytes_sent/1024/1024, 2)  
| sort - total_bytes_sent
```

[This sums up the total payload size sent out by 10.0.2.109 to external endpoints using network streams]

```
10) index=botsv2 src_ip="10.0.2.109" sourcetype="stream:dns" earliest=0  
| rename "query{}" as domain_requested  
| eval query_length = len(domain_requested)  
| search NOT domain_requested="*.in-addr.arpa" NOT  
domain_requested="*.frothly.local"  
| stats max(query_length) as max_len, count by domain_requested  
| sort - max_len
```

[This calculates the character length of requested domains to spot payload-encoded DNS queries]

```
11) index=botsv2 src_ip="10.0.2.109" dest_ip="45.77.65.211" earliest=0  
| stats count, sum(bytes_out) as bytes_sent, min(_time) as first_seen, max(_time) as  
last_seen by sourcetype, dest_port  
| eval first_seen=strftime(first_seen, "%Y-%m-%d %H:%M:%S"),  
last_seen=strftime(last_seen, "%Y-%m-%d %H:%M:%S")
```

[Run this query to analyze the timestamp timeline and traffic volume of the connection to 45.77.65.211]

```
12) index=botsv2 src_ip="10.0.2.109" dest_ip="45.77.65.211" dest_port=9999
sourcetype="stream:http" earliest=0
```

table_time, http_method, site, uri, user_agent, form_data

[Run this query to inspect what Kevin's machine sent to the attacker on port 9999]

```
13) index=botsv2 dest_ip="45.77.65.211" sourcetype="suricata" earliest=0
```

| stats count by alert.signature, alert.category, dest_port

```
| sort - count
```

[To determine what specific threat or malware signature Suricata IDS flagged for the 11,000+ alerts associated with 45.77.65.211, run this query]

14) index=botsv2 src_ip="10.0.2.109" sourcetype="suricata" event_type=alert earliest=0

| stats count by alert.signature, alert.category, dest_ip, dest_port

```
| sort - count
```

[To filter specifically for security alerts generated by Kevin's workstation (10.0.2.109), run this targeted query]

15) index=botsv2 schtasks.exe create

```
| table _time, host, CommandLine, Process_Command_Line, _raw
```

[Shows schtasks processes from powershell]

16) index=botsv2 host=*btun* earliest=0 (EventCode=4688 OR EventCode=1)

```
| eval cmd=coalesce(CommandLine, Process CommandLine, process, raw)
```

```
| search cmd!="*splunk*"
```

```
| search cmd="*powershell*" OR cmd="*winword*" OR cmd="*cmd.exe*" OR  
cmd="*wscript"
```

```
| table time, Account Name, user, cmd
```

| sort time

[filter noise while pointing out powershell exe files of host btun]

17) index=botsv2 (sourcetype="stream:tcp" OR sourcetype="stream:http")

src_ip="10.0.2.107" earliest=0

| table _time, src_ip, dest_ip, dest_port, http_method, uri_path, status

| sort _time

[outbound C2 connection]

18) index=botsv2 "45.77.65.211"

| stats count min(_time) as first_seen max(_time) as last_seen by host, sourcetype,
src_ip, dest_ip, dest_port

| eval first_seen=strftime(first_seen, "%Y-%m-%d %H:%M:%S"),

last_seen=strftime(last_seen, "%Y-%m-%d %H:%M:%S")

[SUS IP investigation]