

SimpleJMX Package

Version 1.1
February 2013

Gray Watson

This manual is licensed by Gray Watson under the Creative Commons Attribution-Share Alike 3.0 License.

Permission is granted to make and distribute verbatim copies of this manual provided the previous license notice and this permission notice are preserved on all copies.

Table of Contents

SimpleJMX	1
1 Start Using Quickly	2
2 Using SimpleJMX	3
2.1 Downloading Jar	3
2.2 Naming Objects	3
2.2.1 @JmxResource Annotation	3
2.2.2 Self Naming Objects	4
2.3 Exposing Fields and Methods	4
2.3.1 @JmxAttributeField Annotation	5
2.3.2 @JmxAttributeMethod Annotation	5
2.3.3 @JmxOperation Annotation	6
2.4 Starting a JMX Server	7
2.5 Registering Objects	7
2.6 Publishing Using Code Definitions	7
2.7 Using the JMX Client	8
2.8 Using With the Spring Framework	9
3 Example Code	11
4 Open Source License	12
Index of Concepts	13

SimpleJMX

Version 1.1 – February 2013

This package provides some classes that publish object using Java's Management Extensions (JMX). These published objects can be investigated with jconsole (Sun's graphical JMX user interface application) or another JMX client. Included is also a programmatic JMX client which you can use to connect to and interrogate remote JMX servers.

To get started quickly using SimpleJMX, see [Chapter 1 \[Quick Start\]](#), page 2. You can also take a look at the the examples section of the document which has various working code packages. See [Chapter 3 \[Examples\]](#), page 11. There is also a [HTML version of this documentation](#).

Gray Watson <http://256.com/gray/>

1 Start Using Quickly

To use SimpleJMX you need to do the following steps. For more information, see [Chapter 2 \[Using\]](#), page 3.

1. Download SimpleJMX from the [SimpleJMX release page](#). See [Section 2.1 \[Downloading\]](#), page 3.
2. Add `@JmxResource` annotation to the top of each class you want to publish via JMX. See [Section 2.2 \[Naming Objects\]](#), page 3.

```
@JmxResource(domainName = "your.domain", description = "Runtime counter")  
public class RuntimeCounter {
```

3. Add `@JmxAttributeField` annotation to each of the attribute fields that you want to expose via reflection over JMX. See [Section 2.3 \[Exposing Items\]](#), page 5.

```
@JmxAttributeField(description = "Start time in millis",  
    isWritable = true)  
private long startTimeMillis;
```

If you want to annotate the get/set/is attribute methods instead then use the `@JmxAttributeMethod` annotation on those methods. See [Section 2.3.2 \[JmxAttributeMethod Annotation\]](#), page 5.

```
@JmxAttributeMethod(description = "Run time in seconds or milliseconds")  
public long getRunTime() {
```

4. Add `@JmxOperation` annotation to each of operation methods that you want to make accessible over JMX. See [Section 2.3.3 \[JmxOperation Annotation\]](#), page 6.

```
@JmxOperation(description = "clear the cache")  
public void clearCache() {
```

5. Start your JMX server. See [Section 2.4 \[Starting Server\]](#), page 7.

```
// create a new JMX server listening on a port  
JmxServer jmxServer = new JmxServer(8000);  
jmxServer.start();
```

6. Register the objects you want to publish via JMX. See [Section 2.5 \[Registering Objects\]](#), page 7.

```
jmxServer.register(someObject);  
jmxServer.register(someOtherObject);
```

For more extensive instructions, see [Chapter 2 \[Using\]](#), page 3.

2 Using SimpleJMX

2.1 Downloading Jar

To get started with SimpleJMX, you will need to download the jar file. The [SimpleJMX release page](#) is the default repository but the jars are also available from the [central maven repository](#) and from [Sourceforge](#).

The code works with Java 5 or later.

2.2 Naming Objects

When you publish an object you need to tell JMX what the object's *unique* name is and where it should be located in the various folders shown by jconsole. There are a couple of different ways to do this with SimpleJMX:

2.2.1 @JmxResource Annotation

The `@JmxResource` annotation is used to define that the resource is to be published via JMX and how it is to be named.

```
@JmxResource(domainName = "your.domain", description = "Runtime counter")  
public class RuntimeCounter {  
    ...  
}
```

The above example shows that the `RuntimeCounter` object is to be published via JMX inside of the `your.domain` folder with a text description.

The fields in `@JmxResource` are:

`domainName`

Domain name of the object which turns into the top-level folder inside of jconsole. This must be specified unless the object is self-naming. See [Section 2.2.2 \[Self Naming\]](#), page 4.

`beanName`

Name of the JMX object in the jconsole folder. The default is to use the class name.

`folderNames`

Optional array of strings which translate into sub-folders below the domain-name folder. Default is for the object to show up in the domain-name folder. The folder names can either be in `name=value` format in which case they should be in alphabetic order by name. They can also just be in `value` format.

Folders are used when you have a large number of JMX objects being published and you want to group the objects so that you can find them faster than scrolling through a large list. For example, all of your database objects could go in the folder "database" while the database connections could go into the sub-folder "database/connections".

```

    @JmxResource(domainName = "your.domain",
        folderNames = { "database", "connections" })
    public class MySqlConnection {

```

description

Textual description of the class for jconsole or other JMX clients. Default is something like: "Information about class-name".

2.2.2 Self Naming Objects

Instead of using the `@JmxResource` annotation to define the name/folders for your JMX object, you can have the object implement the `JmxSelfNaming` interface. This allows the object to name itself and will override any settings from the `@JmxResource` annotation, if it is specified.

It is particularly necessary to make your object `JmxSelfNaming` if there are to be multiple of them published via JMX. For example, if you have multiple database connections that you want to publish then to ensure that they have a *unique* name, each of the objects should be self-naming and should provide a unique name that identifies itself:

```

// we only use this to set the domain name and the folders
@JmxResource(domainName = "your.domain",
    folderNames = { "database", "connections" })
public class DatabaseConnection extends BaseJmxSelfNaming
    implements JmxSelfNaming {
    @Override
    public String getJmxNameOfObject() {
        // return our toString as our name
        return toString();
    }
}

```

In the above example, we extend the `BaseJmxSelfNaming` abstract class which has default implementations for all of the `JmxSelfNaming` methods, so all we need to do is override what we want to change.

The methods in the `JmxSelfNaming` interface are:

`String getJmxDomainName();`

Return the domain name of the object. Return null to use the one from the `@JmxResource` annotation instead.

`String getJmxNameOfObject();`

Return the name of the object. Return null to use the one from the `@JmxResource` annotation instead.

`JmxFolderName[] getJmxFolderNames();`

Return the appropriate array of folder names used to built the associated object name. Return null for no folders in which case the bean will be at the top of the hierarchy in jconsole without any sub-folders.

2.3 Exposing Fields and Methods

Once we have named our object, we need to tell the JMX server which fields and methods should be exposed to the outside world. JMX can expose what it calls attributes, operations, and notifications. At this time, only attributes and operations are supported.

Attributes can be primitives or simple types such as `String` or `java.util.Date`. With SimpleJMX you can expose them by using reflection on the object's fields directly using the `@JmxAttributeField` annotation or instead via the `get/set/is` methods using the `@JmxAttributeMethod` annotation.

Operations are methods that do *not* start with `get/set/is` but which perform some function (ex: `resetTimer()`, `clearCache()`, etc.). They can be exposed with the `@JmxOperation` annotation.

2.3.1 @JmxAttributeField Annotation

SimpleJMX allows you to publish your primitive or simple types by annotating your fields with the `@JmxAttributeField` annotation.

```
@JmxAttributeField(description = "Start time in millis",
    isWritable = true)
private long startTimeMillis;
```

In the above example, the `startTimeMillis` long field will be visible via JMX. It will show its value which can be changed because `isWritable` is set to true. `isReadable` is set to true by default. The description is available in jconsole when you hover over the attribute.

The fields in the `@JmxAttributeField` annotation are:

String description

Description of the attribute for jconsole. Default is something like: "someField attribute".

boolean isReadable

Set to false if the field should not be read through JMX. Default is true.

boolean isWritable

Set to true if the field can be written by JMX. Default is false.

2.3.2 @JmxAttributeMethod Annotation

Instead of publishing the fields directly, SimpleJMX also allows you to publish your attributes by decorating the `get/set/is` methods using the `@JmxAttributeMethod` annotation. This is *only* for methods that start with `getXxx()`, `setXxx(...)`, or `isXxx()`.

The `Xxx` name should match precisely to line up the get and set JMX features. For example, if you are getting and setting the `fooBar` field then it should be `getFooBar()` and `setFooBar(...)`. `isFooBar()` is also allowed if `fooBar` is a `boolean` or `Boolean` field.

Notice that although the field-name is `fooBar` with a lowercase 'f', the method name camel-cases it and turns it into `getFooBar()` with a capital 'F'. In addition, the `getXxx()` method must not return void and must have no arguments. The `setXxx(...)` method must

return `void` and must take a single argument. The `isXxx()` method is allowed if it returns `boolean` or `Boolean` and the method has no arguments.

Exposing a `get` method allows you to do some data conversion when the value is published. Exposing a `set` method allows you to do data validation.

```
@JmxAttributeMethod(description = "Run time in seconds or milliseconds")
public long getRunTime() {
```

The only field in the `@JmxAttributeMethod` annotation is the description. The annotation on the `get...` method shows that it is readable and the annotation on the `set...` method shows that it is writable.

2.3.3 @JmxOperation Annotation

Operations are methods that do *not* start with `get/set/is` but which perform some function. They can be exposed with the `@JmxOperation` annotation. The method can either return `void` or an object. It is recommended that the method return a primitive or a simple object that is in Jconsole's classpath already. Otherwise Jconsole will be unable to display it. It also should not throw an unknown `Exception` class.

```
@JmxOperation(description = "clear the cache")
public void clearCache() {
    ...
}
```

A pattern that is common is to return a `String` from the method to provide some feedback to the remote user and to catch and return any exceptions as a `String`.

```
@JmxOperation(description = "clear the cache")
public void clearCache() {
    try {
        // do the cache clearing here
        return "Cache cleared";
    } catch (Exception e) {
        return "Threw exception: " + e;
    }
}
```

The fields in the `@JmxOperation` annotation are:

String description

Description of the attribute for jconsole. Default is something like "someMethod operation".

String[] parameterNames

Optional array of strings which gives the name of each of the method parameters. The array should be the same length as the `parameterDescriptions` array. Default is something like "p0".

```
@JmxOperation(parameterNames = { "minValue", "maxValue" },
    parameterDescriptions = { "low water mark",
        "high water mark" })
public void resetMaxMin(int minValue, int maxValue) {
    ...
}
```

`String[] parameterDescriptions`

Optional array of strings which describes each of the method parameters. The array should be the same length as the `parameterNames` array.

`OperationAction operationAction`

This optional field is used by the JMX system to describe what sort of work is being done in this operation.

2.4 Starting a JMX Server

The `JmxServer` class provides a server that `jconsole` and other JMX clients can connect to. The easiest way to do this is to choose a port to use, define the server, and then start it:

```
// create a new JMX server listening on a port
JmxServer jmxServer = new JmxServer(8000);
// start our server
jmxServer.start();
```

Before your program exits, it is best to stop the server, so the following try/finally block is a good pattern to use:

```
// create a new JMX server listening on a port
JmxServer jmxServer = new JmxServer(8000);
try {
    // start our server
    jmxServer.start();
    ...
    // register objects with the server and do other stuff here
    ...
} finally {
    // un-register objects
    // stop our server
    jmxServer.stop();
}
```

2.5 Registering Objects

To publish objects via the server via JMX you must register them with the `JmxServer`:

```
jmxServer.register(someObject);
```

There also is an `unregister(...)` method which will un-publish from the server:

```
jmxServer.unregister(someObject);
```

The objects that are registered must be named and the fields and methods that are to be exposed must be specified.

2.6 Publishing Using Code Definitions

Sometimes, you want to expose a class using JMX but you don't control the source code or maybe you don't want to put the SimpleJMX annotations everywhere. If this is the case then you also have the option to expose just about any object programmatically.

The `JmxServer` has a register function which takes just an `Object`, an `ObjectName` which can be generated with the use of the `ObjectNameUtil` class, and an array of attribute-fields, attribute-methods, and operations.

The attribute-fields are specified as an array of `JmxAttributeFieldInfo` objects that are associated with fields that are exposed through reflection:

```
JmxAttributeFieldInfo[] attributeFieldInfos =
    new JmxAttributeFieldInfo[] {
        new JmxAttributeFieldInfo("startMillis", true /* readable */,
            false /* not writable */, "When our timer started"),
    };
```

The attribute-methods are specified as an array of `JmxAttributeMethodInfo` objects that are associated with fields that are exposed through get/set/is methods:

```
JmxAttributeMethodInfo[] attributeMethodInfos =
    new JmxAttributeMethodInfo[] {
        new JmxAttributeMethodInfo("getRunTime",
            "Run time in seconds or milliseconds"),
    };
```

The operations are specified as an array of `JmxOperationInfo` objects that are associated with operation methods:

```
JmxOperationInfo[] operationInfos =
    new JmxOperationInfo[] {
        new JmxOperationInfo("restartTimer", null /* no params */,
            null /* no params */, OperationAction.UNKNOWN,
            "Restart the timer"),
    };
```

To register the object you would then do:

```
jmxServer.register(someObject,
    ObjectNameUtil.makeObjectName("your.domain", "SomeObject"),
    attributeFieldInfos, attributeMethodInfos, operationInfos);
```

Take a look at the random-object example program for a working example. See [\[random object example\]](#), page 11.

2.7 Using the JMX Client

SimpleJMX also includes a programmatic, simple JMX client which you can use to interrogate JMX servers. You connect to the server by specifying the host and port.

```
JmxClient client = new JmxClient("server1", 8000);
```

To get a list of the available beans use the

```
Set<ObjectName> beanNames = jmxClient.getBeanNames();
```

Then you can get the attributes and operations associated with an `ObjectName`:

```
MBeanAttributeInfo[] attributeInfos =
    jmxClient.getAttributeInfo(objectName);
MBeanOperationInfo[] operationInfos =
    jmxClient.getOperationsInfo(objectName);
```

You can then get an attribute from the info or invoke an operation:

```
boolean showSeconds =
    jmxClient.getAttribute(objectName, attributeInfo.getName());
client.invokeOperation(objectName, operationInfo.getName());
```

You can also get attributes by strings instead of `ObjectNames`:

```
boolean showSeconds =
    jmxClient.getAttribute("your.domain", "RuntimeCounter",
        "showSeconds");
```

If you need to construct the object name directly then you can use `ObjectName` static methods. This is particularly useful if you use `Jconsole` to find a bean that you want to operate on via the `JmxClient`. Just copy the `ObjectName` field associated to a bean from `Jconsole` and then do something like the following:

```
int availableProcessors =
    client.getAttribute(
        ObjectName.getInstance("java.lang:type=OperatingSystem"),
        "AvailableProcessors");
```

You can also call operations with string arguments:

```
client.invokeOperation(ObjectName.getInstance("java.lang:type=Memory"),
    "gc");
```

See the `JmxClient` javadocs for more information

2.8 Using With the Spring Framework

SimpleJMX has an optional dependency on the Spring Framework jar(s). This means that if you have the Spring framework included in your project, you can make use of the `BeanPublisher` class which will automatically register the beans from your spring XML configuration files to the `JmxServer` class. The `BeanPublisher` class will register classes that have the `@JmxResource` annotation and the classes that implement the `JmxSelfNaming` interface.

Here's a sample bean configuration:

```
<!-- registers @JmxResource and JmxSelfNaming classes with the server -->
<bean id="beanPublisher" class="com.j256.simplejmx.spring.BeanPublisher">
    <property name="jmxServer" ref="jmxServer" />
</bean>

<!-- our JMX server which publishes our JMX beans -->
<bean id="jmxServer" class="com.j256.simplejmx.server."
```

```
        init-method="start" destroy-method="stop">  
        <property name="registryPort" value="8000" />  
    </bean>
```

Notice that the `JmxServer` is configured with an `init-method` and `destroy-method` which cause the JMX server to be started and stopped when the application context is loaded and closed.

For a working example, take a look at the spring example program. See [\[spring framework example\]](#), page 11.

3 Example Code

Here is some example code to help you get going with SimpleJMX. I often find that code is the best documentation of how to get something working. Please feel free to suggest additional example packages for inclusion here. Source code submissions are welcome as long as you don't get piqued if we don't chose your's.

Simple, basic

This is a simple application which publishes a single object. See the [source code in SVN](#).

Random object example

This is an example showing how to programmatically expose using JMX a random object without SimpleJMX annotations: See the [source code in SVN](#).

Spring Framework example

This is an example showing how you can use SimpleJMX with the Spring Framework. See the [source code in SVN](#).

4 Open Source License

This document is part of the SimpleJMX project.

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The author may be contacted via <http://256.com/sources/simplejmx/>

Index of Concepts

@

@JmxAttributeField annotation	5
@JmxAttributeMethod annotation	5
@JmxOperation annotation	6
@JmxResource annotation	3

A

attributes	5
author	1

C

client, JMX	8
code examples	11

D

description of object	4
directories in jconsole	3
downloading the jars	3
dynamic objects	4

E

examples of code	11
exposing fields	5
exposing get/set/is methods	5
exposing methods	6

F

folders in jconsole	3
---------------------------	---

G

get methods	5
getting started	2

H

how to download the jars	3
how to get started	2
how to use	3

I

introduction	1
is methods	5

J

jconsole	1, 9
jconsole folders	3
jmx client	8
JmxAttributeField annotation	5
JmxAttributeMethod annotation	5
JmxOperation annotation	6
JmxResource annotation	3

W

L

license	12
---------------	----

M

methods, publishing	6
multiple objects	4

N

naming objects	3
notifications, not supported	5

O

object description	4
object domain name	3
object name	3
objects with same name	4
open source license	12
operations	6

P

programmatic publishing	8
publishing fields	5
publishing get/set/is methods	5
publishing methods	6
publishing objects	7

Q

quick start	2
-------------------	---

R

read-only attributes	5
registering objects	7

S

self naming objects	4
set methods	5
simple example	11
simple jmx	1
Spring framework	9
start a JMX server	7

U

using SimpleJMX	3
using with Spring	9